



State of Ohio Environmental Protection Agency

**RE: FINAL PERMIT TO INSTALL
BUTLER COUNTY**

CERTIFIED MAIL

Street Address:

122 S. Front Street

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center
P.O. Box 1049

Application No: 14-05890

Fac ID: 1409010497

DATE: 12/21/2006

Quaker Chemical Corporation
Fred Sansom
14301 Birwood Avenue
Detroit, MI 48238

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action of the Director is final and may be appealed to the Environmental Review Appeals Commission pursuant to Section 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. The appeal must be filed with the Commission within thirty (30) days after notice of the Director's action. The appeal must be accompanied by a filing fee of \$70.00 which the Commission, in its discretion, may reduce if by affidavit you demonstrate that payment of the full amount of the fee would cause extreme hardship. Notice of the filing of the appeal shall be filed with the Director within three (3) days of filing with the Commission. Ohio EPA requests that a copy of the appeal be served upon the Ohio Attorney General's Office, Environmental Enforcement Section. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
309 South Fourth Street, Room 222
Columbus, OH 43215

Sincerely,

Michael W. Ahern, Manager
Permit Issuance and Data Management Section
Division of Air Pollution Control

CC: USEPA

HCDES



**Permit To Install
Terms and Conditions**

**Issue Date: 12/21/2006
Effective Date: 12/21/2006**

FINAL PERMIT TO INSTALL 14-05890

Application Number: 14-05890
Facility ID: 1409010497
Permit Fee: **\$1600**
Name of Facility: Quaker Chemical Corporation
Person to Contact: Fred Sansom
Address: 14301 Birwood Avenue
Detroit, MI 48238

Location of proposed air contaminant source(s) [emissions unit(s)]:
**3431 Yankee Road
Middletown, Ohio**

Description of proposed emissions unit(s):
Eight new blenders controlled by a wet scrubber.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted (i.e., postmarked) quarterly by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon

Quaker Chemical Corporation
PTI Application: 14-05890
Issued: 12/21/2006

Facility ID: 1409010497

the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

Quaker Chemical Corporation
PTI Application: 14-05890
Issued: 12/21/2006

Facility ID: 1409010497

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

Quaker Chemical Corporation
 PTI Application: 14-05890
 Issued: 12/21/2006

Facility ID: 1409010497

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the emissions unit(s) covered by this permit.

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)
 TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

| <u>Pollutant</u> | <u>Tons Per Year</u> |
|------------------|----------------------|
| PE/PM10 | 5.75 |
| VOC | 1.64 |

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (P005) - Blender ABB 01

| Applicable Rules/Requirements | Applicable Emissions Limitations/Control Measures |
|-------------------------------|---|
| ORC 3704.03(T)(4) | See terms and conditions A.2.a, A.2.b, B.1 and B.2. |
| OAC rule 3745-17-07(A)(1) | See term and condition A.2.c. |
| OAC rule 3745-17-11 | See term and condition A.2.d. |
| OAC rule 3745-17-07(B)(1) | See term and condition A.2.e. |

2. Additional Terms and Conditions

- 2.a The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the volatile organic compound (VOC) emissions from this air contaminant source since the uncontrolled potential to emit for VOC emissions is less than ten tons per year.
- 2.b The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the particulate emissions (PE) or particulate emissions 10 microns and less in diameter (PM10) from this air contaminant source because the calculated annual emission rate for PE and PM10 is less than ten tons per year, taking into account the voluntary restrictions accepted by the permittee and the use of a wet scrubber as an air pollution control installed on the source.
- 2.c The visible particulate emissions from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.
- 2.d The PE from the outlet of the scrubber controlling emissions units P005, P006, P007, P008, P009, P010, P011 and P012, combined shall not exceed 13.3 pounds per hour, based on Figure 2 in OAC rule 3745-17-11(B).
- 2.e The visible particulate emissions from any fugitive dust source shall not exceed

Issued: 12/21/2006

20 percent opacity, as a three-minute average.

B. Operational Restrictions

1. This emissions unit shall be operated with a Venturi wet scrubber having an overall control efficiency for particulate matter emissions of at least 81 percent .
2. The total dry material usage in emissions units P005, P006, P007, P008, P009, P010, P011 and P012 combined shall not exceed 6,055,235 pounds per year.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information each month:

the amount, in pounds, of all dry material employed in emissions units P005, P006, P007, P008, P009, P010, P011 and P012 combined.
2. The permittee shall properly install, operate, and maintain equipment to continuously monitor and record the scrubber pressure drop during operation of this emissions unit, including periods of startup and shutdown. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the scrubber pressure drop on daily basis.

Whenever the monitored value for the scrubber pressure drop deviates from the range specified below, the permittee shall promptly investigate the cause of the deviation. The permittee shall maintain records of the following information for each investigation: the date and time the deviation began and the magnitude of the deviation at that time, the date(s) the investigation was conducted, the names of the personnel who conducted the investigation, and the findings and recommendations.

In response to each required investigation to determine the cause of a deviation, the permittee shall take prompt corrective action to bring the operation of the control equipment within the acceptable range specified below, unless the permittee determines that corrective action is not necessary and documents the reasons for that determination and the date and time the deviation ended. The permittee shall maintain records of the following information for each corrective action taken: a description of the corrective action, the date it was completed, the date and time the deviation ended,

Emissions Unit ID: **P005**

the total period of time (in minutes) during which there was a deviation, the pressure drop reading immediately after the corrective action, and the names of the personnel who performed the work. Investigation and records required by this paragraph does not eliminate the need to comply with the requirements of OAC rule 3745-15-06 if it is determined that a malfunction has occurred.

The acceptable range for the pressure drop across the scrubber shall be based upon the manufacturer's specifications until such time as any required emissions testing is conducted.

D. Reporting Requirements

1. The permittee shall submit annual reports which summarize the following for this emissions unit:

the amount, in pounds, of dry materials employed in emissions units P005, P006, P007, P008, P009, P010, P011 and P012 combined for the previous calendar year; and

the total particulate emissions in tons per year from emissions units P005, P006, P007, P008, P009, P010, P011 and P012, combined for the previous calendar year.

The reports shall be submitted by January 31 of each year.

2. The permittee shall submit quarterly reports that identify the following information concerning the operation of the control equipment during the operation of this emissions unit:
 - a. each period of time when the pressure drop across the scrubber was outside of the range specified by the manufacturer;
 - b. an identification of each incident of deviation described in (a) where a prompt investigation was not conducted;
 - c. an identification of each incident of deviation described in (a) where prompt corrective action, that would bring the pressure drop into compliance with the acceptable range, was determined to be necessary and was not taken; and
 - d. an identification of each incident of deviation described in (a) where proper records were not maintained for the investigation and/or the corrective action.

These quarterly reports shall be submitted (i.e., postmarked) by January 31, April 30,

Issued: 12/21/2006

July 31, and October 31 of each year; and each report shall cover the previous calendar quarter.

E. Testing Requirements

1. The uncontrolled potential to emit of VOC emissions for this emissions unit is based on the following information, as supplied by the facility in PTI application 14-05890 as submitted on October 31, 2006:

maximum liquid solvent capacity in emissions unit P005 is 6,573,950 gallons per year x emissions factor of 6.42E-05 lbs per gallon = 422.1 lbs/year or 0.21 ton per year.

2. Compliance with the emission limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following method:

Emission Limitations:

The PE/PM10 emissions from this emissions unit shall not exceed 9.9 tons per year.

Applicable Compliance Method:

Compliance with the annual emissions limitation for PE/PM10 is determined by calculating the sum of the annual maximum dry material usage rate in tons multiplied by the emissions factor of 20 pounds per ton (from AP-42 Table 6.4-1, 1/95) and multiplied by one minus the capture efficiency (90%) of the wet scrubber and the annual maximum dry material usage rate in tons multiplied by the emissions factor of 20 pounds per ton (from AP-42 Table 6.4-1, 1/95) multiplied by the capture efficiency of the wet scrubber (90%) and multiplied by one minus the control efficiency (90%) of the wet scrubber.

Emissions Limitation:

The PE from the outlet of the scrubber controlling emissions units P005, P006, P007, P008, P009, P010, P011 and P012, combined shall not exceed 13.3 pounds per hour

Applicable Compliance Method

If required, compliance with the hourly PE limitation shall be demonstrated through an emissions source test performed in accordance with the requirements of 40 CFR Part 60, Appendix A, Methods 1 - 5.

Emissions Limitation:

The visible particulate emissions from any stack shall not exceed 20 percent opacity,

Emissions Unit ID: P005

as a six-minute average, except as specified by rule.

Applicable Compliance Method:

Compliance shall be determined through visible emission observations performed in accordance with 40 CFR Part 60, Appendix A, Method 9 and the procedures specified in OAC rule 3745-17-03(B)(1).

Emissions Limitation:

The visible particulate emissions from any fugitive dust source shall not exceed 20 percent opacity, as a three-minute average.

Applicable Compliance Method:

Compliance shall be determined through visible emission observations performed in accordance with 40 CFR Part 60, Appendix A, Method 9 and the procedures specified in OAC rule 3745-17-03(B)(3).

3. Compliance with the annual production limitation in term and condition B.2 shall be demonstrated through the record keeping required in term and condition C.1.

F. Miscellaneous Requirements

1. Modeling to demonstrate compliance with the Ohio EPA's "Air Toxic Policy" was not necessary because the emissions unit's maximum annual emissions for each toxic pollutant will be less than 1.0 ton. OAC Chapter 3745-31 requires a permittee to apply for and obtain a new or modified permit to install prior to making a "modification" as defined by OAC rule 3745-31-01. The permittee is hereby advised that a new permit to install application would be required for an emissions unit if changes in the composition of the materials or use of new materials would cause the emissions of any pollutant that has a listed Threshold Limit Value (TLV), as documented in the most current version of the American Conference of Governmental Industrial Hygienists' (ACGIH's) handbook entitled "TLVs and BEIs" ("Threshold Limit Values for Chemical Substances and Physical Agents, Biological Exposure Indices"), to increase to above 1.0 ton per year.

Issued: 12/21/2006

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (P006) - Blender ABB 02

| Applicable Rules/Requirements | Applicable Emissions Limitations/Control Measures |
|--------------------------------------|--|
| ORC 3704.03(T)(4) | See terms and conditions A.2.a, A.2.b, B.1 and B.2. |
| OAC rule 3745-17-07(A)(1) | See term and condition A.2.c. |
| OAC rule 3745-17-11 | See term and condition A.2.d. |
| OAC rule 3745-17-07(B)(1) | See term and condition A.2.e. |

2. Additional Terms and Conditions

- 2.a The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the volatile organic compound (VOC) emissions from this air contaminant source since the uncontrolled potential to emit for VOC emissions is less than ten tons per year.
- 2.b The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the particulate emissions (PE) or particulate emissions 10 microns and less in diameter (PM10) from this air contaminant source because the calculated annual emission rate for PE and PM10 is less than ten tons per year, taking into account the voluntary restrictions accepted by the permittee and the use of a wet scrubber as an air pollution control installed on the source.
- 2.c The visible particulate emissions from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.
- 2.d The PE from the outlet of the scrubber controlling emissions units P005, P006, P007, P008, P009, P010, P011 and P012, combined shall not exceed 13.3 pounds per hour, based on Figure 2 in OAC rule 3745-17-11(B).

Emissions Unit ID: P006

- 2.e The visible particulate emissions from any fugitive dust source shall not exceed 20 percent opacity, as a three-minute average.

B. Operational Restrictions

1. This emissions unit shall be operated with a Venturi wet scrubber having an overall control efficiency for particulate matter emissions of at least 81 percent .
2. The total dry material usage in emissions units P005, P006, P007, P008, P009, P010, P011 and P012 combined shall not exceed 6,055,235 pounds per year.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information each month:

the amount, in pounds, of all dry material employed in emissions units P005, P006, P007, P008, P009, P010, P011 and P012 combined.
2. The permittee shall properly install, operate, and maintain equipment to continuously monitor and record the scrubber pressure drop during operation of this emissions unit, including periods of startup and shutdown. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the scrubber pressure drop on daily basis.

Whenever the monitored value for the scrubber pressure drop deviates from the range specified below, the permittee shall promptly investigate the cause of the deviation. The permittee shall maintain records of the following information for each investigation: the date and time the deviation began and the magnitude of the deviation at that time, the date(s) the investigation was conducted, the names of the personnel who conducted the investigation, and the findings and recommendations.

In response to each required investigation to determine the cause of a deviation, the permittee shall take prompt corrective action to bring the operation of the control equipment within the acceptable range specified below, unless the permittee determines that corrective action is not necessary and documents the reasons for that determination and the date and time the deviation ended. The permittee shall maintain records of the following information for each corrective action taken: a description of the corrective action, the date it was completed, the date and time the deviation ended, the total period of time (in minutes) during which there was a deviation, the pressure drop reading immediately

Issued: 12/21/2006

after the corrective action, and the names of the personnel who performed the work. Investigation and records required by this paragraph does not eliminate the need to comply with the requirements of OAC rule 3745-15-06 if it is determined that a malfunction has occurred.

The acceptable range for the pressure drop across the scrubber shall be based upon the manufacturer's specifications until such time as any required emissions testing is conducted.

D. Reporting Requirements

1. The permittee shall submit annual reports which summarize the following for this emissions unit:

the amount, in pounds, of dry materials employed in emissions units P005, P006, P007, P008, P009, P010, P011 and P012 combined for the previous calendar year; and

the total particulate emissions in tons per year from emissions units P005, P006, P007, P008, P009, P010, P011 and P012, combined for the previous calendar year.

The reports shall be submitted by January 31 of each year.

2. The permittee shall submit quarterly reports that identify the following information concerning the operation of the control equipment during the operation of this emissions unit:
 - a. each period of time when the pressure drop across the scrubber was outside of the range specified by the manufacturer;
 - b. an identification of each incident of deviation described in (a) where a prompt investigation was not conducted;
 - c. an identification of each incident of deviation described in (a) where prompt corrective action, that would bring the pressure drop into compliance with the acceptable range, was determined to be necessary and was not taken; and
 - d. an identification of each incident of deviation described in (a) where proper records were not maintained for the investigation and/or the corrective action.

Emissions Unit ID: P006

These quarterly reports shall be submitted (i.e., postmarked) by January 31, April 30, July 31, and October 31 of each year; and each report shall cover the previous calendar quarter.

E. Testing Requirements

1. The uncontrolled potential to emit of VOC emissions for this emissions unit is based on the following information, as supplied by the facility in PTI application 14-05890 as submitted on October 31, 2006:

maximum liquid solvent capacity in emissions unit P005 is 6,573,950 gallons per year x emissions factor of 6.42E-05 lbs per gallon = 422.1 lbs/year or 0.21 ton per year.

2. Compliance with the emission limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following method:

Emission Limitations:

The PE/PM10 emissions from this emissions unit shall not exceed 9.9 tons per year.

Applicable Compliance Method:

Compliance with the annual emissions limitation for PE/PM10 is determined by calculating the sum of the annual maximum dry material usage rate in tons multiplied by the emissions factor of 20 pounds per ton (from AP-42 Table 6.4-1, 1/95) and multiplied by one minus the capture efficiency (90%) of the wet scrubber and the annual maximum dry material usage rate in tons multiplied by the emissions factor of 20 pounds per ton (from AP-42 Table 6.4-1, 1/95) multiplied by the capture efficiency of the wet scrubber (90%) and multiplied by one minus the control efficiency (90%) of the wet scrubber.

Emissions Limitation:

The PE from the outlet of the scrubber controlling emissions units P005, P006, P007, P008, P009, P010, P011 and P012, combined shall not exceed 13.3 pounds per hour

Applicable Compliance Method

If required, compliance with the hourly PE limitation shall be demonstrated through an emissions source test performed in accordance with the requirements of 40 CFR Part 60, Appendix A, Methods 1 - 5.

Emissions Limitation:

The visible particulate emissions from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.

Issued: 12/21/2006

Applicable Compliance Method:

Compliance shall be determined through visible emission observations performed in accordance with 40 CFR Part 60, Appendix A, Method 9 and the procedures specified in OAC rule 3745-17-03(B)(1).

Emissions Limitation:

The visible particulate emissions from any fugitive dust source shall not exceed 20 percent opacity, as a three-minute average.

Applicable Compliance Method:

Compliance shall be determined through visible emission observations performed in accordance with 40 CFR Part 60, Appendix A, Method 9 and the procedures specified in OAC rule 3745-17-03(B)(3).

3. Compliance with the annual production limitation in term and condition B.2 shall be demonstrated through the record keeping required in term and condition C.1.

F. Miscellaneous Requirements

1. Modeling to demonstrate compliance with the Ohio EPA's "Air Toxic Policy" was not necessary because the emissions unit's maximum annual emissions for each toxic pollutant will be less than 1.0 ton. OAC Chapter 3745-31 requires a permittee to apply for and obtain a new or modified permit to install prior to making a "modification" as defined by OAC rule 3745-31-01. The permittee is hereby advised that a new permit to install application would be required for an emissions unit if changes in the composition of the materials or use of new materials would cause the emissions of any pollutant that has a listed Threshold Limit Value (TLV), as documented in the most current version of the American Conference of Governmental Industrial Hygienists' (ACGIH's) handbook entitled "TLVs and BEIs" ("Threshold Limit Values for Chemical Substances and Physical Agents, Biological Exposure Indices"), to increase to above 1.0 ton per year.

Issued: 12/21/2006

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (P007) - Blender ABB 03

| Applicable Rules/Requirements | Applicable Emissions Limitations/Control Measures |
|--------------------------------------|--|
| ORC 3704.03(T)(4) | See terms and conditions A.2.a, A.2.b, B.1 and B.2. |
| OAC rule 3745-17-07(A)(1) | See term and condition A.2.c. |
| OAC rule 3745-17-11 | See term and condition A.2.d. |
| OAC rule 3745-17-07(B)(1) | See term and condition A.2.e. |

2. Additional Terms and Conditions

- 2.a The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the volatile organic compound (VOC) emissions from this air contaminant source since the uncontrolled potential to emit for VOC emissions is less than ten tons per year.
- 2.b The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the particulate emissions (PE) or particulate emissions 10 microns and less in diameter (PM10) from this air contaminant source because the calculated annual emission rate for PE and PM10 is less than ten tons per year, taking into account the voluntary restrictions accepted by the permittee and the use of a wet scrubber as an air pollution control installed on the source.
- 2.c The visible particulate emissions from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.
- 2.d The PE from the outlet of the scrubber controlling emissions units P005, P006, P007, P008, P009, P010, P011 and P012, combined shall not exceed 13.3 pounds per hour, based on Figure 2 in OAC rule 3745-17-11(B).

Emissions Unit ID: P007

- 2.e** The visible particulate emissions from any fugitive dust source shall not exceed 20 percent opacity, as a three-minute average.

B. Operational Restrictions

1. This emissions unit shall be operated with a Venturi wet scrubber having an overall control efficiency for particulate matter emissions of at least 81 percent .
2. The total dry material usage in emissions units P005, P006, P007, P008, P009, P010, P011 and P012 combined shall not exceed 6,055,235 pounds per year.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information each month:

the amount, in pounds, of all dry material employed in emissions units P005, P006, P007, P008, P009, P010, P011 and P012 combined.
2. The permittee shall properly install, operate, and maintain equipment to continuously monitor and record the scrubber pressure drop during operation of this emissions unit, including periods of startup and shutdown. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the scrubber pressure drop on daily basis.

Whenever the monitored value for the scrubber pressure drop deviates from the range specified below, the permittee shall promptly investigate the cause of the deviation. The permittee shall maintain records of the following information for each investigation: the date and time the deviation began and the magnitude of the deviation at that time, the date(s) the investigation was conducted, the names of the personnel who conducted the investigation, and the findings and recommendations.

In response to each required investigation to determine the cause of a deviation, the permittee shall take prompt corrective action to bring the operation of the control equipment within the acceptable range specified below, unless the permittee determines that corrective action is not necessary and documents the reasons for that determination and the date and time the deviation ended. The permittee shall maintain records of the following information for each corrective action taken: a description of the corrective action, the date it was completed, the date and time the deviation ended, the total period of time (in minutes) during which there was a deviation, the pressure drop reading immediately after the corrective action, and the names of the personnel

Issued: 12/21/2006

who performed the work. Investigation and records required by this paragraph does not eliminate the need to comply with the requirements of OAC rule 3745-15-06 if it is determined that a malfunction has occurred.

The acceptable range for the pressure drop across the scrubber shall be based upon the manufacturer's specifications until such time as any required emissions testing is conducted.

D. Reporting Requirements

1. The permittee shall submit annual reports which summarize the following for this emissions unit:

the amount, in pounds, of dry materials employed in emissions units P005, P006, P007, P008, P009, P010, P011 and P012 combined for the previous calendar year; and

the total particulate emissions in tons per year from emissions units P005, P006, P007, P008, P009, P010, P011 and P012, combined for the previous calendar year.

The reports shall be submitted by January 31 of each year.

2. The permittee shall submit quarterly reports that identify the following information concerning the operation of the control equipment during the operation of this emissions unit:
 - a. each period of time when the pressure drop across the scrubber was outside of the range specified by the manufacturer;
 - b. an identification of each incident of deviation described in (a) where a prompt investigation was not conducted;
 - c. an identification of each incident of deviation described in (a) where prompt corrective action, that would bring the pressure drop into compliance with the acceptable range, was determined to be necessary and was not taken; and
 - d. an identification of each incident of deviation described in (a) where proper records were not maintained for the investigation and/or the corrective action.

These quarterly reports shall be submitted (i.e., postmarked) by January 31, April 30,

Emissions Unit ID: P007

July 31, and October 31 of each year; and each report shall cover the previous calendar quarter.

E. Testing Requirements

1. The uncontrolled potential to emit of VOC emissions for this emissions unit is based on the following information, as supplied by the facility in PTI application 14-05890 as submitted on October 31, 2006:

maximum liquid solvent capacity in emissions unit P005 is 6,573,950 gallons per year x emissions factor of 6.42E-05 lbs per gallon = 422.1 lbs/year or 0.21 ton per year.

2. Compliance with the emission limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following method:

Emission Limitations:

The PE/PM10 emissions from this emissions unit shall not exceed 9.9 tons per year.

Applicable Compliance Method:

Compliance with the annual emissions limitation for PE/PM10 is determined by calculating the sum of the annual maximum dry material usage rate in tons multiplied by the emissions factor of 20 pounds per ton (from AP-42 Table 6.4-1, 1/95) and multiplied by one minus the capture efficiency (90%) of the wet scrubber and the annual maximum dry material usage rate in tons multiplied by the emissions factor of 20 pounds per ton (from AP-42 Table 6.4-1, 1/95) multiplied by the capture efficiency of the wet scrubber (90%) and multiplied by one minus the control efficiency (90%) of the wet scrubber.

Emissions Limitation:

The PE from the outlet of the scrubber controlling emissions units P005, P006, P007, P008, P009, P010, P011 and P012, combined shall not exceed 13.3 pounds per hour

Applicable Compliance Method

If required, compliance with the hourly PE limitation shall be demonstrated through an emissions source test performed in accordance with the requirements of 40 CFR Part 60, Appendix A, Methods 1 - 5.

Emissions Limitation:

The visible particulate emissions from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.

Issued: 12/21/2006

Applicable Compliance Method:

Compliance shall be determined through visible emission observations performed in accordance with 40 CFR Part 60, Appendix A, Method 9 and the procedures specified in OAC rule 3745-17-03(B)(1).

Emissions Limitation:

The visible particulate emissions from any fugitive dust source shall not exceed 20 percent opacity, as a three-minute average.

Applicable Compliance Method:

Compliance shall be determined through visible emission observations performed in accordance with 40 CFR Part 60, Appendix A, Method 9 and the procedures specified in OAC rule 3745-17-03(B)(3).

3. Compliance with the annual production limitation in term and condition B.2 shall be demonstrated through the record keeping required in term and condition C.1.

F. Miscellaneous Requirements

1. Modeling to demonstrate compliance with the Ohio EPA's "Air Toxic Policy" was not necessary because the emissions unit's maximum annual emissions for each toxic pollutant will be less than 1.0 ton. OAC Chapter 3745-31 requires a permittee to apply for and obtain a new or modified permit to install prior to making a "modification" as defined by OAC rule 3745-31-01. The permittee is hereby advised that a new permit to install application would be required for an emissions unit if changes in the composition of the materials or use of new materials would cause the emissions of any pollutant that has a listed Threshold Limit Value (TLV), as documented in the most current version of the American Conference of Governmental Industrial Hygienists' (ACGIH's) handbook entitled "TLVs and BEIs" ("Threshold Limit Values for Chemical Substances and Physical Agents, Biological Exposure Indices"), to increase to above 1.0 ton per year.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (P008) - Blender ABB 04

| Applicable Rules/Requirements | Applicable Emissions Limitations/Control Measures |
|-------------------------------|---|
| ORC 3704.03(T)(4) | See terms and conditions A.2.a, A.2.b, B.1 and B.2. |
| OAC rule 3745-17-07(A)(1) | See term and condition A.2.c. |
| OAC rule 3745-17-11 | See term and condition A.2.d. |
| OAC rule 3745-17-07(B)(1) | See term and condition A.2.e. |

2. Additional Terms and Conditions

- 2.a The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the volatile organic compound (VOC) emissions from this air contaminant source since the uncontrolled potential to emit for VOC emissions is less than ten tons per year.
- 2.b The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the particulate emissions (PE) or particulate emissions 10 microns and less in diameter (PM10) from this air contaminant source because the calculated annual emission rate for PE and PM10 is less than ten tons per year, taking into account the voluntary restrictions accepted by the permittee and the use of a wet scrubber as an air pollution control installed on the source.
- 2.c The visible particulate emissions from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.
- 2.d The PE from the outlet of the scrubber controlling emissions units P005, P006, P007, P008, P009, P010, P011 and P012, combined shall not exceed 13.3 pounds per hour, based on Figure 2 in OAC rule 3745-17-11(B).
- 2.e The visible particulate emissions from any fugitive dust source shall not exceed

Issued: 12/21/2006

20 percent opacity, as a three-minute average.

B. Operational Restrictions

1. This emissions unit shall be operated with a Venturi wet scrubber having an overall control efficiency for particulate matter emissions of at least 81 percent .
2. The total dry material usage in emissions units P005, P006, P007, P008, P009, P010, P011 and P012 combined shall not exceed 6,055,235 pounds per year.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information each month:

the amount, in pounds, of all dry material employed in emissions units P005, P006, P007, P008, P009, P010, P011 and P012 combined.
2. The permittee shall properly install, operate, and maintain equipment to continuously monitor and record the scrubber pressure drop during operation of this emissions unit, including periods of startup and shutdown. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the scrubber pressure drop on daily basis.

Whenever the monitored value for the scrubber pressure drop deviates from the range specified below, the permittee shall promptly investigate the cause of the deviation. The permittee shall maintain records of the following information for each investigation: the date and time the deviation began and the magnitude of the deviation at that time, the date(s) the investigation was conducted, the names of the personnel who conducted the investigation, and the findings and recommendations.

In response to each required investigation to determine the cause of a deviation, the permittee shall take prompt corrective action to bring the operation of the control equipment within the acceptable range specified below, unless the permittee determines that corrective action is not necessary and documents the reasons for that determination and the date and time the deviation ended. The permittee shall maintain records of the following information for each corrective action taken: a description of the corrective action, the date it was completed, the date and time the deviation ended, the total period of time (in minutes) during which there was a deviation, the pressure

Emissions Unit ID: **P008**

drop reading immediately after the corrective action, and the names of the personnel who performed the work. Investigation and records required by this paragraph does not eliminate the need to comply with the requirements of OAC rule 3745-15-06 if it is determined that a malfunction has occurred.

The acceptable range for the pressure drop across the scrubber shall be based upon the manufacturer's specifications until such time as any required emissions testing is conducted.

D. Reporting Requirements

1. The permittee shall submit annual reports which summarize the following for this emissions unit:

the amount, in pounds, of dry materials employed in emissions units P005, P006, P007, P008, P009, P010, P011 and P012 combined for the previous calendar year; and

the total particulate emissions in tons per year from emissions units P005, P006, P007, P008, P009, P010, P011 and P012, combined for the previous calendar year.

The reports shall be submitted by January 31 of each year.

2. The permittee shall submit quarterly reports that identify the following information concerning the operation of the control equipment during the operation of this emissions unit:
 - a. each period of time when the pressure drop across the scrubber was outside of the range specified by the manufacturer;
 - b. an identification of each incident of deviation described in (a) where a prompt investigation was not conducted;
 - c. an identification of each incident of deviation described in (a) where prompt corrective action, that would bring the pressure drop into compliance with the acceptable range, was determined to be necessary and was not taken; and
 - d. an identification of each incident of deviation described in (a) where proper records were not maintained for the investigation and/or the corrective action.

These quarterly reports shall be submitted (i.e., postmarked) by January 31, April 30, July 31, and October 31 of each year; and each report shall cover the previous

Issued: 12/21/2006

calendar quarter.

E. Testing Requirements

1. The uncontrolled potential to emit of VOC emissions for this emissions unit is based on the following information, as supplied by the facility in PTI application 14-05890 as submitted on October 31, 2006:

maximum liquid solvent capacity in emissions unit P008 is 1,643,488 gallons per year x emissions factor of 6.42E-05 lbs per gallon = 105.5 lbs/year or 0.05 ton per year.

2. Compliance with the emission limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following method:

Emission Limitations:

The PE/PM10 emissions from this emissions unit shall not exceed 9.9 tons per year.

Applicable Compliance Method:

Compliance with the annual emissions limitation for PE/PM10 is determined by calculating the sum of the annual maximum dry material usage rate in tons multiplied by the emissions factor of 20 pounds per ton (from AP-42 Table 6.4-1, 1/95) and multiplied by one minus the capture efficiency (90%) of the wet scrubber and the annual maximum dry material usage rate in tons multiplied by the emissions factor of 20 pounds per ton (from AP-42 Table 6.4-1, 1/95) multiplied by the capture efficiency of the wet scrubber (90%) and multiplied by one minus the control efficiency (90%) of the wet scrubber.

Emissions Limitation:

The PE from the outlet of the scrubber controlling emissions units P005, P006, P007, P008, P009, P010, P011 and P012, combined shall not exceed 13.3 pounds per hour

Applicable Compliance Method

If required, compliance with the hourly PE limitation shall be demonstrated through an emissions source test performed in accordance with the requirements of 40 CFR Part 60, Appendix A, Methods 1 - 5.

Emissions Limitation:

The visible particulate emissions from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.

Emissions Unit ID: P008

Applicable Compliance Method:

Compliance shall be determined through visible emission observations performed in accordance with 40 CFR Part 60, Appendix A, Method 9 and the procedures specified in OAC rule 3745-17-03(B)(1).

Emissions Limitation:

The visible particulate emissions from any fugitive dust source shall not exceed 20 percent opacity, as a three-minute average.

Applicable Compliance Method:

Compliance shall be determined through visible emission observations performed in accordance with 40 CFR Part 60, Appendix A, Method 9 and the procedures specified in OAC rule 3745-17-03(B)(3).

3. Compliance with the annual production limitation in term and condition B.2 shall be demonstrated through the record keeping required in term and condition C.1.

F. Miscellaneous Requirements

1. Modeling to demonstrate compliance with the Ohio EPA's "Air Toxic Policy" was not necessary because the emissions unit's maximum annual emissions for each toxic pollutant will be less than 1.0 ton. OAC Chapter 3745-31 requires a permittee to apply for and obtain a new or modified permit to install prior to making a "modification" as defined by OAC rule 3745-31-01. The permittee is hereby advised that a new permit to install application would be required for an emissions unit if changes in the composition of the materials or use of new materials would cause the emissions of any pollutant that has a listed Threshold Limit Value (TLV), as documented in the most current version of the American Conference of Governmental Industrial Hygienists' (ACGIH's) handbook entitled "TLVs and BEIs" ("Threshold Limit Values for Chemical Substances and Physical Agents, Biological Exposure Indices"), to increase to above 1.0 ton per year.

Issued: 12/21/2006

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (P009) - Blender ABB 05

| Applicable Rules/Requirements | Applicable Emissions Limitations/Control Measures |
|--------------------------------------|--|
| ORC 3704.03(T)(4) | See terms and conditions A.2.a, A.2.b, B.1 and B.2. |
| OAC rule 3745-17-07(A)(1) | See term and condition A.2.c. |
| OAC rule 3745-17-11 | See term and condition A.2.d. |
| OAC rule 3745-17-07(B)(1) | See term and condition A.2.e. |

2. Additional Terms and Conditions

- 2.a The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the volatile organic compound (VOC) emissions from this air contaminant source since the uncontrolled potential to emit for VOC emissions is less than ten tons per year.
- 2.b The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the particulate emissions (PE) or particulate emissions 10 microns and less in diameter (PM10) from this air contaminant source because the calculated annual emission rate for PE and PM10 is less than ten tons per year, taking into account the voluntary restrictions accepted by the permittee and the use of a wet scrubber as an air pollution control installed on the source.
- 2.c The visible particulate emissions from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.
- 2.d The PE from the outlet of the scrubber controlling emissions units P005, P006, P007, P008, P009, P010, P011 and P012, combined shall not exceed 13.3 pounds per hour, based on Figure 2 in OAC rule 3745-17-11(B).

Emissions Unit ID: **P009**

- 2.e** The visible particulate emissions from any fugitive dust source shall not exceed 20 percent opacity, as a three-minute average.

B. Operational Restrictions

1. This emissions unit shall be operated with a Venturi wet scrubber having an overall control efficiency for particulate matter emissions of at least 81 percent .
2. The total dry material usage in emissions units P005, P006, P007, P008, P009, P010, P011 and P012 combined shall not exceed 6,055,235 pounds per year.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information each month:

the amount, in pounds, of all dry material employed in emissions units P005, P006, P007, P008, P009, P010, P011 and P012 combined.
2. The permittee shall properly install, operate, and maintain equipment to continuously monitor and record the scrubber pressure drop during operation of this emissions unit, including periods of startup and shutdown. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the scrubber pressure drop on daily basis.

Whenever the monitored value for the scrubber pressure drop deviates from the range specified below, the permittee shall promptly investigate the cause of the deviation. The permittee shall maintain records of the following information for each investigation: the date and time the deviation began and the magnitude of the deviation at that time, the date(s) the investigation was conducted, the names of the personnel who conducted the investigation, and the findings and recommendations.

In response to each required investigation to determine the cause of a deviation, the permittee shall take prompt corrective action to bring the operation of the control equipment within the acceptable range specified below, unless the permittee determines that corrective action is not necessary and documents the reasons for that determination and the date and time the deviation ended. The permittee shall maintain records of the following information for each corrective action taken: a description of the corrective action, the date it was completed, the date and time the deviation ended, the total period of time (in minutes) during which there was a deviation, the pressure drop reading immediately after the corrective action, and the names of the personnel

Issued: 12/21/2006

who performed the work. Investigation and records required by this paragraph does not eliminate the need to comply with the requirements of OAC rule 3745-15-06 if it is determined that a malfunction has occurred.

The acceptable range for the pressure drop across the scrubber shall be based upon the manufacturer's specifications until such time as any required emissions testing is conducted.

D. Reporting Requirements

1. The permittee shall submit annual reports which summarize the following for this emissions unit:

the amount, in pounds, of dry materials employed in emissions units P005, P006, P007, P008, P009, P010, P011 and P012 combined for the previous calendar year; and

the total particulate emissions in tons per year from emissions units P005, P006, P007, P008, P009, P010, P011 and P012, combined for the previous calendar year.

The reports shall be submitted by January 31 of each year.

2. The permittee shall submit quarterly reports that identify the following information concerning the operation of the control equipment during the operation of this emissions unit:
 - a. each period of time when the pressure drop across the scrubber was outside of the range specified by the manufacturer;
 - b. an identification of each incident of deviation described in (a) where a prompt investigation was not conducted;
 - c. an identification of each incident of deviation described in (a) where prompt corrective action, that would bring the pressure drop into compliance with the acceptable range, was determined to be necessary and was not taken; and
 - d. an identification of each incident of deviation described in (a) where proper records were not maintained for the investigation and/or the corrective action.

These quarterly reports shall be submitted (i.e., postmarked) by January 31, April 30,

Emissions Unit ID: P009

July 31, and October 31 of each year; and each report shall cover the previous calendar quarter.

E. Testing Requirements

1. The uncontrolled potential to emit of VOC emissions for this emissions unit is based on the following information, as supplied by the facility in PTI application 14-05890 as submitted on October 31, 2006:

maximum liquid solvent capacity in emissions unit P009 is 9,860,925 gallons per year x emissions factor of 6.42E-05 lbs per gallon = 633.1 lbs/year or 0.32 ton per year.

2. Compliance with the emission limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following method:

Emission Limitations:

The PE/PM10 emissions from this emissions unit shall not exceed 9.9 tons per year.

Applicable Compliance Method:

Compliance with the annual emissions limitation for PE/PM10 is determined by calculating the sum of the annual maximum dry material usage rate in tons multiplied by the emissions factor of 20 pounds per ton (from AP-42 Table 6.4-1, 1/95) and multiplied by one minus the capture efficiency (90%) of the wet scrubber and the annual maximum dry material usage rate in tons multiplied by the emissions factor of 20 pounds per ton (from AP-42 Table 6.4-1, 1/95) multiplied by the capture efficiency of the wet scrubber (90%) and multiplied by one minus the control efficiency (90%) of the wet scrubber.

Emissions Limitation:

The PE from the outlet of the scrubber controlling emissions units P005, P006, P007, P008, P009, P010, P011 and P012, combined shall not exceed 13.3 pounds per hour

Applicable Compliance Method

If required, compliance with the hourly PE limitation shall be demonstrated through an emissions source test performed in accordance with the requirements of 40 CFR Part 60, Appendix A, Methods 1 - 5.

Emissions Limitation:

The visible particulate emissions from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.

Issued: 12/21/2006

Applicable Compliance Method:

Compliance shall be determined through visible emission observations performed in accordance with 40 CFR Part 60, Appendix A, Method 9 and the procedures specified in OAC rule 3745-17-03(B)(1).

Emissions Limitation:

The visible particulate emissions from any fugitive dust source shall not exceed 20 percent opacity, as a three-minute average.

Applicable Compliance Method:

Compliance shall be determined through visible emission observations performed in accordance with 40 CFR Part 60, Appendix A, Method 9 and the procedures specified in OAC rule 3745-17-03(B)(3).

3. Compliance with the annual production limitation in term and condition B.2 shall be demonstrated through the record keeping required in term and condition C.1.

F. Miscellaneous Requirements

1. Modeling to demonstrate compliance with the Ohio EPA's "Air Toxic Policy" was not necessary because the emissions unit's maximum annual emissions for each toxic pollutant will be less than 1.0 ton. OAC Chapter 3745-31 requires a permittee to apply for and obtain a new or modified permit to install prior to making a "modification" as defined by OAC rule 3745-31-01. The permittee is hereby advised that a new permit to install application would be required for an emissions unit if changes in the composition of the materials or use of new materials would cause the emissions of any pollutant that has a listed Threshold Limit Value (TLV), as documented in the most current version of the American Conference of Governmental Industrial Hygienists' (ACGIH's) handbook entitled "TLVs and BEIs" ("Threshold Limit Values for Chemical Substances and Physical Agents, Biological Exposure Indices"), to increase to above 1.0 ton per year.

Issued: 12/21/2006

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (P010) - Blender ABB 06

| Applicable Rules/Requirements | Applicable Emissions Limitations/Control Measures |
|--------------------------------------|--|
| ORC 3704.03(T)(4) | See terms and conditions A.2.a, A.2.b, B.1 and B.2. |
| OAC rule 3745-17-07(A)(1) | See term and condition A.2.c. |
| OAC rule 3745-17-11 | See term and condition A.2.d. |
| OAC rule 3745-17-07(B)(1) | See term and condition A.2.e. |

2. Additional Terms and Conditions

- 2.a The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the volatile organic compound (VOC) emissions from this air contaminant source since the uncontrolled potential to emit for VOC emissions is less than ten tons per year.
- 2.b The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the particulate emissions (PE) or particulate emissions 10 microns and less in diameter (PM10) from this air contaminant source because the calculated annual emission rate for PE and PM10 is less than ten tons per year, taking into account the voluntary restrictions accepted by the permittee and the use of a wet scrubber as an air pollution control installed on the source.
- 2.c The visible particulate emissions from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.
- 2.d The PE from the outlet of the scrubber controlling emissions units P005, P006, P007, P008, P009, P010, P011 and P012, combined shall not exceed 13.3 pounds per hour, based on Figure 2 in OAC rule 3745-17-11(B).

Emissions Unit ID: P010

- 2.e The visible particulate emissions from any fugitive dust source shall not exceed 20 percent opacity, as a three-minute average.

B. Operational Restrictions

1. This emissions unit shall be operated with a Venturi wet scrubber having an overall control efficiency for particulate matter emissions of at least 81 percent .
2. The total dry material usage in emissions units P005, P006, P007, P008, P009, P010, P011 and P012 combined shall not exceed 6,055,235 pounds per year.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information each month:

the amount, in pounds, of all dry material employed in emissions units P005, P006, P007, P008, P009, P010, P011 and P012 combined.
2. The permittee shall properly install, operate, and maintain equipment to continuously monitor and record the scrubber pressure drop during operation of this emissions unit, including periods of startup and shutdown. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the scrubber pressure drop on daily basis.

Whenever the monitored value for the scrubber pressure drop deviates from the range specified below, the permittee shall promptly investigate the cause of the deviation. The permittee shall maintain records of the following information for each investigation: the date and time the deviation began and the magnitude of the deviation at that time, the date(s) the investigation was conducted, the names of the personnel who conducted the investigation, and the findings and recommendations.

In response to each required investigation to determine the cause of a deviation, the permittee shall take prompt corrective action to bring the operation of the control equipment within the acceptable range specified below, unless the permittee determines that corrective action is not necessary and documents the reasons for that determination and the date and time the deviation ended. The permittee shall maintain records of the following information for each corrective action taken: a description of the corrective action, the date it was completed, the date and time the deviation ended, the total period of time (in minutes) during which there was a deviation, the pressure drop reading immediately after the corrective action, and the names of the personnel

Issued: 12/21/2006

who performed the work. Investigation and records required by this paragraph does not eliminate the need to comply with the requirements of OAC rule 3745-15-06 if it is determined that a malfunction has occurred.

The acceptable range for the pressure drop across the scrubber shall be based upon the manufacturer's specifications until such time as any required emissions testing is conducted.

D. Reporting Requirements

1. The permittee shall submit annual reports which summarize the following for this emissions unit:

the amount, in pounds, of dry materials employed in emissions units P005, P006, P007, P008, P009, P010, P011 and P012 combined for the previous calendar year; and

the total particulate emissions in tons per year from emissions units P005, P006, P007, P008, P009, P010, P011 and P012, combined for the previous calendar year.

The reports shall be submitted by January 31 of each year.

2. The permittee shall submit quarterly reports that identify the following information concerning the operation of the control equipment during the operation of this emissions unit:
 - a. each period of time when the pressure drop across the scrubber was outside of the range specified by the manufacturer;
 - b. an identification of each incident of deviation described in (a) where a prompt investigation was not conducted;
 - c. an identification of each incident of deviation described in (a) where prompt corrective action, that would bring the pressure drop into compliance with the acceptable range, was determined to be necessary and was not taken; and
 - d. an identification of each incident of deviation described in (a) where proper records were not maintained for the investigation and/or the corrective action.

These quarterly reports shall be submitted (i.e., postmarked) by January 31, April 30,

Emissions Unit ID: **P010**

July 31, and October 31 of each year; and each report shall cover the previous calendar quarter.

E. Testing Requirements

1. The uncontrolled potential to emit of VOC emissions for this emissions unit is based on the following information, as supplied by the facility in PTI application 14-05890 as submitted on October 31, 2006:

maximum liquid solvent capacity in emissions unit P005 is 6,573,950 gallons per year x emissions factor of 6.42E-05 lbs per gallon = 422.1 lbs/year or 0.21 ton per year.

2. Compliance with the emission limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following method:

Emission Limitations:

The PE/PM10 emissions from this emissions unit shall not exceed 9.9 tons per year.

Applicable Compliance Method:

Compliance with the annual emissions limitation for PE/PM10 is determined by calculating the sum of the annual maximum dry material usage rate in tons multiplied by the emissions factor of 20 pounds per ton (from AP-42 Table 6.4-1, 1/95) and multiplied by one minus the capture efficiency (90%) of the wet scrubber and the annual maximum dry material usage rate in tons multiplied by the emissions factor of 20 pounds per ton (from AP-42 Table 6.4-1, 1/95) multiplied by the capture efficiency of the wet scrubber (90%) and multiplied by one minus the control efficiency (90%) of the wet scrubber.

Emissions Limitation:

The PE from the outlet of the scrubber controlling emissions units P005, P006, P007, P008, P009, P010, P011 and P012, combined shall not exceed 13.3 pounds per hour

Applicable Compliance Method

If required, compliance with the hourly PE limitation shall be demonstrated through an emissions source test performed in accordance with the requirements of 40 CFR Part 60, Appendix A, Methods 1 - 5.

Emissions Limitation:

The visible particulate emissions from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.

Issued: 12/21/2006

Applicable Compliance Method:

Compliance shall be determined through visible emission observations performed in accordance with 40 CFR Part 60, Appendix A, Method 9 and the procedures specified in OAC rule 3745-17-03(B)(1).

Emissions Limitation:

The visible particulate emissions from any fugitive dust source shall not exceed 20 percent opacity, as a three-minute average.

Applicable Compliance Method:

Compliance shall be determined through visible emission observations performed in accordance with 40 CFR Part 60, Appendix A, Method 9 and the procedures specified in OAC rule 3745-17-03(B)(3).

3. Compliance with the annual production limitation in term and condition B.2 shall be demonstrated through the record keeping required in term and condition C.1.

F. Miscellaneous Requirements

1. Modeling to demonstrate compliance with the Ohio EPA's "Air Toxic Policy" was not necessary because the emissions unit's maximum annual emissions for each toxic pollutant will be less than 1.0 ton. OAC Chapter 3745-31 requires a permittee to apply for and obtain a new or modified permit to install prior to making a "modification" as defined by OAC rule 3745-31-01. The permittee is hereby advised that a new permit to install application would be required for an emissions unit if changes in the composition of the materials or use of new materials would cause the emissions of any pollutant that has a listed Threshold Limit Value (TLV), as documented in the most current version of the American Conference of Governmental Industrial Hygienists' (ACGIH's) handbook entitled "TLVs and BEIs" ("Threshold Limit Values for Chemical Substances and Physical Agents, Biological Exposure Indices"), to increase to above 1.0 ton per year.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (P011) - Blender ABB 07

| Applicable Rules/Requirements | Applicable Emissions Limitations/Control Measures |
|-------------------------------|---|
| ORC 3704.03(T)(4) | See terms and conditions A.2.a, A.2.b, B.1 and B.2. |
| OAC rule 3745-17-07(A)(1) | See term and condition A.2.c. |
| OAC rule 3745-17-11 | See term and condition A.2.d. |
| OAC rule 3745-17-07(B)(1) | See term and condition A.2.e. |

2. Additional Terms and Conditions

- 2.a The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the volatile organic compound (VOC) emissions from this air contaminant source since the uncontrolled potential to emit for VOC emissions is less than ten tons per year.
- 2.b The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the particulate emissions (PE) or particulate emissions 10 microns and less in diameter (PM10) from this air contaminant source because the calculated annual emission rate for PE and PM10 is less than ten tons per year, taking into account the voluntary restrictions accepted by the permittee and the use of a wet scrubber as an air pollution control installed on the source.
- 2.c The visible particulate emissions from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.
- 2.d The PE from the outlet of the scrubber controlling emissions units P005, P006, P007, P008, P009, P010, P011 and P012, combined shall not exceed 13.3 pounds per hour, based on Figure 2 in OAC rule 3745-17-11(B).
- 2.e The visible particulate emissions from any fugitive dust source shall not exceed

Issued: 12/21/2006

20 percent opacity, as a three-minute average.

B. Operational Restrictions

1. This emissions unit shall be operated with a Venturi wet scrubber having an overall control efficiency for particulate matter emissions of at least 81 percent .
2. The total dry material usage in emissions units P005, P006, P007, P008, P009, P010, P011 and P012 combined shall not exceed 6,055,235 pounds per year.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information each month:

the amount, in pounds, of all dry material employed in emissions units P005, P006, P007, P008, P009, P010, P011 and P012 combined.
2. The permittee shall properly install, operate, and maintain equipment to continuously monitor and record the scrubber pressure drop during operation of this emissions unit, including periods of startup and shutdown. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the scrubber pressure drop on daily basis.

Whenever the monitored value for the scrubber pressure drop deviates from the range specified below, the permittee shall promptly investigate the cause of the deviation. The permittee shall maintain records of the following information for each investigation: the date and time the deviation began and the magnitude of the deviation at that time, the date(s) the investigation was conducted, the names of the personnel who conducted the investigation, and the findings and recommendations.

In response to each required investigation to determine the cause of a deviation, the permittee shall take prompt corrective action to bring the operation of the control equipment within the acceptable range specified below, unless the permittee determines that corrective action is not necessary and documents the reasons for that determination and the date and time the deviation ended. The permittee shall maintain records of the following information for each corrective action taken: a description of the corrective action, the date it was completed, the date and time the deviation ended, the total period of time (in minutes) during which there was a deviation, the pressure

Emissions Unit ID: **P011**

drop reading immediately after the corrective action, and the names of the personnel who performed the work. Investigation and records required by this paragraph does not eliminate the need to comply with the requirements of OAC rule 3745-15-06 if it is determined that a malfunction has occurred.

The acceptable range for the pressure drop across the scrubber shall be based upon the manufacturer's specifications until such time as any required emissions testing is conducted.

D. Reporting Requirements

1. The permittee shall submit annual reports which summarize the following for this emissions unit:

the amount, in pounds, of dry materials employed in emissions units P005, P006, P007, P008, P009, P010, P011 and P012 combined for the previous calendar year; and

the total particulate emissions in tons per year from emissions units P005, P006, P007, P008, P009, P010, P011 and P012, combined for the previous calendar year.

The reports shall be submitted by January 31 of each year.

2. The permittee shall submit quarterly reports that identify the following information concerning the operation of the control equipment during the operation of this emissions unit:
 - a. each period of time when the pressure drop across the scrubber was outside of the range specified by the manufacturer;
 - b. an identification of each incident of deviation described in (a) where a prompt investigation was not conducted;
 - c. an identification of each incident of deviation described in (a) where prompt corrective action, that would bring the pressure drop into compliance with the acceptable range, was determined to be necessary and was not taken; and
 - d. an identification of each incident of deviation described in (a) where proper records were not maintained for the investigation and/or the corrective action.

These quarterly reports shall be submitted (i.e., postmarked) by January 31, April 30, July 31, and October 31 of each year; and each report shall cover the previous

Issued: 12/21/2006

calendar quarter.

E. Testing Requirements

1. The uncontrolled potential to emit of VOC emissions for this emissions unit is based on the following information, as supplied by the facility in PTI application 14-05890 as submitted on October 31, 2006:

maximum liquid solvent capacity in emissions unit P005 is 6,573,950 gallons per year x emissions factor of 6.42E-05 lbs per gallon = 422.1 lbs/year or 0.21 ton per year.

2. Compliance with the emission limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following method:

Emission Limitations:

The PE/PM10 emissions from this emissions unit shall not exceed 9.9 tons per year.

Applicable Compliance Method:

Compliance with the annual emissions limitation for PE/PM10 is determined by calculating the sum of the annual maximum dry material usage rate in tons multiplied by the emissions factor of 20 pounds per ton (from AP-42 Table 6.4-1, 1/95) and multiplied by one minus the capture efficiency (90%) of the wet scrubber and the annual maximum dry material usage rate in tons multiplied by the emissions factor of 20 pounds per ton (from AP-42 Table 6.4-1, 1/95) multiplied by the capture efficiency of the wet scrubber (90%) and multiplied by one minus the control efficiency (90%) of the wet scrubber.

Emissions Limitation:

The PE from the outlet of the scrubber controlling emissions units P005, P006, P007, P008, P009, P010, P011 and P012, combined shall not exceed 13.3 pounds per hour

Applicable Compliance Method

If required, compliance with the hourly PE limitation shall be demonstrated through an emissions source test performed in accordance with the requirements of 40 CFR Part 60, Appendix A, Methods 1 - 5.

Emissions Limitation:

The visible particulate emissions from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.

Emissions Unit ID: P011

Applicable Compliance Method:

Compliance shall be determined through visible emission observations performed in accordance with 40 CFR Part 60, Appendix A, Method 9 and the procedures specified in OAC rule 3745-17-03(B)(1).

Emissions Limitation:

The visible particulate emissions from any fugitive dust source shall not exceed 20 percent opacity, as a three-minute average.

Applicable Compliance Method:

Compliance shall be determined through visible emission observations performed in accordance with 40 CFR Part 60, Appendix A, Method 9 and the procedures specified in OAC rule 3745-17-03(B)(3).

3. Compliance with the annual production limitation in term and condition B.2 shall be demonstrated through the record keeping required in term and condition C.1.

F. Miscellaneous Requirements

1. Modeling to demonstrate compliance with the Ohio EPA's "Air Toxic Policy" was not necessary because the emissions unit's maximum annual emissions for each toxic pollutant will be less than 1.0 ton. OAC Chapter 3745-31 requires a permittee to apply for and obtain a new or modified permit to install prior to making a "modification" as defined by OAC rule 3745-31-01. The permittee is hereby advised that a new permit to install application would be required for an emissions unit if changes in the composition of the materials or use of new materials would cause the emissions of any pollutant that has a listed Threshold Limit Value (TLV), as documented in the most current version of the American Conference of Governmental Industrial Hygienists' (ACGIH's) handbook entitled "TLVs and BEIs" ("Threshold Limit Values for Chemical Substances and Physical Agents, Biological Exposure Indices"), to increase to above 1.0 ton per year.

Issued: 12/21/2006

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (P012) - Blender ABB 08

| Applicable Rules/Requirements | Applicable Emissions Limitations/Control Measures |
|--------------------------------------|--|
| ORC 3704.03(T)(4) | See terms and conditions A.2.a, A.2.b, B.1 and B.2. |
| OAC rule 3745-17-07(A)(1) | See term and condition A.2.c. |
| OAC rule 3745-17-11 | See term and condition A.2.d. |
| OAC rule 3745-31-02(A)(2) | See terms and conditions A.2.e, B.1 and B.2. |
| OAC rule 3745-17-07(B)(1) | See term and condition A.2.e. |

2. Additional Terms and Conditions

- 2.a The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the volatile organic compound (VOC) emissions from this air contaminant source since the uncontrolled potential to emit for VOC emissions is less than ten tons per year.
- 2.b The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the particulate emissions (PE) or particulate emissions 10 microns and less in diameter (PM10) from this air contaminant source because the calculated annual emission rate for PE and PM10 is less than ten tons per year, taking into account the voluntary restrictions accepted by the permittee and the use of a wet scrubber as an air pollution control installed on the source.
- 2.c The visible particulate emissions from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.
- 2.d The PE from the outlet of the scrubber controlling emissions units P005, P006, P007, P008, P009, P010, P011 and P012, combined shall not exceed 13.3 pounds per hour, based on Figure 2 in OAC rule 3745-17-11(B).

- 2.e The visible particulate emissions from any fugitive dust source shall not exceed 20 percent opacity, as a three-minute average.

B. Operational Restrictions

1. This emissions unit shall be operated with a Venturi wet scrubber having an overall control efficiency for particulate matter emissions of at least 81 percent .
2. The total dry material usage in emissions units P005, P006, P007, P008, P009, P010, P011 and P012 combined shall not exceed 6,055,235 pounds per year.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information each month:

the amount, in pounds, of all dry material employed in emissions units P005, P006, P007, P008, P009, P010, P011 and P012 combined.
2. The permittee shall properly install, operate, and maintain equipment to continuously monitor and record the scrubber pressure drop during operation of this emissions unit, including periods of startup and shutdown. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the scrubber pressure drop on daily basis.

Whenever the monitored value for the scrubber pressure drop deviates from the range specified below, the permittee shall promptly investigate the cause of the deviation. The permittee shall maintain records of the following information for each investigation: the date and time the deviation began and the magnitude of the deviation at that time, the date(s) the investigation was conducted, the names of the personnel who conducted the investigation, and the findings and recommendations.

In response to each required investigation to determine the cause of a deviation, the permittee shall take prompt corrective action to bring the operation of the control equipment within the acceptable range specified below, unless the permittee determines that corrective action is not necessary and documents the reasons for that determination and the date and time the deviation ended. The permittee shall maintain records of the following information for each corrective action taken: a description of the corrective action, the date it was completed, the date and time the deviation ended,

Issued: 12/21/2006

the total period of time (in minutes) during which there was a deviation, the pressure drop reading immediately after the corrective action, and the names of the personnel who performed the work. Investigation and records required by this paragraph does not eliminate the need to comply with the requirements of OAC rule 3745-15-06 if it is determined that a malfunction has occurred.

The acceptable range for the pressure drop across the scrubber shall be based upon the manufacturer's specifications until such time as any required emissions testing is conducted.

D. Reporting Requirements

1. The permittee shall submit annual reports which summarize the following for this emissions unit:

the amount, in pounds, of dry materials employed in emissions units P005, P006, P007, P008, P009, P010, P011 and P012 combined for the previous calendar year; and

the total particulate emissions in tons per year from emissions units P005, P006, P007, P008, P009, P010, P011 and P012, combined for the previous calendar year.

The reports shall be submitted by January 31 of each year.

2. The permittee shall submit quarterly reports that identify the following information concerning the operation of the control equipment during the operation of this emissions unit:
 - a. each period of time when the pressure drop across the scrubber was outside of the range specified by the manufacturer;
 - b. an identification of each incident of deviation described in (a) where a prompt investigation was not conducted;
 - c. an identification of each incident of deviation described in (a) where prompt corrective action, that would bring the pressure drop into compliance with the acceptable range, was determined to be necessary and was not taken; and
 - d. an identification of each incident of deviation described in (a) where proper records were not maintained for the investigation and/or the corrective action.

Emissions Unit ID: P012

These quarterly reports shall be submitted (i.e., postmarked) by January 31, April 30, July 31, and October 31 of each year; and each report shall cover the previous calendar quarter.

E. Testing Requirements

1. The uncontrolled potential to emit of VOC emissions for this emissions unit is based on the following information, as supplied by the facility in PTI application 14-05890 as submitted on October 31, 2006:

maximum liquid solvent capacity in emissions unit P005 is 6,573,950 gallons per year x emissions factor of 6.42E-05 lbs per gallon = 422.1 lbs/year or 0.21 ton per year.

2. Compliance with the emission limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following method:

Emission Limitations:

The PE/PM10 emissions from this emissions unit shall not exceed 9.9 tons per year.

Applicable Compliance Method:

Compliance with the annual emissions limitation for PE/PM10 is determined by calculating the sum of the annual maximum dry material usage rate in tons multiplied by the emissions factor of 20 pounds per ton (from AP-42 Table 6.4-1, 1/95) and multiplied by one minus the capture efficiency (90%) of the wet scrubber and the annual maximum dry material usage rate in tons multiplied by the emissions factor of 20 pounds per ton (from AP-42 Table 6.4-1, 1/95) multiplied by the capture efficiency of the wet scrubber (90%) and multiplied by one minus the control efficiency (90%) of the wet scrubber.

Emissions Limitation:

The PE from the outlet of the scrubber controlling emissions units P005, P006, P007, P008, P009, P010, P011 and P012, combined shall not exceed 13.3 pounds per hour

Applicable Compliance Method

If required, compliance with the hourly PE limitation shall be demonstrated through an emissions source test performed in accordance with the requirements of 40 CFR Part 60, Appendix A, Methods 1 - 5.

Emissions Limitation:

The visible particulate emissions from any stack shall not exceed 20 percent opacity,

Issued: 12/21/2006

as a six-minute average, except as specified by rule.

Applicable Compliance Method:

Compliance shall be determined through visible emission observations performed in accordance with 40 CFR Part 60, Appendix A, Method 9 and the procedures specified in OAC rule 3745-17-03(B)(1).

Emissions Limitation:

The visible particulate emissions from any fugitive dust source shall not exceed 20 percent opacity, as a three-minute average.

Applicable Compliance Method:

Compliance shall be determined through visible emission observations performed in accordance with 40 CFR Part 60, Appendix A, Method 9 and the procedures specified in OAC rule 3745-17-03(B)(3).

3. Compliance with the annual production limitation in term and condition B.2 shall be demonstrated through the record keeping required in term and condition C.1.

F. Miscellaneous Requirements

1. Modeling to demonstrate compliance with the Ohio EPA's "Air Toxic Policy" was not necessary because the emissions unit's maximum annual emissions for each toxic pollutant will be less than 1.0 ton. OAC Chapter 3745-31 requires a permittee to apply for and obtain a new or modified permit to install prior to making a "modification" as defined by OAC rule 3745-31-01. The permittee is hereby advised that a new permit to install application would be required for an emissions unit if changes in the composition of the materials or use of new materials would cause the emissions of any pollutant that has a listed Threshold Limit Value (TLV), as documented in the most current version of the American Conference of Governmental Industrial Hygienists' (ACGIH's) handbook entitled "TLVs and BEIs" ("Threshold Limit Values for Chemical Substances and Physical Agents, Biological Exposure Indices"), to increase to above 1.0 ton per year.