

Facility ID: 0857101349 Issuance type: Title V Final Permit

This version of facility specific terms and conditions was converted from a database format to an HTML file during an upgrade of the Ohio EPA, Division of Air Pollution Control's permitting software. Every attempt has been made to convert the terms and conditions to look and substantively conform to the permit issued or being drafted in STARS. However, the format of the terms may vary slightly from the original. In addition, although it is not expected, there is a slight possibility that a term and condition may have been inadvertently "left out" of this reproduction during the conversion process. Therefore, if this version is to be used as a starting point in drafting a new version of a permit, it is imperative that the entire set of terms and conditions be reviewed to ensure they substantively mimic the issued permit. The official version of any permit issued final by Ohio EPA is kept in the Agency's Legal section. The Legal section may be contacted at (614) 644-3037.

In addition to the terms and conditions, hyperlinks have been inserted into the document so you may more readily access the section of the document you wish to review.

Finally, the term language under "Part III" and before "I. Applicable Emissions Limitations..." has been added to aid in document conversion, and was not part of the original issued permit.

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0857101349 Issuance type: Title V Final Permit

Part II - Specific Facility Terms and Conditions

a State and Federally Enforceable Section

1. Operation Restrictions-

- a. The maximum annual number of production days of operation for this facility shall not exceed 300, based upon a rolling, 12-month summation of the number of days of operation each month (except for final repair, emissions unit K025).
- b. The maximum annual production rate for this facility shall not exceed 348,000 vehicles, based upon a rolling, 12-month summation of the vehicle production rate each month.

2. Monitoring and/or Record Keeping Requirements-

The permittee shall maintain the following information each month for the facility:

- a. The number of vehicles produced.
- b. The rolling, 12-month summation of the vehicle production rates.
- c. The number of days of operation.
- d. The rolling, 12-month summation of the numbers of days of operation.

3. Reporting Requirements-

The permittee shall submit quarterly deviation(excursion) reports that identify the following:

- a. all exceedances of the number of days of operation restriction of 300 (except final repair); and
 - b. all exceedances of the vehicle production rate restriction of 348,000.
- These quarterly deviation reports are due by the dates specified in Part I- General Terms and Conditions of this permit under Section A.1.c.

4. The permittee may be subject to the National Emission Standards for Hazardous Air Pollutants (NESHAP) for Auto & Light Duty Truck (surface coating, 40 CFR Part 63, Subpart IIII). U.S. EPA failed to promulgate this standard by May 15, 2002, the Maximum Achievable Control Technology (MACT) hammer date. In accordance with 40 CFR Part 63, Subpart B (40 CFR Parts 63.50 through 63.56), the permittee shall submit an application to revise the permit to include equivalent emission limitations as a result of a case-by-case MACT determination. The application shall be submitted in two parts. The deadline to submit the Part I application, as specified in 40 CFR Part 63.53, was May 15, 2002.

5. If the final NESHAP standard is not promulgated by the deadline specified by U.S. EPA, the permittee shall submit the Part II application as specified in 40 CFR Part 63.53. The Part II application shall be submitted within 60 days after the deadline to promulgate the respective standard or by May 15, 2003, whichever is later. It must contain the following information, unless otherwise specified by future U.S. EPA regulations:

- a. for a new affected source, the anticipated date of startup of operation;
 - b. the hazardous air pollutants (HAPs) emitted by each affected source in the relevant source category and an estimated total uncontrolled and controlled emission rate for HAPs from the affected source;
 - c. any existing federal, State, or local limitations or requirements applicable to the affected source;
 - d. for each affected emission point or group of affected emission points, an identification of control technology in place;
 - e. information relevant to establishing the MACT floor (or MACT emission limitation), and, at the option of the permittee, a recommended MACT floor; and
 - f. any other information reasonably needed by the permitting authority including, at the discretion of the permitting authority, information required pursuant to Subpart A of 40 CFR Part 63.
- The Part II application for a MACT determination may, but is not required to, contain the following

information:

- a. recommended emission limitations for the affected source and support information (the permittee may recommend a specific design, equipment, work practice, or operational standard, or combination thereof, as an emission limitation);
 - b. a description of the control technologies that would be applied to meet the emission limitation, including technical information on the design, operation, size, estimated control efficiency and any other information deemed appropriate by the permitting authority, and identification of the affected sources to which the control technologies must be applied; and
 - c. relevant parameters to be monitored and frequency of monitoring to demonstrate continuous compliance with the MACT emission limitation over the applicable reporting period.
6. If the NESHAP is promulgated before the Part II application is due for the relevant source category, the permittee may be subject to the rule as an existing major source with a compliance date as specified in the NESHAP. If subject, the permittee shall submit the following notifications:
- a. Unless otherwise specified in the relevant Subpart, within 120 days after promulgation of a 40 CFR Part 63 Subpart to which the source is subject, the permittee shall submit an Initial Notification Report that contains the following information, in accordance with 40 CFR Part 63.9(b)(2):
 - i. the name and mailing address of the permittee;
 - ii. the physical location of the source if it is different from the mailing address;
 - iii. identification of the relevant MACT standard and the source's compliance date;
 - iv. a brief description of the nature, design, size, and method of operation of the source, and an identification of the types of emission points within the affected source subject to the relevant standard and the types of HAPs emitted; and
 - v. a statement confirming the facility is a major source for HAPs.
 - b. Unless otherwise specified in the relevant Subpart, within 60 days following completion of any required compliance demonstration activity specified in the relevant Subpart, the permittee shall submit a notification of compliance status that contains the following information:
 - i. the methods used to determine compliance;
 - ii. the results of any performance tests, visible emission observations, continuous monitoring systems performance evaluations, and/or other monitoring procedures or methods that were conducted;
 - iii. the methods that will be used for determining continuous compliance, including a description of monitoring and reporting requirements and test methods;
 - iv. the type and quantity of HAPs emitted by the source, reported in units and averaging times in accordance with the test methods specified in the relevant Subpart;
 - v. an analysis demonstrating whether the affected source is a major source or an area source;
 - vi. a description of the air pollution control equipment or method for each emission point, including each control device or method for each HAP and the control efficiency (percent) for each control device or method; and
 - vii. a statement of whether or not the permittee has complied with the requirements of the relevant Subpart.
7. The permittee has submitted a PTI modification request for this emissions unit to revise the following operational restrictions:
- a. the maximum annual number of production days of operation for this facility: from 300 to 310, based upon a rolling, 12-month summation of the number of days of operation each month (except for final repair, emissions unit K025); and
 - b. the maximum annual production rate for this facility: from 348,000 to 384,400 vehicles, based upon a rolling, 12-month summation of the monthly vehicle production rates.
- The PTI modification request was submitted on December 9, 2002. Upon the effective date of the PTI modification(s), the permittee shall comply with the following operational restrictions:
- a. the maximum annual number of production days of operation for this facility shall not exceed 310, based upon a rolling, 12-month summation of the number of days of operation each month (except for final repair, emissions unit K025); and
 - b. the maximum annual production rate for this facility shall not exceed 384,400 vehicles, based upon a rolling, 12-month summation of the monthly vehicle production rates.

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0857101349 Issuance type: Title V Final Permit

b State Only Enforceable Section

- 1. The following insignificant emission units are located at this facility:
 - P001- EDP sanding booth

- P002- Guidecoat and minor topcoat sanding booth
- P003- Topcoat Sanding Booth
- P004- Final repair sanding
- T006- Tank #6 engine oil
- T007- Tank #7 auto transmission fluid
- T008- Tank #8 anti-freeze
- T009- Tank #9 anti-freeze
- T010- tank #10 windshield washer solvent
- T011- Tank #11 axle lube
- T012- Tank #12 power steering fluid
- T013- Tank #13 diesel fuel
- Z010- Roll Test
- Z011- Laboratory equipment and laboratory fume hoods
- Z012- Compression and Injection plastic molding equipment
- Z013- Non-continuous solvent recycling units
- Z014- Solvent cold cleaners
- Z015- Grinding, machining and abrasive pneumatic conveying
- Z016- Maintenance welding
- Z017- Arc welding
- Z018- Resistance spot welding
- Z019- Multi-stage phosphate system
- Z020- Feather dusters
- Z021- Vehicle washers prior to shipping
- Z022- Bulk storage material transferring equipment
- Z023- Emergency diesel generators
- Z024- High pressure water cleaning equipment
- Z025- Vehicle fluid fill operations
- Z026- Miscellaneous aerosol spray cans
- Z027- Mechanical repair stalls
- Z028- Mobile equipment battery charging areas
- Z029- Engine subassembly line
- Z030- Radiator subassembly line
- Z031- Trim assembly line
- Z032- Gasoline tank assembly area
- Z033- Material storage
- Z034- Paint pump repair shop
- Z035- Wet/dry sanding booths
- Z036- Leak test areas
- Z037- Parts washer and rinse tanks using detergent cleaners
- Z038- Storage tanks for inorganic liquids including water
- Z039- Pressurized storage tanks for propane, butane and LPG
- Z040- Storage tanks for liquids(<700 gallons)
- Z041- Cleanup activities-onsite removal or removal action
- Z042- Maintenance of interior/exterior building structures
- Z043- Gasoline dispensing facilities
- Z044- Pre-washers
- Z045- Spot sanding and painting

Each insignificant emissions unit at this facility must comply with all applicable State and Federal regulations, as well as any emission limitations and/or control requirements contained within a Permit to Install for the emissions unit.

- [Go to Part III for Emissions Unit B001](#)
- [Go to Part III for Emissions Unit G001](#)
- [Go to Part III for Emissions Unit K020](#)
- [Go to Part III for Emissions Unit K022](#)
- [Go to Part III for Emissions Unit K023](#)
- [Go to Part III for Emissions Unit K025](#)
- [Go to Part III for Emissions Unit K027](#)
- [Go to Part III for Emissions Unit K028](#)
- [Go to Part III for Emissions Unit K029](#)
- [Go to Part III for Emissions Unit K031](#)
- [Go to Part III for Emissions Unit K034](#)
- [Go to Part III for Emissions Unit K035](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0857101349 Issuance type: Title V Final Permit

Part III - Terms and Conditions for Emissions Units

[Go to the top of this document](#)

Facility ID: 0857101349 Emissions Unit ID: B001 Issuance type: Title V Final Permit

A. State and Federally Enforceable Section

The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

1. None.

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Facility-wide, natural gas combustion (excluding ELPO Unit K029)	OAC rule 3745-31-05(A)(3) PTI #08-2506	The requirements of this rule also include compliance with the requirements of OAC rules 3745-17-10(B)(1), 3745-18-06(A), 3745-18-06(E), 3745-21-08(B), and 3745-23-06(B) and 40 CFR, Part 52.21. 17.0 tons/yr particulate emissions (PE)* 71.40 tons/yr carbon monoxide (CO)* 4.68 tons/yr volatile organic compounds (VOC)* *The annual emission limitation is based upon a rolling, 12-month summation. 135.58 tons/yr nitrogen oxides (NOx)* *The annual emission limitation is based upon a rolling, 12-month summation.
	40 CFR, Part 52.21	
	OAC rule 3745-17-10(B)(1) OAC rule 3745-17-07(A)	See A.I.2.a. Visible emissions shall not exceed 20% opacity, as a 6-minute average, except as provided by rule.
	OAC rule 3745-17-11(B)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3) [see A.I.2.b].
	OAC rule 3745-18-06 (A) OAC rule 3745-18-06 (E)	See A.I.2.d. exempt, pursuant to OAC rule 3745-18-06(C) (See A.I.2.c.)
	OAC rules 3745-21-08(B) and 3745-23-06(B)	See A.I.2.e.

2. Additional Terms and Conditions

- a. "Fuel burning equipment" as defined under OAC rule 3745-17-01(B)(5) are subject to an allowable particulate emission rate of 0.020 lb/mmBtu of actual heat input in accordance with OAC rule 3745-17-10(B)(1).

- b. For equipment that combust natural gas, but are not "fuel burning equipment" as defined by OAC rule 3745-17-01(B)(5), gaseous fuels are not considered as part of the process weight for any single, specific process and, therefore, are not included in the process weight rate for determining the allowable particulate emission rate pursuant to Table I of OAC rule 3745-17-11. In addition, the uncontrolled mass rate of particulate emissions from any such piece of equipment are less than 10 lbs/hr. Therefore, pursuant to OAC rule 3745-17-11(A)(2)(a)(ii), Figure II of OAC rule 3745-17-11 does not apply.
- c. There are no sulfur dioxide emission limitations established by OAC Chapter 3745-18 for equipment associated with this emissions unit that are not considered "fuel burning equipment" because the process weight rate is less than 1,000 pounds/hour.
- d. OAC rule 3745-18-06(A) does not establish sulfur dioxide emission limitations for the fuel burning equipment associated with this emissions unit because the emissions unit only employs natural gas as fuel. However, OAC rule 3745-18-06(A) requires that the natural gas being combusted meet certain fuel quality restrictions (a heat content greater than 950 Btu per standard cubic foot and a sulfur content less than 0.6 pound per million standard cubic feet). Because the natural gas being burned in this emissions unit is the standard, pipeline quality natural gas supplied to industrial, commercial, and residential users throughout the State, it is assumed that it meets the fuel quality restrictions; and no monitoring, record keeping or reporting requirements are necessary to ensure ongoing compliance with OAC rule 3745-18-06(A).
- e. The permittee has satisfied the "best available control techniques and operating practices" and "latest available control techniques and operating practices" required pursuant to OAC rules 3745-21-08 and 3745-23-06, respectively by committing to comply with the best available technology requirements established pursuant to OAC rule 3745-31-05(A)(3) in Permit to Install # 08-2506.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

II. Operational Restrictions

- 1. The maximum annual facility-wide natural gas consumption at the Moraine Assembly Plant shall not exceed 1,700 million cubic feet, based upon a rolling, 12-month summation of the monthly natural gas usage rates. This facility-wide natural gas consumption restriction excludes natural gas consumption for emissions unit K029, prime coat (ELPO) line with oven, which replaced emissions unit K021.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

III. Monitoring and/or Record Keeping Requirements

- 1. The permittee shall maintain monthly records of the following information for the facility:
 - a. the natural gas usage rate, in mm cu. ft; and
 - b. the rolling, 12-month summation of the monthly natural gas usage rates, in mm cu. ft.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

IV. Reporting Requirements

- 1. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the rolling, 12-month natural gas usage restriction of 1,700 mm cu. ft. These quarterly deviation reports are due by the dates specified in Part 1- General Terms and Conditions of this permit under Section A.1.c.
- 2. The permittee shall submit annual reports that specify the total facility-wide natural gas consumption (excluding emissions unit K029) for the previous calendar year. These reports shall be submitted by January 31 of each year.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

V. Testing Requirements

- 1. Compliance with the emission limitations in Section A.1. of these terms and conditions shall be determined in accordance with the following methods:
 - a. Emission Limitation -
0.020 lb PE per mmBtu actual heat input

Applicable Compliance Method-
Compliance may be determined by dividing the AP-42 [Table 1.4-2 (revised 7/98)] emission factor of 1.9 lbs (filterable)/mm cu. ft. of natural gas by the heat content for natural gas of 1,000 mmBtu/mm cu. ft.

If required, the permittee shall demonstrate compliance with the PE limitation above in accordance with OAC rule 3745-17-03(B)(9).

- b. Emission Limitation -
17.0 tons/yr PE, as a rolling, 12-month summation

Applicable Compliance Method -

Compliance with the annual allowable PE limitation shall be assumed as long as compliance with the annual (based upon a rolling, 12-month summation) allowable natural gas usage restriction (excluding emissions unit K029) is and the lb PE/mmBtu limitation are maintained (the annual emission limitation was calculated by multiplying the maximum allowable facility-wide natural gas consumption rate (excluding emissions unit K029) of 1,700 mm cu. ft. (as a rolling, 12-month summation) by a nominal heat content of 1000 mmBtu/mm cu. ft. and by the allowable PE limitation of 0.020 lb PE/mmBtu, and then dividing by 2000).

- c. Emission Limitation -
135.58 tons/yr nitrogen oxides, as a rolling, 12-month summation

Applicable Compliance Method -

Compliance with the annual allowable NOx emission limitation shall be assumed as long as compliance with the annual (based upon a rolling, 12-month summation) allowable natural gas usage restriction is maintained (the annual NOx emission limitation was calculated by multiplying the maximum allowable facility-wide natural gas consumption of 1,700 mm cu. ft. (as a rolling, 12-month summation) by a company-derived emission factor of 159.5 lbs NOx/mm cu. ft*, and then dividing by 2000).

* The company-derived emission factor was based upon a natural gas ratio between process and thermal oxidizer abatement of 4.88 to 1.0 (or 83% to 17%) and the respective emission factors of 100 lbs NOx/mm cu. ft. for the process [(AP-42, Chapter 1.4 (revised 7/98)] and 450 lbs NOx/mm cu. ft. for the thermal oxidizer (company-derived)].

- d. Emission Limitation -
71.40 tons/yr carbon monoxide

Applicable Compliance Method -

Compliance with the annual allowable CO emission limitation shall be assumed as long as compliance with the annual (based upon a rolling, 12-month summation) natural gas usage restriction is maintained (the annual CO emission limitation was calculated by multiplying the maximum allowable facility-wide natural gas consumption of 1,700 mm cu. ft. (as a rolling, 12-month summation) by the AP-42 emission factor [Chapter 1.4 (revised 7/98)] of 84 lbs CO/mm cu. ft., and then dividing by 2000).

- e. Emission Limitation -
4.68 tons/yr volatile organic compounds, as a rolling, 12-month summation

Applicable Compliance Method -

Compliance with the annual allowable VOC emission limitation shall be assumed as long as compliance with the annual (based upon a rolling, 12-month summation) allowable natural gas usage restriction is maintained (the annual VOC emission limitation was calculated by multiplying the maximum allowable facility-wide natural gas consumption of 1,700 mm cu. ft. (as a rolling, 12-month summation) by the AP-42 emission factor [Chapter 1.4 (revised 7/98)] of 5.5 lbs VOC/mm cu. ft. and then dividing by 2000).

- f. Emission Limitation-
20% opacity visible emission limitation, as a six-minute average

Applicable Compliance Method-

If required, compliance shall be determined by visible emission evaluations performed in accordance with OAC rule 3745-17-03(B)(1).

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

VI. **Miscellaneous Requirements**

- Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following monitoring and recording keeping, reporting and testing requirements are as stringent or more stringent than the monitoring and record keeping, reporting and testing requirements contained in Permit to Install #08-2506, issued on 10/23/92 and subsequently modified on 8/9/95, 11/22/95 and 11/12/97; A.III, IV and V. The monitoring and record keeping, reporting and testing requirements contained in the above-referenced Permit to Install are subsumed into the monitoring and record keeping, reporting and testing requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying monitoring and record keeping, reporting and testing requirements in the Permit to Install.

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0857101349 Issuance type: Title V Final Permit

[Go to the top of this document](#)

Facility ID: 0857101349 Emissions Unit ID: B001 Issuance type: Title V Final Permit

B. State Enforceable Section

The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

1. None.

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
2. Additional Terms and Conditions		
1. None		

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

II. Operational Restrictions

1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

III. Monitoring and/or Record Keeping Requirements

1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

IV. Reporting Requirements

1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

V. Testing Requirements

1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

VI. Miscellaneous Requirements

1. None

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0857101349 Issuance type: Title V Final Permit

Part III - Terms and Conditions for Emissions Units

[Go to the top of this document](#)

Facility ID: 0857101349 Emissions Unit ID: G001 Issuance type: Title V Final Permit

A. State and Federally Enforceable Section

The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

1. None.

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
gasoline storage tanks: 2-15,000 gallon aboveground storage tanks	OAC rule 3745-21-09(R)	Stage I vapor control - 90% control efficiency for volatile organic compounds (VOCs), submerged fill
gasoline dispensing operation on the vehicle assembly line with Onboard Refueling Vapor Recovery (ORVR)	OAC rule 3745-21-09(DDD)	95% overall control efficiency for VOCs (See A.1.2.a.)
gasoline dispensing facility	OAC rule 3745-31-05(A)(3) PTI 08-3719	The requirements of this rule also include compliance with the requirements of OAC rules 3745-21-09(R) and 3745-21-09(DDD). 4.98 tons organic compounds (OC)/year

2. Additional Terms and Conditions

- a. All the vehicles filled by this gasoline dispensing facility shall be equipped with an ORVR system that achieves a 95% overall control efficiency for VOCs and meets the requirements of 40 CFR 86.099-8. Because an ORVR control system is employed, the other requirements of OAC rule 3745-21-09(DDD) relating to Stage II control systems are not relevant.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

II. Operational Restrictions

- 1. The permittee shall comply with the following operational restrictions for the Stage I vapor control system:
 - a. The vapor balance system shall be kept in good working order and shall be used at all times during the transfer of gasoline.
 - b. There shall be no leaks in the delivery vessel pressure/vacuum relief valves and hatch covers.
 - c. There shall be no leaks in the vapor lines or liquid lines during the transfer of gasoline.
 - d. The transfer of gasoline from a delivery vessel to a stationary storage tank shall be conducted by use of submerged fill into the storage tank. Each submerged fill pipe shall be installed so it is within six (6) inches of the bottom of the storage tank.
 - e. All fill caps shall be "in place" and clamped during normal storage conditions.
 - f. The permittee shall repair within 15 days any leak from the vapor balance system or vapor control system which is employed to meet the requirements of paragraph (R)(1) of OAC rule 3745-21-09 when such leak is equal to or greater than 100 percent of the lower explosive limit as propane, as determined under paragraph (K) of OAC rule 3745-21-10.
- 2. The gasoline throughput for this emissions unit shall not exceed 2,000,000 gallons, based upon a rolling, 12-month summation.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

III. Monitoring and/or Record Keeping Requirements

- 1. OAC rule 3745-21-09(R) does not establish or require a regular leak-checking program. However, for any leak checks performed, the permittee shall maintain records including, at a minimum, the following information:
 - a. Date of inspection.
 - b. Findings (may indicate no leaks discovered or location, nature, and severity of each leak).
 - c. Leak determination method.
 - d. Corrective action (date each leak repaired and reasons for any repair interval in excess of 15 calendar days).
 - e. Inspector's name and signature.
- 2. The permittee shall maintain records of the gasoline throughput during each calendar month and during each rolling, 12-month period.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

IV. Reporting Requirements

- 1. Any leak from the vapor balance system that is not repaired within 15 days after identification shall be reported to the Director within 30 days after the repair is completed.
- 2. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the rolling, 12-month gasoline throughput limitation of 2,000,000 gallons. These quarterly reports shall be submitted in accordance with paragraph A.1.c. of Part I, General Terms and Conditions, of this permit.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

V. **Testing Requirements**

1. Compliance Method

Compliance with the emission limitations in Section A.1. of these terms and conditions shall be determined in accordance with the following methods:

a. Emission Limitation-
4.98 tons OC/year

Applicable Compliance Method-

Compliance with the annual allowable OC emission limitation shall be determined by summing the OC emissions from two gasoline storage tanks' filling and dispensing operations. This calculation shall be based on the annual gasoline throughput using either the EPA "TANKS" program or AP-42 emission factors. The emissions from the fueling of vehicles with ORVR shall be determined by multiplying the gallons of gasoline dispensed by an emission factor of 0.2 gram of VOC/gallon of gasoline (Federal Register/Vol.59. No.66/ Wednesday April 6, 1994/ Rules and Regulations).

b. Emission Limitation-
95% overall control efficiency for VOC's

Applicable Compliance Method-

Compliance with this emission limitation shall be based upon USEPA's measurements of the ORVR system for each vehicle model produced at this facility and as documented in the USEPA's certificate of conformity. The permittee shall maintain records of all such certificates of conformity for the vehicles produced at this facility.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

VI. **Miscellaneous Requirements**

1. None

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0857101349 Issuance type: Title V Final Permit

[Go to the top of this document](#)

Facility ID: 0857101349 Emissions Unit ID: G001 Issuance type: Title V Final Permit

B. State Enforceable Section

The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

1. None.

I. **Applicable Emissions Limitations and/or Control Requirements**

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

	<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
2. Additional Terms and Conditions			
1.	None		

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

II. **Operational Restrictions**

1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

III. **Monitoring and/or Record Keeping Requirements**

- 1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

IV. **Reporting Requirements**

- 1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

V. **Testing Requirements**

- 1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

VI. **Miscellaneous Requirements**

- 1. None

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0857101349 Issuance type: Title V Final Permit

Part III - Terms and Conditions for Emissions Units

[Go to the top of this document](#)

Facility ID: 0857101349 Emissions Unit ID: K020 Issuance type: Title V Final Permit

A. **State and Federally Enforceable Section**

The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

- 1. None.

I. **Applicable Emissions Limitations and/or Control Requirements**

- 1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
pre-phosphate washers; preclean deck	OAC rule 3745-31-05(A)(3) PTI # 08-2506	8.3 lbs/hr, 133.4 lbs/day, 20.01 tons/yr of organic compounds (OC) (The above annual OC emission limitation is based upon a rolling, 12-month summation.) The requirements of this rule also include compliance with the requirements of OAC rule 3745-21-07(G). exempt, pursuant to OAC rule 3745-21-07(G)(9)(g).
	OAC rule 3745-21-07(G)(2)	

2. **Additional Terms and Conditions**

- a. The 8.3 lbs/hr OC limit was established for PTI purposes to reflect the potential to emit for this emissions unit. Therefore, it is not necessary to develop record keeping and/or reporting requirements to ensure compliance with this limit.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

II. **Operational Restrictions**

- 1. The permittee shall employ only water-reducible detergent solutions having vapor pressures for the organics that do not exceed 0.1 mmHg.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for this emissions unit:
 - a. The name and identification number of each material employed.
 - b. The OC content of each material employed, in pounds per gallon.
 - c. The number of gallons of each material employed.
 - d. The total OC emissions from all the materials employed (summation of (b x c) for all materials), in pounds.
 - e. The number of days the emissions unit was in operation.
 - f. The average daily OC emission rate for all the materials employed, i.e., (d/e), in pounds/day (average).
 - g. The rolling, 12-month summation of the monthly OC emission rates, in tons.
 - h. The OC vapor pressure of each material employed, in mmHg.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

IV. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the rolling, 12-month OC emission limitation of 20.01 tons, the daily OC emission limitation of 133.4 lbs, and the vapor pressure limitation of 0.1 mmHg. These quarterly reports shall be submitted in accordance with paragraph A.1.c. of Part I, General Terms and Conditions, of this permit.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

V. Testing Requirements

1. Compliance Method-

Compliance with the emission limitations in Section A.1. of these terms and conditions shall be determined in accordance with the following methods:

 - a. Emission Limitation -
8.3 lbs/hr of OC

Applicable Compliance Method -

Compliance with the OC emission limitation above may be determined by multiplying a company-derived OC emission factor of 0.115 lb OC/unit by the maximum hourly number of units produced (units/hr).

If required, the permittee shall demonstrate compliance with the OC emission limitation above in accordance with Methods 18, 25, or 25A, as appropriate, of 40 CFR, Part 60, Appendix A.
 - b. Emission Limitation-
133.4 lbs/day OC

Applicable Compliance Method-
Compliance with the daily OC emission limitation above shall also be based upon the record keeping requirements specified in Section A.III.1. of this permit.
 - c. Emission Limitation-
20.01 tons OC/yr, as a rolling, 12-month summation

Applicable Compliance Method-
Compliance with the annual OC emission limitation above shall also be based upon the record keeping requirements specified in Section A.III.1. of this permit.
2. The permittee shall use formulation data provided by the material manufacturer or USEPA Method 24 to determine the organic composition (OC content) of each material employed in this emissions unit.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

VI. Miscellaneous Requirements

1. Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following monitoring and recording keeping, reporting and testing requirements are as stringent or more stringent than the monitoring and record keeping, reporting and testing requirements contained in Permit to Install #08-2506, issued on 10/23/92 and subsequently modified on 8/9/95, 11/22/95 and 11/12/97; A.III, IV and V. The monitoring and record keeping, reporting and testing requirements contained in the above-referenced Permit to Install are subsumed into the monitoring and record keeping, reporting and testing requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying monitoring and record keeping, reporting and testing requirements in the Permit to Install.

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0857101349 Issuance type: Title V Final Permit

[Go to the top of this document](#)

Facility ID: 0857101349 Emissions Unit ID: K020 Issuance type: Title V Final Permit

B. State Enforceable Section

The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

- 1. None.

I. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

	<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
2. Additional Terms and Conditions			
1.	None		

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

II. Operational Restrictions

- 1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

III. Monitoring and/or Record Keeping Requirements

- 1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

IV. Reporting Requirements

- 1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

V. Testing Requirements

- 1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

VI. Miscellaneous Requirements

- 1. None

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0857101349 Issuance type: Title V Final Permit

Part III - Terms and Conditions for Emissions Units

[Go to the top of this document](#)

Facility ID: 0857101349 Emissions Unit ID: K022 Issuance type: Title V Final Permit

A. State and Federally Enforceable Section

The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

1. None.

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
primer surfacer system; powder guidecoat	OAC rule 3745-31-05(A)(3) PTI # 08-2506	2.2 lbs/hr, 34.8 lbs/day, 5.22 tons/yr VOC (The above annual emission limitation is based upon a rolling, 12-month summation.)
	OAC rule 3745-21-09(C)(1)(a)(v)	The VOC emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
	40 CFR, Part 60, Subpart MM	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

- a. The 2.2 lbs/hr VOC limitation was established for PTI purposes to reflect the potential to emit for this emissions unit. Therefore, it is not necessary to develop record keeping and/or reporting requirements to ensure compliance with this limit.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

II. Operational Restrictions

1. The permittee shall employ only powder coatings in this emissions unit.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for this emissions unit:
 - a. The name and identification number of each coating, as applied.
 - b. The VOC content of each coating (in lbs/gallon, excluding water and exempt solvents), as applied.
 - c. The number of gallons of each coating (excluding water and exempt solvents) employed.
 - d. The total VOC emissions from all the coatings employed (summation of (bxc) for all coatings), in pounds.
 - e. The number of days the emissions unit was in operation.
 - f. The average daily OC emission rate for all the coatings employed, i.e., (d/e), in pounds/day (average).
 - g. The rolling, 12-month summation of the monthly VOC emission rates, in tons.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

IV. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the rolling,12-month VOC emission limitation of 5.22 tons and of the daily VOC emission limitation of 34.8 pounds. These quarterly reports shall be submitted in accordance with paragraph A.1.c., Part I-General Terms and Conditions, of this permit.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

V. Testing Requirements

1. Compliance Method:

Compliance with the emission limitations in Section A.1. of these terms and conditions shall be determined in accordance with the following methods:

- a. Emission limitation-
2.2 lbs VOC/hr

Applicable Compliance Method-
Compliance may be determined by multiplying the maximum hourly coatings usage rate [gallons (excluding water and exempt solvents)/hr] by the maximum VOC content of all of the coatings (lbs/gallon of coating, excluding water and exempt solvents).

If required, the permittee shall demonstrate compliance in accordance with Methods 25 or 25A, as appropriate, of 40 CFR, Part 60, Appendix A.
- b. Emission Limitation-
34.8 lbs/day VOC

Applicable Compliance Method-
Compliance shall be based upon the record keeping requirements specified in Section A.III.1 of this permit.
- c. Emission Limitation-
5.22 tons VOC/yr, as a rolling, 12-month summation

Applicable Compliance Method-
Compliance shall be based upon the record keeping requirements specified in Section A.III.1 of this permit.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

VI. **Miscellaneous Requirements**

- 1. Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following monitoring and recording keeping, reporting and testing requirements are as stringent or more stringent than the monitoring and record keeping, reporting and testing requirements contained in Permit to Install #08-2506, issued on 10/23/92 and subsequently modified on 8/9/95, 11/22/95 and 11/12/97; A.III, IV and V. The monitoring and record keeping, reporting and testing requirements contained in the above-referenced Permit to Install are subsumed into the monitoring and record keeping, reporting and testing requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying monitoring and record keeping, reporting and testing requirements in the Permit to Install.

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0857101349 Issuance type: Title V Final Permit

[Go to the top of this document](#)

Facility ID: 0857101349 Emissions Unit ID: K022 Issuance type: Title V Final Permit

B. State Enforceable Section

The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

- 1. None.

I. **Applicable Emissions Limitations and/or Control Requirements**

- 1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

	<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
2. Additional Terms and Conditions			
1.	None		

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

II. **Operational Restrictions**

- 1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

III. **Monitoring and/or Record Keeping Requirements**

- 1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

IV. **Reporting Requirements**

- 1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

V. **Testing Requirements**

- 1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

VI. **Miscellaneous Requirements**

- 1. None

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0857101349 Issuance type: Title V Final Permit

Part III - Terms and Conditions for Emissions Units

[Go to the top of this document](#)

Facility ID: 0857101349 Emissions Unit ID: K023 Issuance type: Title V Final Permit

A. State and Federally Enforceable Section

The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

- 1. None.

I. **Applicable Emissions Limitations and/or Control Requirements**

- 1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
topcoat system (See A.I.2.a.)	OAC rule 3745-31-05(A)(3) PTI # 08-2506	0.99 kg of volatile organic compounds (VOC)/liter of coating solids applied or 8.24 lbs VOC/gallon of coating solids deposited 4913.76 lbs/day and 737.06 tons/yr VOC, not including cleanup materials [Emissions of VOC from cleanup materials from this emissions unit are accounted for in the permit for emissions unit K028.] (The above tons/yr emission limitation is a rolling, 12-month summation.) 15.55 lbs/hr particulate limitation is less stringent than the emissions limitation established pursuant to OAC rule 3745-17-11. See A.I.2.b - A.I.2.e. 42.0 tons/yr particulate emissions (PE) The hourly PE limitation of 15.55 lbs/hr is less stringent than the hourly allowable emission rate from OAC rule 3745-17-11.

	The requirements of this rule also include compliance with the requirements of OAC rules 3745-17-11 and 3745-17-07(A).
OAC rule 3745-21-09(C)(1)(c)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
40 CFR, Part 60, Subpart MM	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
OAC rule 3745-17-11(B)	4.5 lbs/hr PE
OAC rule 3745-17-07(A)	Visible PE shall not exceed 20% opacity, as a six-minute average, except as provided by rule.

2. Additional Terms and Conditions

- a. The topcoat system consists of four identical lines. Each of these lines consists of an initial area for application of water-borne basecoat (with flash-off), followed by an area for application of clearcoat (with flash-off), followed by an area for demasking (with flash-off), followed by a bake oven. The VOC emissions from the clearcoat areas and a portion of the demasking areas are controlled through the application of a VOC concentrator and a thermal oxidizer. The VOC emissions from the four bake ovens are controlled through the application of individual thermal oxidizers.
- b. The overall VOC capture efficiency for the clearcoat application areas, clearcoat flash-off areas, demasking areas, and bake ovens shall be equal to or greater than 79.4 percent, by weight.
- c. The VOC concentrator shall operate at a minimum VOC removal efficiency of 90 percent, by weight, or a maximum outlet concentration of 10 ppm, as propane.
- d. The thermal oxidizer, associated with the clearcoat VOC concentrator, shall operate at a minimum VOC destruction efficiency of 95 percent, by weight, or a maximum outlet concentration of 10 ppm, as propane.
- e. The bake oven thermal oxidizers, shall each operate at a minimum VOC destruction efficiency of 90 percent, by weight, or a maximum outlet concentration of 10 ppm, as propane.
- f. .

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

II. Operational Restrictions

1. The maximum annual VOC usage, prior to the application of emission controls, shall not exceed 1302.89 tons, based upon a rolling, 12-month summation of the monthly VOC usage rates.
2. The average combustion temperature within each of the thermal oxidizers referenced in Sections A.1.2.d and A.1.2.e for each 3-hour block of time when the emissions unit is in operation and vehicles are being painted, shall not be more than 50 degrees Fahrenheit below the average combustion temperature during the most recent emission test that demonstrated the emissions units was in compliance.
3. The permittee shall operate the water wash when this emissions unit is in operation.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall maintain monthly records of the following information for this emissions unit:
 - a. The VOC usage rate (uncontrolled) and VOC emission rate (controlled) [see calculation methodology in Section III.2 below], in tons. [The monthly VOC emission and usage rates shall be calculated in accordance with the U.S. EPA's "Protocol for Determining the Daily Volatile Organic Compound Emission Rate of Automobiles and Light-Duty Truck Topcoat Operations" (EPA-450/3-88-028, Dec.1988).]
 - b. The rolling, 12-month summation of the monthly VOC usage rates (uncontrolled), in tons.
 - c. The rolling, 12-month summation of the monthly VOC emission rates (controlled), in tons.
2. The permittee shall maintain records of the topcoat operation that will enable the calculation of the VOC emission rate from this emissions unit in accordance with the U.S. EPA's "Protocol for Determining the Daily Volatile Organic Compound Emission Rate of Automobiles and Light-Duty Truck Topcoat Operations" (EPA-450/3-88-028, Dec.1988).

The permittee shall calculate the VOC emission rate from all the coatings employed in the topcoat operation, in pounds of VOC per gallon of deposited solids, using the overall capture and control efficiency for the control equipment, as determined during the most recent emission test that demonstrated that the emissions unit was in compliance.
3. The permittee shall operate and maintain continuous temperatures monitors and recorders that measure and record the combustion temperature within each of the thermal oxidizers when the emissions unit is in

operation. For each thermal oxidizer, the permittee shall utilize a continuous strip chart recorder. If the strip chart malfunctions, the permittee shall utilize a computer system that records the temperatures every second and at the end of the day prints out the high, low and average temperatures for the day. Units shall be in degrees Fahrenheit. The continuous monitoring and recording devices shall be capable of accurately measuring the desired parameters and the owner or operator shall properly operate and maintain the devices in accordance with the manufacturers' recommendations, with any modifications deemed necessary by the permittee.

4. The permittee shall collect and record the following information for each day for the thermal oxidizers:
 - a. A log of downtime for the capture (collection) system, control device and monitoring equipment when the associated emissions unit was in operation.
 - b. All 3-hour blocks of time during which the average combustion temperature within any of the thermal oxidizers, when the emissions unit was in operation, was more than 50 degrees Fahrenheit below the average combustion temperature measured during the most recent emission test that demonstrated that the emissions unit was in compliance.
5. The permittee shall initiate an inspection and maintenance program designed to help ensure the control equipment is operating in accordance with the manufacturer's specifications. Such an I and M program shall outline the specific steps taken and/or the specific items checked on a routine basis to ensure optimum operation of the thermal oxidizers.
6. The permittee shall document whether or not the water wash was in service when the emissions unit was in operation.
7. The permittee shall operate and maintain a continuous organic monitoring device and recorder that accurately measures and records the VOC concentrations in the exhaust gases entering and leaving the VOC concentrator when the emissions unit is in operation and venting the VOC emissions to the concentrator.

The permittee shall maintain hourly records of the inlet and outlet ppm data obtained and % removal efficiency, and daily records of the results of daily zero/span drift checks.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

IV. Reporting Requirements

1. The permittee shall submit to the Director (the RAPCA) quarterly deviation (excursion) reports that identify all exceedances of the following:
 - a. the VOC content limitations of 0.99 kg VOC / liter of deposited coating solids (8.24 lbs VOC / gallon of deposited coating solids);
 - b. the daily VOC emission limitation of 4913.76 pounds;
 - c. the rolling, 12-month VOC usage rate restriction of 1302.89 tons;
 - d. the rolling, 12-month VOC emission limitation of 737.06 tons;
 - e. all 3-hour blocks of time during which the average combustion temperature within each of the thermal oxidizers was more than 50 degrees Fahrenheit below the average temperature during the most recent emissions test that demonstrated compliance; and
 - f. All 3-hour blocks of time when the VOC concentrator removal efficiency was less than 90% and the VOC outlet concentration was greater than 10 ppm (as propane).

These quarterly deviation reports shall be submitted in accordance with paragraph A.1.c., Part I, of the General Terms and Conditions of this permit.
2. The permittee shall submit annual reports that specify the total VOC emissions and usage rates for this emissions unit for the previous calendar year. These reports shall be submitted by January 31 of each year.
3. By February 15 of each year, and in accordance with Section 18 of the U.S. EPA's "Protocol for determining the Daily Volatile Organic Compound Emission Rate of Automobiles and Light-Duty Truck Topcoat Operations" (EPA-450/3-88-028, December 1988), the permittee shall review the operating conditions and evaluate that the Transfer Efficiency is representative of the most recent test. A statement of this review must be kept on file at the site.
4. The permittee shall submit quarterly summaries that include a log of the downtime for the capture (collection) system, control devices and/or monitoring equipment when the associated emissions unit was in operation.
5. The permittee shall notify the Director (the RAPCA) in writing of any record showing that the water wash was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the RAPCA) within 30 days after the event occurs.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

V. Testing Requirements

1. Compliance Methods-

Compliance with the emission limitations in Section A.1. of these terms and conditions shall be determined in accordance with the following methods:

- a. Emission Limitation:
0.99 kg VOC/liter of deposited coating solids (8.24 lbs VOC/gallon deposited coating solids), after controls
- Applicable Compliance Method -
The permittee shall demonstrate compliance with the VOC content limitation above based on the record keeping requirements in Section A.III.2 of this permit.
- b. Emission Limitation -
4913.76 lbs/day VOC
- Applicable Compliance Method -
The permittee shall demonstrate compliance with the daily allowable VOC emission limitation above based on the record keeping requirements in Section A.III.2 of this permit.
- c. Emission Limitation -
737.06 tons/yr VOC, as a rolling, 12-month summation
- Applicable Compliance Method -
- The permittee shall demonstrate compliance with the annual allowable VOC emission limitation above based on the record keeping requirements in Sections A.III.1 and 2 of this permit.
- d. Emission Limitation -
4.5 lbs/hr PE
- Applicable Compliance Method -
To determine the actual worst-case rate for PE, the following equation may be used:
- $$E = \text{maximum coating solids usage rate, in pounds per hour} \times (1 - TE) \times (1 - CE)$$
- E = PE rate, in pounds per hour
- TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used (based on the results of the most recent transfer efficiency testing)
- CE = control efficiency of the control equipment (assumed to be 98%)
- If required, compliance with the hourly allowable PE limitation shall be demonstrated in accordance with the methods in OAC rule 3745-17-03(B)(10).
- e. Emission Limitation -
42.0 tons/yr PE
- Applicable Compliance Method -
The annual PE shall be calculated by multiplying the latest available, company-derived emission factor (lbs PE/unit produced) by the number of units produced per year, and dividing by 2000.
- f. Emission Limitation-
Visible PE shall not exceed 20% opacity, as a six-minute average, except as provided by rule.
- Applicable Compliance Method-
If required, compliance shall be determined by visible emission evaluations performed in accordance with OAC rule 3745-17-03(B)(1).
- g. Emission Limitation-
The overall VOC capture efficiency for the clearcoat application areas, clearcoat flash-of areas, demasking areas, and bake ovens shall be equal to or greater than 79.4 percent, by weight.
- Applicable Compliance Method-
Compliance with the VOC capture efficiency requirement above shall be based upon the results of emission testing conducted in accordance with the test methods outlined in Section A.V.2. of this permit.
- h. Emission Limitation-
The VOC concentrator shall operate at a minimum VOC removal efficiency of 90 percent, by weight, or a maximum concentration outlet of 10 ppm, as propane.
- Applicable Compliance Method-
Compliance with the VOC removal efficiency or the outlet concentration requirements above shall be based upon the results of emission testing conducted in accordance with the test methods outlined in Section A.V.2. of this permit and also on the record keeping and monitoring requirements specified in Section A.III.5 of this permit.
- i. Emission Limitations-
The thermal oxidizer, following the clearcoat VOC concentrator, shall operate at a minimum VOC destruction efficiency of 95 percent, by weight, or a maximum outlet concentration of 10 ppm, as propane.

The clearcoat bake oven thermal oxidizers, shall each operate at a minimum VOC destruction efficiency of 90 percent, by weight, or a maximum outlet concentration of 10 ppm, as propane.

Applicable Compliance Method-

Compliance with the VOC destruction efficiency requirements above shall be based upon the results of emission testing conducted in accordance with the test methods outlined in Section A.V.2. of this permit.

2. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:
 - a. The emission testing shall be conducted within 1 year prior to permit expiration.
 - b. The emission testing shall be conducted to demonstrate compliance with the overall capture efficiency, the concentrator removal efficiency and the thermal oxidizers' destruction efficiencies.

c. The test(s) shall be conducted while the emissions unit is operating at or near maximum capacity, unless otherwise specified or approved by the RAPCA.

The following test method shall be employed to demonstrate compliance with removal/destruction efficiency requirements: Methods 25 or 25A, as appropriate, of 40 CFR, Part 60, Appendix A. The capture efficiency shall be determined using the test methods specified in 40 CFR Part 51, Appendix M, Method 204 through 204F, or the permittee may request to use an alternative method or procedure for the determination of capture efficiency as specified in the USEPA Guidelines for Determining Capture Efficiency, dated January 9, 1995. Ohio EPA will consider the request, including an evaluation of the applicability, necessity, and validity of the alternative, and may approve the use of the alternative if such approval does not contravene any other applicable requirement. The control efficiency of the concentrator and thermal incinerator system shall be conducted in accordance with the test methods and procedures specified in OAC rule 3745-21-10 and shall measure the percent reduction in mass emissions of organic compounds or organic materials between the inlet and outlet of the control system. The control efficiencies of the concentrator and thermal oxidizers (i.e., the percent reduction in mass emissions between the inlet and outlet of the control system) shall be determined in accordance with the test methods and procedures specified in Methods 25 or 25A, as appropriate, of 40 CFR, Part 60, Appendix A. The test methods and procedures selected shall be based on a consideration of the diversity of the organic species presented and their total concentration, and on a consideration of the potential presence of interfering gases.

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the RAPCA. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the RAPCA's refusal to accept the results of the emission test(s).

Personnel from the RAPCA shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the RAPCA within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the RAPCA.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

VI. Miscellaneous Requirements

1. Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following monitoring and recording keeping, reporting and testing requirements are as stringent or more stringent than the monitoring and record keeping, reporting and testing requirements contained in Permit to Install #08-2506, issued on 10/23/92 and subsequently modified on 8/9/95, 11/22/95 and 11/12/97; A.III, IV and V. The monitoring and record keeping, reporting and testing requirements contained in the above-referenced Permit to Install are subsumed into the monitoring and record keeping, reporting and testing requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying monitoring and record keeping, reporting and testing requirements in the Permit to Install.

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0857101349 Issuance type: Title V Final Permit

[Go to the top of this document](#)

Facility ID: 0857101349 Emissions Unit ID: K023 Issuance type: Title V Final Permit

B. State Enforceable Section

The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

1. None.

I. **Applicable Emissions Limitations and/or Control Requirements**

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	--------------------------------------	--

2. **Additional Terms and Conditions**

1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

II. **Operational Restrictions**

1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

III. **Monitoring and/or Record Keeping Requirements**

1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

IV. **Reporting Requirements**

1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

V. **Testing Requirements**

1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

VI. **Miscellaneous Requirements**

1. None

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0857101349 Issuance type: Title V Final Permit

Part III - Terms and Conditions for Emissions Units

[Go to the top of this document](#)

Facility ID: 0857101349 Emissions Unit ID: K025 Issuance type: Title V Final Permit

A. **State and Federally Enforceable Section**

The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

1. None.

I. **Applicable Emissions Limitations and/or Control Requirements**

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
final repair system	OAC rule 3745-31-05(A)(3)	88.81 lbs/day and 13.32 tons/yr* volatile organic

PTI # 08-2506

compounds (VOC), not including cleanup materials [Emissions of VOC from cleanup materials from this emissions unit are accounted for in the permit for emissions unit K028.]

* based on a rolling, 12-month summation

8.3 tons/yr particulate emissions(PE)

The hourly PE limitation of 3.1 lbs/hr is less stringent than the hourly allowable emission rate from OAC rule 3745-17-11.

The requirements of this rule also include compliance with the requirements of OAC rules 3745-21-09(C)(1)(d), 3745-17-11(B) and 3745-17-07(A).

OAC rule 3745-21-09(C)(1)(d)

4.8 lbs of VOC per gallon of coating, excluding water and exempt solvents (as a daily, volume-weighted average)

OAC rule 3745-17-11(B)(1)

0.71 lb/hr PE

OAC rule 3745-17-07(A)

Visible emissions shall not exceed 20% opacity, as a 6-minute average, except as provided by rule.

2. **Additional Terms and Conditions**

- (a) None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

II. **Operational Restrictions**

- 1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

III. **Monitoring and/or Record Keeping Requirements**

- 1. The permittee shall collect and record the following information for each day for this emissions unit:
 - a. The number of gallons, excluding water and exempt solvents, of each coating employed.
 - b. The daily, volume-weighted average VOC content of all the coatings [in pounds per gallon (excluding water and exempt solvents), as applied, calculated in accordance with the equation specified in paragraph (B)(9) of OAC rule 3745-21-10 for Cvoc,2.
 - c. The total VOC emissions from all the coatings employed, in pounds [summation of (2.b x 1.a) for all coatings].

(The permittee shall be recording the required information for each day at the end of the calendar month.)
- 2. The permittee shall collect and record the following information each month for this emissions unit:
 - a. The name and identification number of each coating, as applied.
 - b. The VOC content, in pounds per gallon (excluding water and exempt solvents) of each coating, as applied.
 - c. The total VOC emissions from all the coatings employed (calculated by summing the daily VOC emission rates (from Section 1.c above) for the calendar month, divided by 2000), in tons.
 - b. The rolling, 12-month summation of the monthly VOC emission rates, in tons.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

IV. **Reporting Requirements**

- 1. The permittee shall notify the Director (the RAPCA) in writing of each daily record showing that the daily, volume-weighted average VOC content exceeded the applicable limitation of 4.8 lbs/gallon of coating, excluding water and exempt solvents. The notification shall include a copy of such record and shall be sent to the Director (the RAPCA) within 45 days after the exceedance occurs.
- 2. The permittee shall submit quarterly deviation (excursion) reports that identify the following:
 - a. all exceedances of the daily VOC emission limitation of 88.81 pounds; and
 - b. all exceedances of the rolling, 12-month VOC emission limitation of 13.32 tons.

All quarterly deviation reports shall be submitted in accordance with Paragraph A.1.c of the General Terms and Conditions of this permit.

3. The permittee shall submit annual reports that specify the total VOC emissions from this emissions unit for the previous calendar year. These reports shall be submitted by January 31 of each year.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

V. **Testing Requirements**

1. Compliance Methods

Compliance with the emission limitations in Section A.1. of these terms and conditions shall be determined in accordance with the following methods:

a. Emission Limitation-

4.8 lbs VOC/gallon coating, excluding water and exempt solvents (daily, volume-weighted average)

Applicable Compliance Method:

Compliance shall be based upon the record keeping requirements specified in Section A.III.1 of this permit. In accordance with OAC rule 3745-21-04(B)(5), USEPA Method 24 shall be used to determine the VOC contents of the coatings. If, pursuant to section 4.3 of Method 24, 40 CFR Part 60, Appendix A, the permittee determines that Method 24 cannot be used for a particular coating, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24.

b. Emission limitation-
88.81 lbs VOC/day

Applicable Compliance Method-

Compliance shall be based upon the record keeping requirements specified in Section A.III.1 of this permit.

c. Emission Limitation-

13.32 tons VOC/yr, as a rolling, 12-month summation

Applicable Compliance Method-

Compliance shall be based upon the record keeping specified in Sections A.III.1 and 2 of this permit.

d. Emission Limitation-
0.71 lb/hr PE

Applicable Compliance Method:

To determine the actual worst-case rate for PE, the following equation may be used:

$E = \text{maximum coating solids usage rate, in pounds per hour} \times (1 - TE) \times (1 - CE)$

E = PE rate, in pounds per hour

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used (based on the results of the most recent transfer efficiency testing)

CE = control efficiency of the control equipment (assumed to be 98%)

If required, compliance with the hourly allowable PE limitation shall be demonstrated in accordance with the methods in OAC rule 3745-17-03(B)(10).

e. Emission Limitation-
8.3 tons/yr PE

Applicable Compliance Method-

The annual PE shall be calculated by multiplying the latest available, company-derived emission factor (lbs PE/unit produced) by the number of units produced per year, and dividing by 2000.

f. Emission Limitation-

Visible emissions shall not exceed 20% opacity, as a six-minute average

Applicable Compliance Method-

If required, compliance shall be determined by visible emissions evaluations performed in accordance with OAC rule 3745-17-03(B)(1).

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

VI. **Miscellaneous Requirements**

1. Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following monitoring and recording keeping, reporting and testing requirements are as stringent or more stringent than the monitoring and record keeping, reporting and testing requirements contained in Permit to Install #08-2506, issued on 10/23/92 and subsequently modified on 8/9/95, 11/22/95 and 11/12/97; A.III, IV and V. The monitoring and record keeping, reporting

and testing requirements contained in the above-referenced Permit to Install are subsumed into the monitoring and record keeping, reporting and testing requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying monitoring and record keeping, reporting and testing requirements in the Permit to Install.

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0857101349 Issuance type: Title V Final Permit

[Go to the top of this document](#)

Facility ID: 0857101349 Emissions Unit ID: K025 Issuance type: Title V Final Permit

B. State Enforceable Section

The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

- 1. None.

I. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

	<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
2. Additional Terms and Conditions			
1.	None		

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

II. Operational Restrictions

- 1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

III. Monitoring and/or Record Keeping Requirements

- 1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

IV. Reporting Requirements

- 1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

V. Testing Requirements

- 1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

VI. Miscellaneous Requirements

- 1. None

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0857101349 Issuance type: Title V Final Permit

Part III - Terms and Conditions for Emissions Units

[Go to the top of this document](#)

Facility ID: 0857101349 Emissions Unit ID: K027 Issuance type: Title V Final Permit

A. State and Federally Enforceable Section

The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

1. None.

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
miscellaneous sealers & adhesives (plant-wide usage)	OAC rule 3745-31-05(A)(3) PTI # 08-2506	17.0 lbs/hr and 37.58 tons/yr* volatile organic compounds (VOC), not including cleanup materials [Emissions of VOC from cleanup materials from this emissions unit are accounted for in the permit for emissions unit K028.]
		The requirements of this rule also include compliance with the requirements of OAC rule 3745-21-09(U)(1)(g).
		* based on a rolling, 12-month summation
	OAC rule 3745-21-09(U)(1)(i)	3.0 lbs VOC/gallons of coating, excluding water and exempt solvent

2. Additional Terms and Conditions

- a. The 17.0 lbs/hr VOC limit was established for PTI purposes to reflect the potential to emit for this emissions unit. Therefore, it is not necessary to develop record keeping and/or reporting requirements to ensure compliance with this limit.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

II. Operational Restrictions

1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for this emissions unit:
 - a. The name and identification number of each coating, as applied.
 - b. The VOC content of each coating, in lbs/gallon (excluding water and exempt solvents), as applied.
 - c. The number of gallons, of each coating (excluding water and exempt solvents), as applied.
 - d. The total VOC emissions from all the coatings employed (summation of (b x c) for all coatings), in pounds.
 - e. The rolling, 12-month summation of the monthly VOC emission rates, in tons.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

IV. Reporting Requirements

1. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any monthly record showing the use of noncomplying coatings (i.e., for VOC content). The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days following the end of the calendar month.
2. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the rolling, 12-month VOC emission limitation of 37.58 tons. All quarterly deviation reports shall be submitted in accordance with Paragraph A.1.c of the General Terms and Conditions of this permit.
3. The permittee shall submit annual reports that specify the total VOC emissions from this emissions unit for the

previous calendar year. These reports shall be submitted by January 31 of each year.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

V. **Testing Requirements**

1. Compliance Methods:

Compliance with the emission limitations in Section A.1. of these terms and conditions shall be determined in accordance with the following methods:

a. Emission limitation-
17.0 lbs/hr

Applicable Compliance Method-

Compliance with the hourly allowable VOC emission limitation may be determined by multiplying the maximum number of truck frames processed (number of truck frames processed/hr) by the most recent, company-derived emission factor (lb VOC/truck frame processed).

b. Emission Limitation-
37.58 tons VOC/yr, as a rolling, 12-month summation

Applicable Compliance Method-

Compliance shall be based upon the record keeping requirements specified in Section A.III.1. of this permit.

c. Emission Limitation-
3.0 lbs VOC/gallon coating, excluding water and exempt solvents

Applicable Compliance Method:

Compliance shall be based upon the record keeping requirements specified in Section A.III.1 of this permit. In accordance with OAC rule 3745-21-04(B)(5), USEPA Method 24 shall be used to determine the VOC contents of the coatings. If, pursuant to section 4.3 of Method 24, 40 CFR Part 60, Appendix A, the permittee determines that Method 24 cannot be used for a particular coating, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

VI. **Miscellaneous Requirements**

1. Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following monitoring and recording keeping, reporting and testing requirements are as stringent or more stringent than the monitoring and record keeping, reporting and testing requirements contained in Permit to Install #08-2506, issued on 10/23/92 and subsequently modified on 8/9/95, 11/22/95 and 11/12/97; A.III, IV and V. The monitoring and record keeping, reporting and testing requirements contained in the above-referenced Permit to Install are subsumed into the monitoring and record keeping, reporting and testing requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying monitoring and record keeping, reporting and testing requirements in the Permit to Install.

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0857101349 Issuance type: Title V Final Permit

[Go to the top of this document](#)

Facility ID: 0857101349 Emissions Unit ID: K027 Issuance type: Title V Final Permit

B. State Enforceable Section

The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

1. None.

I. **Applicable Emissions Limitations and/or Control Requirements**

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Applicable Emissions Limitations/Control

Operations, Property, and/or Equipment Applicable Rules/Requirements Measures

2. **Additional Terms and Conditions**

1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

II. **Operational Restrictions**

1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

III. **Monitoring and/or Record Keeping Requirements**

1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

IV. **Reporting Requirements**

1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

V. **Testing Requirements**

1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

VI. **Miscellaneous Requirements**

1. None

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0857101349 Issuance type: Title V Final Permit

Part III - Terms and Conditions for Emissions Units

[Go to the top of this document](#)

Facility ID: 0857101349 Emissions Unit ID: K028 Issuance type: Title V Final Permit

A. State and Federally Enforceable Section

The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

1. None.

I. **Applicable Emissions Limitations and/or Control Requirements**

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
miscellaneous solvent usage/cleanup (flushing, wiping and brushing, floor cleaning, paint purging, booth cleaning, windshield cleaning, body wiping)	OAC rule 3745-31-05(A)(3) PTI #08-2506	629.0 tons/yr organic compounds (OC), based on a rolling, 12-month summation
	OAC rule 3745-21-07(G)	The requirements of this rule also include compliance with the requirements of OAC rule 3745-21-07(G). none (See Section A.II.1.)

2. **Additional Terms and Conditions**

(a) None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

II. Operational Restrictions

1. The use of any photochemically reactive material, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit is prohibited. This operational restriction applies only to the solvents employed in floor cleaning that is not related to coating booths and body wiping that occurs outside of the coating booths. The other solvent usages described in "Operations, Property and/or Equipment" are associated with emissions units that are subject to OAC rule 3745-21-09 and, therefore, are not subject to OAC rule 3745-21-07.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall maintain monthly records of the following information for this emissions unit:
 - a. The company's identification for each solvent employed.
 - b. The number of gallons of each solvent material (starting inventory).
 - c. The number of gallons of each solvent material received.
 - d. The number of gallons of each solvent material (ending inventory).
 - e. The number of gallons of each solvent material shipped off site for disposal.
 - f. The OC content of each solvent material employed, in lbs/gallon.
 - g. The OC emissions from each solvent material employed [f x (b + c - d - e)], in pounds.
 - h. The total OC emissions from all the solvent materials employed [summation of g for all solvents/2000], in tons.
 - i. The rolling, 12-month summation of the monthly OC emission rates, in tons.
 - j. For only those floor cleaning and body wiping solvents subject to OAC rule 3745-21-07, documentation on whether or not each solvent material employed is a photochemically reactive material.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

IV. Reporting Requirements

1. The permittee shall submit annual reports that specify the total OC emissions from this emissions unit for the previous calendar year. These reports shall be submitted by January 31 of each year.
2. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the rolling, 12-month OC emission limitation of 629 tons. All quarterly deviation reports shall be submitted in accordance with Paragraph A.1.c of the General Terms and Conditions of this permit.
3. For only those floor cleaning and body wiping solvents subject to OAC rule 3745-21-07, the permittee shall submit deviation reports that identify all periods of time during which any photochemically reactive material was employed in this emissions unit. Each report shall identify the cause for the use of the photochemically reactive material(s), and the estimated total quantity of the material(s) emitted during each such day, in pounds. Each report shall be submitted to the Director (the RAPCA) within 30 days of the date of occurrence.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

V. Testing Requirements

1. Compliance Methods

Compliance with the emission limitations in Section A.1. of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitation-
629 tons VOC/yr, as a rolling, 12-month summation

Applicable Compliance Method-
Compliance shall be based upon the record keeping requirements specified in Section A.III.1 of this permit.
2. Formulation data or USEPA Method 24 shall be used to determine the OC content of the solvents.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

VI. Miscellaneous Requirements

1. Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following monitoring and recording keeping, reporting and

testing requirements are as stringent or more stringent than the monitoring and record keeping, reporting and testing requirements contained in Permit to Install #08-2506, issued on 10/23/92 and subsequently modified on 8/9/95, 11/22/95 and 11/12/97; A.III, IV and V. The monitoring and record keeping, reporting and testing requirements contained in the above-referenced Permit to Install are subsumed into the monitoring and record keeping, reporting and testing requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying monitoring and record keeping, reporting and testing requirements in the Permit to Install.

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0857101349 Issuance type: Title V Final Permit

[Go to the top of this document](#)

Facility ID: 0857101349 Emissions Unit ID: K028 Issuance type: Title V Final Permit

B. State Enforceable Section

The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

- 1. None.

I. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

	<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
2. Additional Terms and Conditions			
1.	None		

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

II. Operational Restrictions

- 1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

III. Monitoring and/or Record Keeping Requirements

- 1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

IV. Reporting Requirements

- 1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

V. Testing Requirements

- 1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

VI. Miscellaneous Requirements

- 1. None

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0857101349 Issuance type: Title V Final Permit

Part III - Terms and Conditions for Emissions Units

[Go to the top of this document](#)

Facility ID: 0857101349 Emissions Unit ID: K029 Issuance type: Title V Final Permit

A. State and Federally Enforceable Section

The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

1. None.

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
electrocoating dip tank w/ natural gas-fired oven (ELPO) controlled with a thermal oxidizer	OAC rule 3745-31-05(A)(3) PTI #08-3527	12.21 lbs/hr, 28.34 tons/yr* volatile organic compounds (VOC), not including cleanup materials [Emissions of VOC from cleanup materials from this emissions unit are accounted for in the permit for emissions unit K028.] See Sections A.I.2.a through c. from natural gas combustion: 25.6 tons/yr* nitrogen oxides (NOx) 21.50 tons/yr* carbon monoxide (CO) * based on a rolling, 12-month summation The requirements of this rule also include compliance with the requirements of OAC rules 3745-18-06(E), 3745-21-08(B), and 3745-23-06(B). OAC rule 3745-21-09(C)(1)(a)(i) The VOC content limitation specified by this rule is less stringent than the VOC content limitation established pursuant to OAC rule 3745-31-05(A)(3). 40 CFR, Part 60, Subpart MM The VOC content limitation specified by this rule is less stringent than the VOC content limitation established pursuant to OAC rule 3745-31-05(A)(3). OAC rule 3745-18-06 (E) exempt, pursuant to OAC rule 3745-18-06(C) (See A.I.2.d.) OAC rules 3745-21-08(B) and 3745-23-06(B) See A.I.2.e. OAC rule 3745-17-11 See A.I.2.f. OAC rule 3745-17-07(A) See A.I.2.g.

2. Additional Terms and Conditions

- a. The VOC content of the coatings employed in the electrocoating (ELPO) dip tank of this emissions unit shall comply with the VOC content limitation of 0.74 lb/gallon of coating, as a monthly, volume-weighted average, excluding water and exempt solvents, before the application of emission controls.
- b. The coatings employed in the electrocoating (ELPO) dip tank of this emissions unit shall comply with the limitation of 0.10 kg VOC/liter of applied coating solids, or 0.82 pound VOC/gallon of applied coating solids, as a monthly, volume-weighted average, before the application of emission controls.
- c. The VOC emissions from the cure oven of this emissions unit shall be controlled by a thermal oxidizer. The thermal oxidizer shall operate at a minimum VOC destruction efficiency of 90%, by weight. The overall VOC control efficiency for this emissions unit shall be no less than 63%, by weight.
- d. There are no sulfur dioxide emission limitations established by OAC Chapter 3745-18 for equipment associated with this emissions unit that are not considered "fuel burning equipment" because the process weight rate is less than 1,000 pounds/hour.
- e. The permittee has satisfied the "best available control techniques and operating practices" and "latest available control techniques and operating practices" required pursuant to OAC rules 3745-21-08 and

3745-23-06, respectively by committing to comply with the best available technology requirements established pursuant to OAC rule 3745-31-05(A)(3) in Permit to Install # 08-3527.

- f. The uncontrolled mass rate of particulate emissions from this emissions unit is less than 10 pounds per hour. Therefore, pursuant to OAC rule 3745-17-11(A)(2)(a)(ii), Figure II of OAC rule 3745-17-11 does not apply. In addition, Table I of OAC rule 3745-17-11 does not apply because the process weight, as defined in OAC rule 3745-17-01(B)(14), is equal to zero.
- g. This emissions unit is exempt from the visible particulate emission limitations specified in OAC rule 3745-17-07(A), pursuant to OAC rule 3745-17-07(A)(3)(h), because the emissions unit is not subject to the requirements of OAC rule 3745-17-11.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

II. Operational Restrictions

1. The average combustion temperature within the thermal oxidizer, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature during the most recent emissions test that demonstrated the emissions unit was in compliance.
2. All VOC emissions from the oven shall be captured and contained for discharge through the thermal oxidizer.
3. The maximum natural gas usage for the oven associated with this emissions unit shall not exceed 512 million cubic feet, based upon a rolling, 12-month summation of the monthly natural gas usage rates.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information for each month for the ELPO dip tank:
 - a. The name and identification of each material added to the dip tank.
 - b. The VOC content, in pounds per gallon (including water and exempt solvents) of each material added to the tank.
 - c. The volume of each coating material added to the dip tank (including water and exempt solvents), in gallons.
 - d. The volume percent (as a decimal fraction) solids of each coating material added to the dip tank.
 - e. The volume percent (as a decimal fraction) of water and exempt solvents of each coating material added to the dip tank.
 - f. The calculated volume-weighted average VOC content, lb VOC/gallon, of the combination of materials added to the dip tank, excluding water and exempt solvents (see Section A.V.1.a).
 - g. The calculated, pounds VOC per gallon of coating applied solids (see Section A.V.1.b).
 - h. The calculated, controlled, VOC emission rate, in tons (see Section A.V.1.d).
 - i. The number of hours of operation.
 - j. The average hourly VOC emission rate, in pounds/hr (average) .
 - k. A log or record of the downtime for the capture (collection system), control device and monitoring equipment when the associated emissions unit was in operation.
 - l. All 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature within the thermal oxidizer was more than 50 degrees Fahrenheit below the average temperature of the exhaust gases during the most recent performance test that demonstrated the emissions unit was in compliance.
2. The permittee shall maintain monthly records of the following information for this emissions unit:
 - a. The total amount of natural gas usage (million cubic feet).
 - b. The rolling, 12-month summation of the monthly natural gas usage rates, in million cubic feet.
3. The permittee shall operate and maintain continuous temperatures monitors and recorders that measure and record the combustion temperature within each of the thermal oxidizers when the emissions unit is in operation. For each thermal oxidizer, the permittee shall utilize a continuous strip chart recorder. If the strip chart malfunctions, the permittee shall utilize a computer system that records the temperatures every second and at the end of the day prints out the high, low and average temperatures for the day. Units shall be in degrees Fahrenheit. The continuous monitoring and recording devices shall be capable of accurately measuring the desired parameters and the owner or operator shall properly operate and maintain the devices in accordance with the manufacturers 'recommendations, with any modifications deemed necessary by the permittee.
4. The permittee shall collect and record the following information for each day for the thermal oxidizers:

- a. A log of downtime for the capture (collection) system, control device and monitoring equipment when the associated emissions unit was in operation.
- b. All 3-hour blocks of time during which the average combustion temperature within any of the thermal oxidizers, when the emissions unit was in operation, was more than 50 degrees Fahrenheit below the average combustion temperature measured during the most recent emission test that demonstrated that the emissions unit was in compliance.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

IV. Reporting Requirements

1. The permittee shall notify the Director (the RAPCA) in writing of any monthly record showing the use of any noncomplying coating material [i.e., for VOC content (0.74 lb VOC/gallon of coating, excluding water and exempt solvents)]. The notification shall include a copy of such record and shall be sent to the Director (the RAPCA) within 30 days following the end of the calendar month.
2. The permittee shall submit annual reports that specify the total VOC emissions this emissions unit for the previous calendar year. These reports shall be submitted by January 31 of each year.
3. The permittee shall submit to the Director (the RAPCA) quarterly deviation (excursion) reports that include the following:
 - a. an identification of all 3-hour blocks of time during which the average combustion temperature was more than 50 degrees Fahrenheit below the average combustion temperature during the most recent performance test that the emissions unit was in compliance;
 - b. an identification of all exceedances of the rolling, 12-month gas usage restriction of 512 million cubic feet; and
 - c. an identification of all exceedances of the rolling, 12-month VOC emission limitation of 28.34 tons.

The quarterly reports shall be submitted in accordance with paragraph A.1.c. of the General Terms and Conditions of this permit.
4. The permittee shall notify the Director (the RAPCA) in writing of any monthly record showing the use of any noncomplying coating material [i.e., for VOC emission rate (0.82 lb VOC/gallon of applied coating solids)]. The notification shall include a copy of such record and shall be sent to the Director (the RAPCA) within 30 days following the end of the calendar month.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

V. Testing Requirements

1. Compliance Method:

Compliance with the emission limitations in Section A.1. of these terms and conditions shall be determined in accordance with the following methods:

 - a. Emission Limitation-

0.74 lb VOC/gallon of coating, excluding water and exempt solvents, before the application of emission controls

Applicable Compliance Method-
The calculated monthly, volume-weighted average VOC content of the combination of materials added to the dip tank, in lbs/gallon, excluding water and exempt solvents, shall be determined in accordance with the following:

 - i. Sum the volumes, in gallons, of all the individual materials added to the dip tank, from Section A.III.1.c.
 - ii. Sum (b x c), from Section A.III.1, for all the individual materials added to the dip tank to determine total VOC, in pounds.
 - iii. Sum (c x e), from Section A.III.1, for all the individual materials added to the dip tank to determine total volume of water and exempt solvents, in gallons.
 - iv. Subtract 1.a.iii from 1.a.i to determine total volume of materials added to the dip tank, in gallons (excluding water and exempt solvents).
 - v. Divide 1.a.ii by 1.a.iv to determine the monthly, volume-weighted average VOC content of the combination of materials added to the dip tank, in lbs/gallon, excluding water and exempt solvents.
 - b. Emission Limitation-

0.82 lb VOC/gallon of applied coating solids, before the application of emission control

Applicable Compliance Method-
The calculated monthly, volume-weighted average VOC emission rate of the combination of materials added to the dip tank, in lbs/gallon of applied coating solids shall be determined in accordance with the following:

 - i. Determine the total monthly solids volume, in gallons, for all the individual materials added to the dip tank by summing (c x d), from Section A.III.1, for the month for all materials added;

use of smoke tubes.

ii. Measure the VOC emissions from the oven exhausts (north and south inlets to thermal oxidizer), the outlet from the thermal oxidizer, and the outlet from the uncontrolled stacks associated with this emissions unit (the rinse enclosure ambient exhausts). The VOC measurements shall be in accordance with the test methods and procedures specified in Methods 25 or 25A, as appropriate, of 40 CFR, Part 60, Appendix A.

iii. Calculate capture efficiency as follows: sum the total mass VOC emission rates measured from the north and south oven exhausts, divide by the sum of the total mass VOC emission rates measured from the dip tank ambient exhaust, the rinse enclosure ambient exhausts, and the north and south oven exhaust, and multiply by 100% as represented by the following equation:

$$\frac{(\text{VOCm NO exhaust} + \text{VOCm SO exhaust})}{(\text{VOCm NO exhaust} + \text{VOCm SO exhaust} + \text{VOCm DT exhaust} + \text{VOCm RE})} \times 100\%$$

where: VOCm is VOC mass, i.e. lbs/hr, NO is North Oven, SO is South Oven, DT is dip tank, RE is rinse enclosure

e. Determine the thermal oxidizer VOC destruction efficiency (i.e., the percent reduction in mass emissions between the inlet and outlet of the control system) in accordance with the test methods and procedures specified in Methods 25 or 25A, as appropriate, of 40 CFR, Part 60, Appendix A.

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the appropriate Ohio EPA District Office or local air agency. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA District Office's or local air agency's refusal to accept the results of the emission test(s).

Personnel from the appropriate Ohio EPA District Office or local air agency shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the appropriate Ohio EPA District Office or local air agency within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the appropriate Ohio EPA District Office or local air agency.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

VI. Miscellaneous Requirements

- Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following monitoring and recording keeping, reporting and testing requirements are as stringent or more stringent than the monitoring and record keeping, reporting and testing requirements contained in Permit to Install #08-2506, issued on 10/23/92 and subsequently modified on 8/9/95, 11/22/95 and 11/12/97; A.III, IV and V. The monitoring and record keeping, reporting and testing requirements contained in the above-referenced Permit to Install are subsumed into the monitoring and record keeping, reporting and testing requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying monitoring and record keeping, reporting and testing requirements in the Permit to Install.

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0857101349 Issuance type: Title V Final Permit

[Go to the top of this document](#)

Facility ID: 0857101349 Emissions Unit ID: K029 Issuance type: Title V Final Permit

B. State Enforceable Section

The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

- None.

I. Applicable Emissions Limitations and/or Control Requirements

- The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

	<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
2.	Additional Terms and Conditions		

- 1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

II. Operational Restrictions

- 1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

III. Monitoring and/or Record Keeping Requirements

- 1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

IV. Reporting Requirements

- 1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

V. Testing Requirements

- 1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

VI. Miscellaneous Requirements

- 1. None

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0857101349 Issuance type: Title V Final Permit

Part III - Terms and Conditions for Emissions Units

[Go to the top of this document](#)

Facility ID: 0857101349 Emissions Unit ID: K031 Issuance type: Title V Final Permit

A. State and Federally Enforceable Section

The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

- 1. None.

I. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	--------------------------------------	--

windshield glass system	OAC rule 3745-31-03(A)(3) PTI # 08-3719	117.8 lbs/day, 16.53 tons/yr* volatile organic compounds (VOC), excluding cleanup
-------------------------	--	---

* based on a rolling, 12-month summation

The requirements of this rule also include compliance with the requirements of OAC rule 3745-21-07(G)(9)(g).

See Section A.I.2.a.

OAC rule 3745-21-07(G)(9)(g)

2. Additional Terms and Conditions

- a. The maximum VOC content of each coating material employed in this emissions unit shall not exceed the following:

- (a)
- i. 7.3 lbs VOC/gallon of coating, excluding water and exempt solvents, for the clear prime;
 - ii. 5.1 lbs VOC/gallon of coating, excluding water and exempt solvents, for the black prime; and
 - iii. 0.08 lb VOC/gallon of coating, excluding water and exempt solvents, for the urethane sealer.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

II. Operational Restrictions

1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for this emissions unit:
 - a. The company identification and type (i.e., clear prime, black prime, or urethane sealer) of each coating employed.
 - b. The number of gallons, excluding water and exempt solvents, of each coating employed.
 - c. The VOC content of each coating employed, excluding water and exempt solvents, in pounds per gallon, as applied.
 - d. The total VOC emission rate from all the coatings employed (summation of (b x c) for all coatings, divided by 2000), in tons.
 - e. The rolling, 12-month summation of the monthly VOC emission rates, in tons.
 - f. The total number of days the emissions unit was in operation.
 - g. The average daily VOC emission rate for all the coatings employed, i.e., (d)/(f), in pounds per day (average).

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

IV. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the rolling, 12-month VOC emission limitation of 16.53 tons and the daily VOC emission limitation of 117.8 pounds. The quarterly reports shall be submitted in accordance with paragraph A.1.c., Paragraph Part I-General Terms and Conditions.
2. The permittee shall notify the Director (the RAPCA) in writing of each monthly record showing the use of noncomplying coatings (i.e., for VOC contents). The notification shall include a copy of such record and shall be sent to the Director (the RAPCA) within 30 days following the end of the calendar month.
3. The permittee shall submit annual reports that specify the total VOC emissions from this emissions unit for the previous calendar year. These reports shall be submitted by January 31 of each year.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

V. Testing Requirements

1. Compliance Method

Compliance with the emission limitations in Section A.1. of these terms and conditions shall be determined in accordance with the following methods:

 - a. Emission Limitation-
117.8 lbs VOC/day, excluding cleanup

Applicable Compliance Methods-
Compliance shall be based upon the record keeping requirements specified in Section A.III.1 of this permit.
 - b. Emission Limitation-
16.53 tons VOC/yr (excluding cleanup), as a rolling, 12-month summation

Applicable Compliance Methods-
Compliance shall be based upon the record keeping requirements specified in Section A.III.1 of this permit.
 - c. VOC content Limitations:

- 7.3 lbs VOC/gallon of coating (clear prime)
- 5.1 lbs VOC/gallon of coating (black prime)
- 0.08 lbs VOC/gallon of coating (urethane sealer)

Applicable Compliance Method:
 The permittee shall demonstrate compliance with the VOC content limitations above based on the record keeping requirements specified in Section A.III.1 of this permit.

- 2. In accordance with OAC rule 3745-21-04(B)(5), USEPA Method 24 shall be used to determine the VOC contents of the coatings. If, pursuant to section 4.3 of Method 24, 40 CFR Part 60, Appendix A, the permittee determines that Method 24 cannot be used for a particular coating, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

VI. Miscellaneous Requirements

- 1. Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following monitoring and recording keeping, reporting and testing requirements are as stringent or more stringent than the monitoring and record keeping requirements, reporting and testing requirements contained in Permit to Install #08-3719, issued on 03/25/98; A.III, IV and V. The monitoring and record keeping, reporting and testing requirements contained in the above-referenced Permit to Install are subsumed into the monitoring and record keeping, reporting and testing requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying monitoring and record keeping, reporting and testing requirements in the Permit to Install.

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0857101349 Issuance type: Title V Final Permit

[Go to the top of this document](#)

Facility ID: 0857101349 Emissions Unit ID: K031 Issuance type: Title V Final Permit

B. State Enforceable Section

The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

- 1. None.

I. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
2. Additional Terms and Conditions		
1. None		

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

II. Operational Restrictions

- 1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

III. Monitoring and/or Record Keeping Requirements

- 1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

IV. Reporting Requirements

- 1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

V. **Testing Requirements**

- 1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

VI. **Miscellaneous Requirements**

- 1. None

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0857101349 Issuance type: Title V Final Permit

Part III - Terms and Conditions for Emissions Units

[Go to the top of this document](#)

Facility ID: 0857101349 Emissions Unit ID: K034 Issuance type: Title V Final Permit

A. State and Federally Enforceable Section

The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

- 1. None.

I. **Applicable Emissions Limitations and/or Control Requirements**

- 1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
maintenance paint booth for metal and non-metal parts	OAC rule 3745-31-05(A)(3) PTI 08-3893	7 lbs/hr, 40 lbs/day, and 4.20 tons/yr volatile organic compounds (VOC) (from all the coatings used for the metal and non-metal parts, combined) [See A.I.2.a and b.) [Emissions of VOC from cleanup materials from this emissions unit are accounted for in the permit for emissions unit K028.] 2.41 tons/yr particulate emissions (PE) The requirements of this rule also include compliance with the requirements of OAC rules 3745-21-09(U)(2)(e)(i), 3745-17-07(A), 3745-17-11(B) and 3745-21-07(G)(2). on the days when coating non-metal parts: The hourly emission limitation specified by this rule is less stringent than the hourly emission limitation established pursuant to OAC rule 3745-31-05(A)(3). The daily limitation specified by this rule is as stringent as the daily limitation established pursuant to OAC rule 3745-31-05(A)(3).
	OAC rule 3745-21-07(G)(2)	0.551 lb/hr particulate emissions (PE) Visible PE shall not exceed 20% opacity, as a six-minute average, except as provided by rule. on the days when coating metal parts: The maximum daily coating usage for this emissions unit shall not exceed 8 gallons.
	OAC rule 3745-17-11(B) OAC rule 3745-17-07(A) OAC rule 3745-21-09(U)(2)(e)(i)	

2. **Additional Terms and Conditions**

- a. The hourly VOC emission limitation was established for PTI purposes to reflect the potential to emit for

this emissions unit. Therefore, it is not necessary to develop record keeping and/or reporting requirements to ensure compliance with this limit.

- b. All the coatings employed in this emissions unit will be considered to be photochemically reactive materials.
- c. Emissions from the cleanup materials employed in this emissions unit are accounted for in emissions unit K028.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

II. Operational Restrictions

1. The permittee shall operate the paint overspray filter when the spray painting application associated with this emissions unit is in operation.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each day for this emissions unit:
 - a. The company identification for each coating employed.
 - b. The volume, in gallons, of each coating employed.
 - c. The total volume, in gallons, of all the coatings employed. (It will be assumed by the permittee that all coatings employed are employed for metal parts.)
 - d. The VOC content of each coating employed, in pounds per gallon.
 - e. The total VOC emission rate for all the coatings employed [summation of (b x d) for all coatings], in pounds.
2. The permittee shall document whether or not the paint overspray filter was in service when the paint spraying application associated with this emissions unit is in operation.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

IV. Reporting Requirements

1. For the coating of metal parts, the permittee shall notify the Director (the RAPCA) in writing of any daily record showing that the coating line employed more than the allowable maximum daily coating usage limitation of 8 gallons. The notification shall include a copy of such record and shall be sent to the Director (the RAPCA) within 45 days after the exceedance occurs.
2. The permittee shall submit quarterly deviation (excursion) reports that identify each day during which the VOC emission rate from the coatings used for the metal and non-metal parts, combined, exceeded 40 pounds, and the actual VOC emission rate for each such day.
3. The quarterly deviation reports shall be submitted in accordance with paragraph A.1.c of the General Terms and Conditions of this permit.
4. The permittee shall notify the Director (the RAPCA) in writing of any record showing that the paint overspray filter not in service when the paint spraying application associated with this emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the RAPCA) within 30 days after the event occurs.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

V. Testing Requirements

1. Compliance Method

Compliance with the emission limitation(s) in Section A.1. of these terms and conditions shall be determined in accordance with the following method(s):

 - a. Emissions Limitation-
7 lbs/hour of VOC (for the coatings used for metal and non-metal parts)

Applicable Compliance Method-
Compliance may be determined by multiplying the maximum VOC content of all the coatings employed (lbs/gallon) by the maximum hourly coating usage rate (gallons/hr).

If required, compliance with the hourly allowable VOC emission limitation shall be demonstrated in accordance with Methods 18, 25, or 25A, as appropriate, of 40 CFR, Part 60, Appendix A.
 - b. Emission Limitation-

40 lbs VOC/day (from all the coatings used for the metal and non-metal parts, combined)

Applicable Compliance Method-
Compliance shall be based upon the record keeping requirements specified in Section A.III.1 of this permit.

c. Emission Limitation-
4.20 tons VOC/yr

Applicable Compliance Method-
As long as compliance with the daily VOC emission limitation is maintained, compliance with the annual VOC emission limitation shall be assumed (the annual allowable VOC emission limitation is less than the annual potential to emit for VOC). The annual potential to emit for VOC is determined by multiplying the daily limitation by 365, and then dividing by 2000).

d. Emission Limitation-
less than or equal to 8.0 gallons of coating per day (for the coatings used for the metal parts)

Applicable compliance Method-
Compliance shall be based upon the record keeping specified in Section A.III.1 of this permit.

e. Emission Limitation -
0.551 lb/hr PE

Applicable Compliance Method -
To determine the actual worst-case rate for PE, the following equation may be used:

$$E = \text{maximum coating solids usage rate, in pounds per hour} \times (1 - TE) \times (1 - CE)$$

$$E = \text{PE rate, in pounds per hour}$$

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used

CE = control efficiency of the control equipment

If required, compliance with the hourly allowable PE limitation shall be demonstrated in accordance with the methods in OAC rule 3745-17-03(B)(10).

f. Emission Limitation -
2.41 tons/yr PE

Applicable Compliance Method -
The annual allowable PE limitation was developed by multiplying the hourly allowable PE limitation by 8760, and then dividing by 2000. Therefore, provided compliance is shown with the hourly limitation, compliance shall also be shown with the annual limitation.

2. Formulation data or USEPA Method 24 shall be used to determine the VOC contents of the coatings and cleanup materials employed in this emissions.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

VI. **Miscellaneous Requirements**

1. None

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0857101349 Issuance type: Title V Final Permit

[Go to the top of this document](#)

Facility ID: 0857101349 Emissions Unit ID: K034 Issuance type: Title V Final Permit

B. State Enforceable Section

The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

1. None.

I. **Applicable Emissions Limitations and/or Control Requirements**

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
2. Additional Terms and Conditions		
1. None		

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

II. **Operational Restrictions**

1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

III. **Monitoring and/or Record Keeping Requirements**

1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

IV. **Reporting Requirements**

1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

V. **Testing Requirements**

1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

VI. **Miscellaneous Requirements**

1. None

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0857101349 Issuance type: Title V Final Permit

Part III - Terms and Conditions for Emissions Units

[Go to the top of this document](#)

Facility ID: 0857101349 Emissions Unit ID: K035 Issuance type: Title V Final Permit

A. State and Federally Enforceable Section

The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

1. None.

I. **Applicable Emissions Limitations and/or Control Requirements**

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Hinge Sealer	OAC rule 3745-31-05(A)(3) PTI 08-3917	64.0 lbs/day and 9.0* tons/yr of volatile organic compounds(VOC) 3.23 lbs VOC/gallon of coating, excluding water and exempt solvents

*based on a rolling, 12-month summation

OAC rule 3745-21-09(U)(1)(d)

The VOC content limitation specified by this rule is less stringent than the VOC content limitation established pursuant to OAC rule 3745-31-05(A)(3).

2. **Additional Terms and Conditions**

- (a) None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

II. **Operational Restrictions**

1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

III. **Monitoring and/or Record Keeping Requirements**

1. The permittee shall collect and record the following information each month for this emissions unit:
 - a. The name and identification number of each sealer material, as applied.
 - b. The VOC content of each sealer material (in pounds/gallon, excluding water and exempt solvents), as applied.
 - c. The number of gallons (excluding water and exempt solvents) of each sealer material employed.
 - d. The total VOC emissions from all the sealer materials employed [summation of (b x c) for all sealer materials], in pounds.
 - e. The rolling, 12-month summation of the VOC emission rate, in tons.
 - f. The total number of days the emission unit was in operation.
 - g. The average daily VOC emission rate for all the sealer materials employed, i.e., (d)/(f), in pounds per day.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

IV. **Reporting Requirements**

1. The permittee shall notify the Director (the RAPCA) in writing of any monthly record showing the use of noncomplying sealer materials. The notification shall include a copy of such record and shall be sent to the Director (the RAPCA) within 30 days following the end of the calendar month.
2. The permittee shall submit to the Director (the RAPCA) quarterly deviation (excursion) reports that include the following:
 - a. All exceedances of the rolling, 12-month VOC emission limitation of 9.0 tons.
 - b. All exceedances of the daily VOC emission limitation of 64.0 pounds.

The quarterly reports shall be submitted in accordance with paragraph A.1.c. of the General Terms and Conditions of this permit.
3. The permittee shall also submit annual reports that specify the total VOC emissions from this emissions unit for the previous calendar year. These reports shall be submitted by January of each year.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

V. **Testing Requirements**

1. Compliance Method:

Compliance with the emission limitations in Section A.1. of these terms and conditions shall be determined in accordance with the following methods:

 - a. Emission limitation-
64.0 lbs VOC/day

Applicable Compliance Method-
Compliance shall be based upon the record keeping requirements specified in Section A.III.1 of this permit.
 - b. Emission limitation-
9.0 ton VOC/yr, as a rolling, 12-month summation

Applicable Compliance Method-
Compliance shall based upon the record keeping requirements as specified in Section A.III.1 of this permit.

- c. Emission limitation-
3.23 lbs VOC/gallon of coating, excluding water and exempt solvents

Applicable Compliance Method-
Compliance shall based upon the record keeping requirements specified in Section A.III.1of this permit. In accordance with OAC rule 3745-21-04(B)(5), USEPA Method 24 shall be used to determine the VOC contents of the coatings. If, pursuant to Section 4.3 of Method 24, 40 CFR, Part 60, Appendix A, the permittee determines that Method 24 cannot be used for a particular coating, the permittee shall notify the Administrator of the USEPA and shall use formulation data for that coating to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24.

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

VI. **Miscellaneous Requirements**

- 1. None

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0857101349 Issuance type: Title V Final Permit

[Go to the top of this document](#)

Facility ID: 0857101349 Emissions Unit ID: K035 Issuance type: Title V Final Permit

B. State Enforceable Section

The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

- 1. None.

I. **Applicable Emissions Limitations and/or Control Requirements**

- 1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

	<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
2. Additional Terms and Conditions			
1.	None		

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

II. **Operational Restrictions**

- 1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

III. **Monitoring and/or Record Keeping Requirements**

- 1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

IV. **Reporting Requirements**

- 1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

V. **Testing Requirements**

1. None

[Go to the top of this document](#)

[Go to the top of Part III for this Emissions Unit](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION.

VI. **Miscellaneous Requirements**

1. None