

Facility ID: 0125041404 Issuance type: Final State Permit To Operate

This version of facility specific terms and conditions was converted from a database format to an HTML file during an upgrade of the Ohio EPA, Division of Air Pollution Control's permitting software. Every attempt has been made to convert the terms and conditions to look and substantively conform to the permit issued or being drafted in STARS. However, the format of the terms may vary slightly from the original. In addition, although it is not expected, there is a slight possibility that a term and condition may have been inadvertently "left out" of this reproduction during the conversion process. Therefore, if this version is to be used as a starting point in drafting a new version of a permit, it is imperative that the entire set of terms and conditions be reviewed to ensure they substantively mimic the issued permit. The official version of any permit issued final by Ohio EPA is kept in the Agency's Legal section. The Legal section may be contacted at (614) 644-3037.

In addition to the terms and conditions, hyperlinks have been inserted into the document so you may more readily access the section of the document you wish to review.

Finally, the term language under "Part II" and before "A. Applicable Emissions Limitations..." has been added to aid in document conversion, and was not part of the original issued permit.

[Go to Part II for Emissions Unit K001](#)

[Go to Part II for Emissions Unit K002](#)

[Go to Part II for Emissions Unit K003](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0125041404 Emissions Unit ID: K001 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (a) None.

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Pressure cylinder paint line (Dot 39) with 1.5 MMBtu/hr gas-fired burner used to heat booth make-up air.	OAC Rule 3745-21-09(U)(1)(c)	The emission limit specified in this rule is less stringent than the emission limitations established in PTI No. 01-08579.
	OAC Rule 3745-35-07	The volatile organic compound (VOC) emissions from K001 shall not exceed 45 tons per year from coating and cleanup material usage based upon a rolling, 12-month summation of the emissions.
	OAC Rule 3745-31-05 PTI No. 01-08579	The annual, individual and combined hazardous air pollutant (HAP) emissions from all emissions units at this facility shall not exceed 9.9 tons per year and 24.9 tons per year, respectively. VOC emissions shall not exceed 35.0 lbs/hr, excluding cleanup.
	OAC Rule 3745-17-11(B)(1) OAC Rule 3745-17-07(A)(1)	Maximum VOC content shall not exceed 3.5 pounds of VOC per gallon of coating, excluding water and exempt solvents, as a daily volume-weighted average. See A.2.a below. 0.551 pound of particulate emissions per hour. Visible particulate emissions shall not exceed 20% opacity as a six-minute average, except as provided by rule.

2. **Additional Terms and Conditions**
 - (a) Maximum VOC content shall not exceed 6.8 pounds of VOC per gallon of cleanup, excluding water and exempt solvents.
The facility-wide individual and combined HAP emissions are effectively limited to less than 10 tons and 25 tons per year, respectively, by limiting the total VOC emissions from K001, K002 and K003.

B. Operational Restrictions

1. The maximum annual coating usage for K001 shall not exceed 27,337 gallons, based upon a rolling, 12-month summation of the coating usage figures.
2. The maximum annual cleanup material usage for K001 shall not exceed 372 gallons, based upon a rolling, 12-month summation of the cleanup material usage figures, after subtracting the cleanup material drummed for shipment off site.
3. The permittee shall operate the dry filtration system whenever K001 is in operation.
4. This emissions unit shall be operated and maintained in accordance with the manufacturer's recommendations.

Spray booth exhaust filters shall be maintained (changed or cleaned) regularly per the manufacturer's recommendations in order to maintain the highest effective level of particulate emissions control.

5. The permittee shall maintain a minimum stack height of thirty three (33) feet above ground for this emissions unit. All air contaminant emissions from this emissions unit shall be emitted through the stack.

C. Monitoring and/or Record Keeping Requirements

1. The permittee shall maintain monthly records of the following information for this emissions unit:
 - a. The coating usage for each month.
 - b. The cleanup material usage for each month.
 - c. The rolling, 12-month summation of the coating usage figures.
 - d. The rolling, 12-month summation of the cleanup material usage figures.
 - e. The individual HAP and total combined HAP content of each coating and cleanup material employed.
2. The permittee shall collect and record the following information on a monthly basis for this emissions unit:
 - a. the name and identification of each type of coating and cleanup material employed;
 - b. the VOC content of each type of coating and cleanup material employed (excluding water and exempt solvents), as applied, in pounds per gallon;
 - c. the VOC content of each type of coating and cleanup material employed, in pounds per gallon;
 - d. the number of gallons of each type of coating and cleanup material employed;
 - e. the number of gallons of each type of cleanup material drummed for shipment off site;
 - f. the total VOC emissions from all coatings and cleanup materials employed, in tons, i.e., the sum of the emissions for all the coatings and cleanup materials employed minus the potential emissions associated with the amount of cleanup material drummed for shipment off site; and
 - g. the rolling 12-month summation of the total VOC emissions from all the coatings and cleanup materials employed, in tons.
3. The permittee shall maintain daily records that document any time periods when the dry filtration system was not in service when K001 was in operation.
4. The permittee shall calculate, in accordance with the equation specified in paragraph (B)(9) of OAC rule 3745-21-10 for CVOC,2, and maintain records of the daily volume-weighted average VOC content of all coatings, as applied, on each day when any paint with a VOC content in excess of the applicable limit is applied.

D. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports which identify all exceedances of the rolling, 12-month usage limitations for coatings and cleanup materials and all exceedances of the rolling, 12-month emission limitation for VOC emissions. These reports are due by the dates described in Part 1 - General Terms and Conditions of this permit under section A.1.
2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily or monthly record showing that the VOC content of any coating exceeded the applicable limitation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 45 days after the exceedance occurs.
3. The permittee shall submit annual reports which specify the total VOC emissions, total emissions of each individual HAP, total coating usage, and total cleanup material usage for K001 for the previous calendar year. These reports shall be submitted by January 31 of each year and shall include the emission calculations.
4. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any monthly record showing that the VOC content of any cleanup material exceeded the applicable limitation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 45 days after the exceedance occurs.
5. The permittee shall notify the Director (the appropriate District Office or local air agency) in writing of any daily record showing that the dry filtration system was not in service when K001 was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate District Office or local air agency) within 30 days after the event occurs.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

Emission limitation:
The yearly VOC emissions for K001 shall not exceed 45 tons per year.

Applicable Compliance Method:
Compliance with the 45 tons per year shall be based upon the record keeping requirements specified in Section C.2.

Emission Limitation:
3.5 pounds VOC per gallon of coating, excluding water and exempt solvents, as a daily volume-weighted average.

Applicable Compliance Method:
Compliance shall be based upon the record keeping requirements specified in Sections C.2 and C.4. In

accordance with OAC rule 3745-21-04(B)(5), USEPA Method 24 shall be used to determine the VOC contents of the coatings. If, pursuant to section 4.3 of Method 24, 40 CFR Part 60, Appendix A, an owner or operator determines that Method 24 cannot be used for a particular coating, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24.

Emission Limitation:

6.8 pounds VOC per gallon of cleanup material, excluding water and exempt solvents.

Applicable Compliance Method:

Compliance shall be based upon the record keeping requirements specified in Section C.2. Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound contents of the cleanup materials.

Emission limitation:

The particulate matter emissions shall not exceed 0.551 lb per hour.

Applicable Compliance Method:

To determine the emissions rate for particulate matter, the following equation shall be used:

$E = \text{maximum coating solids usage rate (pounds/hr)} \times (1-TE) \times (1-CE)$

Where:

E = particulate matter emissions rate (lbs/hr)

TE = transfer efficiency of painting equipment in decimal form (use 0.50), transfer efficiency is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used

CE = control efficiency of the control equipment in decimal form (99% for filters)

Emission Limitation:

Visible particulate emissions shall not exceed 20% opacity as a six-minute average, except as provided by rule.

Applicable Compliance Method:

If required, the permittee shall demonstrate compliance with this emission limitation by the method specified in OAC rule 3745-17-03(B)(1)

F. Miscellaneous Requirements

1. Pursuant to OAC rule 3745-35-07, the following terms and conditions of this permit are federally enforceable: A - F.

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0125041404 Emissions Unit ID: K002 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (a) None.

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Pressure cylinder paint line (4BA) with 1.5 MMBtu/hr gas-fired burner used to heat booth make-up air.	OAC Rule 3745-21-09(U)(1)(c)	The emission limit specified in this rule is less stringent than the emission limitations established in PTI No. 01-08579.
	OAC Rule 3745-35-07	The volatile organic compound (VOC) emissions from K002 shall not exceed 45 tons per year from coating and cleanup material usage based upon a rolling, 12-month summation of the emissions.
	OAC Rule 3745-31-05 PTI No. 01-08579	The annual, individual and combined hazardous air pollutant (HAP) emissions from all emissions units at this facility shall not exceed 9.9 tons per year and 24.9 tons per year, respectively. VOC emissions shall not exceed 35.0 lbs/hr, excluding cleanup.

Maximum VOC content shall not exceed 3.5 pounds of VOC per gallon of coating, excluding water and exempt solvents, as a daily volume-weighted average.

See A.2.a below.

OAC Rule 3745-17-11(B)(1)

0.551 pound of particulate emissions per hour.

OAC Rule 3745-17-07(A)(1)

Visible particulate emissions shall not exceed 20% opacity as a six-minute average, except as provided by rule.

2. Additional Terms and Conditions

- (a) Maximum VOC content shall not exceed 6.8 pounds of VOC per gallon of cleanup, excluding water and exempt solvents.
The facility-wide individual and combined HAP emissions are effectively limited to less than 10 tons and 25 tons per year, respectively, by limiting the total VOC emissions from K001, K002 and K003.

B. Operational Restrictions

- 1. The maximum annual coating usage for K002 shall not exceed 27,337 gallons, based upon a rolling, 12-month summation of the coating usage figures.
- 2. The maximum annual cleanup material usage for K002 shall not exceed 372 gallons, based upon a rolling, 12-month summation of the cleanup material usage figures, after subtracting the cleanup material drummed for shipment off site.
- 3. The permittee shall operate the dry filtration system whenever K002 is in operation.
- 4. This emissions unit shall be operated and maintained in accordance with the manufacturer's recommendations. Spray booth exhaust filters shall be maintained (changed or cleaned) regularly per the manufacturer's recommendations in order to maintain the highest effective level of particulate emissions control.
- 5. The permittee shall maintain a minimum stack height of thirty three (33) feet above ground for this emissions unit. All air contaminant emissions from this emissions unit shall be emitted through the stack.

C. Monitoring and/or Record Keeping Requirements

- 1. The permittee shall maintain monthly records of the following information for this emissions unit:
 - a. The coating usage for each month.
 - b. The cleanup material usage for each month.
 - c. The rolling, 12-month summation of the coating usage figures.
 - d. The rolling, 12-month summation of the cleanup material usage figures.
 - e. The individual HAP and total combined HAP content of each coating and cleanup material employed.
- 2. The permittee shall collect and record the following information on a monthly basis for this emissions unit:
 - a. the name and identification of each type of coating and cleanup material employed;
 - b. the VOC content of each type of coating and cleanup material employed (excluding water and exempt solvents), as applied, in pounds per gallon;
 - c. the VOC content of each type of coating and cleanup material employed, in pounds per gallon;
 - d. the number of gallons of each type of coating and cleanup material employed;
 - e. the number of gallons of each type of cleanup material drummed for shipment off site;
 - f. the total VOC emissions from all coatings and cleanup materials employed, in tons, i.e., the sum of the emissions for all the coatings and cleanup materials employed minus the potential emissions associated with the amount of cleanup material drummed for shipment off site; and
 - g. the rolling 12-month summation of the total VOC emissions from all the coatings and cleanup materials employed, in tons.
- 3. The permittee shall maintain daily records that document any time periods when the dry filtration system was not in service when K002 was in operation.
- 4. The permittee shall calculate, in accordance with the equation specified in paragraph (B)(9) of OAC rule 3745-21-10 for CVOC,2, and maintain records of the daily volume-weighted average VOC content of all coatings, as applied, on each day when any paint with a VOC content in excess of the applicable limit is applied.

D. Reporting Requirements

- 1. The permittee shall submit quarterly deviation (excursion) reports which identify all exceedances of the rolling, 12-month usage limitations for coatings and cleanup materials and all exceedances of the rolling, 12-month emission limitation for VOC emissions. These reports are due by the dates described in Part 1 - General Terms and Conditions of this permit under section A.1.
- 2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily or monthly record showing that the VOC content of any coating exceeded the applicable limitation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 45 days after the exceedance occurs.

3. The permittee shall submit annual reports which specify the total VOC emissions, total emissions of each individual HAP, total coating usage, and total cleanup material usage for K002 for the previous calendar year. These reports shall be submitted by January 31 of each year and shall include the emission calculations.
4. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any monthly record showing that the VOC content of any cleanup material exceeded the applicable limitation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 45 days after the exceedance occurs.
5. The permittee shall notify the Director (the appropriate District Office or local air agency) in writing of any daily record showing that the dry filtration system was not in service when K002 was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate District Office or local air agency) within 30 days after the event occurs.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):
Emission limitation:
The yearly VOC emissions for K002 shall not exceed 45 tons per year.

Applicable Compliance Method:
Compliance with the 45 tons per year shall be based upon the record keeping requirements specified in Section C.2.
Emission Limitation:
3.5 pounds VOC per gallon of coating, excluding water and exempt solvents, as a daily volume-weighted average.

Applicable Compliance Method:
Compliance shall be based upon the record keeping requirements specified in Sections C.2 and C.4. In accordance with OAC rule 3745-21-04(B)(5), USEPA Method 24 shall be used to determine the VOC contents of the coatings. If, pursuant to section 4.3 of Method 24, 40 CFR Part 60, Appendix A, an owner or operator determines that Method 24 cannot be used for a particular coating, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24.
Emission Limitation:
6.8 pounds VOC per gallon of cleanup material, excluding water and exempt solvents.

Applicable Compliance Method:
Compliance shall be based upon the record keeping requirements specified in Section C.2. Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound contents of the cleanup materials.
Emission limitation:
The particulate matter emissions shall not exceed 0.551 lb per hour.

Applicable Compliance Method:
To determine the emissions rate for particulate matter, the following equation shall be used:

$$E = \text{maximum coating solids usage rate (pounds/hr)} \times (1 - TE) \times (1 - CE)$$

Where:

E = particulate matter emissions rate (lbs/hr)
TE = transfer efficiency of painting equipment in decimal form (use 0.50), transfer efficiency is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used
CE = control efficiency of the control equipment in decimal form (99% for filters)
Emission Limitation:
Visible particulate emissions shall not exceed 20% opacity as a six-minute average, except as provided by rule.

Applicable Compliance Method:
If required, the permittee shall demonstrate compliance with this emission limitation by the method specified in OAC rule 3745-17-03(B)(1)

F. Miscellaneous Requirements

1. Pursuant to OAC rule 3745-35-07, the following terms and conditions of this permit are federally enforceable: A - F.

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0125041404 Emissions Unit ID: K003 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.

(a) None.

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Three-station silk screening operation	OAC Rule 3745-21-09(U)(1)	Exemption from emission limitation in OAC Rule 3745-21-09(U)(1) per OAC Rule 3745-21-09(U)(2)(e)(ii)
	OAC Rule 3745-35-07	The volatile organic compound (VOC) emissions from K003 shall not exceed 5.0 tons per year from coating and cleanup material usage based upon a rolling, 12-month summation of the emissions. 5.2 lbs VOC per gallon of coating, excluding water and exempt solvents. 6.8 lbs VOC per gallon of cleanup material, excluding water and exempt solvents.
	OAC Rule 3745-31-05 PTI No. 01-08565	The annual, individual and combined hazardous air pollutant (HAP) emissions from all emissions units at this facility shall not exceed 9.9 tons per year and 24.9 tons per year, respectively. VOC emissions shall not exceed 5.2 lbs/hr, excluding cleanup. See B.1-3 below. The requirements of this rule also include compliance with the requirements of OAC rule 3745-21-09(U)(2)(e)(iii).

2. **Additional Terms and Conditions**

(a) The facility-wide individual and combined HAP emissions are effectively limited to less than 10 tons and 25 tons per year, respectively, by limiting the total VOC emissions from K001, K002 and K003.

B. Operational Restrictions

1. The maximum annual coating usage for K003 shall not exceed 952 gallons, based upon a rolling, 12-month summation of the coating usage figures.
2. The maximum annual cleanup material usage for K003 shall not exceed 730 gallons, based upon a rolling, 12-month summation of the cleanup material usage figures.
3. The permittee shall not employ more than 10 gallons of coatings per day in this emissions unit, pursuant to 3745-21-09(U)(2)(e)(ii).

C. Monitoring and/or Record Keeping Requirements

1. The permittee shall maintain monthly records of the following information for this emissions unit:
 - a. The coating usage for each month.
 - b. The cleanup material usage for each month.
 - c. The rolling, 12-month summation of the coating usage figures.
 - d. The rolling, 12-month summation of the cleanup material usage figures.
 - e. The individual HAP and total combined HAP content of each coating and cleanup material employed.
2. The permittee shall collect and record the following information on a monthly basis for this emissions unit:
 - a. the name and identification of each type of coating and cleanup material employed;
 - b. the VOC content of each type of coating and cleanup material employed (excluding water and exempt solvents), as applied, in pounds per gallon;
 - c. the VOC content of each type of coating and cleanup material employed, in pounds per gallon;
 - d. the number of gallons of each type of coating and cleanup material employed;
 - e. the number of gallons of each type of cleanup material drummed for shipment off site;
 - f. the total VOC emissions from all coatings and cleanup materials employed, in tons, i.e., the sum of the emissions for all the coatings and cleanup materials employed minus the potential emissions associated with the amount of cleanup material drummed for shipment off site; and

g. the rolling 12-month summation of the total VOC emissions from all the coatings and cleanup materials employed, in tons.

3. The permittee shall maintain daily records of the total gallons of each coating employed and the total gallons of all coatings employed.

D. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports which identify all exceedances of the rolling, 12-month usage limitations for coatings and cleanup materials and all exceedances of the rolling, 12-month emission limitation for VOC emissions. These reports are due by the dates described in Part 1 - General Terms and Conditions of this permit under section A.1.
2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any monthly record showing that the VOC content of any coating and/or cleanup material exceeded the applicable limitation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 45 days after the exceedance occurs.
3. The permittee shall submit annual reports which specify the total VOC emissions, total emissions of each individual HAP, total coating usage, and total cleanup material usage for K001 for the previous calendar year. These reports shall be submitted by January 31 of each year and shall include the emission calculations.
4. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of each daily record showing that the coatings usage exceeded the 10 gpd usage limitation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 45 days after the exceedance occurs.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

Emission limitation:

The yearly VOC emissions for K003 shall not exceed 5.0 tons per year.

Applicable Compliance Method:

Compliance with the 5.0 tons per year shall be determined by the record keeping requirements specified in Section C.2.

Emission Limitation:

5.2 pounds VOC per gallon of coating, excluding water and exempt solvents.

Applicable Compliance Method:

Compliance shall be based upon the record keeping requirements specified in Section C.2. In accordance with OAC rule 3745-21-04(B)(5), USEPA Method 24 shall be used to determine the VOC contents of the coatings. If, pursuant to section 4.3 of Method 24, 40 CFR Part 60, Appendix A, an owner or operator determines that Method 24 cannot be used for a particular coating, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24.

Emission Limitation:

6.8 pounds VOC per gallon of cleanup material, excluding water and exempt solvents.

Applicable Compliance Method:

Compliance shall be based upon the record keeping requirements specified in Section C.2. Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound contents of the cleanup materials.

F. Miscellaneous Requirements

1. Pursuant to OAC rule 3745-35-07, the following terms and conditions of this permit are federally enforceable: A - F.