



Environmental Protection Agency

John R. Kasich, Governor
Mary Taylor, Lt. Governor
Scott J. Nally, Director

3/8/2011

Mr. Mark Connor, Sr.
Toledo Fiber Products Corp.
2959 Nebraska Ave.
Toledo, OH 43608

RE: FINAL AIR POLLUTION PERMIT-TO-INSTALL AND OPERATE
Facility ID: 0448011909
Permit Number: P0107657
Permit Type: Initial Installation
County: Lucas

Certified Mail

No	TOXIC REVIEW
No	PSD
No	SYNTHETIC MINOR TO AVOID MAJOR NSR
No	CEMS
No	MACT/GACT
No	NSPS
No	NESHAPS
No	NETTING
No	MAJOR NON-ATTAINMENT
No	MODELING SUBMITTED
No	SYNTHETIC MINOR TO AVOID TITLE V
No	FEDERALLY ENFORCABLE PTIO (FEPTIO)

Dear Permit Holder:

Enclosed please find a final Air Pollution Permit-to-Install and Operate (PTIO) which will allow you to install, modify, and/or operate the described emissions unit(s) in the manner indicated in the permit. Because this permit contains conditions and restrictions, please read it very carefully. Please complete a survey at www.epa.ohio.gov/dapc/permitsurvey.aspx and give us feedback on your permitting experience. We value your opinion.

The issuance of this PTI is a final action of the Director and may be appealed to the Environmental Review Appeals Commission pursuant to Section 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. The appeal must be filed with the Commission within thirty (30) days after notice of the Director's action. The appeal must be accompanied by a filing fee of \$70.00, made payable to "Ohio Treasurer Josh Mandel," which the Commission, in its discretion, may reduce if by affidavit you demonstrate that payment of the full amount of the fee would cause extreme hardship. Notice of the filing of the appeal shall be filed with the Director within three (3) days of filing with the Commission. Ohio EPA requests that a copy of the appeal be served upon the Ohio Attorney General's Office, Environmental Enforcement Section. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
309 South Fourth Street, Room 222
Columbus, OH 43215

If you have any questions, please contact Toledo Department of Environmental Services at (419)936-3015 or the Office of Compliance Assistance and Pollution Prevention at (614) 644-3469. This permit can be accessed electronically on the DAPC Web page, www.epa.ohio.gov/dapc, by clicking the "Issued Air Pollution Control Permits" link.

Sincerely,

Michael W. Ahern, Manager
Permit Issuance and Data Management Section, DAPC

Cc: TDES



FINAL

**Division of Air Pollution Control
Permit-to-Install and Operate
for
Toledo Fiber Products Corp.**

Facility ID:	0448011909
Permit Number:	P0107657
Permit Type:	Initial Installation
Issued:	3/8/2011
Effective:	3/8/2011
Expiration:	3/8/2021



Division of Air Pollution Control
Permit-to-Install and Operate
for
Toledo Fiber Products Corp.

Table of Contents

Authorization 1
A. Standard Terms and Conditions 3
1. What does this permit-to-install and operate ("PTIO") allow me to do?..... 4
2. Who is responsible for complying with this permit? 4
3. What records must I keep under this permit? 4
4. What are my permit fees and when do I pay them?..... 4
5. When does my PTIO expire, and when do I need to submit my renewal application? 4
6. What happens to this permit if my project is delayed or I do not install or modify my source? 5
7. What reports must I submit under this permit? 5
8. If I am required to obtain a Title V operating permit in the future, what happens to the operating provisions and PER obligations under this permit? 5
9. What are my obligations when I perform scheduled maintenance on air pollution control equipment? ... 5
10. Do I have to report malfunctions of emissions units or air pollution control equipment? If so, how must I report? 5
11. Can Ohio EPA or my local air agency inspect the facility where the emission unit(s) is/are located? 6
12. What happens if one or more emissions units operated under this permit is/are shut down permanently? 6
13. Can I transfer this permit to a new owner or operator?..... 6
14. Does compliance with this permit constitute compliance with OAC rule 3745-15-07, "air pollution nuisance"? 7
15. What happens if a portion of this permit is determined to be invalid? 7
B. Facility-Wide Terms and Conditions..... 8
C. Emissions Unit Terms and Conditions 10
1. P901, FL#1 11



Authorization

Facility ID: 0448011909
Application Number(s): A0041308
Permit Number: P0107657
Permit Description: Toledo Fiber Products Corp. -Fiber Line #1: Material handling controlled by full enclosure with bag filters. Emissions unit P901 includes fiber preparation, lay-down, resin impregnation, natural gas fired curing oven (4.0 MMBtu/hr capacity) and cooling table.
Permit Type: Initial Installation
Permit Fee: \$500.00
Issue Date: 3/8/2011
Effective Date: 3/8/2011
Expiration Date: 3/8/2021
Permit Evaluation Report (PER) Annual Date: Jan 1 - Dec 31, Due Feb 15

This document constitutes issuance to:

Toledo Fiber Products Corp.
1245 E. Manhattan Blvd.
Toledo, OH 43608

of a Permit-to-Install and Operate for the emissions unit(s) identified on the following page.


Ohio EPA District Office or local air agency responsible for processing and administering your permit:

Toledo Department of Environmental Services
348 South Erie Street
Toledo, OH 43604
(419)936-3015

The above named entity is hereby granted this Permit-to-Install and Operate for the air contaminant source(s) (emissions unit(s)) listed in this section pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the described emissions unit(s) will operate in compliance with applicable State and federal laws and regulations.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency


Scott J. Nally
Director



Authorization (continued)

Permit Number: P0107657
Permit Description: Toledo Fiber Products Corp. -Fiber Line #1: Material handling controlled by full enclosure with bag filters. Emissions unit P901 includes fiber preparation, lay-down, resin impregnation, natural gas fired curing oven (4.0 MMBtu/hr capacity) and cooling table.

Permits for the following Emissions Unit(s) or groups of Emissions Units are in this document as indicated below:

Emissions Unit ID:	P901
Company Equipment ID:	FL#1
Superseded Permit Number:	
General Permit Category and Type:	Not Applicable



A. Standard Terms and Conditions

1. What does this permit-to-install and operate ("PTIO") allow me to do?

This permit allows you to install and operate the emissions unit(s) identified in this PTIO. You must install and operate the unit(s) in accordance with the application you submitted and all the terms and conditions contained in this PTIO, including emission limits and those terms that ensure compliance with the emission limits (for example, operating, recordkeeping and monitoring requirements).

2. Who is responsible for complying with this permit?

The person identified on the "Authorization" page, above, is responsible for complying with this permit until the permit is revoked, terminated, or transferred. "Person" means a person, firm, corporation, association, or partnership. The words "you," "your," or "permittee" refer to the "person" identified on the "Authorization" page above.

The permit applies only to the emissions unit(s) identified in the permit. If you install or modify any other equipment that requires an air permit, you must apply for an additional PTIO(s) for these sources.

3. What records must I keep under this permit?

You must keep all records required by this permit, including monitoring data, test results, strip-chart recordings, calibration data, maintenance records, and any other record required by this permit for five years from the date the record was created. You can keep these records electronically, provided they can be made available to Ohio EPA during an inspection at the facility. Failure to make requested records available to Ohio EPA upon request is a violation of this permit requirement.

4. What are my permit fees and when do I pay them?

There are two fees associated with permitted air contaminant sources in Ohio:

- PTIO fee. This one-time fee is based on a fee schedule in accordance with Ohio Revised Code (ORC) section 3745.11, or based on a time and materials charge for permit application review and permit processing if required by the Director.

You will be sent an invoice for this fee after you receive this PTIO and payment is due within 30 days of the invoice date. You are required to pay the fee for this PTIO even if you do not install or modify your operations as authorized by this permit.

- Annual emissions fee. Ohio EPA will assess a separate fee based on the total annual emissions from your facility. You self-report your emissions in accordance with Ohio Administrative Code (OAC) Chapter 3745-78. This fee assessed is based on a fee schedule in ORC section 3745.11 and funds Ohio EPA's permit compliance oversight activities. Unless otherwise specified, facilities subject to one or more synthetic minor restrictions must use Ohio EPA's "Air Services" to submit annual emissions associated with this permit requirement. Ohio EPA will notify you when it is time to report your emissions and to pay your annual emission fees.

5. When does my PTIO expire, and when do I need to submit my renewal application?

This permit expires on the date identified at the beginning of this permit document (see "Authorization" page above) and you must submit a renewal application to renew the permit. Ohio EPA will send a renewal notice to you approximately six months prior to the expiration date of this permit. However, it is very important that you submit a complete renewal permit application (postmarked prior to expiration of this permit) even if you do not receive the renewal notice.

If a complete renewal application is submitted before the expiration date, Ohio EPA considers this a timely application for purposes of ORC section 119.06, and you are authorized to continue operating the emissions unit(s) covered by this permit beyond the expiration date of this permit until final action is taken by Ohio EPA on the renewal application.

6. What happens to this permit if my project is delayed or I do not install or modify my source?

This PTIO expires 18 months after the issue date identified on the "Authorization" page above unless otherwise specified if you have not (1) started constructing the new or modified emission sources identified in this permit, or (2) entered into a binding contract to undertake such construction. This deadline can be extended by up to 12 months, provided you apply to Ohio EPA for this extension within a reasonable time before the 18-month period has ended and you can show good cause for any such extension.

7. What reports must I submit under this permit?

An annual permit evaluation report (PER) is required in addition to any malfunction reporting required by OAC rule 3745-15-06 or other specific rule-based reporting requirement identified in this permit. Your PER due date is identified in the Authorization section of this permit.

8. If I am required to obtain a Title V operating permit in the future, what happens to the operating provisions and PER obligations under this permit?

If you are required to obtain a Title V permit under OAC Chapter 3745-77 in the future, the permit-to-operate portion of this permit will be superseded by the issued Title V permit. From the effective date of the Title V permit forward, this PTIO will effectively become a PTI (permit-to-install) in accordance with OAC rule 3745-31-02(B). The following terms and conditions will no longer be applicable after issuance of the Title V permit: Section B, Term 1.b) and Section C, for each emissions unit, Term a)(2).

The PER requirements in this permit remain effective until the date the Title V permit is issued and is effective, and cease to apply after the effective date of the Title V permit. The final PER obligation will cover operations up to the effective date of the Title V permit and must be submitted on or before the submission deadline identified in this permit on the last day prior to the effective date of the Title V permit.

9. What are my obligations when I perform scheduled maintenance on air pollution control equipment?

You must perform scheduled maintenance of air pollution control equipment in accordance with OAC rule 3745-15-06(A). If scheduled maintenance requires shutting down or bypassing any air pollution control equipment, you must also shut down the emissions unit(s) served by the air pollution control equipment during maintenance, unless the conditions of OAC rule 3745-15-06(A)(3) are met. Any emissions that exceed permitted amount(s) under this permit (unless specifically exempted by rule) must be reported as deviations in the annual permit evaluation report (PER), including nonexempt excess emissions that occur during approved scheduled maintenance.

10. Do I have to report malfunctions of emissions units or air pollution control equipment? If so, how must I report?

If you have a reportable malfunction of any emissions unit(s) or any associated air pollution control system, you must report this to the Toledo Department of Environmental Services in accordance with

OAC rule 3745-15-06(B). Malfunctions that must be reported are those that result in emissions that exceed permitted emission levels. It is your responsibility to evaluate control equipment breakdowns and operational upsets to determine if a reportable malfunction has occurred.

If you have a malfunction, but determine that it is not a reportable malfunction under OAC rule 3745-15-06(B), it is recommended that you maintain records associated with control equipment breakdown or process upsets. Although it is not a requirement of this permit, Ohio EPA recommends that you maintain records for non-reportable malfunctions.

11. Can Ohio EPA or my local air agency inspect the facility where the emission unit(s) is/are located?

Yes. Under Ohio law, the Director or his authorized representative may inspect the facility, conduct tests, examine records or reports to determine compliance with air pollution laws and regulations and the terms and conditions of this permit. You must provide, within a reasonable time, any information Ohio EPA requests either verbally or in writing.

12. What happens if one or more emissions units operated under this permit is/are shut down permanently?

Ohio EPA can terminate the permit terms associated with any permanently shut down emissions unit. "Shut down" means the emissions unit has been physically removed from service or has been altered in such a way that it can no longer operate without a subsequent "modification" or "installation" as defined in OAC Chapter 3745-31.

You should notify Ohio EPA of any emissions unit that is permanently shut down by submitting¹ a certification that identifies the date on which the emissions unit was permanently shut down. The certification must be submitted by an authorized official from the facility. You cannot continue to operate an emissions unit once the certification has been submitted to Ohio EPA by the authorized official.

You must comply with all recordkeeping and reporting for any permanently shut down emissions unit in accordance with the provisions of the permit, regulations or laws that were enforceable during the period of operation, such as the requirement to submit a PER, air fee emission report, or malfunction report. You must also keep all records relating to any permanently shutdown emissions unit, generated while the emissions unit was in operation, for at least five years from the date the record was generated.

Again, you cannot resume operation of any emissions unit certified by the authorized official as being permanently shut down without first applying for and obtaining a permit pursuant to OAC Chapter 3745-31.

13. Can I transfer this permit to a new owner or operator?

You can transfer this permit to a new owner or operator. If you transfer the permit, you must follow the procedures in OAC Chapter 3745-31, including notifying Ohio EPA or the local air agency of the change in ownership or operator. Any transferee of this permit must assume the responsibilities of the transferor permit holder.

¹ Permittees that use Ohio EPA's "Air Services" can mark the affected emissions unit(s) as "permanently shutdown" in the facility profile along with the date the emissions unit(s) was permanently removed and/or disabled. Submitting the facility profile update will constitute notifying of the permanent shutdown of the affected emissions unit(s).

14. Does compliance with this permit constitute compliance with OAC rule 3745-15-07, "air pollution nuisance"?

This permit and OAC rule 3745-15-07 prohibit operation of the air contaminant source(s) regulated under this permit in a manner that causes a nuisance. Ohio EPA can require additional controls or modification of the requirements of this permit through enforcement orders or judicial enforcement action if, upon investigation, Ohio EPA determines existing operations are causing a nuisance.

15. What happens if a portion of this permit is determined to be invalid?

If a portion of this permit is determined to be invalid, the remainder of the terms and conditions remain valid and enforceable. The exception is where the enforceability of terms and conditions are dependent on the term or condition that was declared invalid.

B. Facility-Wide Terms and Conditions

1. This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).
 - a) For the purpose of a permit-to-install document, the facility-wide terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (1) None.
 - b) For the purpose of a permit-to-operate document, the facility-wide terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (1) None.

C. Emissions Unit Terms and Conditions



1. P901, FL#1

Operations, Property and/or Equipment Description:

Fiber Line #1: Material handling controlled by full enclosure with bag filters. Emissions unit P901 includes fiber preparation, lay-down, resin impregnation, natural gas fired curing oven (4.0 MMBtu/hr capacity) and cooling table.

a) This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

(1) For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.

a. b)(1)f., b)(2)h., d)(3) through d)(6), e)(1), f)(1)g., and f)(2)

(2) For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.

a. None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
	Material handling, controlled by full enclosure with a baghouse	
a.	OAC rule 3745-31-05(A)(3), As effective 11/30/01	Particulate emissions (PE) from the material handling system baghouse shall not exceed 0.98 pound per hour and 4.29 tons per year. Visible emissions of fugitive dust shall not exceed 10% opacity as a 3-minute average.
b.	OAC rule 3745-17-07(B)	See b)(2)i.
c.	OAC rule 3745-17-08(B)	See b)(2)c. through b)(2)f.
d.	OAC rule 3745-31-05(A)(3)(a)(ii)	See b)(2)b.
	Semi-cure (preheat) oven, steam heated, utilizing low VOC materials	

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
e.	OAC rule 3745-31-05(A)(3), As effective 11/30/01	<p>PE from the semi-cure oven stack shall not exceed 0.0543 pound per hour and 0.238 ton per year.</p> <p>Carbon Monoxide (CO) from the semi-cure oven stack shall not exceed 0.33 pound per hour and 1.45 ton per year.</p> <p>Nitrogen Oxides (NO_x) from the semi-cure oven stack shall not exceed 0.39 pound per hour and 1.71 ton per year.</p> <p>Sulfur Dioxide (SO₂) from the semi-cure oven stack shall not exceed 0.0024 pound per hour and 0.01 ton per year.</p> <p>Volatile Organic Compounds (VOC) from the semi-cure oven stack shall not exceed 0.506 pound per hour and 2.216 ton per year.</p> <p>Visible emissions from the semi-cure oven stack shall not exceed 10% opacity as a 6-minute average.</p>
f.	ORC 3704.03(F)(4)(c)	See b)(2)h.
g.	OAC rule 3745-17-07(A)(1)	See b)(2)i.
h.	OAC rule 3745-17-11(B)(1)	See b)(2)g.
i.	OAC rule 3745-31-05(A)(3)(a)(ii), As effective 12/01/06	See b.(2)b.

(2) Additional Terms and Conditions

- a. The permittee has satisfied the Best Available Technology (BAT) requirements pursuant to OAC paragraph 3745-31-05(A)(3), as effective November 30, 2001, in this permit. On December 1, 2006, paragraph (A)(3) of OAC rule 3745-31-05 was revised to conform to ORC changes effective August 3, 2006 (S.B. 265 changes), such that BAT is no longer required by State regulations for NAAQS pollutant less than ten tons per year. However, that rule revision has not been approved by U.S. EPA as a revision to Ohio's State Implementation Plan (SIP). Therefore, until the SIP revision occurs and the U.S. EPA approves the revisions to OAC rule 3745-31-05, the requirement to satisfy BAT still exists as part of the federally-approved SIP for Ohio. Once U.S. EPA approves the December 1,



2006 version of OAC rule 3745-31-05, then these emission limits/control measures no longer apply.

The following terms and conditions shall become void after U.S. EPA approves the rule revision: b)(1)a., b)(1)e., b)(2)a., f)(1)a., and f)(1)c. through f)(1)f.

- b. This rule paragraph applies once U.S. EPA approves the December 1, 2006 version of OAC rule 3745-31-05 as part of the State Implementation Plan.

The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the carbon monoxide (CO), nitrogen oxides (NOx), particulate emissions (PE), sulfur dioxide (SO2) and volatile organic compounds (VOC) emissions from this air contaminant source since the uncontrolled potential to emit for CO, NOx, PE, SO2, and VOC is less than ten tons per year.

- c. The material handling operation(s) that are covered by this permit and subject to the requirements of OAC rules 3745-17-07 and 3745-17-08 are listed below:

Fiber line material handling.

- d. The permittee shall employ reasonably available control measures for the above-identified material handling operation(s) for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to perform the following control measure(s) to ensure compliance:

<u>material handling operation(s)</u>	<u>control measure(s)</u>
fiber line material handling	full enclosure with baghouse inherent to the process

Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

- e. For each material handling operation that is not adequately enclosed, the above-identified control measure(s) shall be implemented if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measure(s) is (are) necessary to ensure compliance with the above-mentioned applicable requirements. Any required implementation of the control measure(s) shall continue during the operation of the material handling operation(s) until further observation confirms that use of the control measure(s) is unnecessary.
- f. Implementation of the above-mentioned control measure(s) in accordance with the terms and conditions of this permit is appropriate and sufficient to satisfy the requirements of OAC rule 3745-17-08 and OAC rule 3745-31-05.
- g. Particulate emissions from this emissions unit shall not exceed 5.1 pounds per hour.
- h. In order to demonstrate compliance with the "Toxic Air Contaminant Statute", the Director has established, per ORC 3704.03(F)(4)(c), a limit for formaldehyde emissions, which shall not exceed 5.45 pound(s) per day from the semi-cure

oven stack. This daily allowable emissions rate was calculated by multiplying the approved daily operating schedule submitted in the permit application, by the emission rate modeled (to determine the ground level concentration).

- i. Visible particulate emissions from the stack(s) serving this emissions unit shall not exceed twenty opacity as a six-minute average, except as provided by rule.
- j. Visible emissions of fugitive dust from this emissions unit shall not exceed twenty percent opacity as a three-minute average.

c) Operational Restrictions

- (1) The permittee shall operate the material handling system baghouse whenever this emissions unit is in operation.

d) Monitoring and/or Recordkeeping Requirements

- (1) The permittee shall maintain daily records that document any time periods when the material handling system baghouse was not in service when the emissions unit was in operation.
- (2) The permittee shall perform daily checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the stack and for any visible emissions of fugitive dust from the egress points (i.e., building windows, doors, roof monitors, etc.) serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:
 - a. The location and color of the emissions;
 - b. Whether the emissions are representative of normal operations;
 - c. If the emissions are not representative of normal operations, the cause of the abnormal emissions;
 - d. The total duration of any visible emissions incident; and
 - e. Any corrective actions taken to minimize or eliminate the visible emissions.

If visible emissions are present, a visible emissions incident has occurred. The observer does not have to document the exact start and end times for the visible emissions incident under item (d) above or continue the daily check until the incident has ended. The observer may indicate that the visible emissions incident was continuous during the observation period (or, if known, continuous during the operation of the emissions unit). With respect to the documentation of corrective actions, the observer may indicate that no corrective actions were taken if the visible emissions were representative of normal operations, or specify the minor corrective actions that were taken to ensure that the emissions unit continued to operate under normal conditions, or specify the corrective actions that were taken to eliminate abnormal visible emissions.

- (3) Emission unit P901 was evaluated based on the actual materials and the design parameters of the emissions unit's) exhaust system, as specified by the permittee in the permit application. The "Toxic Air Contaminant Statute", ORC 3704.03(F), was applied

to this/these emissions unit(s) for each toxic air contaminant listed in OAC rule 3745-114-01, using data from the permit application; and modeling was performed for each toxic air contaminant(s) emitted using an air dispersion model SCREEN 3.0. The predicted 1-hour maximum ground-level concentration result(s) from the approved air dispersion model, was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC), calculated as described in the Ohio EPA guidance document entitled "Review of New Sources of Air Toxic Emissions, Option A", as follows:

- a. The exposure limit, expressed as a time-weighted average concentration for a conventional 8-hour workday and a 40-hour workweek, for each toxic compound(s) emitted from the emissions unit(s), (as determined from the raw materials processed and/or coatings or other materials applied) has been documented from one of the following sources and in the following order of preference (TLV was and shall be used, if the chemical is listed):
 - i. Threshold limit value (TLV) from the American Conference of Governmental Industrial Hygienists' (ACGIH) "Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices"; or
 - ii. STEL (short term exposure limit) or the ceiling value from the American Conference of Governmental Industrial Hygienists' (ACGIH) "Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices"; the STEL or ceiling value is multiplied by 0.737 to convert the 15-minute exposure limit to an equivalent 8-hour TLV.
- b. The TLV is divided by ten to adjust the standard from the working population to the general public (TLV/10).
- c. This standard is/was then adjusted to account for the duration of the exposure or the operating hours of the emissions unit(s), i.e., "24" hours per day and "7" days per week, from that of 8 hours per day and 5 days per week. The resulting calculation was (and shall be) used to determine the Maximum Acceptable Ground-Level Concentration (MAGLC):

$$TLV/10 \times 8/24 \times 5/7 = TLV/42 = MAGLC$$

- d. The following summarizes the results of dispersion modeling for the significant toxic contaminants or "worst case" toxic contaminant(s):

Toxic Contaminant: formaldehyde

TLV (mg/m³): 0.27

Maximum Hourly Emission Rate (lbs/hr): 0.226

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 6.41

MAGLC (ug/m³): 6.47

Having demonstrated that emissions of formaldehyde, from emissions unit P901, is estimated to be equal or greater than eighty per cent, but less than 100 per

cent of the maximum acceptable ground level concentration (MAGLC), shall not operate the emissions unit(s) at a rate that would exceed the daily emissions rate, process weight rate, and/or restricted hours of operations, as allowed in this permit; and any new raw material or processing agent shall not be applied without evaluating each component toxic air contaminant in accordance with the "Toxic Air Contaminant Statute", ORC 3704.03(F).

- (4) Prior to making any physical changes to or changes in the method of operation of the emissions unit(s), that could impact the parameters or values that were used in the predicted 1-hour maximum ground-level concentration", the permittee shall re-model the change(s) to demonstrate that the MAGLC has not been exceeded. Changes that can affect the parameters/values used in determining the 1-hour maximum ground-level concentration include, but are not limited to, the following:
- a. Changes in the composition of the materials used or the use of new materials, that would result in the emission of a new toxic air contaminant with a lower Threshold Limit Value (TLV) than the lowest TLV previously modeled;
 - b. Changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any toxic air contaminant listed in OAC rule 3745-114-01, that was modeled from the initial (or last) application;
 - c. Physical changes to the emissions unit(s) or its/their exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Toxic Air Contaminant Statute", ORC 3704.03(F), will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to a non-restrictive change to a parameter or process operation, where compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), has been documented. If the change(s) meet(s) the definition of a "modification", or if a new toxic is emitted, or the modeled toxic(s) is/are expected to exceed the previous modeled level(s), then the permittee shall apply for and obtain a final permit-to-install prior to the change. The Director may consider any significant departure from the operations of the emissions unit, described in the permit-to-install application, as a modification that results in greater emissions than the emissions rate modeled to determine the ground level concentration; and may require the permittee to submit a permit-to-install application for the increased emissions.

- (5) The permittee shall collect, record, and retain the following information for each toxic evaluation conducted to determine compliance with the "Toxic Air Contaminant Statute":
- a. A description of the parameters/values used in each compliance demonstration and the parameters or values changed for any re-evaluation of the toxic(s) modeled (the composition of materials, new toxic contaminants emitted, change in stack/exhaust parameters, etc.);
 - b. The Maximum Acceptable Ground-Level Concentration (MAGLC) for each significant toxic contaminant or worst-case contaminant, calculated in accordance with the "Toxic Air Contaminant Statute", ORC 3704.03(F);

- c. A copy of the computer model run(s), that established the predicted 1-hour maximum ground-level concentration that demonstrated the emissions unit(s) to be in compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), initially and for each change that requires re-evaluation of the toxic air contaminant emissions; and
 - d. The documentation of the initial evaluation of compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), and documentation of any determination that was conducted to re-evaluate compliance due to a change made to the emissions unit(s) or the materials applied.
 - (6) The permittee shall maintain a record of any change made to a parameter or value used in the dispersion model, used to demonstrate compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), through the predicted 1-hour maximum ground-level concentration. The record shall include the date and reason(s) for the change and if the change would increase the ground-level concentration.
- e) Reporting Requirements
 - (1) The permittee shall include in the annual Permit Evaluation Report (PER) any exceedance of the daily limitation on toxic air emissions or any deviation from a restriction on the process or hours of operation, as established by the Director, in order to maintain any toxic air contaminant below its MAGLC. The permittee shall also include in the PER any changes made, during the calendar year, to a parameter or value entered into the dispersion model that was used to maintain compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), through the predicted 1-hour maximum ground-level concentration. If no changes to the emissions, emissions unit(s), or the exhaust stack have been made, then the report shall include a statement to this effect.
 - (2) The permittee shall identify the following information in the annual permit evaluation report in accordance with the monitoring requirements for visible emissions in term number d)(2) above:
 - a. All days during which any visible particulate emissions were observed from the stack serving this emissions unit;
 - b. All days during which any visible emissions of fugitive dust were observed from the egress points (i.e., building windows, doors, roof monitors, etc.) serving this emissions unit; and
 - c. Any corrective actions taken to minimize or eliminate the visible particulate emissions from the stack and/or visible emissions of fugitive dust.
 - (3) Annual Permit Evaluation Report (PER) forms will be mailed to the permittee at the end of the reporting period specified in the Authorization section of this permit. The permittee shall submit the PER in the form and manner provided by the director by the due date identified in the Authorization section of this permit. The PER shall cover a reporting period of no more than twelve-months for each air contaminant source identified in this permit.

f) Testing Requirements

(1) Compliance with the limitation(s) in b) of these terms and conditions shall be determined in accordance with the following method(s):

a. Emission Limitation:

10% opacity as a six minute average (semi-cure oven stack)

Applicable Compliance Method:

If required, compliance shall be determined through visible emission observations performed in accordance with Method 9 of 40 CFR Part 60, Appendix A using the methods and procedures specified in OAC rule 3745-17-03(B)(1).

b. Emission Limitation:

20% opacity as a six minute average (semi-cure oven stack)

Applicable Compliance Method:

If required, compliance shall be determined through visible emission observations performed in accordance with Method 9 of 40 CFR Part 60, Appendix A using the methods and procedures specified in OAC rule 3745-17-03(B)(1).

c. Emission Limitation:

PE shall not exceed 0.98 pound per hour (material handling system baghouse)

Applicable Compliance Method:

If required, the permittee shall demonstrate compliance with this emission limitation through emission testing performed in accordance with Methods 1 thru 5 of 40 CFR Part 60 Appendix A using the methods and procedures specified in OAC rule 3745-17-03(B)(10).

d. Emission Limitation:

PE shall not exceed 4.29 tons per year (material handling system baghouse)

Applicable Compliance Method:

This emission limitation was developed by multiplying the hourly allowable particulate emission limitation (0.98 lb/hr) by the maximum annual hours of operation (8760 hrs), and then dividing by 2000 lbs/ton. Therefore, if compliance is shown with the hourly limitation, compliance shall also be shown with the annual emission limitation.

e. Emission Limitation:

PE shall not exceed 0.0543 pound per hour (semi-cure oven stack)

Applicable Compliance Method:

If required, the permittee shall demonstrate compliance with this emission limitation through emission testing performed in accordance with Methods 1 thru 5 of 40 CFR Part 60 Appendix A using the methods and procedures specified in OAC rule 3745-17-03(B)(10).

f. Emission Limitation:

PE shall not exceed 0.238 ton per year (semi-cure oven stack)

Applicable Compliance Method:

This emission limitation was developed by multiplying the hourly allowable particulate emission limitation (0.0543 lb/hr) by the maximum annual hours of operation (8760 hrs), and then dividing by 2000 lbs/ton. Therefore, if compliance is shown with the hourly limitation, compliance shall also be shown with the annual emission limitation.

g. Emission Limitation:

Formaldehyde emissions from the semi-cure oven stack shall not exceed 5.45 pound(s) per day.

Applicable Compliance Method:

Compliance may be demonstrated by the following one-time calculation. Multiply the formaldehyde emission factor supplied by the permittee (8.1E-05 lb/lb) by the maximum hourly production rate (2800 lb/hr), and multiply by the maximum daily hours of operation (24 hours/day) to obtain the maximum daily formaldehyde emission rate.

If required, the permittee shall determine a site-specific emission factor using Methods 1 through 4 of 40 CFR Part 60, Appendix A and Method 316 of 40 CFR Part 63, Appendix A. Alternative U.S. EPA approved test methods may be used with prior written approval from the Ohio EPA.

h. Emission Limitation:

Visible emissions of fugitive dust from the material handling system shall not exceed 10% opacity as a 3-minute average. Visible emissions of fugitive dust shall not exceed 20% opacity as a 3-minute average.

Applicable Compliance Method:

Compliance with the limitation for visible emissions of fugitive dust shall be determined through visible emissions observations performed in accordance U.S. EPA Method 9 and the procedures specified in OAC rule 3745-17-03(B)(3).

i. Emission Limitation:

PE shall not exceed 5.1 pounds per hour (semi-cure oven stack).

Applicable Compliance Method:

If required, the permittee shall demonstrate compliance using Methods 1 through 5 of 40 CFR Part 60, Appendix A. Alternative U.S. EPA approved test methods may be used with prior written approval from the Ohio EPA.

(2) The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:

- a. The emission testing shall be conducted within 60 days after achieving the maximum production rate at which the emissions unit will be operated, but not later than 180 days after initial startup of the emissions unit.
- b. The emission testing shall be conducted to determine a site-specific emission factor for formaldehyde emissions.
- c. The following test method(s) shall be employed to demonstrate compliance with the allowable mass emission rate(s):

Methods 1 through 4 of 40 CFR Part 60, Appendix A and Method 316 of 40 CFR Part 63, Appendix A. Alternative U.S. EPA approved test methods may be used with prior approval from the Ohio EPA.

- d. The test(s) shall be conducted while the emissions unit is operating at or near its maximum capacity and using resin containing the highest formaldehyde content that will be used, unless otherwise specified or approved by the appropriate Ohio EPA District Office or local air agency.
- e. Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the appropriate Ohio EPA District Office or local air agency. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA District Office's or local air agency's refusal to accept the results of the emission test(s).
- f. Personnel from the appropriate Ohio EPA District Office or local air agency shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.
- g. During the emission test, the permittee shall record the average temperature of the semi-cure oven and the resin application rate in pounds per hour for each test run, and include this information in the written test report. A copy of the resin formulation data that includes the free formaldehyde content shall also be included in the written test report.

- h. A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the appropriate Ohio EPA District Office or local air agency within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the appropriate Ohio EPA District Office or local air agency.
- g) Miscellaneous Requirements
 - (1) None.