



State of Ohio Environmental Protection Agency

**RE: FINAL PERMIT TO INSTALL  
WOOD COUNTY**

**CERTIFIED MAIL**

Street Address:

122 S. Front Street

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center  
P.O. Box 1049

**Application No: 03-13300**

**Fac ID: 0387000259**

**DATE: 10/5/2006**

Evergreen Recycling and Disposal Facilit  
Karen Dolliver  
2625 East Broadway  
Northwood, OH 43619

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action of the Director is final and may be appealed to the Environmental Review Appeals Commission pursuant to Section 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. The appeal must be filed with the Commission within thirty (30) days after notice of the Director's action. The appeal must be accompanied by a filing fee of \$70.00 which the Commission, in its discretion, may reduce if by affidavit you demonstrate that payment of the full amount of the fee would cause extreme hardship. Notice of the filing of the appeal shall be filed with the Director within three (3) days of filing with the Commission. Ohio EPA requests that a copy of the appeal be served upon the Ohio Attorney General's Office, Environmental Enforcement Section. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission  
309 South Fourth Street, Room 222  
Columbus, OH 43215

Sincerely,

*Michael W. Ahern*

Michael W. Ahern, Manager  
Permit Issuance and Data Management Section  
Division of Air Pollution Control

CC: USEPA

NWDO



STATE OF OHIO ENVIRONMENTAL PROTECTION AGENCY

**FINAL PERMIT TO INSTALL 03-13300**

Application Number: 03-13300  
Facility ID: 0387000259  
Permit Fee: **\$800**  
Name of Facility: Evergreen Recycling and Disposal Facilit  
Person to Contact: Karen Dolliver  
Address: 2625 East Broadway  
Northwood, OH 43619

Location of proposed air contaminant source(s) [emissions unit(s)]:  
**2625 East Broadway  
Northwood, Ohio**

Description of proposed emissions unit(s):  
**Municipal solid waste landfill with active gas flare system.**

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency



Director

## Part I - GENERAL TERMS AND CONDITIONS

### A. State and Federally Enforceable Permit-To-Install General Terms and Conditions

#### 1. Monitoring and Related Recordkeeping and Reporting Requirements

- a. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall maintain records that include the following, where applicable, for any required monitoring under this permit:
  - i. The date, place (as defined in the permit), and time of sampling or measurements.
  - ii. The date(s) analyses were performed.
  - iii. The company or entity that performed the analyses.
  - iv. The analytical techniques or methods used.
  - v. The results of such analyses.
  - vi. The operating conditions existing at the time of sampling or measurement.
- b. Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.
- c. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall submit required reports in the following manner:
  - i. Reports of any required monitoring and/or recordkeeping of federally enforceable information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
  - ii. Quarterly written reports of (i) any deviations from federally enforceable emission limitations, operational restrictions, and control device operating parameter limitations, excluding deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06, that have been detected by the testing, monitoring and recordkeeping requirements specified in this permit, (ii) the probable cause of such deviations, and (iii) any corrective actions or preventive measures taken, shall be made to

**Evergreen Recycling and Disposal Facility**  
**PTI Application: 03-13300**  
**Issued: 10/5/2006**

**Facility ID: 0387000259**

the appropriate Ohio EPA District Office or local air agency. The written reports shall be submitted (i.e., postmarked) quarterly, by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. See B.9 below if no deviations occurred during the quarter.

- iii. Written reports, which identify any deviations from the federally enforceable monitoring, recordkeeping, and reporting requirements contained in this permit shall be submitted (i.e., postmarked) to the appropriate Ohio EPA District Office or local air agency every six months, by January 31 and July 31 of each year for the previous six calendar months. If no deviations occurred during a six-month period, the permittee shall submit a semi-annual report, which states that no deviations occurred during that period.
  - iv. If this permit is for an emissions unit located at a Title V facility, then each written report shall be signed by a responsible official certifying that, based on information and belief formed after reasonable inquiry, the statements and information in the report are true, accurate, and complete.
- d. The permittee shall report actual emissions pursuant to OAC Chapter 3745-78 for the purpose of collecting Air Pollution Control Fees.

## **2. Scheduled Maintenance/Malfunction Reporting**

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction, i.e., upset, of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. (The definition of an upset condition shall be the same as that used in OAC rule 3745-15-06(B)(1) for a malfunction.) The verbal and written reports shall be submitted pursuant to OAC rule 3745-15-06.

Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emission unit(s) that is (are) served by such control system(s).

## **3. Risk Management Plans**

If the permittee is required to develop and register a risk management plan pursuant to section 112(r) of the Clean Air Act, as amended, 42 U.S.C. 7401 et seq. ("Act"), the permittee shall comply with the requirement to register such a plan.

#### 4. Title IV Provisions

If the permittee is subject to the requirements of 40 CFR Part 72 concerning acid rain, the permittee shall ensure that any affected emissions unit complies with those requirements. Emissions exceeding any allowances that are lawfully held under Title IV of the Act, or any regulations adopted thereunder, are prohibited.

#### 5. Severability Clause

A determination that any term or condition of this permit is invalid shall not invalidate the force or effect of any other term or condition thereof, except to the extent that any other term or condition depends in whole or in part for its operation or implementation upon the term or condition declared invalid.

#### 6. General Requirements

- a. The permittee must comply with all terms and conditions of this permit. Any noncompliance with the federally enforceable terms and conditions of this permit constitutes a violation of the Act, and is grounds for enforcement action or for permit revocation, revocation and re-issuance, or modification
- b. It shall not be a defense for the permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the federally enforceable terms and conditions of this permit.
- c. This permit may be modified, revoked, or revoked and reissued, for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or revocation, or of a notification of planned changes or anticipated noncompliance does not stay any term and condition of this permit.
- d. This permit does not convey any property rights of any sort, or any exclusive privilege.
- e. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying or revoking this permit or to determine compliance with this permit. Upon request, the permittee shall also furnish to the Director or an authorized representative of the Director, copies of records required to be kept by this permit. For information claimed to be confidential in the submittal to the Director, if the Administrator of the U.S. EPA requests such information, the permittee may furnish such records directly to the Administrator along with a claim of confidentiality.

**Evergreen Recycling and Disposal Facility**  
**PTI Application: 03-13300**  
**Issued: 10/5/2006**

**Facility ID: 0387000259**

## **7. Fees**

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable permit-to-install fees within 30 days after the issuance of any permit-to-install. The permittee shall pay all applicable permit-to-operate fees within thirty days of the issuance of the invoice.

## **8. Federal and State Enforceability**

Only those terms and conditions designated in this permit as federally enforceable, that are required under the Act, or any its applicable requirements, including relevant provisions designed to limit the potential to emit of a source, are enforceable by the Administrator of the U.S. EPA and the State and by citizens (to the extent allowed by section 304 of the Act) under the Act. All other terms and conditions of this permit shall not be federally enforceable and shall be enforceable under State law only.

## **9. Compliance Requirements**

- a. Any document (including reports) required to be submitted and required by a federally applicable requirement in this permit shall include a certification by a responsible official that, based on information and belief formed after reasonable inquiry, the statements in the document are true, accurate, and complete.
- b. Upon presentation of credentials and other documents as may be required by law, the permittee shall allow the Director of the Ohio EPA or an authorized representative of the Director to:
  - i. At reasonable times, enter upon the permittee's premises where a source is located or the emissions-related activity is conducted, or where records must be kept under the conditions of this permit.
  - ii. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit, subject to the protection from disclosure to the public of confidential information consistent with ORC section 3704.08.
  - iii. Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit.

**Evergreen Recycling and Disposal Facility**  
**PTI Application: 03-13300**  
**Issued: 10/5/2006**

**Facility ID: 0387000259**

- iv. As authorized by the Act, sample or monitor at reasonable times substances or parameters for the purpose of assuring compliance with the permit and applicable requirements.
- c. The permittee shall submit progress reports to the appropriate Ohio EPA District Office or local air agency concerning any schedule of compliance for meeting an applicable requirement. Progress reports shall be submitted semiannually, or more frequently if specified in the applicable requirement or by the Director of the Ohio EPA. Progress reports shall contain the following:
  - i. Dates for achieving the activities, milestones, or compliance required in any schedule of compliance, and dates when such activities, milestones, or compliance were achieved.
  - ii. An explanation of why any dates in any schedule of compliance were not or will not be met, and any preventive or corrective measures adopted.

#### **10. Permit-To-Operate Application**

- a. If the permittee is required to apply for a Title V permit pursuant to OAC Chapter 3745-77, the permittee shall submit a complete Title V permit application or a complete Title V permit modification application within twelve (12) months after commencing operation of the emissions units covered by this permit. However, if the proposed new or modified source(s) would be prohibited by the terms and conditions of an existing Title V permit, a Title V permit modification must be obtained before the operation of such new or modified source(s) pursuant to OAC rule 3745-77-04(D) and OAC rule 3745-77-08(C)(3)(d).
- b. If the permittee is required to apply for permit(s) pursuant to OAC Chapter 3745-35, the source(s) identified in this permit is (are) permitted to operate for a period of up to one year from the date the source(s) commenced operation. Permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the source(s) covered by this permit.

#### **11. Best Available Technology**

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

**Evergreen Recycling and Disposal Facilit**  
**PTI Application: 03-13300**  
**Issued: 10/5/2006**

**Facility ID: 0387000259**

**12. Air Pollution Nuisance**

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

**Evergreen Recycling and Disposal Facility**  
**PTI Application: 03-13300**  
**Issued: 10/5/2006**

**Facility ID: 0387000259**

### **13. Permit-To-Install**

A permit-to-install must be obtained pursuant to OAC Chapter 3745-31 prior to "installation" of "any air contaminant source" as defined in OAC rule 3745-31-01, or "modification", as defined in OAC rule 3745-31-01, of any emissions unit included in this permit.

## **B. State Only Enforceable Permit-To-Install General Terms and Conditions**

### **1. Compliance Requirements**

The emissions unit(s) identified in this Permit shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

### **2. Reporting Requirements**

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping of state-only enforceable information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from state-only required emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted (i.e., postmarked) quarterly, by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

### **3. Permit Transfers**

Any transferee of this permit shall assume the responsibilities of the prior permit holder.

**Evergreen Recycling and Disposal Facilit**  
**PTI Application: 03-13300**  
**Issued: 10/5/2006**

**Facility ID: 0387000259**

The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

**Evergreen Recycling and Disposal Facility**  
**PTI Application: 03-13300**  
**Issued: 10/5/2006**

**Facility ID: 0387000259**

**4. Authorization To Install or Modify**

If applicable, authorization to install or modify any new or existing emissions unit included in this permit shall terminate within eighteen months of the effective date of the permit if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

**5. Construction of New Sources(s)**

This permit does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. This permit does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the application and terms and conditions of this permit. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of this permit does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Issuance of this permit is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

**6. Public Disclosure**

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

**7. Applicability**

This Permit to Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate application must be made to the Director for the installation or modification of any other emissions unit(s).

**8. Construction Compliance Certification**

Evergreen Recycling and Disposal Facilit  
 PTI Application: 03-13300  
 Issued: 10/5/2006

Facility ID: 0387000259

If applicable, the applicant shall provide Ohio EPA with a written certification (see enclosed form if applicable) that the facility has been constructed in accordance with the permit-to-install application and the terms and conditions of the permit-to-install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

**9. Additional Reporting Requirements When There Are No Deviations of Federally Enforceable Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations (See Section A of This Permit)**

If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly (i.e., postmarked), by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters.

**C. Permit-To-Install Summary of Allowable Emissions**

SUMMARY (for informational purposes only)  
 TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
NMOC (fugitive)	56.10
Methane (fugitive)	8745.00
PE (fugitive)	374.23
Carbon Monoxide	234.20
Nitrogen Oxides	43.06
Sulfur Dioxide	9.46
NMOC (flare)	3.37
Methane (flare)	524.70
PE (flare)	10.77
HCl (flare)	4.56

**Evergreen Recycling and Disposal Facilit**  
**PTI Application: 03-13300**  
**Issued: 10/5/2006**

**Facility ID: 0387000259**

**Part II - FACILITY SPECIFIC TERMS AND CONDITIONS**

**A. State and Federally Enforceable Permit To Install Facility Specific Terms and Conditions**

None

**B. State Only Enforceable Permit To Install Facility Specific Terms and Conditions**

None

**Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. State and Federally Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
F005 - paved and unpaved roadways and parking areas	OAC rule 3745-31-05 (A)(3)	194.51 tons fugitive particulate emissions (PE)/year
paved roadways and parking areas (See A.I.2.a.)	OAC rule 3745-31-05 (A)(3)	There shall be no visible PE except for one minute during any 60-minute period.
	OAC rule 3745-17-07 (B)	best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (See A.I.2.c, and A.I.2.e through A.I.2.i.)
	OAC rule 3745-17-08 (A)	See A.I.2.j.
	OAC rule 3745-17-08 (A)	See A.I.2.k.
unpaved roadways and parking areas (See A.I.2.b.)	OAC rule 3745-31-05 (A)(3)	There shall be no visible PE except for three minutes during any 60-minute period.
	OAC rule 3745-17-07 (B)	best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (See A.I.2.d through A.I.2.i.)
	OAC rule 3745-17-08 (A)	See A.I.2.j.
		See A.I.2.k.

15

**Everg**

**PTI A**

**Issued: 10/5/2006**

Emissions Unit ID: **F005**

## 2. Additional Terms and Conditions

- 2.a** The paved roadways and parking areas that are covered by this permit and subject to the above-mentioned requirements are listed below:

paved roadways:

all paved roadway segments

paved parking areas:

all paved parking areas

- 2.b** The unpaved roadways and parking areas that are covered by this permit and subject to the above-mentioned requirements are listed below:

unpaved roadways:

all unpaved roadway segments

unpaved parking areas:

all unpaved parking areas

- 2.c** The permittee shall employ best available control measures on all paved roadways and parking areas for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to treat the paved roadways and parking areas by watering and sweeping at sufficient treatment frequencies to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

- 2.d** The permittee shall employ best available control measures on all unpaved roadways and parking areas for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to treat the unpaved roadways and parking areas by watering at sufficient treatment frequencies to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

- 2.e** The needed frequencies of implementation of the control measures shall be determined by the permittee's inspections pursuant to the monitoring section of this permit. Implementation of the control measures shall not be necessary for a paved or unpaved roadway or parking area that is covered with snow and/or ice

or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Implementation of any control measure may be suspended if unsafe or hazardous driving conditions would be created by its use.

- 2.f** Any unpaved roadway or parking area, which during the term of this permit is paved or takes the characteristics of a paved surface due to the application of certain types of dust suppressants, may be controlled with the control measure(s) specified above for paved surfaces. Any unpaved roadway or parking area that takes the characteristics of a paved roadway or parking area due to the application of certain types of dust suppressants shall remain subject to the visible emission limitation for unpaved roadways and parking areas. Any unpaved roadway or parking area that is paved shall be subject to the visible emission limitation for paved roadways and parking areas.
- 2.g** The permittee shall promptly remove, in such a manner as to minimize or prevent resuspension, earth and/or other material from paved streets onto which such material has been deposited by trucking or earth moving equipment or erosion by water or other means.
- 2.h** Open-bodied vehicles transporting materials likely to become airborne shall have such materials covered at all times if the control measure is necessary for the materials being transported.
- 2.i** Implementation of the above-mentioned control measures in accordance with the terms and conditions of this permit is appropriate and sufficient to satisfy the best available technology requirements of OAC rule 3745-31-05.
- 2.j** This emissions unit is exempt from the visible particulate emission limitations specified in OAC rule 3745-17-07 (B) pursuant to OAC rule 3745-17-07 (B)(11)(e).
- 2.k** The permittee is not located within an "Appendix A" area as identified in OAC rule 3745-17-08. Therefore, pursuant to OAC rule 3745-17-08 (A), this emissions unit is exempt from the requirements of OAC rule 3745-17-08 (B).

## II. Operational Restrictions

None



each calendar quarter.

#### **IV. Reporting Requirements**

1. The permittee shall submit deviation reports, in accordance with the General Terms and Conditions of this permit, that identify any of the following occurrences:
  - a. each day during which an inspection was not performed by the required frequency, excluding an inspection which was not performed due to an exemption for snow and/or ice cover or precipitation; and
  - b. each instance when a control measure, that was to be implemented as a result of an inspection, was not implemented.

## V. Testing Requirements

1. Compliance with the emission limitations specified in A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

- a. Emission Limitation:  
194.51 tons fugitive PE/year

Applicable Compliance Method:

The emission limitation was established by summing the total, uncontrolled emissions from paved and unpaved roadways and parking areas and applying a 90%\* control efficiency for use of best available control measures.

The permittee may demonstrate compliance as follows:

- i. for paved roadways and parking areas, multiply the appropriate emission factor from AP-42, Chapter 13.2.1.2 (revised 12/03) by the maximum vehicle miles traveled; and
- ii. for unpaved roadways and parking areas, multiply the appropriate emission factor from AP-42, Chapter 13.2.2.2 (revised 12/03) by the maximum vehicle miles traveled.

Therefore, provided compliance is shown with the requirements of this permit to apply best available control measures, compliance with the annual limitation will be assumed.

\*Compliance with the visible emission restrictions through the application of best available control measures represents a control efficiency equivalent to 90%.

- b. Emission Limitation:  
There shall be no visible particulate emissions from the paved roadways and parking areas except for one minute during any 60-minute period.

Applicable Compliance Method:

If required, compliance with the visible PE limitation listed above shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 2002, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(d) of OAC rule 3745-17-03.

**Evergreen Recycling and Disposal Facility**  
**PTI Application: 02-12200**  
**Issue**

**Facility ID: 0387000259**

**Emissions Unit ID: F005**

- c. Emission Limitation:  
There shall be no visible particulate emissions from the unpaved roadways and parking areas except for three minutes during any 60-minute period

**Everg****PTI A****Issued: 10/5/2006**Emissions Unit ID: **F005**Applicable Compliance Method:

If required compliance with the visible PE limitation listed above shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 2002 , and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(d) of OAC rule 3745-17-03.

**VI. Miscellaneous Requirements**

1. The issuance of this permit (PTI #03-13300) does not authorized the permittee to engage in any activity associated with expansion of the current Evergreen Recycling and Disposal Facility until permit approval has been issued by the Ohio EPA, Division of Solid and Infectious Waste Management (through the final issuance of PTI #03-15314) allowing for a vertical expansion.

**B. State Only Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
F005 - paved and unpaved roadways and parking areas	None	None

**2. Additional Terms and Conditions**

**2.a** None

**II. Operational Restrictions**

None

**III. Monitoring and/or Recordkeeping Requirements**

None

**IV. Reporting Requirements**

None

**V. Testing Requirements**

None

**VI. Miscellaneous Requirements**

None

24

**Everg**

**PTI A**

**Issued: 10/5/2006**

Emissions Unit ID: **F005**

**Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. State and Federally Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>
P901 - municipal solid waste and asbestos landfill with active gas collection, open flare, and associated material handling operations, temporary storage/stock piles, and temporary, unpaved construction roadways	OAC rule 3745-31-05 (A)(3)
	OAC rule 3745-17-07 (B)(1)

Emissions Unit ID: P901

	Applicable Emissions Limitations/Control Measures	(NO <sub>x</sub> )/hour; 43.06 tons NO <sub>x</sub> /year
OAC rule 3745-17-08 (B)		
40 CFR, Part 61, Subpart M	See A.I.2.a.	2.16 pounds sulfur dioxide (SO <sub>2</sub> )/hour;
40 CFR Part 60, Subpart WWW	<u>Passive/Fugitive Emissions:</u> 56.10 tons fugitive nonmethane organic compounds (NMOC)/year  8,745.00 tons fugitive methane/year	9.46 tons SO <sub>2</sub> /year  2.46 pounds PE/hour; 10.77 tons PE/year (See A.I.2.q.)  1.04 pound hydrogen chloride (HCl)/hour;
40 CFR, Part 63, Subpart AAAA	179.72 tons fugitive particulate emissions (PE)/year	4.56 tons HCl/year
	Visible fugitive PE shall not exceed 20% opacity, as a three-minute average from operations not associated with asbestos-containing material (ACM).	See A.I.2.r.
	best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (See A.I.2.b through A.I.2.e.)	See A.I.2.s.
	See A.I.2.f through A.I.2.m for requirements and limitations associated with ACM.	See A.I.2.t.
	<u>Flare Emissions:</u> 0.77 pound NMOC/hour; 3.37 tons NMOC/year  119.795 pounds methane/hour; 524.70 tons methane/year  53.47 pounds carbon monoxide (CO)/hour; 234.20 tons CO/year  9.83 pounds nitrogen oxides	See A.I.2.m through A.I.2.p, A.II.1 through A.II.6, A.III.1 through A.III.8, A.IV.1 through A.IV.6.  See A.IV.3 and A.VI.5 through A.VI.12.

## **2. Additional Terms and Conditions**

**2.a** The requirements of this rule include compliance with the terms and conditions of this permit. The requirements of this rule also include compliance with the requirements of 40 CFR Part 60, Subpart WWW and 40 CFR Part 63, Subpart AAAA.

**2.b** The landfill fugitive dust operations/sources that are covered by this permit and subject to the requirements of OAC rule 3745-31-05 are listed below:

- i. waste dumping/unloading
- ii. waste compaction
- iii. soil excavation and handling
- iv. temporary storage/stock piles
- v. temporary unpaved construction roadways

**2.c** The permittee shall employ best available control measures for the above-identified landfill fugitive dust operations/sources for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to treat with water and/or any other suitable dust suppression chemicals at sufficient treatment frequencies in order to ensure compliance.

**2.d** The above-mentioned control measures shall be employed if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measures are necessary to ensure compliance with the above-mentioned applicable requirements. Any required implementation of the control measures shall continue during any such operation until further observation confirms that use of the measures is unnecessary.

Implementation of the control measures shall not be necessary for fugitive dust sources which are covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements.

**2.e** Implementation of the above-mentioned control measures in accordance with the

terms and conditions of this permit is appropriate and sufficient to satisfy the requirements of OAC rule 3745-31-05.

- 2.f** There shall be no visible emissions from asbestos-containing waste materials (ACM) during on-site transportation, transfer, deposition, or compacting operations.
- 2.g** The permittee shall inspect each load of ACM delivered to the facility. The inspection shall consist of a visual examination to ensure that each shipment of ACM is received intact, leak-tight containers labeled with appropriate hazard warning labels, the name of the generator, and the location of waste generation. The inspection also shall determine whether the waste shipment records accompany the consignment and accurately describe the waste material and quantity.

If on the basis of the inspection, the waste material is found to be improperly received, the load shall be disposed of in accordance with the procedures in the "Asbestos Spill Contingency Plan", and the discrepancy shall be noted on the waste shipment record.

- 2.h** Deposition and burial operations shall be conducted in a manner which prevents handling by equipment or persons that causes asbestos-containing waste materials to be broken up or dispersed before the materials are buried.
- 2.i** The permittee shall cover and compact asbestos wastes in accordance with the following:
- i. As soon as practicable after the placement of friable asbestos, but no later than the end of each working day, the asbestos-containing waste materials deposited at the site during the operating day shall be covered with at least 12 inches of non-ACM. Once the ACM are covered, the area may be compacted.
  - ii. Care should be taken to ensure that disposed asbestos shall not be re-excavated in subsequent operations. Any accidentally exposed material shall be immediately recovered in accordance with the provisions of condition i above.
  - iii. ACM shall be separated from the landfill final grade by no less than 24 inches of compacted non-ACM and a permanent cover of vegetation, or in

Emissions Unit ID: P901

accordance with current requirements for closure, whichever is more stringent.

- 2.j** The permittee shall implement and maintain an "Asbestos Disposal Operating Procedure and Spill Contingency Plan" ("Plan") consisting of; authorized personnel training, inspection and disposal operating procedures, non-conforming load response procedures, inventory and maintenance procedures for safety and emissions control equipment, record keeping procedures, and emergency notification procedures. Authorized personnel shall be knowledgeable in the procedures, and the Plan shall be available for inspection at this facility at all times.
- 2.k** Emissions control equipment shall be available for wetting and containing asbestos in the event of a release or non-conforming load disposal. All equipment required to implement the Plan shall be maintained in accordance with good engineering practices to ensure that the equipment is in a ready-to-use condition and in an appropriate location for use.
- 2.l** The permittee shall establish restricted access, adequate to deter the unauthorized entry of the general public and any unauthorized personnel, within 100 feet of the unloading, deposition, and burial areas of the asbestos-containing waste material. A hazard warning shall display the following information on signs not less than 20 x 14 inches in size, posted so they are visible before entering an area with asbestos waste disposal operations in progress:

"ASBESTOS WASTE DISPOSAL SITE  
DO NOT CREATE DUST  
BREATHING ASBESTOS IS HAZARDOUS TO YOUR HEALTH"

The letter sizes and styles shall be of a visibility at least equal to the following specifications: one inch sans serif, gothic or block in the first and second line; and at least three-fourths inches sans serif, gothic or block in the third line; and fourteen point gothic in the fourth line. Spacing between any two lines must be at least equal to the height of the upper two lines.

- 2.m** The active gas collection system shall satisfy the following requirements, as specified in 40 CFR Part 60.752(b)(2)(ii)(A):
- i. The system shall be designed to handle the maximum expected gas flow rate from the entire area of the landfill that warrants control over the intended use period of the gas control or treatment system equipment.
  - ii. The system shall collect gas from each area, cell, or group of cells in the landfill in which the initial solid waste has been placed for a period of 5 years or more if active, or 2 years or more if closed or at final grade.
  - iii. The system shall collect gas at a sufficient extraction rate.
  - iv. The system shall be designed to minimize off-site migration of subsurface gas.
- 2.n** Except as provided in A.1.2.o, any collected gas shall be vented to an open flare designed and operated as follows:
- i. The flare shall be designed for and operated with no visible emissions, except for periods of time not to exceed a total of 5 minutes during any 2 consecutive hours.
  - ii. The flare shall be operated with a flame present at all times.
  - iii. The permittee shall comply with either the requirements in paragraphs (a) and (b) or the requirements in paragraph (c):

Emissions Unit ID: P901

- (a) Flares shall be used only with the net heating value of the gas being combusted being 11.2 MJ/scm (300 BTU/scf) or greater if the flare is steam-assisted or air-assisted; or with the net heating value of the gas being combusted being 7.45 MJ/scm (200 BTU/scf) or greater if the flare is non-assisted. The net heating value of the gas being combusted shall be determined as follows:

where

Ht = net heating value of the sample, MJ/scm; where the net enthalpy per mole of off-gas is based on combustion at 25°C and 760 mmHg, but the standard temperature for determining the volume corresponding to one mole is 20°C;

K = constant,  $1.740 \times 10^{-7}$  (1/ppm)(g mole/scm)(MJ/kcal)  
 where the standard temperature for (g mole/scm) is 20°C;

Ci = concentration of sample component i in ppm on a wet basis, as measured for organics by Reference Method 18 and measured for hydrogen and carbon monoxide by ASTM D1946-77; and

Hi = net heat of combustion of sample component i, kcal/g mole at 25°C and 760 mmHg. The heats of combustion may be determined using ASTM D2382-76 (incorporated by reference as specified in 40 CFR Part 60.17) if published values are not available or cannot be calculated.

- (b) A steam-assisted and non-assisted flare shall be designed for and operated with an exit velocity of less than 18.3 m/sec (60 ft/sec), except:
- (i) steam-assisted and non-assisted flares designed for and operated with an exit velocity equal to or greater than 18.3 m/sec but less than 122 m/sec (400 ft/sec) are allowed if the net heating value of the gas being combusted is greater than 37.3 MJ/scm (1,000 BTU/scf); and
  - (ii) steam-assisted and non-assisted flares designed for and operated with an exit velocity of less than the velocity, Vmax, and less than 122 m/sec (400 ft/sec) are allowed, as determined by the following equation:

$$\text{Log}_{10} (V_{\text{max}}) = (\text{HT} + 28.8)/31.7$$

where

$V_{max}$  = maximum permitted velocity, M/sec

28.8 = constant

31.7 = constant

HT = net heating value as determined in section A.I.2.n.iii(a) above

- (iii) Flares shall be used that have a diameter of 3 inches or greater, are non-assisted, have a hydrogen content of 8.0 percent (by volume) or greater, and are designed for and operated with an exit velocity less than 37.2 m/sec (122 ft/sec) and less than the velocity,  $V_{max}$ , as determined by the following equation:

$$V_{max} = (X_{H_2} - K_1) * K_2$$

where

$V_{max}$  = maximum permitted velocity, m/sec

$K_1$  = constant, 6.0 volume-percent hydrogen

$K_2$  = constant, 3.9(m/sec)/volume-percent hydrogen

$X_{H_2}$  = volume-percent of hydrogen, on a wet basis, as calculated by using the American Society for Testing and Materials (ASTM) Method D1946-77.

- (c) Air-assisted flares shall be designed and operated with an exit velocity less than the velocity,  $V_{max}$ , as determined by the following equation:

$$V_{max} = 8.706 + 0.7084 (HT)$$

where

$V_{max}$  = maximum permitted velocity, m/sec

8.706 = constant

0.7084 = constant

HT = net heating value as determined in section A.I.2.n.iii(a) above

- 2.o** All collected gas shall comply with at least one of the following requirements:
- i. The collected gas may be routed to a flare designed and operated in accordance with the requirements in Section A.I.2.n.  
  
AND/OR
  - ii. The collected gas may be routed to a control system designed and operated to reduce NMOC by 98 weight-percent, or, when an enclosed combustion device is used for control, to either reduce NMOC by 98 weight percent or reduce the outlet NMOC concentration to less than 20 parts per million by volume, dry basis as hexane at 3 percent oxygen. If a boiler or process heater is used as the control device, the landfill gas stream shall be introduced into the flame zone.  
  
AND/OR
  - iii. The collected gas may be routed to a treatment system that processes the collected gas for subsequent sale or use. All emissions from any atmospheric vent from the gas treatment system shall meet subject to the requirements of 40 CFR 60.752(b)(2)(iii) (A) or (B).
- 2.p** The collection and control system may be capped or removed provided that all of the following conditions are met, as specified in 40 CFR Part 60.752(b)(2)(v):
- i. The landfill shall no longer be accepting solid waste and be permanently closed, pursuant to 40 CFR Part 60.258.60.
  - ii. The collection and control system shall have been in operation a minimum of 15 years.
  - iii. The calculated NMOC gas produced by the landfill shall be less than 55 tons per year on three successive test dates. The test dates shall be no less than 90 days apart, and no more than 180 days apart.
- 2.q** All particulate emissions from the flare are assumed to be particulate matter less than 10 microns in size (PM<sub>10</sub>).
- 2.r** This emissions unit is exempt from the visible particulate emission limitations

Emissions Unit ID: P901

specified in OAC rule 3745-17-07 (B) pursuant to OAC rule 3745-17-07 (B)(11)(e).

- 2.s** This facility is not located within an "Appendix A" area as identified in OAC rule 3745-17-08. Therefore, pursuant to OAC rule 3745-17-08 (A), this emissions unit is exempt from the requirements of OAC rule 3745-17-08 (B).
- 2.t** The requirements established pursuant to this rule are less stringent or equivalent to the requirements of OAC rule 3745-31-05 (A)(3).

## **II. Operational Restrictions**

1. The permittee shall operate the collection system with negative pressure at each well except under the following conditions:
  - a. a fire or increased well temperature (the permittee shall record instances when positive pressure occurs in efforts to avoid a fire);
  - b. use of a geomembrane or synthetic cover (the permittee shall develop acceptable pressure limits in the design plan); and
  - c. a decommissioned well (A well may experience a static positive pressure after shutdown to accommodate for declining flows. All design changes shall be approved by the Northwest District Office).
2. The permittee shall operate each interior well in the collection system with a landfill gas temperature less than 55 degrees Celsius and with either a nitrogen level less than 20% or an oxygen level less than 5%. If a well exceeds one of these operating parameters, action shall be initiated to correct the exceedance within 5 calendar days. If correction of the exceedance cannot be achieved within 15 calendar days of the first measurement, the gas collection system shall be expanded to correct the exceedance within 120 days of the initial exceedance. Any attempted corrective measure shall not cause exceedances of other operational or performance standards. An alternative timeline for correcting the exceedance may be submitted to the Northwest District Office.

The permittee may establish a higher operating temperature, nitrogen, or oxygen value at a particular well. A higher operating value demonstration shall show supporting data that the elevated parameter does not cause fires or significantly inhibit anaerobic decomposition by killing methanogens.

3. The permittee shall operate the collection system so that the methane concentration is less than 500 parts per million above background at the surface of the landfill. For

exceedances, refer to section A.III.2.d.

4. The permittee shall operate the collection system such that all collected gases are vented to a control system designed and operated in compliance with Conditions A.I.2.m and A.I.2.n. In the event the collection or control system is inoperable, the gas mover system shall be shut down and all valves in the collection and control system contributing to venting of the gas to the atmosphere shall be closed within one hour.
5. The permittee shall operate the flare at all times when the collected gas is routed to the system.
6. A pilot flame shall be maintained at all times in the flare's pilot burner, or a fail-close valve shall be installed to cease gas flow to the flare when there is no flame present.

### **III. Monitoring and/or Recordkeeping Requirements**

1. For the active gas collection system, the permittee shall install a sampling port for each well and record the following information on a monthly basis:
  - a. the gauge pressure in the gas collection header at each individual well;
  - b. the nitrogen or oxygen concentration in the landfill gas; and
  - c. the temperature of the landfill gas.
2. The permittee shall monitor surface concentrations of methane on a quarterly basis as follows:
  - a. The surface concentrations of methane shall be monitored along the entire perimeter of the collection area and along a serpentine pattern spaced 30 meters apart (or a site-specific established spacing) for each collection area.
  - b. The background concentration shall be determined by moving the probe inlet upwind and downwind outside the boundary of the landfill at a distance of at least 30 meters from the perimeter wells.
  - c. Surface emission monitoring shall be performed in accordance with section 4.3.1 or Method 21 of Appendix A of 40 CFR Part 60, except that the probe inlet shall be placed within 5 to 10 centimeters of the ground. Monitoring shall be performed during typical meteorological conditions.

- d. Any reading of 500 parts per million or more above background at any location shall be recorded as a monitored exceedance and the actions specified below shall be taken. As long as the specified actions are taken, the exceedance is not a violation of the operational requirement listed in Section A.II.3:
  - i. The location of each monitored exceedance shall be marked and the location recorded.
  - ii. Cover maintenance or adjustments to the vacuum of the adjacent wells to increase the gas collection in the vicinity of each exceedance shall be made and the location shall be remonitored within 10 calendar days of detecting the exceedance.
  - iii. If the remonitoring of the location shows a second exceedance, additional corrective action shall be taken and the location shall be monitored again within 10 days of the second exceedance. If the remonitoring shows a third exceedance for the same location, a new well or other collection device shall be installed within 120 calendar days of the initial exceedance. An alternative remedy to the exceedance, such as upgrading the blower, header pipes, or control device, and a corresponding time line for installation may be submitted to the Ohio EPA for approval. No further monitoring of that location is required until the action specified has been taken.
  - iv. Any location that initially showed an exceedance but has methane concentration less than 500 ppm methane above background at the 10-day remonitoring specified above shall be remonitored 1 month from the initial exceedance. If the 1-month remonitoring shows a concentration less than 500 parts per million above background, no further monitoring of that location is required until the next quarterly monitoring period. If the 1-month remonitoring shows an exceedance, the actions specified above shall be taken.
3. The permittee shall install, calibrate, maintain, and operate the following equipment in accordance with the manufacturer's specifications:
  - a. a heat sensing device, such as an ultraviolet beam sensor or thermocouple, at the pilot light or the flame itself to indicate the continuous presence of a flame; and
  - b. a device that records flow to or bypass of the flare. The permittee shall either:
    - i. calibrate and maintain a gas flow rate measuring device that shall record

the flow to the flare at least every 15 minutes; or

- ii. secure the bypass line valve in the closed position with a car-seal or a lock-and-key type configuration. A visual inspection of the seal or closure mechanism shall be performed at least once every month to ensure that the valve is maintained in the closed position and that the gas flow is not diverted through the bypass line.

4. The permittee shall maintain the following information for the life of the control equipment as measured during the initial performance test or compliance demonstration:

- a. the maximum expected gas generation flow rate as calculated based on the following:

- i. For sites with unknown year-to-year solid waste acceptance rate:

$$Q_m = 2L_oR(e^{-kc} - e^{-kt})$$

where,

$Q_m$  = maximum expected gas generation flow rate, cubic meters per year  
 $L_o$  = methane generation potential, cubic meters per megagram solid waste

$R$  = average annual acceptance rate, megagrams per year

$k$  = methane generation rate constant, year<sup>-1</sup>

$t$  = age of the landfill at equipment installation plus the time the owner or operator intends to use the gas mover equipment or active life of the landfill, whichever is less (if the equipment is installed after closure,  $t$  is the age of the landfill at installation, years)

$c$  = time since closure, years (for an active landfill  $c = 0$  and  $e^{-kc} = 1$ )

- ii. For sites with known year-to-year solid waste acceptance rate:

.

where,

$Q_m$  = maximum expected gas generation flow rate, cubic meters per year

$k$  = methane generation rate constant, per year

$L_o$  = methane generation potential, cubic meters per megagram solid

Emissions Unit ID: P901

waste

$M_i$  = mass of solid waste in the  $i^{\text{th}}$  section, megagrams

$t_i$  = age of the  $i^{\text{th}}$  section, years

- iii. If a collection and control system has been installed, actual flow data may be used to project the maximum expected gas generation flow rate instead of, or in conjunction with, the equations in paragraphs A.III.4.a.i. and A.III.4.a.ii. If the landfill is still accepting waste, the actual measure flow data will not equal the maximum expected gas generation rate, so calculations using the equations in Sections A.III.4.a.i or A.III.4.a.ii or other methods shall be used to predict the maximum expected gas generation rate over the intended period of use of the gas control system equipment. The permittee may use another method to determine the maximum gas generation flow rate if the method has been approved by the Ohio EPA.
  - b. the density of wells, horizontal collectors, surface collectors, or other gas extraction devices determined using the procedures specified in 40 CFR Part 60.759 (a)(1);
  - c. the flare type (i.e., steam-assisted, air-assisted, or non-assisted);
  - d. all visible emission readings;
  - e. heat content determinations of the gas;
  - f. flow rate or bypass flow rate measurements;
  - g. exit velocity determinations made during the performance test as specified in 40 CFR Part 60.18; and
  - h. continuous records of the flare flame monitoring and all periods of operation during which the flare flame is absent.
5. The permittee shall properly install, operate, and maintain a device to continuously monitor the flare flame when the emissions unit is in operation. The monitoring device and any recorder shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manuals. In addition, the permittee shall record the following information each day:
  - a. all periods of time during which there was no flame; and
  - b. the downtime for the flare and monitoring equipment when the collection and control systems are in operation.

6. The permittee shall maintain, for the life of the collection system, an up-to-date, readily accessible, plot map showing each existing and planned collector in the system and providing a unique identification location for each collector.
7. The permittee shall keep for at least 5 years, up-to-date, readily accessible, on-site records of (a) the maximum design capacity of the landfill, (b) the current amount of solid waste in place, and (c) the year-by-year waste acceptance rate. Off-site records may be maintained if they are retrievable within 4 hours. Either hard copy or electronic formats are acceptable. These records may also be required by the Ohio EPA, Division of Solid and Infectious Waste Management, and shall satisfy this permit condition.
8. The permittee shall conduct surface testing around the perimeter of the collection area along a pattern that traverses the landfill at 30-meter intervals and where visual observations indicate elevated concentrations of landfill gas, such as distressed vegetation and cracks or seeps in the cover.
9. The permittee shall maintain a waste shipment record for all ACM. The waste shipment record shall be legible, complete, signed and dated by the waste generator and waste disposal site operator, and shall include the following information:
  - a. the name of the work site or facility where the asbestos-containing waste was generated and the mailing address and telephone number of the facility owner;
  - b. the name, mailing address, and telephone number of the owner or operator (waste generator) responsible for handling, packing, marking, and labeling the asbestos-containing waste material;
  - c. the name, mailing address, telephone number, and site location of the active waste disposal site designated by the generator to receive the asbestos-containing waste material for disposal;
  - d. the name and address of the local, state, or U.S. EPA regional office responsible for administering the asbestos NESHAP program;
  - e. a description of the asbestos-containing waste materials included in the waste shipment;
  - f. the number and type of containers included in the waste shipment;

Emissions Unit ID: P901

- g. the approximate volume of asbestos-containing waste material included in the waste shipment, in cubic yards;
- h. special handling instructions or additional information relative to the waste shipment the generator may specify;
- i. a certification that the contents of the consignment are fully and accurately described by proper shipping name and are classified, packed, marked, and labeled, and are in all respects in proper condition for transport by highway according to applicable international and governmental regulations;
- j. the name, address, and telephone number of the transporter;
- k. a signature by the transporter to acknowledge receipt of the asbestos-containing waste shipment described by the waste generator in section A.III.9.a through A.III.9.j;
- l. a discrepancy indication space to be completed by the transporter or waste shipment owner or operator if any improperly contained asbestos waste is observed or if there is any discrepancy in the quantity of asbestos shipped and the quantity of asbestos waste received at the asbestos waste disposal site; and
- m. a signature by the waste disposal site operator to acknowledge receipt of the asbestos-containing waste shipment described by the waste generator in section A.III.9.a through A.III.9.i, except as noted in the discrepancy indication space.

As soon as possible, and no longer than thirty days after receipt of the waste, the original, completed copy of the signed waste shipment record shall be sent to the waste generator. The remaining copy shall be retained for the waste site disposal record.

- 10. The permittee shall maintain records of the (a) location, (b) depth, (c) area, and (d) quantity, in cubic yards, of all asbestos-containing waste material within the disposal site on a map or a diagram of the disposal area.
- 11. Except as otherwise provided in this section, the permittee shall perform inspections of the landfill fugitive dust operations/sources in accordance with the following frequencies:

<u>landfill fugitive dust operations/sources</u>	<u>minimum inspection frequency</u>
waste dumping/unloading operation	once during each day of
waste compaction operation	once during each day of

Issued: 10/5/2006

soil excavation and handling operation	once	during	each	day	of
wind erosion from landfill surfaces and stockpiles operation	once	during	each	day	of
temporary unpaved construction roadways operation	once	during	each	day	of

12. The purpose of the inspections is to determine the need for implementing best available control measures for particulate emissions. The inspections shall be performed during representative, normal operating conditions. No inspection shall be necessary for a landfill fugitive dust operation/source that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Any required inspection that is not performed due to any of the above identified events shall be performed as soon as such event(s) has (have) ended, except if the next inspection is within one week.
13. The permittee shall maintain records of the following information:
- the date and reason any required inspection was not performed;
  - the date of each inspection where it was determined by the permittee that it was necessary to implement the control measure(s);
  - the dates the control measure(s) was (were) implemented; and
  - on a calendar quarter basis, the total number of days the control measure(s) was (were) implemented.

The information in (d) shall be kept separately for each landfill fugitive dust operation/source identified above, and shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

14. The permit to install for this emissions unit was evaluated based on information contained in the permit to install application. Prior to any physical change or change in the method of operation involving the control device(s) associated with this emissions unit\*, the permittee shall conduct an evaluation to determine if the change would constitute a "modification" as defined in OAC rule 3745-31-01. If any physical change in, or change(s) in the method of operation is (are) defined as a modification, then the permittee shall obtain a final permit to install modification prior to performing such change. The permittee shall collect, record and retain all evaluation information and

Emissions Unit ID: P901

the final determination when modification evaluations are performed.

\*A physical change or change in the method of operation involving the control device(s) could involve but not be limited to such changes as installing an additional control device or increasing the capacity of an existing control device.

#### **IV. Reporting Requirements**

1. The permittee shall submit a closure report to the Northwest District Office within 30 days of waste acceptance cessation. The Ohio EPA may request additional information as may be necessary to verify that permanent closure has taken place in accordance with the requirements of 40 CFR Part 258.60. If a closure report has been submitted to the Ohio EPA, no additional wastes may be placed into the landfill without filing a notification of modification as described in 40 CFR Part 60.7 (a)(4).
2. The permittee shall submit an equipment removal report to the Northwest District Office 30 days prior to removal or cessation of operation of the control equipment. The equipment removal report shall contain the information specified in 40 CFR Part 60.757 (e)(1). The Ohio EPA may request additional information as may be necessary to verify that all of the conditions for removal in 40 CFR Part 60.752 (b)(2)(v) have been met.
3. The permittee shall submit semi-annual reports of the following recorded information:
  - a. the value and length of time for any exceedance(s) of the applicable parameters contained in Sections A.II.1 and A.II.2;
  - b. the description and duration of all periods when the gas stream is not vented to off-site facilities and is diverted from the control device (flare) through a bypass line or the indication of bypass flow;
  - c. the description and duration of all periods when the control device (flare) was not operating for a period exceeding 1 hour and length of time the control device was not operating;
  - d. all periods of time when the collection system was not operating in excess of 5 days;
  - e. the location of each exceedance of the 500 parts per million methane concentration and the concentration recorded at each location for which an exceedance was recorded in the previous month; and
  - f. the date of installation and location of each well or collection system expansion added pursuant to 40 CFR Part 60.755 (a)(3), (b), and (c)(4).

These reports shall be submitted by January 31 and July 31 of each year and shall cover the previous six month period.

4. The permittee shall submit the following information with the initial performance test report required pursuant to 40 CFR Part 60.8\*:
  - a. a diagram of the collection system which indicates the collection system positioning, including all wells, horizontal collectors, surface collectors, or other gas extraction devices, including the locations of any areas excluded from collection and the proposed sites for the future collection system expansion;
  - b. the data upon which the sufficient density of wells, horizontal collectors, surface collectors, or other gas extraction devices and the gas mover equipment sizing are based;
  - c. the documentation of the presence of asbestos or nondegradable material for each area from which collection wells have been excluded based on the presence of asbestos or nondegradable material;
  - d. the sum of the gas generation flow rates for all areas from which collection wells have been excluded based on nonproductivity and the calculations of gas generation flow rate for each excluded area;
  - e. the provisions for increasing gas mover equipment capacity with increased gas generation flow rate, if the present gas mover equipment is inadequate to move the maximum flow rate expected over the life of the landfill; and
  - f. the provisions for the control of off-site migration.

The permittee shall submit a written report of the results of the initial performance test(s) to the Northwest District Office within 60 days after achieving the maximum production rate at which the affected facility will be operated, but not later than 180 days after the initial startup of such facility.

\* The municipal solid waste and asbestos landfill is an existing operation, and as such, the permittee has already met the requirements specified above.

5. The permittee shall submit quarterly deviation (excursion) reports, in accordance with the General Terms and Conditions of this permit, that identify any of the following occurrences:

- a. each day during which an inspection was not performed by the required frequency, excluding an inspection which was not performed due to an exemption for snow and/or ice cover or precipitation; and
  - b. each instance when a control measure that was to be implemented as a result of an inspection was not implemented.
6. As soon as possible, and no longer than 30 days after receipt of asbestos containing waste (ACM), the permittee shall send a copy of the signed waste shipment record to the waste generator.
7. Upon discovering a discrepancy between the quantity of waste designated on a waste shipment record and the quantity actually received, the permittee shall attempt to reconcile the discrepancy with the waste generator. If the discrepancy is not resolved within 15 days after receiving the waste, the permittee shall immediately report the discrepancy, in writing, to the, local, district, state, or U.S. EPA regional office responsible for administering the asbestos NESHAP program for the waste generator (identified in the waste shipment record), and, if different, the Northwest District Office. The written report shall include a description of the discrepancy, the attempts to reconcile the discrepancy, and a copy of the waste shipment record.
8. The permittee shall submit, upon closure of the facility, a copy of the records of the asbestos waste disposal locations and quantities.
9. The permittee shall notify the Northwest District Office in writing at least 45 days prior to excavating or otherwise disturbing any asbestos-containing waste material that has been deposited at a waste disposal site and is covered. If the excavation will begin on a date other than the one contained in the original notice, notice of the new start date must be provided at least 10 working days before excavation begins and in no event shall the excavation begin earlier than the date specified in the original notification. The following information shall be included in the notice:
  - a. the scheduled starting and completion dates;
  - b. the reason for disturbing the waste;
  - c. the procedures the permittee shall use to control emissions during the excavation, storage, transport, and ultimate disposal of the excavated asbestos-containing waste material (if deemed necessary, the Northwest District Office may require changes in the proposed emission control procedures);
  - d. the location(s) of any temporary storage site(s); and

- e. the location of the final disposal site.
10. The permittee shall notify the Northwest District Office of any load of asbestos-containing material which is rejected, or any non-conforming load disposed of in accordance with the "Asbestos Spill Contingency Plan." Notification shall be provided as soon as possible by a phone contact, followed in writing by the next working day. The written notification shall provide a copy of the waste shipment record (WSR), if available, or when waste is not shipped with a WSR, provide available information concerning vehicle identification, source of the load, a description of the load, nature of discrepancy, and the location of disposal. If possible, non-conforming loads of suspect friable material shall be detained, or the location of disposal protected from damage, until the Ohio EPA is informed and provided the opportunity to inspect.
11. Pursuant to the New Source Performance Standards (NSPS), the source owner/operator is hereby advised of the requirements to report the following at the appropriate times\*:
- a. construction date (no later than 30 days after such date);
  - b. actual start-up date (within 15 days after such date); and
  - c. date of performance testing (if required, at least 30 days prior to testing).

Reports are to be sent to:

Ohio Environmental Protection Agency  
DAPC - Permit Management Unit  
Lazarus Government Center  
P.O. Box 1049  
Columbus, OH 43216-1049

and

Ohio EPA, Northwest District Office  
347 North Dunbridge Road  
Bowling Green, OH 43402

- \* The municipal solid waste and asbestos landfill is an existing operation, and as such, the permittee has already met the requirements specified above.

## **V. Testing Requirements**

Emissions Unit ID: P901

1. Compliance with the emission limitation(s) specified in Section A.1.1 of the terms and conditions of this permit shall be determined in accordance with the following method(s):

- a. Emission Limitations:  
56.10 tons fugitive NMOC/year

8,745.00 tons fugitive methane/year

Applicable Compliance Method:

The permittee may demonstrate compliance with the above emission limitations using the Landfill Gas Emission Model (LandGEM). Based on the results of the model, maximum potential emissions will occur in the year 2009 and are based on the following:

- i. 9.69 x 10<sup>6</sup> Mg refuse in place (2005);
- ii. annual waste acceptance rate of 2,100,000 Mg per year;
- iii. maximum landfill capacity of 16,500,000 Mg; and
- iv. a landfill gas collection system capture efficiency of 75%, based on engineering design.

The annual limitations represent the maximum potentials to emit, therefore no recordkeeping, deviation reporting, or compliance method calculations are required to demonstrate compliance with the above limitations.

- b. Emission Limitation  
179.72 tons fugitive PE/year

Applicable Compliance Method

The emission limitation was established by summing the total, uncontrolled emissions from the temporary, unpaved roadways and material handling operations associated with the landfill construction activities and applying a 75% control efficiency for the use of best available control measures.

The permittee may demonstrate compliance as follows:

- i. for unpaved roadways, multiply the appropriate emission factor from AP-42, Chapter 13.2.2.2 (revised 12/03) by the maximum vehicle miles traveled.
- ii. for material handling operations, multiply the appropriate emission factor

from AP-42, Chapter 13.2.4 (1/95) by the maximum material throughput.

Therefore, provided compliance is shown with the requirements of this permit to apply best available control measures, compliance with the annual limitation will be assumed.

- c. Emission Limitations: Flare Emissions  
0.77 pound NMOC/hour and 3.37 tons NMOC/year

119.795 pounds methane/hour and 524.70 tons methane/year

Applicable Compliance Method:

The permittee may demonstrate compliance with the above emission limitations using the Landfill Gas Emission Model (LandGEM). Based on the results of the model, maximum emissions will occur in the year 2009 and are based on the following:

- i. 9.69 x 10<sup>6</sup> Mg refuse in place (2005);
  - ii. annual waste acceptance rate of 2,100,000 Mg per year;
  - iii. maximum landfill capacity of 16,500,000 Mg; and
  - iv. a landfill gas collection system capture efficiency of 75%, based on engineering design.
  - v. applying a 98% control efficiency from the flare for the control of NMOC and methane emissions; and
  - vi. a maximum operating schedule of 8,760 hours/year.
- d. Emission Limitation: Flare Emissions  
53.47 pounds CO/hour and 234.20 tons CO/year

Applicable Compliance Method:

The permittee may demonstrate compliance with the hourly emission limitation by multiplying the flare manufacturer's emission factor of 0.37 lb CO/mmBtu by a flare capacity of 144.5 mmBtu/hour.

The annual emission limitation was developed by multiplying the hourly emission

Emissions Unit ID: P901

limitation by a maximum operating schedule of 8760 hours/year, and then dividing by 2000 pounds/ton. Therefore, provided compliance is shown with the hourly limitation, compliance with the annual limitation will be assumed.

- e. Emission Limitation: Flare Emissions  
 9.83 pounds NO<sub>x</sub>/hour and 43.06 tons NO<sub>x</sub>/year

Applicable Compliance Method:

The permittee may demonstrate compliance with the hourly emission limitation by multiplying the flare manufacturer's emission factor of 0.068 lb NO<sub>x</sub>/mmBtu by a flare capacity of 144.5 mmBtu/hour.

The annual emission limitation was developed by multiplying the hourly emission limitation by a maximum operating schedule of 8760 hours/year, and then dividing by 2000 pounds/ton. Therefore, provided compliance is shown with the hourly limitation, compliance with the annual limitation will be assumed.

- f. Emission Limitation: Flare Emissions  
 2.16 pounds SO<sub>2</sub>/hour and 9.46 tons SO<sub>2</sub>/year

Applicable Compliance Method:

The permittee may demonstrate compliance with the hourly emission limitation in accordance with AP-42, Section 2.4, equations 3, 4, & 7 Municipal Solid Waste Landfills (11/98) and the following:

- i. landfill gas combustion rate of 4,300 scfm; and
- ii. sulfur concentration in the landfill gas = 49.6 ppmv.

The annual emission limitation was developed by multiplying the hourly emission limitation by a maximum operating schedule of 8760 hours/year, and then dividing by 2000 pounds/ton. Therefore, provided compliance is shown with the hourly limitation, compliance with the annual limitation will be assumed.

- g. Emission Limitation: Flare Emissions  
 2.46 pounds PE/hour and 10.77 tons PE/year

Applicable Compliance Method:

The permittee may demonstrate compliance with the hourly emission limitation by multiplying the appropriate emission factor from AP-42, Table 2.4.5 (11/98) of 17.0 lbs PE/10<sup>6</sup> dscf methane by a landfill gas combustion rate of 4,300 dscfm, 0.56 cubic foot methane/cubic foot of landfill gas, and 60 minutes/hour.

The annual emission limitation was developed by multiplying the hourly emission

Emissions Unit ID: P901

limitation by a maximum operating schedule of 8760 hours/year, and then dividing by 2000 pounds/ton. Therefore, provided compliance is shown with the hourly limitation, compliance with the annual limitation will be assumed.

- h. Emission Limitation: Flare Emissions  
 1.04 pound HCl/hour and 4.56 tons HCl/year

Applicable Compliance Method:

The permittee may demonstrate compliance with the hourly emission limitation in accordance with AP-42, Section 2.4, equations 3, 4, & 10 Municipal Solid Waste Landfills (11/98) and the following:

- i. landfill gas combustion rate of 4,300 scfm; and
- ii. chloride ion concentration in the landfill gas = 42.0 ppmv.

The annual emission limitation was developed by multiplying the hourly emission limitation by a maximum operating schedule of 8760 hours/year, and then dividing by 2000 pounds/ton. Therefore, provided compliance is shown with the hourly limitation, compliance with the annual limitation will be assumed.

- i. Emission Limitation:  
 Visible fugitive PE shall not exceed 20% opacity, as a three-minute average from operations not associated with asbestos-containing material (ACM).

Applicable Compliance Method:

If required, compliance with the visible fugitive emission limitation shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 2002, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(d) of OAC rule 3745-17-03.

- j. Emission Limitation:  
 There shall be no visible emissions from asbestos-containing waste materials (ACM) during on-site transportation, transfer, deposition, or compacting operations.

Applicable Compliance Method:

If required, compliance with the visible emission limitation specified above shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 2002, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(d) of OAC rule 3745-17-03.

k. Emission Limitation:

There shall be no visible emissions from the flare, except for periods of time not to exceed a total of 5 minutes during any two consecutive hours.

Applicable Compliance Method:

If required, compliance with the visible emission limitation specified above shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 2002, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(d) of OAC rule 3745-17-03.

**VI. Miscellaneous Requirements**

1. Upon closure of the facility, Best Available Technology (BAT), under OAC rule 3745-31-05 (A)(3), requires that the permittee comply with the following provisions of OAC rule 3745-20-07 and submit a copy of the records of the asbestos waste disposal locations and quantities to the Director (Northwest District Office).
  - a. Each owner or operator of an inactive asbestos waste disposal site shall either:
    - i. discharge no visible emissions to the outside air from an inactive waste disposal site; OR
    - ii. cover the asbestos-containing waste material with at least six inches of nonasbestos-containing material, and grow and maintain a cover of vegetation on the area adequate to prevent exposure of the asbestos-containing waste material; OR
    - iii. cover the asbestos-containing material with at least two feet of compacted nonasbestos-containing material, and maintain the cover to prevent exposure of the asbestos-containing waste material.
  - b. Unless a natural barrier adequately deters access by the general public, each owner or operator of an inactive asbestos waste disposal site shall install and maintain warning signs and fencing as follows, or comply with section A.VI.1.a.ii. or A.VI.1.a.iii above:
    - i. The owner or operator shall display warning signs at all entrances and at intervals of three hundred feet or less along the property line of the site or along the perimeter of the sections of the site where asbestos-containing waste material was deposited. The warning signs must:
      - (a) be posted in such a manner and location that a person can easily read the legend; and
      - (b) conform to the requirements for a twenty inch by fourteen inch upright format warning sign and display the following legend in the

lower panel with letter sizes of at least one inch sans serif, gothic, or block. Spacing between any two lines must be at least equal to the height of the upper of the two lines:

"ASBESTOS WASTE DISPOSAL SITE  
DO NOT CREATE DUST  
BREATHING ASBESTOS IS HAZARDOUS TO YOUR HEALTH"

- ii. The owner or operator shall fence the perimeter of the site in a manner adequate to deter access by the general public.
  - iii. Upon request and submission of appropriate information, the Director will determine whether a fence or a natural barrier adequately deters access by the public.
  - iv. When requesting a determination on whether a natural barrier adequately deters public access, the owner or operator shall supply information enabling the Director to determine whether a fence or a natural barrier adequately deters access by the general public.
- c. The owner or operator may use an alternative control method that has received prior approval from the Director rather than comply with the requirements of Sections A.VI.1.a or A.VI.1.b of these terms and conditions.
- d. Each owner or operator of an inactive waste disposal site shall notify the Director in writing at least forty-five days prior to excavating or otherwise disturbing or removing any asbestos-containing waste material. If the excavation will begin on a date other than the one contained in the original notice, notice of the new start date must be provided to the Director at least ten working days before excavation begins. In no event shall excavation begin earlier than the date specified in the original notification. Each owner or operator shall include the following information in the notice:
- i. the scheduled starting and completion dates;
  - ii. the reason(s) for disturbing the waste;
  - iii. the procedures to be used to control emissions during the excavation, storage, transport, and ultimate disposal of the excavated asbestos-containing material. If deemed necessary, the director may

- require changes in the emission control procedures to be used; and
- iv. the location(s) of any temporary storage site and the final disposal site.
- e. Within sixty days of a site becoming inactive, the owner or operator shall record a notation of the presence of asbestos-containing material on the deed to the facility property and on any other instrument that would normally be examined during the title search. This notation will, in perpetuity, notify any potential purchaser of the property that:
- i. the land has been used for the disposal of asbestos-containing waste material; and
  - ii. the survey plot and record of the location and quantity of asbestos-containing waste disposed of within the disposal site required in paragraph (C)(2) of rule 3745-20-06 of the Ohio Administrative Code has been filed with the Director; and
  - iii. the site is subject to Chapter 3745-20 of the Ohio Administrative Code and 40 CFR Part 61, Subpart M.
2. There shall be no open burning in violation of Ohio Administrative Code rule 3745-19 at this facility.
  3. The application and enforcement of the provisions of the New Source Performance Standards (NSPS), as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60, are delegated to the Ohio Environmental Protection Agency. The requirements for 40 CFR Part 60 are also federally enforceable.
  4. This emissions unit is subject to 40 CFR Part 63, Subpart AAAA, National Emission Standards for Hazardous Air Pollutants: Municipal Solid Waste Landfills. Compliance with 40 CFR Part 63, Subpart AAAA is determined in the same way it is determined for 40 CFR Part 60, Subpart WWW, including performance testing, monitoring of the collection system, continuous parameter monitoring, and other credible evidence. In addition, continuous parameter monitoring data (see A.III.3) are used to demonstrate compliance with the operating conditions for control systems.
  5. This emissions unit is subject to 40 CFR Part 63, Subpart A -- General Provisions. Table 1 of 40 CFR Part 63, Subpart AAAA outlines the applicability of the General Provisions as they apply to Subpart AAAA. The following citations of the General

Provisions are applicable but not suitable for use in a permit with regards to the development of specific terms and conditions:

Part 63 Citation

63.1(a)  
63.1(b)  
63.1(e)  
63.2  
63.4  
63.5(b)  
63.6(f)

Terms A.VI.7 through A.VI.12 address applicable startup, shutdown, and malfunction requirements contained in the General Provisions.

6. In accordance with 40 CFR 63.1960, the permittee shall develop and implement a written startup, shutdown, and malfunction (SSM) plan according to the provisions in 40 CFR 63.6(e)(3). A copy of the SSM plan must be maintained on site.
7. During periods of startup, shutdown, and malfunction, the affected source shall be operated according to the written startup, shutdown, and malfunction plan. (63.6(e)(3)(ii))
8. Equipment malfunctions shall be corrected as soon as practicable in accordance with the startup, shutdown, and malfunction plan. (63.6(e)(1)(ii))
9. The permittee shall maintain relevant records for the source of the following:
  - a. the occurrence and duration of each startup, shutdown, and malfunction of operation. (63.10(b)(2)(i))
  - b. the occurrence and duration of each malfunction of air pollution control equipment. (63.10(b)(2)(ii))
  - c. maintenance performed on air pollution control equipment. (63.10(b)(2)(iii))
  - d. actions taken during periods of startup, shutdown, or malfunction that deviate from the submitted plan. (63.10(b)(2)(iv))
  - e. all information necessary to demonstrate compliance with the startup, shutdown, malfunction, and startup plan. (63.10(b)(2)(v)).
10. If actions taken during a periodic startup, shutdown, or malfunction of an affected source are consistent with procedures specified in the source's startup, shutdown, and

malfunction plan, this shall be included in the periodic startup, shutdown, and malfunction report. This report shall be submitted semi-annually within 30 days of the end of each semi-annual period during which a startup, shutdown, or malfunction occurred.

11. If actions taken during a periodic startup, shutdown, or malfunction of an affected source are not consistent with procedures specified in the source's startup, shutdown, and malfunction plan, this shall be reported within 2 days of commencing the inconsistent action by phone or FAX, followed by a letter postmarked or delivered within 7 days of the end of the event. This immediate startup, shutdown, and malfunction report shall include the circumstances of the incident and the reasons for not following the startup, shutdown, and malfunction plan.
12. The issuance of this permit (PTI #03-13300) does not authorized the permittee to engage in any activity associated with expansion of the current Evergreen Recycling and Disposal Facility until permit approval has been issued by the Ohio EPA, Division of Solid and Infectious Waste Management (through the final issuance of PTI #03-15314) allowing for a vertical expansion.

**B. State Only Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P901 - municipal solid waste and asbestos landfill with active gas collection, open flare, and associated material handling operations	OAC rule 3745-20-05	See B.I.2.a.
	OAC rule 3745-20-06	See B.I.2.a.
	OAC rule 3745-20-07	See B.I.2.a.

**2. Additional Terms and Conditions**

- 2.a The requirements of this rule are equivalent to the requirements of OAC rule 3745-31-05 (A)(3) contained in the State and Federally Enforceable Section of Part III for this emissions unit.

**II. Operational Restrictions**

None

**III. Monitoring and/or Recordkeeping Requirements**

1. The permit to install for this emissions unit (P901) was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Hydrogen Chloride  
 TLV (mg/m3): 5.5

57

**Everg**

**PTI A**

**Issued: 10/5/2006**

Emissions Unit ID: P901

Maximum Hourly Emission Rate (lbs/hr): 1.04

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 0.22  
MAGLC (ug/m3): 130.95

2. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
  - a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
  - b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
  - c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).
3. If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluation to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

**Evergreen Recycling and Disposal Facility**  
**PTI Application: 02-12200**  
**Issue:**

**Facility ID: 0387000259**

Emissions Unit ID: P901

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.)
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

**IV. Reporting Requirements**

None

**IV. Reporting Requirements**

None

**V. Testing Requirements**

None

**VI. Miscellaneous Requirements**

None