



State of Ohio Environmental Protection Agency

Street Address:

Lazarus Gov. Center
122 S. Front Street
Columbus, OH 43215

TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center
P.O. Box 1049
Columbus, OH 43216-1049

**RE: FINAL PERMIT TO INSTALL MODIFICATION
MONTGOMERY COUNTY
Application No: 08-03320**

CERTIFIED MAIL

Y	TOXIC REVIEW
	PSD
	SYNTHETIC MINOR
	CEMS
	MACT
	NSPS
	NESHAPS
	NETTING
	MAJOR NON-ATTAINMENT
	MODELING SUBMITTED
	GASOLINE DISPENSING FACILITY

DATE: 7/18/2002

Hohman Plating & Mfg Inc
Connie Nazar
814 Hillrose Ave
Dayton, OH 45404-1199

Enclosed Please find a modification to the Ohio EPA Permit To Install referenced above which will modify the terms and conditions.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
236 East Town Street, Room 300
Columbus, Ohio 43215

Very truly yours,

Thomas G. Rigo, Manager
Field Operations and Permit Section
Division of Air Pollution Control

cc: USEPA

RAPCA



FINAL ADMINISTRATIVE MODIFICATION OF PERMIT TO INSTALL 08-03320

Application Number: 08-03320

APS Premise Number: 0857040217

Permit Fee: **\$0**

Name of Facility: Hohman Plating & Mfg Inc

Person to Contact: Connie Nazar

Address: 814 Hillrose Ave
Dayton, OH 45404-1199

Location of proposed air contaminant source(s) [emissions unit(s)]:
814 Hillrose Ave
Dayton, Ohio

Description of proposed emissions unit(s):
Pickling and stripping operations and solutions; administrative modification to PTI 08-03320 issued March 15, 2001.

The above named entity is hereby granted a modification to the permit to install described above pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this modification does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described source(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans included in the application, the above described source(s) of pollutants will be granted the necessary operating permits.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements Related to Monitoring and Recordkeeping Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may

be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions

and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit to Install is applicable only to the emissions unit(s) identified in the Permit to Install. Separate application must be made to the Director for the installation or modification of any other emissions unit(s).

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

13. Source Operation and Operating Permit Requirements After Completion of Construction

- a. If the permittee is required to apply for a Title V permit pursuant to OAC Chapter 3745-77, the permittee shall submit a complete Title V permit application or a complete Title V permit modification application within twelve (12) months after commencing operation of the emissions units covered by this permit. However, if the proposed new or modified source(s) would be prohibited by the terms and conditions of an existing Title V permit, a Title V permit modification must be obtained before the operation of such new or modified source(s) pursuant to OAC rule 3745-77-04(D) and OAC rule 3745-77-08(C)(3)(d).

- b. If the permittee is required to apply for permit(s) pursuant to OAC Chapter 3745-35, the source(s) identified in this Permit To Install is (are) permitted to operate for a period of up to one year from the date the source(s) commenced operation. Permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within thirty (30) days after commencing operation of the source(s) covered by this permit.

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

**SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS**

<u>Pollutant</u>	<u>Tons Per Year</u>
hydrofluoric acid	0.0012
nitric acid	2.275
sulfuric acid	0.153
sodium hydroxide	0.056
chromic acid	0.0016
hydrochloric acid	0.13

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P020 - Strip plating pretreatment system B, with packed bed scrubber control (Tanks: AC.AP.HA.840, AC.AP.NA.847, AC.AP.NA.848, AC.ST.NI.853, AC.ST.RC.852, AC.ST.RS.850, AK.ST.TL.855, NT.PW.CW.839, NT.PW.CW.849, NT.PW.CW.851, AC.AP.NA.013, AC.AP.TA.018, NT.PW.CW.014, and NT.PW.CW.019)(modification)	OAC rule 3745-31-05(A)(3)	0.513 lb/hour and 1.60 TPY nitric acid (as particulates); 0.0004 lb/hour and 0.0012 TPY hydrofluoric acid; 0.0064 lb/hour and 0.02 TPY sulfuric acid (as particulates); 0.004 lb/hour and 0.013 TPY sodium hydroxide (as particulate)
	OAC rule 3745-17-07(A)(1)	Visible emissions shall not exceed 20% opacity, as a six-minute average, except as provided by rule
	OAC rule 3745-17-11(B)(1)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

2. **Additional Terms and Conditions**

- 2.a None

B. Operational Restrictions

1. The pressure drop across the scrubber shall be continuously maintained at a value of not less than 0.75 inch of water at all times while the emissions unit is in operation.

2. The pH of the scrubber liquor shall be maintained within a range of 5 to 10.
3. The scrubber water flow rate shall be continuously maintained at a value of not less than 3 gallons per minute at all times while the emissions unit is in operation.
4. The maximum annual operating hours for this emissions unit shall not exceed 6240.

C. Monitoring and/or Record keeping Requirements

1. The permittee shall properly operate and maintain equipment to continuously monitor the static pressure drop across the scrubber, the pH of the scrubber liquor, and the scrubber water flow rate while the emissions unit is in operation. The monitoring devices and any recorders shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations, instructions and operating manuals.
2. The permittee shall collect and record the following information each day:
 - a. The pressure drop across the scrubber, in inches of water.
 - b. The pH of the scrubber liquor.
 - c. The scrubber water flow rate, in gallons per minute.
 - d. The operating times for the capture (collection) system, control device, monitoring equipment, and the associated emissions unit.
3. The permittee shall maintain monthly records of the operating hours for this emissions unit.
4. The permit to install for this emissions unit (P020) was evaluated based on the actual materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: nitric acid

TLV (mg/m³): 5.16

Maximum Hourly Emission Rate (lbs/hr): 0.513

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 14.90

MAGLC (ug/m³): 122.86

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. Changes in the composition of the materials used, or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
 - b. Changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
 - c. Physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).
5. If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

- a. A description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. Documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. Where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. In accordance with Section A.2. of the General Terms and Conditions of this permit, the permittee shall submit quarterly deviation (excursion) reports that identify all periods of time during which the following scrubber parameters were not maintained at or above the required levels:
 - a. The static pressure drop across the scrubber.
 - b. The pH of the scrubber liquor.
 - c. The scrubber water flow rate.
2. The permittee shall submit annual reports which identify any exceedances of the annual operating hours limitation, as well as the corrective actions that were taken to achieve compliance. These reports shall be submitted by January 31 of each year.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.1. of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation -
0.513 lb/hour nitric acid (as particulates)

Applicable Compliance Method -
Compliance with this allowable emission rate was demonstrated in a performance test conducted on November 18, 1997 with results showing an average nitric acid emission rate of 0.093 lb/hour. Ongoing compliance shall be based upon the established operating parameters for the packed bed scrubber control system.
 - b. Emission Limitation -
1.60 TPY nitric acid (as particulates)

Applicable Compliance Method -
The 1.60 TPY emission limitation was developed by multiplying the maximum hourly emission rate by a maximum annual operating schedule of 6240 hours/year. Therefore, compliance shall be based upon the 12-month summation of the number of operating hours times the maximum hourly emission rate, divided by 2,000 pounds per ton.
 - c. Emission Limitation -
0.0004 lb/hour hydrofluoric acid

Applicable Compliance Method -

Compliance shall be determined by calculations using air emissions models specified in the Metal Finishing Facility Risk Screening Tool (MFFRST), EPA/600/R-01/057, July 2001. Ongoing compliance shall be based upon the established operating parameters for the packed bed scrubber control system.

- d. Emission Limitation -
0.0012 TPY hydrofluoric acid

Applicable Compliance Method -

The 0.0012 TPY emission limitation was developed by multiplying the 0.0004 lb/hour emission rate by a maximum annual operating schedule of 6240 hours/year. Therefore, compliance shall be based upon the 12-month summation of the number of operating hours times 0.0004 lb/hour, divided by 2,000 pounds per ton.

- e. Emission Limitation -
0.0064 lb/hour sulfuric acid (as particulates)

Applicable Compliance Method -

Compliance shall be determined by calculations using air emissions models specified in the Metal Finishing Facility Risk Screening Tool (MFFRST), EPA/600/R-01/057, July 2001. Ongoing compliance shall be based upon the established operating parameters for the packed bed scrubber control system.

- f. Emission Limitation -
0.02 TPY sulfuric acid (as particulates)

Applicable Compliance Method -

The 0.02 TPY emission limitation was developed by multiplying the 0.0064 lb/hour emission rate by a maximum annual operating schedule of 6240 hours/year. Therefore, compliance shall be based upon the 12-month summation of the number of operating hours times 0.0064 lb/hour, divided by 2,000 pounds per ton.

- g. Emission Limitation -
0.004 lb/hour sodium hydroxide (as particulates)

Applicable Compliance Method -

Compliance shall be determined by calculations using air emissions models specified in the Metal Finishing Facility Risk Screening Tool (MFFRST), EPA/600/R-01/057, July 2001.

- h. Emission Limitation -
0.013 TPY sodium hydroxide (as particulates)

Applicable Compliance Method -

The 0.013 TPY emission limitation was developed by multiplying the 0.004 lb/hour emission rate by a maximum annual operating schedule of 6240 hours/year. Therefore, compliance shall be based upon the 12-month summation of the number of operating hours times 0.004 lb/hour, divided by 2,000 pounds per ton.

- i. Emission Limitation -
20% opacity, as a six-minute average

Applicable Compliance Method -

Compliance shall be determined by visible emission evaluations performed in accordance with procedures specified in OAC rule 3745-17-03(B)(1) using the methods and procedures specified in USEPA Reference Method 9.

F. Miscellaneous Requirements

None

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P022 - Strip & post treatment system D, with packed bed scrubber control (Tanks: AC.AP.NA.518, AC.AP.NA.846, AC.AP.PM.502, AC.AP.PM.843, AC.SF.CR.796, AC.SF.DW.100, AC.SF.PS.182, AC.ST.CU.858, AC.ST.PS.791, AK.ST.CU.832, MU.SF.XX.795, A C . A P . N A . 0 1 0 , and NT.PW.CW.011) (modification)	OAC rule 3745-31-05(A)(3)	0.216 lb/hour and 0.675 TPY nitric acid (as particulates);
		0.0005 lb/hour and 0.0016 TPY chromic acid (as particulates);
		0.03 lb/hour and 0.13 TPY hydrochloric acid;
		0.0424 lb/hour and 0.133 TPY sulfuric acid (as particulates);
		0.014 lb/hour and 0.043 TPY sodium hydroxide (as particulates)
	OAC rule 3745-17-07(A)(1)	Visible emissions shall not exceed 20% opacity, as a six-minute average, except as provided by rule.
	OAC rule 3745-17-11(B)(1)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

2.a None

B. Operational Restrictions

1. The pressure drop across the scrubber shall be continuously maintained at a value of not less than 0.25 inch of water at all times while the emissions unit is in operation.
2. The pH of the scrubber liquor shall be maintained within a range of 5 to 10.
3. The scrubber water flow rate shall be continuously maintained at a value of not less than 3 gallons per minute at all times while the emissions unit is in operation.
4. The maximum annual operating hours for this emissions unit shall not exceed 6240.

C. Monitoring and/or Record keeping Requirements

1. The permittee shall properly operate and maintain equipment to continuously monitor the static pressure drop across the scrubber, the pH of the scrubber liquor, and the scrubber water flow rate while the emissions unit is in operation. The monitoring devices and any recorders shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations, instructions and operating manuals.
2. The permittee shall collect and record the following information each day:
 - a. The pressure drop across the scrubber, in inches of water.
 - b. The pH of the scrubber liquor.
 - c. The scrubber water flow rate, in gallons per minute.
 - d. The operating times for the capture (collection) system, control device, monitoring equipment, and the associated emissions unit.
3. The permittee shall maintain monthly records of the operating hours for this emissions unit.

D. Reporting Requirements

1. In accordance with Section A.2. of the General Terms and Conditions of this permit, the permittee shall submit quarterly deviation (excursion) reports that identify all periods of time during which the following scrubber parameters were not maintained at or above the required levels:
 - a. The static pressure drop across the scrubber.
 - b. The pH of the scrubber liquor.
 - c. The scrubber water flow rate.

2. The permittee shall submit annual reports which identify any exceedances of the annual operating hours limitation, as well as the corrective actions that were taken to achieve compliance. These reports shall be submitted by January 31 of each year.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.1. of these terms and conditions shall be determined in accordance with the following method(s):

- a. Emission Limitation -
0.216 lb/hour nitric acid (as particulates)

Applicable Compliance Method -

Compliance with this allowable emission rate was demonstrated in a performance test conducted on November 18, 1997 with results showing an average nitric acid emission rate of 0.023 lb/hour. Ongoing compliance shall be based upon the established operating parameters for the packed bed scrubber control system.

- b. Emission Limitation -
0.675 TPY nitric acid (as particulates)

Applicable Compliance Method -

The 0.675 TPY emission limitation was developed by multiplying the maximum hourly emission rate by a maximum annual operating schedule of 6240 hours/year. Therefore, compliance shall be based upon the 12-month summation of the number of operating hours times the maximum hourly emission rate, divided by 2,000 pounds per ton.

- c. Emission Limitation -
0.0005 lb/hour chromic acid (as particulates)

Applicable Compliance Method -

Compliance shall be determined by calculations using air emissions models specified in the Metal Finishing Facility Risk Screening Tool (MFFRST), EPA/600/R-01/057, July 2001. Ongoing compliance shall be based upon the established operating parameters for the packed bed scrubber control system.

- d. Emission Limitation -
0.0016 TPY chromic acid (as particulates)

Applicable Compliance Method -

The 0.0016 TPY emission limitation was developed by multiplying the 0.0005 lb/hour emission rate by a maximum annual operating schedule of 6240 hours/year. Therefore, compliance shall be based upon the 12-month summation of the number of operating hours times 0.0005 lb/hour, divided by 2,000 pounds per ton.

- e. Emission Limitation -
0.03 lb/hour hydrochloric acid

Applicable Compliance Method -

Compliance shall be determined by calculations using air emissions models specified in the Metal Finishing Facility Risk Screening Tool (MFFRST), EPA/600/R-01/057, July 2001. Ongoing compliance shall be based upon the established operating parameters for the packed bed scrubber control system.

- f. Emission Limitation -
0.13 TPY hydrochloric acid

Applicable Compliance Method -

The 0.13 TPY emission limitation was developed by multiplying the 0.03 lb/hour emission rate by a maximum annual operating schedule of 6240 hours/year. Therefore, compliance shall be based upon the 12-month summation of the number of operating hours times 0.03 lb/hour, divided by 2,000 pounds per ton.

- g. Emission Limitation -
0.0424 lb/hour sulfuric acid (as particulates)

Applicable Compliance Method -

Compliance shall be determined by calculations using air emissions models specified in the Metal Finishing Facility Risk Screening Tool (MFFRST), EPA/600/R-01/057, July 2001. Ongoing compliance shall be based upon the established operating parameters for the packed bed scrubber control system.

- h. Emission Limitation -
0.133 TPY sulfuric acid (as particulates)

Applicable Compliance Method -

The 0.133 TPY emission limitation was developed by multiplying the 0.0424 lb/hour emission rate by a maximum annual operating schedule of 6240 hours/year. Therefore, compliance shall be based upon the 12-month summation of the number of operating hours times 0.0424 lb/hour, divided by 2,000 pounds per ton.

- i. Emission Limitation -
0.014 lb/hour sodium hydroxide (as particulates)

Applicable Compliance Method -

Compliance shall be determined by calculations using air emissions models specified in the Metal Finishing Facility Risk Screening Tool (MFFRST), EPA/600/R-01/057, July 2001.

- j. Emission Limitation -
0.043 TPY sodium hydroxide (as particulates)

Applicable Compliance Method -

The 0.043 TPY emission limitation was developed by multiplying the 0.014 lb/hour emission rate by a maximum annual operating schedule of 6240 hours/year. Therefore, compliance shall be based upon the 12-month summation of the number of operating hours times 0.014 lb/hour, divided by 2,000 pounds per ton.

- k. Emission Limitation -
20% opacity, as a six-minute average

Applicable Compliance Method -

Compliance shall be determined by visible emission evaluations performed in accordance with procedures specified in OAC rule 3745-17-03(B)(1) using the methods and procedures specified in USEPA Reference Method 9.

F. Miscellaneous Requirements

- 1. Modeling to demonstrate compliance with the Ohio EPA's "Air Toxic Policy" was not necessary because the emissions unit's maximum annual emissions for each toxic compound will be less than 1.0 ton. OAC Chapter 3745-31 requires permittees to apply for and obtain a new or modified permit to install prior to making a "modification" as defined by OAC rule 3745-31-01. The permittee is hereby advised that changes in the composition of the materials, or use of new materials, that would cause the emissions of any pollutant that has a listed TLV to increase to above 1.0 ton per year may require the permittee to apply for and obtain a new permit to install.