OhioEPA

State of Ohio Environmental Protection Agency

Street Address:
Lazarus Gov. Center
122 S. Front Street
Columbus, OH 43215

TELE: (614) 644-3020 **FAX:** (614) 644-2329

Mailing Address:
Lazarus Gov. Center
P.O. Box 1049
Columbus, OH 43216-1049

RE: DRAFT PERMIT TO INSTALL
MONTGOMERY COUNTY
Application No: 08-04257

CERTIFIED MAIL

	TOXIC REVIEW
	PSD
	SYNTHETIC MINOR
	CEMS
	MACT
	NSPS
	NESHAPS
	NETTING
	MAJOR NON-ATTAINMENT
	MODELING SUBMITTED
	GASOLINE DISPENSING FACILITY

DATE: 6/14/2001

DMAX Ltd
Dave Hackett
3100 Dryden Rd
Moraine, OH

You are hereby notified that the Ohio Environmental Protection Agency has made a draft action recommending that the Director issue a Permit to Install for the air contaminant source(s) [emissions unit(s)] shown on the enclosed draft permit. This draft action is not an authorization to begin construction or modification of your emissions unit(s). The purpose of this draft is to solicit public comments on the proposed installation. A public notice concerning the draft permit will appear in the Ohio EPA Weekly Review and the newspaper in the county where the facility will be located. Public comments will be accepted by the field office within 30 days of the date of publication in the newspaper. Any comments you have on the draft permit should be directed to the appropriate field office within the comment period. A copy of your comments should also be mailed to Robert Hodanbosi, Division of Air Pollution Control, Ohio EPA, P.O. Box 1049, Columbus, OH, 43266-0149.

A Permit to Install may be issued in proposed of final form based on the draft action, any written public comments received within 30 days of the public notice, or record of a public meeting if one is held. You will be notified in writing of a scheduled public meeting. Upon issuance of a final Permit to Install a fee of **$900** will be due. Please do not submit any payment now.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469. If you have any questions about this draft permit, please contact the field office where you submitted your application, or Mike Ahern, Field Operations & Permit Section at (614) 644-3631.

Very truly yours,

Thomas G. Rigo, Manager
Field Operations and Permit Section
Division of Air Pollution Control

CC: **USEPA** **RAPCA**
Miami Valley Regional Planning Comm KY IN

DRAFT PERMIT TO INSTALL 08-04257

Application Number:	08-04257
APS Premise Number:	0857103196
Permit Fee:	**To be entered upon final issuance**
Name of Facility:	DMAX Ltd
Person to Contact:	Dave Hackett
Address:	3100 Dryden Rd Moraine, OH 454390000

Location of proposed air contaminant source(s) [emissions unit(s)]:
3100 Dryden Rd
Moraine, **Ohio**

Description of proposed emissions unit(s):
hot test stand 1-9; chapter 31 replacing 08-3840 issued 7-15-98.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

_____
Director

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements Related to Monitoring and Recordkeeping Requirements

The permittee shall submit required reports in the following manner:

a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.

b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may

be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit to Install is applicable only to the emissions unit(s) identified in the Permit to Install. Separate application must be made to the Director for the installation or modification of any other emissions unit(s).

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

13. Source Operation and Operating Permit Requirements After Completion of Construction

a. If the permittee is required to apply for a Title V permit pursuant to OAC Chapter 3745-77, the permittee shall submit a complete Title V permit application or a complete Title V permit modification application within twelve (12) months after commencing operation of the emissions units covered by this permit. However, if the proposed new or modified source(s) would be prohibited by the terms and conditions of an existing Title V permit, a Title V permit modification must be <u>obtained before</u> the operation of such new or modified source(s) pursuant to OAC rule 3745-77-04(D) and OAC rule 3745-77-08(C)(3)(d).

b. If the permittee is required to apply for permit(s) pursuant to OAC Chapter 3745-35, the source(s) identified in this Permit To Install is (are) permitted to operate for a period of up to one year from the date the source(s) commenced operation. Permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within thirty (30) days

after commencing operation of the source(s) covered by this permit.

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

Pollutant	Tons Per Year
CO	43.36
NOx	31.54
OC	11.79
SO2	7.88
PM	7.88

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
P001 - Hot Test Stand No. 1, (Modification, see Section F.)	OAC rule 3745-31-05(A)(3)	1.1 lb/hr and 4.82 TPY carbon monoxide (CO); 0.8 lb/hr and 3.50 TPY nitrogen oxides (NOx); 0.3 lb/hr and 1.31 TPY organic compounds (OC); 0.2 lb/hr and 0.88 TPY sulfur dioxide (SO2); 0.2 lb/hr and 0.88 TPY particulate emissions (PE); 15% opacity, as a six-minute average
	OAC rule 3745-17-07(A)	The opacity limitation specified by this rule is less stringent than the opacity limitation established pursuant to OAC rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

2.a The 1.1 lb CO/hr, 0.8 lb NOx/hr, 0.3 lb OC/hr, 0.2 lb SO2/hr, and 0.2 lb PE/hr limitations were established for PTI purposes to reflect the potential to emit for this emissions unit, based on the testing protocol submitted on April 19, 2001 by the permittee. Therefore, it is not necessary to develop record keeping and/or reporting requirements to ensure compliance with these limitations.

B. Operational Restrictions

None

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall maintain monthly records of the following information:

   a. The total number of engines tested; and

   b. The total engine running time compiled for all engines tested during the month.

D. Reporting Requirements

None

E. Testing Requirements

1. Compliance with the emission limitations in Section A.I.1. of this permit shall be determined in accordance with the following methods:

   a. Emission Limitation -
   1.1 lb CO/hr

   Applicable Compliance Method -
   Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the 0.01 lb CO/hp-hr emission factor established during the January 2001 performance testing. If required, compliance shall be also be determined by using Reference Method 10, as specified in 40 CFR Part 60, Appendix A.

   b. Emission Limitation -
   4.82 TPY CO

   Applicable Compliance Method -
   The 4.82 TPY limitation was developed by multiplying the specified allowable emission rate of 1.1 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

   c. Emission Limitation -
   0.8 lb NOx/hr

   Applicable Compliance Method -
   Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the 0.008 lb NOx/hp-hr emission factor established during the January 2001 performance testing. If required, compliance shall also be determined by using

Reference Method 7, as specified in 40 CFR Part 60, Appendix A.

d. Emission Limitation -
3.50 TPY NOx

Applicable Compliance Method -
The 3.50 TPY limitation was developed by multiplying the specified allowable emission rate of 0.8 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

e. Emission Limitation -
0.3 lb OC/hr

Applicable Compliance Method -
Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the emission factor, 0.003 lb OC/hp-hr (AP-42, Table 3.3-1 (10/96)).

f. Emission Limitation -
1.31 TPY OC

Applicable Compliance Method -
The 1.31 TPY limitation was developed by multiplying the specified allowable emission rate of 0.3 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

g. Emission Limitation -
0.2 lb SO2/hr

Applicable Compliance Method -
Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the emission factor, 0.002 lb SO2/hp-hr (AP-42, Table 3.3-1 (10/96)).

h. Emission Limitation -
0.88 TPY SO2

Applicable Compliance Method -
The 0.88 TPY limitation was developed by multiplying the specified allowable emission rate of 0.2 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

i. Emission Limitation -
0.2 lb PE/hr

Applicable Compliance Method -
Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the emission factor, 0.002 lb PE/hp-hr (AP-42, Table 3.3-1, (10/96)). If required, compliance shall be also be determined by using Reference Method 5, as specified in 40 CFR Part 60, Appendix A.

j. Emission Limitation -
0.88 TPY PE

Applicable Compliance Method -
The 0.88 TPY limitation was developed by multiplying the specified allowable emission rate of 0.2 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

k. Emission Limitation -
15% opacity, as a six-minute average

Applicable Compliance Method -
Compliance shall be determined by visible emission evaluations performed in accordance with OAC rule 3745-17-03(B)(3) using the methods and procedures specified in USEPA Method 9.

F. Miscellaneous Requirements

1. This is a modification to PTI # 08-03840 and results in the following net increases in emissions for emissions units P001 through P009 combined: + 38.58 TPY CO, + 21.99 TPY NOx, + 11.31 OC, + 5.66 TPY SO2, and + 5.49 TPY PE.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
P002 - Hot Test Stand No. 2	OAC rule 3745-31-05(A)(3)	1.1 lb/hr and 4.82 TPY carbon monoxide (CO); 0.8 lb/hr and 3.50 TPY nitrogen oxides (NOx); 0.3 lb/hr and 1.31 TPY organic compounds (OC); 0.2 lb/hr and 0.88 TPY sulfur dioxide (SO2); 0.2 lb/hr and 0.88 TPY particulate emissions (PE); 15% opacity, as a six-minute average
	OAC rule 3745-17-07(A)	The opacity limitation specified by this rule is less stringent than the opacity limitation established pursuant to OAC rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

2.a The 1.1 lb CO/hr, 0.8 lb NOx/hr, 0.3 lb OC/hr, 0.2 lb SO2/hr, and 0.2 lb PE/hr limitations were established for PTI purposes to reflect the potential to emit for this emissions unit, based on the testing protocol submitted on April 19, 2001 by the permittee. Therefore, it is not necessary to develop record keeping and/or reporting requirements to ensure compliance with these limitations.

B. Operational Restrictions

C:\temp\permits3\10653.wpd

None

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall maintain monthly records of the following information:

   a. The total number of engines tested; and

   b. The total engine running time compiled for all engines tested during the month.

D. Reporting Requirements

None

E. Testing Requirements

1. Compliance with the emission limitations in Section A.I.1. of this permit shall be determined in accordance with the following methods:

   a. Emission Limitation -
   1.1 lb CO/hr

   Applicable Compliance Method -
   Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the 0.01 lb CO/hp-hr emission factor established during the January 2001 performance testing. If required, compliance shall be also be determined by using Reference Method 10, as specified in 40 CFR Part 60, Appendix A.

   b. Emission Limitation -
   4.82 TPY CO

   Applicable Compliance Method -
   The 4.82 TPY limitation was developed by multiplying the specified allowable emission rate of 1.1 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

   c. Emission Limitation -
   0.8 lb NOx/hr

   Applicable Compliance Method -
   Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the 0.008 lb NOx/hp-hr emission factor established during the January 2001 performance testing. If required, compliance shall also be determined by using Reference Method 7, as specified in 40 CFR Part 60, Appendix A.

C:\temp\permits3\10653.wpd

d. Emission Limitation -
3.50 TPY NOx

Applicable Compliance Method -
The 3.50 TPY limitation was developed by multiplying the specified allowable emission rate of 0.8 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

e. Emission Limitation -
0.3 lb OC/hr

Applicable Compliance Method -
Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the emission factor, 0.003 lb OC/hp-hr (AP-42, Table 3.3-1 (10/96)).

f. Emission Limitation -
1.31 TPY OC

Applicable Compliance Method -
The 1.31 TPY limitation was developed by multiplying the specified allowable emission rate of 0.3 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

g. Emission Limitation -
0.2 lb SO2/hr

Applicable Compliance Method -
Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the emission factor, 0.002 lb SO2/hp-hr (AP-42, Table 3.3-1 (10/96)).

h. Emission Limitation -
0.88 TPY SO2

Applicable Compliance Method -
The 0.88 TPY limitation was developed by multiplying the specified allowable emission rate of 0.2 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

i. Emission Limitation -
0.2 lb PE/hr

C:\temp\permits3\10653.wpd

Applicable Compliance Method -
Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the emission factor, 0.002 lb PE/hp-hr (AP-42, Table 3.3-1, (10/96)). If required, compliance shall be also be determined by using Reference Method 5, as specified in 40 CFR Part 60, Appendix A.

j. Emission Limitation -
0.88 TPY PE

Applicable Compliance Method -
The 0.88 TPY limitation was developed by multiplying the specified allowable emission rate of 0.2 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

k. Emission Limitation -
15% opacity, as a six-minute average

Applicable Compliance Method -
Compliance shall be determined by visible emission evaluations performed in accordance with OAC rule 3745-17-03(B)(3) using the methods and procedures specified in USEPA Method 9.

F. Miscellaneous Requirements

1. This is a modification to PTI # 08-03840 and results in the following net increases in emissions for emissions units P001 through P009 combined: + 38.58 TPY CO, + 21.99 TPY NOx, + 11.31 OC, + 5.66 TPY SO2, and + 5.49 TPY PE.

C:\temp\permits3\10653.wpd

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
P003 - Hot Test Stand No. 3	OAC rule 3745-31-05(A)(3)	1.1 lb/hr and 4.82 TPY carbon monoxide (CO); 0.8 lb/hr and 3.50 TPY nitrogen oxides (NOx); 0.3 lb/hr and 1.31 TPY organic compounds (OC); 0.2 lb/hr and 0.88 TPY sulfur dioxide (SO2); 0.2 lb/hr and 0.88 TPY particulate emissions (PE); 15% opacity, as a six-minute average
	OAC rule 3745-17-07(A)	The opacity limitation specified by this rule is less stringent than the opacity limitation established pursuant to OAC rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

2.a The 1.1 lb CO/hr, 0.8 lb NOx/hr, 0.3 lb OC/hr, 0.2 lb SO2/hr, and 0.2 lb PE/hr limitations were established for PTI purposes to reflect the potential to emit for this emissions unit, based on the testing protocol submitted on April 19, 2001 by the permittee. Therefore, it is not necessary to develop record keeping and/or reporting requirements to ensure compliance with these limitations.

B. Operational Restrictions

C:\temp\permits3\10653.wpd

None

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall maintain monthly records of the following information:

   a. The total number of engines tested; and

   b. The total engine running time compiled for all engines tested during the month.

D. Reporting Requirements

None

E. Testing Requirements

1. Compliance with the emission limitations in Section A.I.1. of this permit shall be determined in accordance with the following methods:

   a. Emission Limitation -
   1.1 lb CO/hr

   Applicable Compliance Method -
   Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the 0.01 lb CO/hp-hr emission factor established during the January 2001 performance testing. If required, compliance shall be also be determined by using Reference Method 10, as specified in 40 CFR Part 60, Appendix A.

   b. Emission Limitation -
   4.82 TPY CO

   Applicable Compliance Method -
   The 4.82 TPY limitation was developed by multiplying the specified allowable emission rate of 1.1 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

   c. Emission Limitation -
   0.8 lb NOx/hr

   Applicable Compliance Method -
   Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the 0.008 lb NOx/hp-hr emission factor established during the January 2001 performance testing. If required, compliance shall also be determined by using Reference Method 7, as specified in 40 CFR Part 60, Appendix A.

C:\temp\permits3\10653.wpd

d. Emission Limitation -
3.50 TPY NOx

Applicable Compliance Method -
The 3.50 TPY limitation was developed by multiplying the specified allowable emission rate of 0.8 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

e. Emission Limitation -
0.3 lb OC/hr

Applicable Compliance Method -
Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the emission factor, 0.003 lb OC/hp-hr (AP-42, Table 3.3-1 (10/96)).

f. Emission Limitation -
1.31 TPY OC

Applicable Compliance Method -
The 1.31 TPY limitation was developed by multiplying the specified allowable emission rate of 0.3 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

g. Emission Limitation -
0.2 lb SO2/hr

Applicable Compliance Method -
Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the emission factor, 0.002 lb SO2/hp-hr (AP-42, Table 3.3-1 (10/96)).

h. Emission Limitation -
0.88 TPY SO2

Applicable Compliance Method -
The 0.88 TPY limitation was developed by multiplying the specified allowable emission rate of 0.2 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

i. Emission Limitation -
0.2 lb PE/hr

C:\temp\permits3\10653.wpd

Applicable Compliance Method -
Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the emission factor, 0.002 lb PE/hp-hr (AP-42, Table 3.3-1, (10/96)). If required, compliance shall be also be determined by using Reference Method 5, as specified in 40 CFR Part 60, Appendix A.

j. Emission Limitation -
0.88 TPY PE

Applicable Compliance Method -
The 0.88 TPY limitation was developed by multiplying the specified allowable emission rate of 0.2 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

k. Emission Limitation -
15% opacity, as a six-minute average

Applicable Compliance Method -
Compliance shall be determined by visible emission evaluations performed in accordance with OAC rule 3745-17-03(B)(3) using the methods and procedures specified in USEPA Method 9.

F. Miscellaneous Requirements

1. This is a modification to PTI # 08-03840 and results in the following net increases in emissions for emissions units P001 through P009 combined: + 38.58 TPY CO, + 21.99 TPY NOx, + 11.31 OC, + 5.66 TPY SO2, and + 5.49 TPY PE.

C:\temp\permits3\10653.wpd

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
P004 - Hot Test Stand No. 4	OAC rule 3745-31-05(A)(3)	1.1 lb/hr and 4.82 TPY carbon monoxide (CO); 0.8 lb/hr and 3.50 TPY nitrogen oxides (NOx); 0.3 lb/hr and 1.31 TPY organic compounds (OC); 0.2 lb/hr and 0.88 TPY sulfur dioxide (SO2); 0.2 lb/hr and 0.88 TPY particulate emissions (PE); 15% opacity, as a six-minute average
	OAC rule 3745-17-07(A)	The opacity limitation specified by this rule is less stringent than the opacity limitation established pursuant to OAC rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

2.a The 1.1 lb CO/hr, 0.8 lb NOx/hr, 0.3 lb OC/hr, 0.2 lb SO2/hr, and 0.2 lb PE/hr limitations were established for PTI purposes to reflect the potential to emit for this emissions unit, based on the testing protocol submitted on April 19, 2001 by the permittee. Therefore, it is not necessary to develop record keeping and/or reporting requirements to ensure compliance with these limitations.

B. Operational Restrictions

C:\temp\permits3\10653.wpd

None

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall maintain monthly records of the following information:

   a. The total number of engines tested; and

   b. The total engine running time compiled for all engines tested during the month.

D. Reporting Requirements

None

E. Testing Requirements

1. Compliance with the emission limitations in Section A.I.1. of this permit shall be determined in accordance with the following methods:

   a. Emission Limitation -
   1.1 lb CO/hr

   Applicable Compliance Method -
   Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the 0.01 lb CO/hp-hr emission factor established during the January 2001 performance testing. If required, compliance shall be also be determined by using Reference Method 10, as specified in 40 CFR Part 60, Appendix A.

   b. Emission Limitation -
   4.82 TPY CO

   Applicable Compliance Method -
   The 4.82 TPY limitation was developed by multiplying the specified allowable emission rate of 1.1 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

   c. Emission Limitation -
   0.8 lb NOx/hr

   Applicable Compliance Method -
   Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the 0.008 lb NOx/hp-hr emission factor established during the January 2001 performance testing. If required, compliance shall also be determined by using Reference Method 7, as specified in 40 CFR Part 60, Appendix A.

C:\temp\permits3\10653.wpd

d. Emission Limitation -
3.50 TPY NOx

Applicable Compliance Method -
The 3.50 TPY limitation was developed by multiplying the specified allowable emission rate of 0.8 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

e. Emission Limitation -
0.3 lb OC/hr

Applicable Compliance Method -
Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the emission factor, 0.003 lb OC/hp-hr (AP-42, Table 3.3-1 (10/96)).

f. Emission Limitation -
1.31 TPY OC

Applicable Compliance Method -
The 1.31 TPY limitation was developed by multiplying the specified allowable emission rate of 0.3 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

g. Emission Limitation -
0.2 lb SO2/hr

Applicable Compliance Method -
Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the emission factor, 0.002 lb SO2/hp-hr (AP-42, Table 3.3-1 (10/96)).

h. Emission Limitation -
0.88 TPY SO2

Applicable Compliance Method -
The 0.88 TPY limitation was developed by multiplying the specified allowable emission rate of 0.2 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

i. Emission Limitation -
0.2 lb PE/hr

C:\temp\permits3\10653.wpd

Applicable Compliance Method -
Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the emission factor, 0.002 lb PE/hp-hr (AP-42, Table 3.3-1, (10/96)). If required, compliance shall be also be determined by using Reference Method 5, as specified in 40 CFR Part 60, Appendix A.

j. Emission Limitation -
0.88 TPY PE

Applicable Compliance Method -
The 0.88 TPY limitation was developed by multiplying the specified allowable emission rate of 0.2 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

k. Emission Limitation -
15% opacity, as a six-minute average

Applicable Compliance Method -
Compliance shall be determined by visible emission evaluations performed in accordance with OAC rule 3745-17-03(B)(3) using the methods and procedures specified in USEPA Method 9.

F. Miscellaneous Requirements

1. This is a modification to PTI # 08-03840 and results in the following net increases in emissions for emissions units P001 through P009 combined: + 38.58 TPY CO, + 21.99 TPY NOx, + 11.31 OC, + 5.66 TPY SO2, and + 5.49 TPY PE.

C:\temp\permits3\10653.wpd

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
P005 - Hot Test Stand No. 5	OAC rule 3745-31-05(A)(3)	1.1 lb/hr and 4.82 TPY carbon monoxide (CO); 0.8 lb/hr and 3.50 TPY nitrogen oxides (NOx); 0.3 lb/hr and 1.31 TPY organic compounds (OC); 0.2 lb/hr and 0.88 TPY sulfur dioxide (SO2); 0.2 lb/hr and 0.88 TPY particulate emissions (PE); 15% opacity, as a six-minute average
	OAC rule 3745-17-07(A)	The opacity limitation specified by this rule is less stringent than the opacity limitation established pursuant to OAC rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

2.a The 1.1 lb CO/hr, 0.8 lb NOx/hr, 0.3 lb OC/hr, 0.2 lb SO2/hr, and 0.2 lb PE/hr limitations were established for PTI purposes to reflect the potential to emit for this emissions unit, based on the testing protocol submitted on April 19, 2001 by the permittee. Therefore, it is not necessary to develop record keeping and/or reporting requirements to ensure compliance with these limitations.

B. Operational Restrictions

C:\temp\permits3\10653.wpd

None

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall maintain monthly records of the following information:

   a. The total number of engines tested; and

   b. The total engine running time compiled for all engines tested during the month.

D. Reporting Requirements

None

E. Testing Requirements

1. Compliance with the emission limitations in Section A.I.1. of this permit shall be determined in accordance with the following methods:

   a. Emission Limitation -
   1.1 lb CO/hr

   Applicable Compliance Method -
   Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the 0.01 lb CO/hp-hr emission factor established during the January 2001 performance testing. If required, compliance shall be also be determined by using Reference Method 10, as specified in 40 CFR Part 60, Appendix A.

   b. Emission Limitation -
   4.82 TPY CO

   Applicable Compliance Method -
   The 4.82 TPY limitation was developed by multiplying the specified allowable emission rate of 1.1 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

   c. Emission Limitation -
   0.8 lb NOx/hr

   Applicable Compliance Method -
   Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the 0.008 lb NOx/hp-hr emission factor established during the January 2001 performance testing. If required, compliance shall also be determined by using Reference Method 7, as specified in 40 CFR Part 60, Appendix A.

C:\temp\permits3\10653.wpd

d. Emission Limitation -
3.50 TPY NOx

Applicable Compliance Method -
The 3.50 TPY limitation was developed by multiplying the specified allowable emission rate of 0.8 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

e. Emission Limitation -
0.3 lb OC/hr

Applicable Compliance Method -
Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the emission factor, 0.003 lb OC/hp-hr (AP-42, Table 3.3-1 (10/96)).

f. Emission Limitation -
1.31 TPY OC

Applicable Compliance Method -
The 1.31 TPY limitation was developed by multiplying the specified allowable emission rate of 0.3 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

g. Emission Limitation -
0.2 lb SO2/hr

Applicable Compliance Method -
Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the emission factor, 0.002 lb SO2/hp-hr (AP-42, Table 3.3-1 (10/96)).

h. Emission Limitation -
0.88 TPY SO2

Applicable Compliance Method -
The 0.88 TPY limitation was developed by multiplying the specified allowable emission rate of 0.2 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

i. Emission Limitation -
0.2 lb PE/hr

C:\temp\permits3\10653.wpd

Applicable Compliance Method -
Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the emission factor, 0.002 lb PE/hp-hr (AP-42, Table 3.3-1, (10/96)). If required, compliance shall be also be determined by using Reference Method 5, as specified in 40 CFR Part 60, Appendix A.

j. Emission Limitation -
0.88 TPY PE

Applicable Compliance Method -
The 0.88 TPY limitation was developed by multiplying the specified allowable emission rate of 0.2 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

k. Emission Limitation -
15% opacity, as a six-minute average

Applicable Compliance Method -
Compliance shall be determined by visible emission evaluations performed in accordance with OAC rule 3745-17-03(B)(3) using the methods and procedures specified in USEPA Method 9.

F. Miscellaneous Requirements

1. This is a modification to PTI # 08-03840 and results in the following net increases in emissions for emissions units P001 through P009 combined: + 38.58 TPY CO, + 21.99 TPY NOx, + 11.31 OC, + 5.66 TPY SO2, and + 5.49 TPY PE.

C:\temp\permits3\10653.wpd

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
P006 - Hot Test Stand No. 6	OAC rule 3745-31-05(A)(3)	1.1 lb/hr and 4.82 TPY carbon monoxide (CO); 0.8 lb/hr and 3.50 TPY nitrogen oxides (NOx); 0.3 lb/hr and 1.31 TPY organic compounds (OC); 0.2 lb/hr and 0.88 TPY sulfur dioxide (SO2); 0.2 lb/hr and 0.88 TPY particulate emissions (PE); 15% opacity, as a six-minute average
	OAC rule 3745-17-07(A)	The opacity limitation specified by this rule is less stringent than the opacity limitation established pursuant to OAC rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

2.a The 1.1 lb CO/hr, 0.8 lb NOx/hr, 0.3 lb OC/hr, 0.2 lb SO2/hr, and 0.2 lb PE/hr limitations were established for PTI purposes to reflect the potential to emit for this emissions unit, based on the testing protocol submitted on April 19, 2001 by the permittee. Therefore, it is not necessary to develop record keeping and/or reporting requirements to ensure compliance with these limitations.

B. Operational Restrictions

C:\temp\permits3\10653.wpd

None

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall maintain monthly records of the following information:

   a. The total number of engines tested; and

   b. The total engine running time compiled for all engines tested during the month.

D. Reporting Requirements

None

E. Testing Requirements

1. Compliance with the emission limitations in Section A.I.1. of this permit shall be determined in accordance with the following methods:

   a. Emission Limitation -
   1.1 lb CO/hr

   Applicable Compliance Method -
   Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the 0.01 lb CO/hp-hr emission factor established during the January 2001 performance testing. If required, compliance shall be also be determined by using Reference Method 10, as specified in 40 CFR Part 60, Appendix A.

   b. Emission Limitation -
   4.82 TPY CO

   Applicable Compliance Method -
   The 4.82 TPY limitation was developed by multiplying the specified allowable emission rate of 1.1 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

   c. Emission Limitation -
   0.8 lb NOx/hr

   Applicable Compliance Method -
   Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the 0.008 lb NOx/hp-hr emission factor established during the January 2001 performance testing. If required, compliance shall also be determined by using Reference Method 7, as specified in 40 CFR Part 60, Appendix A.

C:\temp\permits3\10653.wpd

d. Emission Limitation -
3.50 TPY NOx

Applicable Compliance Method -
The 3.50 TPY limitation was developed by multiplying the specified allowable emission rate of 0.8 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

e. Emission Limitation -
0.3 lb OC/hr

Applicable Compliance Method -
Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the emission factor, 0.003 lb OC/hp-hr (AP-42, Table 3.3-1 (10/96)).

f. Emission Limitation -
1.31 TPY OC

Applicable Compliance Method -
The 1.31 TPY limitation was developed by multiplying the specified allowable emission rate of 0.3 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

g. Emission Limitation -
0.2 lb SO2/hr

Applicable Compliance Method -
Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the emission factor, 0.002 lb SO2/hp-hr (AP-42, Table 3.3-1 (10/96)).

h. Emission Limitation -
0.88 TPY SO2

Applicable Compliance Method -
The 0.88 TPY limitation was developed by multiplying the specified allowable emission rate of 0.2 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

i. Emission Limitation -
0.2 lb PE/hr

C:\temp\permits3\10653.wpd

Applicable Compliance Method -
Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the emission factor, 0.002 lb PE/hp-hr (AP-42, Table 3.3-1, (10/96)). If required, compliance shall be also be determined by using Reference Method 5, as specified in 40 CFR Part 60, Appendix A.

j. Emission Limitation -
0.88 TPY PE

Applicable Compliance Method -
The 0.88 TPY limitation was developed by multiplying the specified allowable emission rate of 0.2 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

k. Emission Limitation -
15% opacity, as a six-minute average

Applicable Compliance Method -
Compliance shall be determined by visible emission evaluations performed in accordance with OAC rule 3745-17-03(B)(3) using the methods and procedures specified in USEPA Method 9.

F. Miscellaneous Requirements

1. This is a modification to PTI # 08-03840 and results in the following net increases in emissions for emissions units P001 through P009 combined: + 38.58 TPY CO, + 21.99 TPY NOx, + 11.31 OC, + 5.66 TPY SO2, and + 5.49 TPY PE.

C:\temp\permits3\10653.wpd

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
P007 - Hot Test Stand No. 7	OAC rule 3745-31-05(A)(3)	1.1 lb/hr and 4.82 TPY carbon monoxide (CO); 0.8 lb/hr and 3.50 TPY nitrogen oxides (NOx); 0.3 lb/hr and 1.31 TPY organic compounds (OC); 0.2 lb/hr and 0.88 TPY sulfur dioxide (SO2); 0.2 lb/hr and 0.88 TPY particulate emissions (PE); 15% opacity, as a six-minute average
	OAC rule 3745-17-07(A)	The opacity limitation specified by this rule is less stringent than the opacity limitation established pursuant to OAC rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

2.a The 1.1 lb CO/hr, 0.8 lb NOx/hr, 0.3 lb OC/hr, 0.2 lb SO2/hr, and 0.2 lb PE/hr limitations were established for PTI purposes to reflect the potential to emit for this emissions unit, based on the testing protocol submitted on April 19, 2001 by the permittee. Therefore, it is not necessary to develop record keeping and/or reporting requirements to ensure compliance with these limitations.

B. Operational Restrictions

C:\temp\permits3\10653.wpd

None

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall maintain monthly records of the following information:

   a. The total number of engines tested; and

   b. The total engine running time compiled for all engines tested during the month.

D. Reporting Requirements

None

E. Testing Requirements

1. Compliance with the emission limitations in Section A.I.1. of this permit shall be determined in accordance with the following methods:

   a. Emission Limitation -
   1.1 lb CO/hr

   Applicable Compliance Method -
   Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the 0.01 lb CO/hp-hr emission factor established during the January 2001 performance testing. If required, compliance shall be also be determined by using Reference Method 10, as specified in 40 CFR Part 60, Appendix A.

   b. Emission Limitation -
   4.82 TPY CO

   Applicable Compliance Method -
   The 4.82 TPY limitation was developed by multiplying the specified allowable emission rate of 1.1 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

   c. Emission Limitation -
   0.8 lb NOx/hr

   Applicable Compliance Method -
   Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the 0.008 lb NOx/hp-hr emission factor established during the January 2001 performance testing. If required, compliance shall also be determined by using Reference Method 7, as specified in 40 CFR Part 60, Appendix A.

C:\temp\permits3\10653.wpd

d. Emission Limitation -
3.50 TPY NOx

Applicable Compliance Method -
The 3.50 TPY limitation was developed by multiplying the specified allowable emission rate of 0.8 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

e. Emission Limitation -
0.3 lb OC/hr

Applicable Compliance Method -
Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the emission factor, 0.003 lb OC/hp-hr (AP-42, Table 3.3-1 (10/96)).

f. Emission Limitation -
1.31 TPY OC

Applicable Compliance Method -
The 1.31 TPY limitation was developed by multiplying the specified allowable emission rate of 0.3 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

g. Emission Limitation -
0.2 lb SO2/hr

Applicable Compliance Method -
Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the emission factor, 0.002 lb SO2/hp-hr (AP-42, Table 3.3-1 (10/96)).

h. Emission Limitation -
0.88 TPY SO2

Applicable Compliance Method -
The 0.88 TPY limitation was developed by multiplying the specified allowable emission rate of 0.2 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

i. Emission Limitation -
0.2 lb PE/hr

C:\temp\permits3\10653.wpd

Applicable Compliance Method -
Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the emission factor, 0.002 lb PE/hp-hr (AP-42, Table 3.3-1, (10/96)). If required, compliance shall be also be determined by using Reference Method 5, as specified in 40 CFR Part 60, Appendix A.

j. Emission Limitation -
0.88 TPY PE

Applicable Compliance Method -
The 0.88 TPY limitation was developed by multiplying the specified allowable emission rate of 0.2 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

k. Emission Limitation -
15% opacity, as a six-minute average

Applicable Compliance Method -
Compliance shall be determined by visible emission evaluations performed in accordance with OAC rule 3745-17-03(B)(3) using the methods and procedures specified in USEPA Method 9.

F. Miscellaneous Requirements

1. This is a modification to PTI # 08-03840 and results in the following net increases in emissions for emissions units P001 through P009 combined: + 38.58 TPY CO, + 21.99 TPY NOx, + 11.31 OC, + 5.66 TPY SO2, and + 5.49 TPY PE.

C:\temp\permits3\10653.wpd

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
P008 - Hot Test Stand No. 8	OAC rule 3745-31-05(A)(3)	1.1 lb/hr and 4.82 TPY carbon monoxide (CO); 0.8 lb/hr and 3.50 TPY nitrogen oxides (NOx); 0.3 lb/hr and 1.31 TPY organic compounds (OC); 0.2 lb/hr and 0.88 TPY sulfur dioxide (SO2); 0.2 lb/hr and 0.88 TPY particulate emissions (PE); 15% opacity, as a six-minute average
	OAC rule 3745-17-07(A)	The opacity limitation specified by this rule is less stringent than the opacity limitation established pursuant to OAC rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

2.a The 1.1 lb CO/hr, 0.8 lb NOx/hr, 0.3 lb OC/hr, 0.2 lb SO2/hr, and 0.2 lb PE/hr limitations were established for PTI purposes to reflect the potential to emit for this emissions unit, based on the testing protocol submitted on April 19, 2001 by the permittee. Therefore, it is not necessary to develop record keeping and/or reporting requirements to ensure compliance with these limitations.

B. Operational Restrictions

C:\temp\permits3\10653.wpd

None

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall maintain monthly records of the following information:

   a. The total number of engines tested; and

   b. The total engine running time compiled for all engines tested during the month.

D. Reporting Requirements

None

E. Testing Requirements

1. Compliance with the emission limitations in Section A.I.1. of this permit shall be determined in accordance with the following methods:

   a. Emission Limitation -
   1.1 lb CO/hr

   Applicable Compliance Method -
   Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the 0.01 lb CO/hp-hr emission factor established during the January 2001 performance testing. If required, compliance shall be also be determined by using Reference Method 10, as specified in 40 CFR Part 60, Appendix A.

   b. Emission Limitation -
   4.82 TPY CO

   Applicable Compliance Method -
   The 4.82 TPY limitation was developed by multiplying the specified allowable emission rate of 1.1 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

   c. Emission Limitation -
   0.8 lb NOx/hr

   Applicable Compliance Method -
   Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the 0.008 lb NOx/hp-hr emission factor established during the January 2001 performance testing. If required, compliance shall also be determined by using Reference Method 7, as specified in 40 CFR Part 60, Appendix A.

C:\temp\permits3\10653.wpd

d. Emission Limitation -
3.50 TPY NOx

Applicable Compliance Method -
The 3.50 TPY limitation was developed by multiplying the specified allowable emission rate of 0.8 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

e. Emission Limitation -
0.3 lb OC/hr

Applicable Compliance Method -
Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the emission factor, 0.003 lb OC/hp-hr (AP-42, Table 3.3-1 (10/96)).

f. Emission Limitation -
1.31 TPY OC

Applicable Compliance Method -
The 1.31 TPY limitation was developed by multiplying the specified allowable emission rate of 0.3 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

g. Emission Limitation -
0.2 lb SO2/hr

Applicable Compliance Method -
Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the emission factor, 0.002 lb SO2/hp-hr (AP-42, Table 3.3-1 (10/96)).

h. Emission Limitation -
0.88 TPY SO2

Applicable Compliance Method -
The 0.88 TPY limitation was developed by multiplying the specified allowable emission rate of 0.2 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

i. Emission Limitation -
0.2 lb PE/hr

C:\temp\permits3\10653.wpd

Applicable Compliance Method -
Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the emission factor, 0.002 lb PE/hp-hr (AP-42, Table 3.3-1, (10/96)). If required, compliance shall be also be determined by using Reference Method 5, as specified in 40 CFR Part 60, Appendix A.

j. Emission Limitation -
0.88 TPY PE

Applicable Compliance Method -
The 0.88 TPY limitation was developed by multiplying the specified allowable emission rate of 0.2 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

k. Emission Limitation -
15% opacity, as a six-minute average

Applicable Compliance Method -
Compliance shall be determined by visible emission evaluations performed in accordance with OAC rule 3745-17-03(B)(3) using the methods and procedures specified in USEPA Method 9.

F. Miscellaneous Requirements

1. This is a modification to PTI # 08-03840 and results in the following net increases in emissions for emissions units P001 through P009 combined: + 38.58 TPY CO, + 21.99 TPY NOx, + 11.31 OC, + 5.66 TPY SO2, and + 5.49 TPY PE.

C:\temp\permits3\10653.wpd

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
P009 - Hot Test Stand No. 9	OAC rule 3745-31-05(A)(3)	1.1 lb/hr and 4.82 TPY carbon monoxide (CO); 0.8 lb/hr and 3.50 TPY nitrogen oxides (NOx); 0.3 lb/hr and 1.31 TPY organic compounds (OC); 0.2 lb/hr and 0.88 TPY sulfur dioxide (SO2); 0.2 lb/hr and 0.88 TPY particulate emissions (PE); 15% opacity, as a six-minute average
	OAC rule 3745-17-07(A)	The opacity limitation specified by this rule is less stringent than the opacity limitation established pursuant to OAC rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

2.a The 1.1 lb CO/hr, 0.8 lb NOx/hr, 0.3 lb OC/hr, 0.2 lb SO2/hr, and 0.2 lb PE/hr limitations were established for PTI purposes to reflect the potential to emit for this emissions unit, based on the testing protocol submitted on April 19, 2001 by the permittee. Therefore, it is not necessary to develop record keeping and/or reporting requirements to ensure compliance with these limitations.

B. Operational Restrictions

C:\temp\permits3\10653.wpd

None

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall maintain monthly records of the following information:

   a. The total number of engines tested; and

   b. The total engine running time compiled for all engines tested during the month.

D. Reporting Requirements

None

E. Testing Requirements

1. Compliance with the emission limitations in Section A.I.1. of this permit shall be determined in accordance with the following methods:

   a. Emission Limitation -
   1.1 lb CO/hr

   Applicable Compliance Method -
   Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the 0.01 lb CO/hp-hr emission factor established during the January 2001 performance testing. If required, compliance shall be also be determined by using Reference Method 10, as specified in 40 CFR Part 60, Appendix A.

   b. Emission Limitation -
   4.82 TPY CO

   Applicable Compliance Method -
   The 4.82 TPY limitation was developed by multiplying the specified allowable emission rate of 1.1 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

   c. Emission Limitation -
   0.8 lb NOx/hr

   Applicable Compliance Method -
   Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the 0.008 lb NOx/hp-hr emission factor established during the January 2001 performance testing. If required, compliance shall also be determined by using Reference Method 7, as specified in 40 CFR Part 60, Appendix A.

C:\temp\permits3\10653.wpd

d. Emission Limitation -
3.50 TPY NOx

Applicable Compliance Method -
The 3.50 TPY limitation was developed by multiplying the specified allowable emission rate of 0.8 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

e. Emission Limitation -
0.3 lb OC/hr

Applicable Compliance Method -
Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the emission factor, 0.003 lb OC/hp-hr (AP-42, Table 3.3-1 (10/96)).

f. Emission Limitation -
1.31 TPY OC

Applicable Compliance Method -
The 1.31 TPY limitation was developed by multiplying the specified allowable emission rate of 0.3 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

g. Emission Limitation -
0.2 lb SO2/hr

Applicable Compliance Method -
Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the emission factor, 0.002 lb SO2/hp-hr (AP-42, Table 3.3-1 (10/96)).

h. Emission Limitation -
0.88 TPY SO2

Applicable Compliance Method -
The 0.88 TPY limitation was developed by multiplying the specified allowable emission rate of 0.2 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

i. Emission Limitation -
0.2 lb PE/hr

C:\temp\permits3\10653.wpd

Applicable Compliance Method -
Compliance shall be demonstrated by multiplying the average test protocol horsepower output (100 hp) by the emission factor, 0.002 lb PE/hp-hr (AP-42, Table 3.3-1, (10/96)). If required, compliance shall be also be determined by using Reference Method 5, as specified in 40 CFR Part 60, Appendix A.

j. Emission Limitation -
0.88 TPY PE

Applicable Compliance Method -
The 0.88 TPY limitation was developed by multiplying the specified allowable emission rate of 0.2 lb/hr by the maximum annual operating schedule of 8,760 hrs/yr. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

k. Emission Limitation -
15% opacity, as a six-minute average

Applicable Compliance Method -
Compliance shall be determined by visible emission evaluations performed in accordance with OAC rule 3745-17-03(B)(3) using the methods and procedures specified in USEPA Method 9.

F. Miscellaneous Requirements

1. This is a modification to PTI # 08-03840 and results in the following net increases in emissions for emissions units P001 through P009 combined: + 38.58 TPY CO, + 21.99 TPY NOx, + 11.31 OC, + 5.66 TPY SO2, and + 5.49 TPY PE.

C:\temp\permits3\10653.wpd