



State of Ohio Environmental Protection Agency

Street Address:

Lazarus Gov. Center  
122 S. Front Street  
Columbus, OH 43215

TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center  
P.O. Box 1049  
Columbus, OH 43216-1049

**RE: FINAL PERMIT TO INSTALL  
FRANKLIN COUNTY  
Application No: 01-08418**

**CERTIFIED MAIL**

	TOXIC REVIEW
	PSD
	SYNTHETIC MINOR
	CEMS
	MACT
	NSPS
	NESHAPS
	NETTING
	MAJOR NON-ATTAINMENT
Y	MODELING SUBMITTED
	GASOLINE DISPENSING FACILITY

**DATE: 7/17/2001**

Three C Body Shop  
Bob Juniper  
1469 Harrisburg Pike  
Columbus, OH 43223

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission  
236 East Town Street, Room 300  
Columbus, Ohio 43215

Very truly yours,

Thomas G. Rigo, Manager  
Field Operations and Permit Section  
Division of Air Pollution Control

cc: USEPA

CDO



**Permit To Install  
Terms and Conditions**

**Issue Date: 7/17/2001  
Effective Date: 7/17/2001**

**FINAL PERMIT TO INSTALL 01-08418**

Application Number: 01-08418  
APS Premise Number: 0125041355  
Permit Fee: **\$400**  
Name of Facility: Three C Body Shop  
Person to Contact: Bob Juniper  
Address: 1469 Harrisburg Pike  
Columbus, OH 43223

Location of proposed air contaminant source(s) [emissions unit(s)]:  
**1469 Harrisburg Pike  
Columbus, Ohio**

Description of proposed emissions unit(s):  
**Two team blowtherm expert downdraft spray booths.**

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

## Part I - GENERAL TERMS AND CONDITIONS

### A. Permit to Install General Terms and Conditions

#### 1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

#### 2. Reporting Requirements Related to Monitoring and Recordkeeping Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

#### 3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

#### 4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may

be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

**5. Scheduled Maintenance/Malfunction Reporting**

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

**6. Permit Transfers**

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

**7. Air Pollution Nuisance**

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

**8. Termination of Permit to Install**

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

**9. Construction of New Sources(s)**

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

**10. Public Disclosure**

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

**11. Applicability**

This Permit to Install is applicable only to the emissions unit(s) identified in the Permit to Install. Separate application must be made to the Director for the installation or modification of any other emissions unit(s).

**12. Best Available Technology**

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

**13. Source Operation and Operating Permit Requirements After Completion of Construction**

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within thirty (30) days after commencing operation of the emissions unit(s) covered by this permit.

**14. Construction Compliance Certification**

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and

conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

**15. Fees**

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

**B. Permit to Install Summary of Allowable Emissions**

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

**SUMMARY (for informational purposes only)**  
**TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS**

<u>Pollutant</u>	<u>Tons Per Year</u>
VOC	6.5 tpy

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K005 - spray paint booth with dry filtration for the repainting (refinishing) of motor vehicles	OAC rule 3745-31-05(A)(3)	<p>Volatile organic compound (VOC) emissions shall not exceed 7.6 pounds per hour, excluding cleanup and 6.5 tons per year, including cleanup. See A.2.a below.</p> <p>See B.1. below.</p>
	OAC rule 3745-21-09(U)(2)(c)	The VOC content limit requirements of OAC rule 3745-21-09(U)(1) do not apply.

2. **Additional Terms and Conditions**

- 2.a The 7.6 pounds of VOC per hour limitation for this emissions unit was established to reflect the hourly potential to emit and to show compliance with the Ohio EPA Air Toxics Policy. Therefore, it is not necessary to develop record keeping and/or reporting requirements to ensure compliance with this limit.

**B. Operational Restrictions**

1. The permittee shall operate the dry filtration system whenever this emissions unit is in operation.
2. The permittee shall maintain a minimum stack height of twenty five (25) feet above ground as measured from the ground to the top of the stack for this emissions unit. All air contaminant emissions from this emissions unit shall be emitted through the stack.

**C. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall collect and record the following information on a monthly basis for the purpose of determining annual VOC emissions:

- a. The name and identification of each type of coating and cleanup material employed.
  - b. The VOC content of each type of coating employed (excluding water and exempt solvents), as applied, in pounds per gallon.
  - c. The VOC content of each type of cleanup material, in pounds per gallon.
  - d. The number of gallons of each type of coating and cleanup material employed.
  - e. The number of gallons of each type of cleanup material drummed for shipment off-site.
  - f. The total VOC emissions from all coatings and cleanup materials employed, in pounds or tons. i.e., the sum of all coatings and cleanup materials times the respective VOC contents minus the amount of cleanup material drummed for shipment off-site, in pounds or tons (number of gallons of cleanup times the respective VOC content ).
2. The permittee shall maintain daily records that document any time periods when the dry filtration system was not in service when the emissions unit was in operation.
  3. The permit to install for this emissions unit (K005) was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model. The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant:

Pollutant: Titanium Dioxide

TLV (mg/m<sup>3</sup>): 10

Maximum Hourly Emission Rate (lbs/hr): 7.6

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m<sup>3</sup>): 150.7

MAGLC (ug/m<sup>3</sup>): 238 ug/m<sup>3</sup>

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the

handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;

- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
  - b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
  - c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.
4. The permittee shall collect and record the following information for each change where the air toxic modeling was required pursuant to the Air Toxic Policy:
- a. background data that describes the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.); and
  - b. a copy of the resulting computer model runs that show the results of the application of the Air Toxic Policy for the change.

#### **D. Reporting Requirements**

- 1. If the annual emission limit of 6.5 tons per year of VOC is exceeded at any time within the calendar year, the permittee shall submit an emissions report which specifies the total VOC emissions from this emissions unit and the period of time the exceedance occurred. This report shall be submitted within 30 days after the deviation occurs.

2. The permittee shall notify the Central District Office in writing of any daily record showing that the dry filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Central District Office within 30 days after the event occurs.

**E. Testing Requirements**

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):
  - a. Emissions Limitation:  
Volatile organic compound emissions shall not exceed 7.6 pounds per hour, excluding cleanup.  
  
Applicable Compliance Method:  
Compliance with the hourly VOC emission limit shall be demonstrated by multiplying the maximum VOC content of the coating employed (7.6 lbs VOC per gallon) by the maximum usage in one hour (1 gallon per hour).
  - b. Emission Limitation:  
Volatile organic compound emissions shall not exceed 6.5 tons per year, including cleanup.  
  
Applicable Compliance Method:  
Compliance with the annual VOC emission limitation shall be determined by the summing the monthly emissions for the calendar year recorded in Section C.1.f. above.
2. The VOC content of the coatings and clean-up materials shall be determined according to OAC rule 3745-21-10(B). USEPA Methods 24 shall be used to determine the VOC contents for coatings. If, pursuant to section 4.3 of Method 24, 40 CFR Part 60, Appendix A, an owner or operator determines that Method 24 cannot be used for a particular coating or ink, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating or ink to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A.

**F. Miscellaneous Requirements**

None

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K006 - spray paint booth with dry filtration for the repainting (refinishing) of motor vehicles	OAC rule 3745-31-05(A)(3)	Volatile organic compound (VOC) emissions shall not exceed 7.6 pounds per hour, excluding cleanup and 6.5 tons per year, including cleanup. See A.2.a below.
	OAC rule 3745-21-09(U)(2)(c)	See B.1. below.  The VOC content limit requirements of OAC rule 3745-21-09(U)(1) do not apply.

2. **Additional Terms and Conditions**

- 2.a The 7.6 pounds of VOC per hour limitation for this emissions unit was established to reflect the hourly potential to emit and to show compliance with the Ohio EPA Air Toxics Policy. Therefore, it is not necessary to develop record keeping and/or reporting requirements to ensure compliance with this limit.

**B. Operational Restrictions**

1. The permittee shall operate the dry filtration system whenever this emissions unit is in operation.
2. The permittee shall maintain a minimum stack height of twenty five (25) feet above ground as measured from the ground to the top of the stack for this emissions unit. All air contaminant emissions from this emissions unit shall be emitted through the stack.

**C. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall collect and record the following information on a monthly basis for the purpose of determining annual VOC emissions:
  - a. The name and identification of each type of coating and cleanup material employed.
  - b. The VOC content of each type of coating employed (excluding water and exempt solvents), as applied, in pounds per gallon.
  - c. The VOC content of each type of cleanup material, in pounds per gallon.
  - d. The number of gallons of each type of coating and cleanup material employed.
  - e. The number of gallons of each type of cleanup material drummed for shipment off-site.
  - f. The total VOC emissions from all coatings and cleanup materials employed, in pounds or tons. i.e., the sum of all coatings and cleanup materials times the respective VOC contents minus the amount of cleanup material drummed for shipment off-site, in pounds or tons (number of gallons of cleanup times the respective VOC content ).
2. The permittee shall maintain daily records that document any time periods when the dry filtration system was not in service when the emissions unit was in operation.
3. The permit to install for this emissions unit (K006) was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Titanium Dioxide

TLV (mg/m3): 10

Maximum Hourly Emission Rate (lbs/hr): 7.6

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 150.7

MAGLC (ug/m3): 238 ug/m3

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still

satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
  - b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
  - c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.
4. The permittee shall collect and record the following information for each change where the air toxic modeling was required pursuant to the Air Toxic Policy:
- a. background data that describes the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.); and
  - b. a copy of the resulting computer model runs that show the results of the application of the Air Toxic Policy for the change.

**D. Reporting Requirements**

1. If the annual emission limit of 6.5 tons per year of VOC is exceeded at any time within the calendar year, the permittee shall submit an emissions report which specifies the total VOC emissions from this emissions unit and the period of time the exceedance occurred. This report shall be submitted within 30 days after the deviation occurs.
2. The permittee shall notify the Central District Office in writing of any daily record showing that the dry filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Central District Office within 30 days after the event occurs.

**E. Testing Requirements**

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):
  - a. Emissions Limitation:  
Volatile organic compound emissions shall not exceed 7.6 pounds per hour, excluding cleanup.  
  
Applicable Compliance Method:  
Compliance with the hourly VOC emission limit shall be demonstrated by multiplying the maximum VOC content of the coating employed (7.6 lbs VOC per gallon) by the maximum usage in one hour (1 gallon per hour).
  - b. Emission Limitation:  
Volatile organic compound emissions shall not exceed 6.5 tons per year, including cleanup.  
  
Applicable Compliance Method:  
Compliance with the annual VOC emission limitation shall be determined by the summing the monthly emissions for the calendar year recorded in Section C.1.f. above.
2. The VOC content of the coatings and clean-up materials shall be determined according to OAC rule 3745-21-10(B). USEPA Methods 24 shall be used to determine the VOC contents for coatings. If, pursuant to section 4.3 of Method 24, 40 CFR Part 60, Appendix A, an owner or operator determines that Method 24 cannot be used for a particular coating or ink, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating or ink to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A.

**F. Miscellaneous Requirements**

None

**NEW SOURCE REVIEW FORM B**

PTI Number: 01-08418

Facility ID: 0125041355

FACILITY NAME Three C Body Shop

FACILITY DESCRIPTION Two team blowtherm expert downdraft spray booths. CITY/TWP Columbus

SIC CODE 5511 SCC CODE 4-02-025-01 EMISSIONS UNIT ID K005

EMISSIONS UNIT DESCRIPTION downdraft spray paint booth

DATE INSTALLED 10/01

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter					
PM <sub>10</sub>					
Sulfur Dioxide					
Organic Compounds		7.6 lb/hr	6.5 tpy	7.6 lb/hr	6.5 tpy
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? \_\_\_\_\_ NESHAP? \_\_\_\_\_ PSD? \_\_\_\_\_ OFFSET POLICY? \_\_\_\_\_

**WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?**

**Enter Determination** - See additional terms and conditions.

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? yes

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$ \_\_\_\_\_

**TOXIC AIR CONTAMINANTS**

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED\*? x YES \_\_\_\_\_ NO \_\_\_\_\_

IDENTIFY THE AIR CONTAMINANTS: titanium dioxide, methyl isobutyl ketone, toluene, xylenes, acetone, etc.

**NEW SOURCE REVIEW FORM B**

PTI Number: 01-08418

Facility ID: 0125041355

FACILITY NAME Three C Body Shop

FACILITY DESCRIPTION Two team blowtherm expert downdraft spray booths. CITY/TWP Columbus

SIC CODE 5511 SCC CODE 4-02-025-01 EMISSIONS UNIT ID K006

EMISSIONS UNIT DESCRIPTION downdraft spray paint booth

DATE INSTALLED 10/01

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter					
PM <sub>10</sub>					
Sulfur Dioxide					
Organic Compounds		7.6 lbs/hr	6.5 tpy	7.6 lbs/hr	6.5 tpy
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? \_\_\_\_\_ NESHAP? \_\_\_\_\_ PSD? \_\_\_\_\_ OFFSET POLICY? \_\_\_\_\_

**WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?**

**Enter Determination** - See additional terms and conditions.

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? yes

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$ \_\_\_\_\_

**TOXIC AIR CONTAMINANTS**

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED\*? x YES \_\_\_\_\_ NO \_\_\_\_\_

IDENTIFY THE AIR CONTAMINANTS: titanium dioxide, methyl isobutyl ketone, toluene, xylenes, acetone, etc.

**Ohio EPA Permit to Install Information Form** Please describe below any documentation which is being submitted with this recommendation (must be sent the same day). Electronic items should be submitted with the e-mail transmitting the PTI terms, and in software that CO can utilize. If mailing any hard copy, this section must be printed as a cover page. All items must be clearly labeled indicating the PTI name and number. Submit **hard copy items to Pam McGraner**, AQM&P, DAPC, Central Office, and electronic files to [airpti@epa.state.oh.us](mailto:airpti@epa.state.oh.us)

*Please fill out the following. If the checkbox does not work, replace it with an 'X'*

Electronic	<b>Additional information File Name Convention (your PTI # plus this letter)</b>	Hard Copy	None
------------	--	-----------	------

**NEW SOURCE REVIEW FORM B**

PTI Number: 01-08418

Facility ID: 0125041355

FACILITY NAME Three C Body Shop

FACILITY DESCRIPTION Two team blowtherm expert downdraft spray booths. CITY/TWP Columbus

Calculations (required)	<input checked="" type="checkbox"/>	0000000c.wpd	<input type="checkbox"/>	
Modeling form/results	<input type="checkbox"/>	0000000s.wpd	<input checked="" type="checkbox"/>	<input type="checkbox"/>
PTI Application (complete or partial)*	<input type="checkbox"/>	0000000a.wpd	<input type="checkbox"/>	<input checked="" type="checkbox"/>
BAT Study	<input type="checkbox"/>	0000000b.wpd	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Other/misc.	<input type="checkbox"/>	0000000t.wpd	<input type="checkbox"/>	<input checked="" type="checkbox"/>

\* Mandatory for netting, PSD, nonattainment NSR, 112(g), 21-07(G)(9)(g) and 21-09(U)(2)(f) - 2 complete copies.

Please complete (see comment bubble to the left for additional instructions):

**NSR Discussion**

Three-C Body Shop is applying for a permit to install for two new paint booths at an existing facility. The paint booths are used to refinish automobiles. Both paint booths use HVLP guns and a dry filtration system to control particulate. The paint booths are subject to the requirements of OAC rule 3745-31-05(A)(3) and 3745-21-09(U)(2)(c). All terms and conditions were selected using the template for body shops. The annual and hourly VOC content of coatings/cleanup materials and the usage provided by the PTI application. Modeling was performed to assure compliance with the Air Toxics Policy. The maximum ground level concentrations determined by the modeling were well below the MAGLC. A hard copy of the modeling will be sent to central office.

Calculations:

Hourly VOC limit:

(max. VOC content of coating) x (maximum annual usage)

$(7.6 \text{ lbs VOC/gal}) \times (1 \text{ gal/hr}) = 7.6 \text{ lbs VOC/hr}$

Annual VOC limit:

summation: (specific VOC content) x (maximum coating usage/cleanup material)

$(4.2 \text{ lbs VOC/gal}) \times (575 \text{ gal/yr}) = 1.21 \text{ ton/yr} +$   
 $(6.6 \text{ lbs VOC/gal}) \times (1035 \text{ gal/yr}) = 3.42 \text{ ton/yr} +$   
 $(4.6 \text{ lbs VOC/gal}) \times (127 \text{ gal/yr}) = 0.3 \text{ ton/yr} +$   
 $(7.6 \text{ lbs VOC/gal}) \times (18 \text{ gal/yr}) = 0.07 \text{ ton/yr} +$   
 $(4.8 \text{ lbs VOC/gal}) \times (110 \text{ gal/yr}) = 0.3 \text{ ton/yr} = 6.5 \text{ tons/year}$

Please complete for these type permits (For PSD/NSR Permit, place mouse over this text):

Synthetic Minor Determination and/or  Netting Determination  
Permit To Install ENTER PTI NUMBER HERE

**A. Source Description**

**B. Facility Emissions and Attainment Status**

C:\temp\permits3\3105.wpd

**NEW SOURCE REVIEW FORM B**

PTI Number: 01-08418

Facility ID: 0125041355

FACILITY NAME Three C Body Shop

FACILITY DESCRIPTION Two team blowtherm expert downdraft spray booths.

CITY/TWP Columbus

**C. Source Emissions**

**D. Conclusion**

**PLEASE PROVIDE ADDITIONAL NOTES OR COMMENTS AS NECESSARY:**

**NONE**

**Please complete:**

**SUMMARY (for informational purposes only)  
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS**

<u>Pollutant</u>	<u>Tons Per Year</u>
VOC	6.5 tpy

**NEW SOURCE REVIEW FORM B**

PTI Number: 01-08418

Facility ID: 0125041355

FACILITY NAME Three C Body Shop

---

FACILITY DESCRIPTION Two team blowtherm expert downdraft  
spray booths.

---

CITY/TWP Columbus

---