



State of Ohio Environmental Protection Agency

Street Address:

Lazarus Gov. Center
122 S. Front Street
Columbus, OH 43215

TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center
P.O. Box 1049
Columbus, OH 43216-1049

**RE: FINAL PERMIT TO INSTALL
MADISON COUNTY
Application No: 01-08192**

CERTIFIED MAIL

	TOXIC REVIEW
	PSD
	SYNTHETIC MINOR
	CEMS
	MACT
	NSPS
	NESHAPS
	NETTING
	MAJOR NON-ATTAINMENT
	MODELING SUBMITTED
	GASOLINE DISPENSING FACILITY

DATE: 1/9/2001

Showa Aluminum Corporation of America
Robert Feltz
10500 ODay Harrison Road
Mount Sterling, OH 43143

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
236 East Town Street, Room 300
Columbus, Ohio 43215

Very truly yours,

Thomas G. Rigo
Field Operations and Permit Section
Division of Air Pollution Control

cc: USEPA

CDO



FINAL PERMIT TO INSTALL 01-08192

Application Number: 01-08192

APS Premise Number: 0149000088

Permit Fee: **\$800**

Name of Facility: Showa Aluminum Corporation of America

Person to Contact: Robert

Address: 10500 ODay Harrison Road
Mount Sterling, OH 43143

Location of proposed air contaminant source(s) [emissions unit(s)]:

**10500 ODay Harrison Road
Mount Sterling, Ohio**

Description of proposed emissions unit(s):

Roller Leveler and automatic tube cleaner.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Part I - GENERAL TERMS AND CONDITIONS

A. State and Federally Enforceable Permit To Install General Terms and Conditions

1. Monitoring and Related Recordkeeping and Reporting Requirements

- a. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall maintain records that include the following, where applicable, for any required monitoring under this permit:
 - i. The date, place (as defined in the permit), and time of sampling or measurements.
 - ii. The date(s) analyses were performed.
 - iii. The company or entity that performed the analyses.
 - iv. The analytical techniques or methods used.
 - v. The results of such analyses.
 - vi. The operating conditions existing at the time of sampling or measurement.
- b. Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.
- c. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall submit required reports in the following manner:
 - i. Reports of any required monitoring and/or recordkeeping of federally enforceable information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
 - ii. Quarterly written reports of (i) any deviations from federally enforceable emission limitations, operational restrictions, and control device operating parameter limitations, excluding deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06, that have been detected by the testing, monitoring and recordkeeping requirements specified in this permit, (ii) the probable cause of such deviations, and (iii) any corrective actions or preventive measures taken, shall be made to the appropriate Ohio EPA District Office or local air agency. The written reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. See B.11 below if no deviations occurred during the quarter.

- iii. Written reports, which identify any deviations from the federally enforceable monitoring, recordkeeping, and reporting requirements contained in this permit shall be submitted to the appropriate Ohio EPA District Office or local air agency every six months, i.e., by January 31 and July 31 of each year for the previous six calendar months. If no deviations occurred during a six-month period, the permittee shall submit a semi-annual report, which states that no deviations occurred during that period.
- iv. Each written report shall be signed by a responsible official certifying that, based on information and belief formed after reasonable inquiry, the statements and information in the report are true, accurate, and complete.

2. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction, i.e., upset, of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. (The definition of an upset condition shall be the same as that used in OAC rule 3745-15-06(B)(1) for a malfunction.) The verbal and written reports shall be submitted pursuant to OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emission unit(s) that is (are) served by such control system(s).

3. Risk Management Plans

If the permittee is required to develop and register a risk management plan pursuant to section 112(r) of the Clean Air Act, as amended, 42 U.S.C. 7401 et seq. ("Act"), the permittee shall comply with the requirement to register such a plan.

4. Title IV Provisions

If the permittee is subject to the requirements of 40 CFR Part 72 concerning acid rain, the permittee shall ensure that any affected emissions unit complies with those requirements. Emissions exceeding any allowances that are lawfully held under Title IV of the Act, or any regulations adopted thereunder, are prohibited.

5. Severability Clause

A determination that any term or condition of this permit is invalid shall not invalidate the force or effect of any other term or condition thereof, except to the extent that any other term or condition depends in whole or in part for its operation or implementation upon the term or condition declared invalid.

6. General Requirements

- a. The permittee must comply with all terms and conditions of this permit. Any noncompliance with the federally enforceable terms and conditions of this permit constitutes a violation of the Act, and is grounds for enforcement action or for permit revocation, revocation and reissuance, or modification, or for denial of a permit renewal application.
- b. It shall not be a defense for the permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the federally enforceable terms and conditions of this permit.
- c. This permit may be modified, reopened, revoked, or revoked and reissued, for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or revocation, or of a notification of planned changes or anticipated noncompliance does not stay any term and condition of this permit.
- d. This permit does not convey any property rights of any sort, or any exclusive privilege.
- e. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon request, the permittee shall also furnish to the Director or an authorized representative of the Director, copies of records required to be kept by this permit. For information claimed to be confidential in the submittal to the Director, if the Administrator of the U.S. EPA requests such information, the permittee may furnish such records directly to the Administrator along with a claim of confidentiality.

7. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit To Install fees within 30 days after the issuance of this Permit To Install.

8. Federal and State Enforceability

Only those terms and conditions designated in this permit as federally enforceable, that are required under the Act, or any of its applicable requirements, including relevant provisions designed to limit the potential to emit of a source, are enforceable by the Administrator of the U.S. EPA, the State, and citizens under the Act. All other terms and conditions of this permit shall not be federally enforceable and shall be enforceable under State law only.

9. Compliance Requirements

- a. Any document (including reports) required to be submitted and required by a federally applicable requirement in this permit shall include a certification by a responsible official that, based on information and belief formed after reasonable inquiry, the statements in the document are true, accurate, and complete.

- b. Upon presentation of credentials and other documents as may be required by law, the permittee shall allow the Director of the Ohio EPA or an authorized representative of the Director to:
 - i. At reasonable times, enter upon the permittee's premises where a source is located or the emissions-related activity is conducted, or where records must be kept under the conditions of this permit.
 - ii. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit, subject to the protection from disclosure to the public of confidential information consistent with ORC section 3704.08.
 - iii. Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit.
 - iv. As authorized by the Act, sample or monitor at reasonable times substances or parameters for the purpose of assuring compliance with the permit and applicable requirements.
- c. The permittee shall submit progress reports to the appropriate Ohio EPA District Office or local air agency concerning any schedule of compliance for meeting an applicable requirement. Progress reports shall be submitted semiannually, or more frequently if specified in the applicable requirement or by the Director of the Ohio EPA. Progress reports shall contain the following:
 - i. Dates for achieving the activities, milestones, or compliance required in any schedule of compliance, and dates when such activities, milestones, or compliance were achieved.
 - ii. An explanation of why any dates in any schedule of compliance were not or will not be met, and any preventive or corrective measures adopted.

10. Permit To Operate Application

- a. If the permittee is required to apply for a Title V permit pursuant to OAC Chapter 3745-77, the permittee shall submit a complete Title V permit application or a complete Title V permit modification application within twelve (12) months after commencing operation of the emissions units covered by this permit. However, if the proposed new or modified source(s) would be prohibited by the terms and conditions of an existing Title V permit, a Title V permit modification must be obtained before the operation of such new or modified source(s) pursuant to OAC rule 3745-77-04(D) and OAC rule 3745-77-08(C)(3)(d).
- b. If the permittee is required to apply for permit(s) pursuant to OAC Chapter 3745-35, the source(s) identified in this Permit To Install is (are) permitted to operate for a period of up to one year from the date the source(s) commenced operation. Permission to operate is

granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within thirty (30) days after commencing operation of the source(s) covered by this permit.

11. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

B. State Only Enforceable Permit To Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements Related to Monitoring and Recordkeeping Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping of state-only enforceable information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from state-only required emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

4. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

5. Termination of Permit To Install

This permit to install shall terminate within eighteen months of the effective date of the permit to install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may

be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

6. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources are inadequate or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities prove to be inadequate or cannot meet applicable standards.

7. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

8. Applicability

This Permit to Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate application must be made to the Director for the installation or modification of any other emissions unit(s).

9. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit To Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

10. Additional Reporting Requirements When There Are No Deviations of Federally Enforceable Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations (See Section A of This Permit)

If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters.

C. Permit To Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

**SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS**

<u>Pollutant</u>	<u>Tons Per Year</u>
VOC	5.26

Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

A. State and Federally Enforceable Permit To Install Facility Specific Terms and Conditions

None

B. State Only Enforceable Permit To Install Facility Specific Terms and Conditions

None

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
L015 - Automatic tube cleaner, 24 mm ED line, with catalytic incinerator	OAC rule 3745-31-05 (A) (3)	Volatile organic compound (VOC) emissions shall not exceed 1.0 pound per hour and 4.38 tons per year. See A.I.2.a, and A.II.1 and A.II.2 below.
	OAC rule 3745-21-09 (O) (4)	The requirements of this rule also include compliance with the requirements of OAC rule 3745-21-09 (O) (4).
		See A.II.3, 4 and 5 below.

2. **Additional Terms and Conditions**

- 2.a The pound per hour VOC limit reflects the potential to emit for this emissions unit. Therefore, it is not necessary to develop recordkeeping and/or reporting requirements to ensure compliance with this limit.

II. Operational Restrictions

1. The facility shall employ a catalytic incinerator with a minimum control efficiency of 95% to control VOC emissions from this emissions unit whenever the emissions unit is in operation.
2. The average temperature of the exhaust gases immediately before the catalyst bed, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance. The average temperature difference across the catalyst bed, for any 3-hour block of time when the emissions unit is in operation, shall not be less than 80 percent of the average temperature difference during the most recent emission test that demonstrated the emissions unit was in compliance.
3. The automatic tube cleaner shall employ equipment, such as a drying tunnel or rotating (tumbling) basket, sufficient to prevent cleaned parts from carrying out solvent liquid or vapor.

4. The automatic tube cleaner shall be equipped with covers that shall be used to close off the entrance and exit of the unit when it is not in use.
5. The automatic tube cleaner shall be operated and maintained in accordance with the following practices to minimize solvent evaporation from the unit:
 - a. Use no workplace fans near the cleaner opening, and ensure that exhaust ventilation does not exceed 65 cubic feet per minute per square foot of cleaner opening, unless a higher rate is necessary to meet Occupational Safety and Health Administration requirements.
 - b. Minimize openings during operation so that entrances and exits silhouette workloads with an average clearance between the parts and the edge of the cleaner opening of less than 10 percent of the width of the opening.
 - c. Provide downtime covers for closing off the entrance and exit during shutdown hours.
 - d. Minimize carry-out emissions by:
 - i. Racking parts so that solvent drains freely from parts and is not trapped.
 - ii. Maintaining the vertical conveyor speed at less than 11 feet per minute.
 - e. Store waste solvent only in covered containers.
 - f. Repair solvent leaks immediately, or shut down the cleaner.
 - g. Operate the cleaner such that water cannot be visually detected in solvent exiting the water separator.
 - h. Place downtime covers over entrances and exits of the cleaner at all times when the conveyors and exhausts are not being operated.
 - i. Clean only materials that are neither porous nor absorbent.

III. Monitoring and/or Recordkeeping Requirements

1. The permittee shall operate and maintain continuous temperature monitors and recorder(s) which measure and record(s) the temperature immediately upstream and downstream of the incinerator's catalyst bed when the emissions unit is in operation. Units shall be in degrees Fahrenheit. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitors and recorder(s) shall be installed, calibrated, operated and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.

2. The permittee shall collect and record the following information each day:
 - a. All 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature of the exhaust gases immediately before the catalyst bed was more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
 - b. All 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature difference across the catalyst bed was less than 80 percent of the average temperature difference during the most recent emission test that demonstrated the emissions unit was in compliance.
 - c. A log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation.

IV. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports that identify all 3-hour blocks of time when the emissions unit was in operation during which the average temperature of the exhaust gases immediately before the catalyst bed or the average temperature difference across the catalyst bed does not comply with the temperature limitations specified above.
2. If the annual emission limit of 4.38 tons per year of VOC is exceeded at any time within the calendar year, the permittee shall submit an emissions report which specifies the total VOC emissions from this emissions unit and the period of time the exceedance occurred. This report shall be submitted within 30 days after the deviation occurs.

V. Testing Requirements

1. Compliance with the emission limitation of these terms and conditions shall be determined in accordance with the following method(s):

- a. Emission Limitation:

Volatile organic compound (VOC) emissions shall not exceed 1.0 pound per hour and 4.38 tons per year.

Applicable Compliance Method:

Compliance with the hourly and annual VOC limitation shall be determined by using the following calculations as provided by the facility:

Maximum uncontrolled VOC emissions are 6.92 lbs per hour.

Control efficiency is 95% and capture efficiency is 90%. The capture efficiency of 90% is derived from engineering calculations provided in the PTI application.

$$(6.92 \text{ lb/hr} * (1 - 0.90)) + (6.92 \text{ lb/hr} * (0.90) * (1 - 0.95)) = 1.0 \text{ lb VOC/hr}$$

Annual VOC emissions: $(1.0 \text{ lb VOC/hr}) \times (8760 \text{ hours/year}) \times (1 \text{ ton}/2000 \text{ lbs}) = 4.38 \text{ ton/year}$

b. Emission Limitation:

This emissions unit shall employ a catalytic incinerator with a minimum control efficiency of 95% to control VOC emissions.

Applicable Compliance Method:

The permittee shall conduct, or have conducted, VOC emission testing for this emissions unit to demonstrate compliance with the minimum overall reduction and minimum control efficiency requirements of Section A.II.1 in accordance with the following requirements:

- i. The emission testing shall be conducted within 90 days of start up of the emissions unit.
 - ii. The following test method(s) shall be employed to determine the minimum control efficiency of the control equipment serving this emissions unit: 40 CFR Part 60, Appendix A, Methods 1 through 4, 25 or 25A.
 - iii. The test(s) shall be conducted while this emissions unit is venting VOC emissions to the catalytic incinerator. This emissions unit shall be operated at or near its maximum capacity, unless otherwise specified or approved by the Ohio EPA, Central District Office.
- c. The minimum control efficiency of the control equipment serving this emissions unit shall be demonstrated based upon the results of the control efficiency tests specified above. The control efficiency (i.e., the percent reduction in mass emissions between the inlet and outlet of the control system) shall be determined in accordance with the test methods and procedures specified in V.1.b above and OAC rule 3745-21-10. The test methods and procedures selected shall be based on a consideration of the diversity of the organic species present and their total concentration, and on a consideration of the potential presence of interfering gases.
- d. Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Ohio EPA, Central District Office. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA, Central District Office's refusal to accept the results of the emission test(s).

Personnel from the Ohio EPA, Central District Office shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid

characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the Ohio EPA, Central District Office within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the Ohio EPA, Central District Office.

VI. Miscellaneous Requirements

None

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
L015 - Automatic tube cleaner, 24 mm ED line, with catalytic incinerator		

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

1. The permit to install for this emissions unit, L015, was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Aliphatic petroleum distillates (stoddard solvent)

TLV (mg/m3): 525

Maximum Hourly Emission Rate (lbs/hr): 1.0

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 95.51

MAGLC (ug/m3): 12,500

2. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy"

is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

3. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"
 - a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
 - c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

Page 18 of 22

Showa Aluminum Corporation of America

PTI Application: **01-08192**

Issued: 1/9/2001

Facility ID: **0149000088**

Emissions Unit ID: L015

None

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P023 - Roller leveler, 24 mm line, with catalytic incinerator, Chapter 31 modification to PTI 01-4502	OAC rule 3745-31-05 (A) (3)	<p>Volatile organic compound (VOC) emissions shall not exceed 0.2 pound per hour and 0.88 ton per year. See A.I.2.a, and A.II.1 and 2 below.</p> <p>The requirements of this rule also include compliance with the requirements of OAC rule 3745-21-09 (B) (6).</p>
	OAC rule 3745-21-09 (B) (6)	OAC rule 3745-21-09 (U) does not apply per this rule.

2. **Additional Terms and Conditions**

- 2.a The pound per hour VOC limit reflects the potential to emit for this emissions unit. Therefore, it is not necessary to develop recordkeeping and/or reporting requirements to ensure compliance with this limit.

II. Operational Restrictions

1. The facility shall employ a catalytic incinerator with a minimum control efficiency of 95% to control VOC emissions from this emissions unit whenever the emissions unit is in operation.
2. The average temperature of the exhaust gases immediately before the catalyst bed, for any 3-hour block of time when the emissions unit is in operation, shall not be less than 600 degrees Fahrenheit. The average temperature difference across the catalyst bed, for any 3-hour block of time when the emissions unit is in operation, shall not be less than 50 degrees Fahrenheit.

III. Monitoring and/or Recordkeeping Requirements

1. The permittee shall operate and maintain continuous temperature monitors and recorder(s) which measure and record(s) the temperature immediately upstream and downstream of the incinerator's catalyst bed when the emissions unit is in operation. Units shall be in degrees Fahrenheit. The

monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitors and recorder(s) shall be installed, calibrated, operated and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.

2. The permittee shall collect and record the following information each day:
 - a. All 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature of the exhaust gases immediately before the catalyst bed was less than 600 degrees Fahrenheit.
 - b. All 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature difference across the catalyst bed was less than 50 degrees Fahrenheit.
 - c. A log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation.

IV. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports that identify all 3-hour blocks of time when the emissions unit was in operation during which the average temperature of the exhaust gases immediately before the catalyst bed or the average temperature difference across the catalyst bed does not comply with the temperature limitations specified above.

V. Testing Requirements

1. Compliance with the emission limitation of these terms and conditions shall be determined in accordance with the following method(s):

- a. Emission Limitation:

Volatile organic compound (VOC) emissions shall not exceed 0.2 pound per hour and 0.88 ton per year.

Applicable Compliance Method:

Compliance with the hourly and annual VOC limitation shall be determined by using the following calculations as provided by the facility:

Maximum solvent usage is 0.59 gallons/hour
VOC content of solvent is 6.7 lb VOC/gallon

$$(0.59 \text{ gallon/hour}) \times (6.7 \text{ lb VOC/gallon}) = 3.95 \text{ lb VOC/hour uncontrolled}$$

Capture efficiency is 100% and destruction efficiency of catalytic incinerator is 95%. The capture efficiency of 100% is derived from engineering calculations provided in the PTI application.

$$(3.95 \text{ lb VOC/hour}) \times (1 - 0.95) = 0.2 \text{ lb VOC/hour controlled}$$

$$\text{Annual VOC emissions: } (0.2 \text{ lb VOC/hr}) \times (8760 \text{ hours/year}) \times (1 \text{ ton}/2000 \text{ lbs}) = 0.88 \text{ ton/year}$$

b. Emission Limitation:

This emissions unit shall employ a catalytic incinerator with a minimum control efficiency of 95% to control VOC emissions.

Applicable Compliance Method:

If required, the following test method(s) shall be employed to determine the overall control efficiency of the control equipment serving this emissions unit: 40 CFR Part 60, Appendix A, Methods 1-4 and 18, 25 or 25A.

VI. Miscellaneous Requirements

1. This air permit-to-install replaces air permit-to-install 01-4502 issued on July 28, 1993.

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P023 - Roller leveler, 24 mm line, with catalytic incinerator, Chapter 31 modification to PTI 01-4502		

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

1. Modeling to demonstrate compliance with the Ohio EPA's "Air Toxic Policy" was not necessary because the emissions unit's maximum annual emissions for each toxic compound will be less than 1.0 ton. OAC Chapter 3745-31 requires permittees to apply for and obtain a new or modified permit to install prior to making a "modification" as defined by OAC rule 3745-31-01. The permittee is hereby advised that changes in the composition of the materials, or use of new materials, that would cause the emissions of any pollutant that has a listed TLV to increase to above 1.0 ton per year may require the permittee to apply for and obtain a new permit to install.

NEW SOURCE REVIEW FORM B

PTI Number: 01-08192

Facility ID: 0149000088

Emissions Unit ID: P023

FACILITY NAME Showa Aluminum Corporation of America

FACILITY DESCRIPTION Roller Leveler and automatic tube cleaner. CITY/TWP Mount Sterling

NEW SOURCE REVIEW FORM B

PTI Number: 01-08192

Facility ID: 0149000088

FACILITY NAME Showa Aluminum Corporation of America

FACILITY DESCRIPTION Roller Leveler and automatic tube cleaner. CITY/TWP Mount Sterling

SIC CODE 3714 SCC CODE 3-14-999-99 EMISSIONS UNIT ID L015

EMISSIONS UNIT DESCRIPTION Automatic tube cleaner, 24 mm ED line, with catalytic incinerator

DATE INSTALLED 1994 (to be modified in July 2001)

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter					
PM ₁₀					
Sulfur Dioxide					
Organic Compounds	Attainment			1.0 lb/hr	4.38
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? _____ NESHAP? _____ PSD? _____ OFFSET POLICY? _____

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Compliance with applicable rules and regulations; use of catalytic incinerator.

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? Yes

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$ _____

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? X YES _____ NO _____

IDENTIFY THE AIR CONTAMINANTS: petroleum distillates (stoddard solvent)

NEW SOURCE REVIEW FORM B

PTI Number: 01-08192

Facility ID: 0149000088

FACILITY NAME Showa Aluminum Corporation of America

FACILITY DESCRIPTION Roller Leveler and automatic tube cleaner. CITY/TWP Mount Sterling

SIC CODE 3714 SCC CODE 3-14-999-99 EMISSIONS UNIT ID P023

EMISSIONS UNIT DESCRIPTION Roller leveler, 24 mm line, with catalytic incinerator, modification to PTI 01 4502

DATE INSTALLED July 2001 (PTI modification)

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter					
PM ₁₀					
Sulfur Dioxide					
Organic Compounds	Attainment			0.2 lb/hr	0.88
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? _____ NESHAP? _____ PSD? _____ OFFSET POLICY? _____

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Compliance with applicable rules and regulations; use of catalytic incinerator

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? No

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$ _____

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? _____ YES X NO

IDENTIFY THE AIR CONTAMINANTS: _____

NEW SOURCE REVIEW FORM B

PTI Number: 01-08192

Facility ID: 0149000088

FACILITY NAME Showa Aluminum Corporation of America

FACILITY DESCRIPTION Roller Leveler and automatic tube cleaner. CITY/TWP Mount Sterling

Ohio EPA Permit to Install Information Form Please describe below any documentation which is being submitted with this recommendation (must be sent the same day). Electronic items should be submitted with the e-mail transmitting the PTI terms, and in software that CO can utilize. If mailing any hard copy, this section must be printed as a cover page. All items must be clearly labeled indicating the PTI name and number. Submit **hard copy items to Pam McGraner**, AQM&P, DAPC, Central Office, and electronic files to airpti@epa.state.oh.us

<i>Please fill out the following. If the checkbox does not work, replace it with an 'X'</i>	<u>Electroni</u> <u>c</u>	<u>Additional information File</u> <u>Name Convention (your PTI</u> <u># plus this letter)</u>	<u>Hard</u> <u>Copy</u>	<u>None</u>
Calculations (required)	<input checked="" type="checkbox"/>	0000000c.wpd	<input type="checkbox"/>	
Modeling form/results	<input type="checkbox"/>	0000000s.wpd	<input checked="" type="checkbox"/>	<input type="checkbox"/>
PTI Application (complete or partial)*	<input type="checkbox"/>	0000000a.wpd	<input type="checkbox"/>	<input type="checkbox"/>
BAT Study	<input type="checkbox"/>	0000000b.wpd	<input type="checkbox"/>	<input type="checkbox"/>
Other/misc.	<input type="checkbox"/>	0000000t.wpd	<input type="checkbox"/>	<input type="checkbox"/>

* Mandatory for netting, PSD, nonattainment NSR, 112(g), 21-07(G)(9)(g) and 21-09(U)(2)(f) - 2 complete copies.

Please complete (see comment bubble to the left for additional instructions):

NSR Discussion

Showa Aluminum Corporation of America (Showa) submitted a PTI application to update the permit status of its facility located at 10500 O'Day Harrison Road, Mt. Sterling, Madison County. Showa manufactures aluminum components for the automotive industry; they also manufacture aluminum photocopier tubes. Showa, a Title V facility, is located in Madison County which is in attainment for all pollutants. PSD does not apply to this facility and MACT rules do not apply to these emissions units.

This PTI is for two emissions units at Showa, L015 and P023. L015, the automatic tube cleaner, 24 mm ED line, with catalytic incinerator, was previously unpermitted. OAC rule 3745-21-09 (O) (4) applies to this unit. This unit is subject to the Air Toxics Policy and hard copy modeling results are being submitted. P023, the roller leveler, 24 mm line, with catalytic incinerator is a Chapter 31 modification to PTI 01-4502. OAC rule 3745-21-09 (B) (6) applies to P023 in lieu of complying with the pounds of VOC per gallon of solids limitations contained in 3745-21-09 (U); a catalytic incinerator with 95% control efficiency will be installed as BAT for this unit. P023 is not subject to the Air Toxics Policy because the emissions unit's maximum annual emissions for each toxic compound will be less than 1.0 ton.

Emissions calculations are provided below. Please contact Mike Ebner at 728-3807 if you have any questions.

L015 - Automatic tube cleaner, 24 mm ED line, with catalytic incinerator
 Maximum solvent usage is 1.05 gallons/hour
 VOC content of solvent is 6.59 lb VOC/gallon
 (1.05 gallon/hour) x (6.59 lb VOC/gallon) = 6.92 lb VOC/hour uncontrolled

Capture efficiency is 90% and destruction efficiency of catalytic incinerator is 95%.
 (6.92 lb/hr x (1 - 0.90)) + (6.92 lb/hr x (0.90) x (1 - 0.95)) = 1.0 lb VOC/hr
 Annual VOC emissions: (1.0 lb VOC/hr) x (8760 hours/year) x (1 ton/2000 lbs) = 4.38 ton/year

NEW SOURCE REVIEW FORM B

PTI Number: 01-08192

Facility ID: 0149000088

FACILITY NAME Showa Aluminum Corporation of America

FACILITY DESCRIPTION Roller Leveler and automatic tube cleaner. CITY/TWP Mount Sterling

P023 - Roller leveler, 24 mm line, with catalytic incinerator
Maximum solvent usage is 0.59 gallons/hour
VOC content of solvent is 6.7 lb VOC/gallon
(0.59 gallon/hour) x (6.7 lb VOC/gallon) = 3.95 lb VOC/hour uncontrolled

Capture efficiency is 100% and destruction efficiency of catalytic incinerator is 95%.
(3.95 lb VOC/hour) x (1 - 0.95) = 0.2 lb VOC/hour controlled
Annual VOC emissions: (0.2 lb VOC/hr) x (8760 hours/year) x (1 ton/2000 lbs) = 0.88 ton/year

Please complete for these type permits (For PSD/NSR Permit, place mouse over this text):

Synthetic Minor Determination and/or Netting Determination
Permit To Install ENTER PTI NUMBER HERE

A. Source Description

B. Facility Emissions and Attainment Status

C. Source Emissions

D. Conclusion

PLEASE PROVIDE ADDITIONAL NOTES OR COMMENTS AS NECESSARY:

NONE

Please complete:

SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
VOC	5.26