

Synthetic Minor Determination and/or **Netting Determination**
Permit To Install 02-19250

A. Source Description

Mar-Zane, Inc. - Plant #28 located at 2800 Center Street in Youngstown, Ohio is proposing to modify its hot-mix asphalt plant. The 445 TPH plant will be derated to 365 TPH production and will burn fuel oils and waste oil as fuel, in addition to natural gas.

B. Facility Emissions and Attainment Status

This facility has requested a synthetic minor permit because the maximum potential to emit, at 8,760 hours per year, for this emissions unit exceeds Title V and PSD thresholds. The potential to emit for 2 pollutants exceeds one or both thresholds as follows: 289.36 TPY of SO₂ and 258.99 TPY of VOC. These emissions would make the facility a major source and it would be subject to Title V permitting and PSD requirements. Federally enforceable restrictions will lower potential emissions of the above mentioned pollutants to less than 100 TPY. The potential emissions of all other pollutants do not reach the 100 TPY level.

C. Source Emissions

Mar-Zane, Inc. has requested federally enforceable restrictions of varying monthly production limits and 400,000 production tons for the annual restriction. With the proposed production limitation the annual CO, SO₂, VOC, NO_x and PE/PM₁₀ emissions will be limited to 26.00 TPY, 20.8 TPY, 32.40 TPY, 11.00 TPY, and 6.10 TPY, respectively.

D. Conclusion

Mar-Zane, Inc. has requested federally enforceable production restrictions. With the proposed production restrictions, the annual SO₂ and VOC emissions will be limited to 20.8 TPY and 32.40 TPY, respectively.



State of Ohio Environmental Protection Agency

Street Address:

Lazarus Gov. Center
122 S. Front Street
Columbus, OH 43215

TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center
P.O. Box 1049
Columbus, OH 43216-1049

**RE: DRAFT PERMIT TO INSTALL
MAHONING COUNTY
Application No: 02-19250**

DATE: 5/13/2004

Mar-Zane, Inc., Plant 28
Ronald P. Morrison
P.O. Box 1585
Zanesville, OH 437021585

CERTIFIED MAIL

Y	TOXIC REVIEW
	PSD
Y	SYNTHETIC MINOR
	CEMS
	MACT
Subpart I	NSPS
	NESHAPS
	NETTING
	MAJOR NON-ATTAINMENT
Y	MODELING SUBMITTED
	GASOLINE DISPENSING FACILITY

You are hereby notified that the Ohio Environmental Protection Agency has made a draft action recommending that the Director issue a Permit to Install for the air contaminant source(s) [emissions unit(s)] shown on the enclosed draft permit. This draft action is not an authorization to begin construction or modification of your emissions unit(s). The purpose of this draft is to solicit public comments on the proposed installation. A public notice concerning the draft permit will appear in the Ohio EPA Weekly Review and the newspaper in the county where the facility will be located. Public comments will be accepted by the field office within 30 days of the date of publication in the newspaper. Any comments you have on the draft permit should be directed to the appropriate field office within the comment period. A copy of your comments should also be mailed to Robert Hodanbosi, Division of Air Pollution Control, Ohio EPA, P.O. Box 1049, Columbus, OH, 43266-0149.

A Permit to Install may be issued in proposed or final form based on the draft action, any written public comments received within 30 days of the public notice, or record of a public meeting if one is held. You will be notified in writing of a scheduled public meeting. Upon issuance of a final Permit to Install a fee of **\$1250** will be due. Please do not submit any payment now.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469. If you have any questions about this draft permit, please contact the field office where you submitted your application, or Mike Ahern, Field Operations & Permit Section at (614) 644-3631.

Very truly yours,

Michael W. Ahern, Supervisor
Field Operations and Permit Section
Division of Air Pollution Control

cc: USEPA NEDO Eastgate Development & Transportation Study WV PA

MAHONING COUNTY

PUBLIC NOTICE

ISSUANCE OF DRAFT PERMIT TO INSTALL **02-19250** FOR AN AIR CONTAMINANT SOURCE FOR **MAR-ZANE, INC., PLANT 28**

On 5/13/2004 the Director of the Ohio Environmental Protection Agency issued a draft action of a Permit To Install an air contaminant source for **Mar-Zane, Inc., Plant 28**, located at **2800 Center Street, Youngstown, Ohio**.

Installation of the air contaminant source identified below may proceed upon final issuance of Permit To Install 02-19250:

Chapter 31 modification to allow the use of alternative fuels.

Comments concerning this draft action, or a request for a public meeting, must be sent in writing to the address identified below no later than thirty (30) days from the date this notice is published. All inquiries concerning this draft action may be directed to the contact identified below.

Dennis Bush, Ohio EPA, Northeast District Office, 2110 East Aurora Road, Twinsburg, OH 44087 [(330)425-9171]



Permit To Install

Issue Date: To be entered upon final issuance

Terms and Conditions

Effective Date: To be entered upon final issuance

DRAFT PERMIT TO INSTALL 02-19250

Application Number: 02-19250

APS Premise Number: 0250110985

Permit Fee: **To be entered upon final issuance**

Name of Facility: Mar-Zane, Inc., Plant 28

Person to Contact: Ronald P. Morrison

Address: P.O. Box 1585
Zanesville, OH 437021585

Location of proposed air contaminant source(s) [emissions unit(s)]:

**2800 Center Street
Youngstown, Ohio**

Description of proposed emissions unit(s):

Chapter 31 modification to allow the use of alternative fuels.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may

be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions

and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

13. Source Operation and Operating Permit Requirements After Completion of Construction

- a. If the permittee is required to apply for a Title V permit pursuant to OAC Chapter 3745-77, the permittee shall submit a complete Title V permit application or a complete Title V permit modification application within twelve (12) months after commencing operation of the emissions units covered by this permit. However, if the proposed new or modified source(s) would be prohibited by the terms and conditions of an existing Title V permit, a Title V permit modification must be obtained before the operation of such new or modified source(s) pursuant to OAC rule 3745-77-04(D) and OAC rule 3745-77-08(C)(3)(d).

- b. If the permittee is required to apply for permit(s) pursuant to OAC Chapter 3745-35, the source(s) identified in this Permit To Install is (are) permitted to operate for a period of up to one year from the date the source(s) commenced operation. Permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the source(s) covered by this permit.

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

**SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS**

<u>Pollutant</u>	<u>Tons Per Year</u>
PM	6.10
PM-10	4.25
SO2	20.8
CO	26.00
NOx	11.00
VOC	32.40

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

- The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
<p>P901 - 365 TPH (derated from 445 TPH) drum-mix asphalt plant, equipped with a cyclone and a fabric filter baghouse. Modification of P901 to add ability to burn fuels other than natural gas, including nos. 2, 4, and 6 oils and on-spec used oil.</p>	<p>OAC rule 3745-31-05(A)(3)</p>	<p>While burning natural gas, nos. 2, 4 or 6 fuel oils, or on-spec used oil, the following emission limitations shall be met:</p>
<p>The terms and conditions of this PTI supercede the terms and conditions of PTI 02-2852 for P901, issued on June 16, 1999.</p>		<p>11.15 lbs/hr and 6.10 TPY of particulate emissions (PE) from the stack serving this emissions unit</p>
		<p>47.45 lbs/hr and 26.00 TPY of carbon monoxide (CO)</p>
		<p>20.08 lbs/hr and 11.00 TPY of nitrogen oxides (NOx)</p>
		<p>66.07 lbs/hr (slag mixes), 21.2 lbs/hr (non-slag mixes) and 20.8 TPY of sulfur dioxide (SO2)</p>
		<p>59.13 lbs/hr and 32.40 TPY of volatile organic compounds (VOC)</p>
		<p>Emissions of fugitive PE shall not exceed 2.56 TPY.</p>
		<p>The requirements of this rule also include compliance with the requirements of 40 CFR, Part 60, Subpart I.</p>

	<p>Best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see section A.2.a).</p>
OAC rule 3745-31-05 (C)	<p>See sections A.2.b. through A.2.e.</p> <p>SO₂: 20.8 tons per rolling, 12-month period</p> <p>VOC: 32.40 tons per rolling, 12-month period</p>
40 CFR Part 60, Subpart I	<p>0.04 gr of PE/dscf of exhaust gas</p> <p>Visible emissions from the stack serving this emissions unit shall not exceed 20% opacity, as a six-minute average.</p>
OAC rule 3745-17-11(B)	<p>The emission limitation in this rule is less stringent than the limit established pursuant to OAC rule 3745-31-05(A)(3).</p>
OAC rule 3745-17-07(A)	<p>The visible emission limitation in this rule is less stringent than the limit established pursuant to OAC rule 3745-31-05(A)(3).</p>
OAC rule 3745-18-06(E)(2)	<p>The emission limitation in this rule is less stringent than the limit established pursuant to OAC rule 3745-31-05(A)(3).</p>
OAC rule 3745-17-08(B)	<p>The control measure requirements in this rule are less stringent than those established pursuant to OAC rule 3745-31-05(A)(3).</p>
OAC rule 3745-17-07(B)	<p>The visible emission limitation in this rule is less stringent than the limit established pursuant to OAC rule 3745-31-05(A)(3).</p>

OAC rule 3745-23-06(B) and OAC rule 3745-21-08(B)

The permittee has satisfied the "latest available control techniques and operating practices" required pursuant to OAC rule 3745-21-08(B) and OAC rule 3745-23-06(B) by committing to comply with the best available technology requirements established pursuant to OAC rule 3745-31-05(A)(3) in this permit to install.

See section A.2.f.

2. Additional Terms and Conditions

- 2.a The permittee shall ensure that the baghouse is operated with sufficient air volume to minimize or eliminate visible fugitive emissions from the rotary drum.
- 2.b No visible emissions of fugitive dust from the enclosures for the hot aggregate elevator, vibrating screens, and weigh hopper.
- 2.c Visible emissions of fugitive dust (from areas other than the enclosures for the hot aggregate elevator, vibrating screens, and weigh hopper) shall be less than or equal to 10% opacity, as a 3-minute average.
- 2.d The drop height of the front end loader bucket shall be minimized to the extent possible in order to minimize or eliminate visible emissions of fugitive dust from the aggregate storage bins.
- 2.e The aggregate loaded into the storage bins shall have a moisture content sufficient to minimize the visible emissions of fugitive dust from conveyors and all transfer points to the dryer.
- 2.f On November 5, 2002, OAC rule 3745-21-08 was revised to delete paragraph (B); therefore, paragraph (B) is no longer part of the state regulations. However, that rule revision has not yet been submitted to the U.S. EPA as a revision to Ohio State Implementation Plan (SIP).

When the SIP revision occurs and the U.S. EPA approves the revisions to OAC rule 3745-21-08, the requirement to satisfy the "best available control techniques and operating practices" will no longer exist as part of the federally-approved SIP for Ohio, and this term and condition will no longer be applicable to this emissions unit.

B. Operational Restrictions

1. Annual asphalt production from this emissions unit shall not exceed 400,000 tons per year, of which not more than 150,000 tons per year shall be asphalt made with slag. Each of these production restrictions shall be based on a rolling, 12-month summation of the monthly production rates.

To ensure enforceability during the first 12 calendar months of operation under the provisions of this permit, the permittee shall not exceed the production levels specified in the following table:

<u>MONTH(s)</u>	<u>MAXIMUM ALLOWABLE CUMULATIVE ASPHALT PRODUCTION (TONS)</u>	
	<u>Total</u>	<u>Slag Mix</u>
1	70,000	25,000
1-2	140,000	50,000
1-3	200,000	75,000
1-4	270,000	100,000
1-5	340,000	125,000
1-6	400,000	150,000
1-7	400,000	150,000
1-8	400,000	150,000
1-9	400,000	150,000
1-10	400,000	150,000
1-11	400,000	150,000
1-12	400,000	150,000

After the first 12 calendar months of operation under the provisions of this permit, compliance with the annual production restriction shall be based upon a rolling, 12-month summation of the monthly production rates.

2. The permittee may substitute recycled asphalt aggregates in the raw material feed mix in amounts not to exceed 50 percent of all aggregate materials introduced at any given time.
3. The pressure drop across the baghouse shall be maintained within the range of 1 to 8 inches of water column at all times while the emissions unit is in operation.
4. All recycled, used oil burned in emissions unit P901 shall meet the following specifications:

Contaminant/Property Allowable Specifications

arsenic	5 ppm, maximum
cadmium	2 ppm, maximum
chromium	10 ppm, maximum
lead	100 ppm, maximum
PCB's	50 ppm, maximum*
total halogens	4000 ppm maximum**
mercury	1 ppm, maximum

flash point	100 F, minimum
heat content	135,000 Btu/gallon, minimum

* If the permittee is burning used oil with any quantifiable level >2 ppm <50 ppm of PCB's, then the permittee is subject to any applicable requirements found under 40 CFR, Part 279, Subparts G and H and 40 CFR 761.20 (e).

** Used oil containing more than 1000 ppm total halogens is presumed to be a hazardous waste under the rebuttable presumption provided under 40 CFR 279.10 (b)(1)(ii) and OAC rule 3745-279-10 (B)(1)(b). Therefore, the permittee may receive and burn used oil exceeding 1000 ppm of total halogens (but less than 4000 ppm, maximum) only if the used oil burner has demonstrated the used oil does not contain any hazardous waste pursuant to OAC rule 3745-279-63.

5. The permittee may not burn any used oil which does not meet the specifications listed in OAC rule 3745-279-11 without first obtaining an air permit to install that authorizes the burning of such used oil. The burning of used oil that does not meet specifications listed in OAC rule 3745-279-11 is subject to OAC rule 3745-279-60 through 67 and the applicable portions of 40 CFR, Part 761. In addition, if the permittee is burning used oil which exceeds the mercury limitation and falls below the heat content limitation, then this may trigger the requirement to apply for and obtain a permit to install.
6. The burning of hazardous waste is prohibited without first complying with all applicable state and federal hazardous waste and air regulations and permits.
7. The permittee shall conduct burner performance tuning for purposes of minimizing emissions. Burner performance tuning shall contain at a minimum the evaluation of and adjustment to manufacturer's specifications of the following:
 - i. fuel flow to the burner (for fuel oil and on spec used oil);
 - ii. differential pressure of the baghouse to ensure proper air flow through the plant;
 - iii. flue gas analysis (of gases present in the drum and or stack) for CO, O₂, CO₂, and NO_x;
 - iv. fuel pressure; and
 - v. for burners that require compressed air for proper operation, correct pressure at the burner.
8. The permittee shall conduct an initial burner tuning within 30 production days after commencement of the production season. The permittee shall conduct another burner tuning within the time period of 90 to 120 production days after the initial burner tuning. For purposes of this permit, the production season is defined as the time period between the date the first ton of asphalt is produced and the date that the last ton of asphalt is produced during the same

calendar year.

9. In addition to the burner tuning required above, the permittee shall conduct additional burner tuning, within 30 production days , for each type of fuel burned during the production season that is different than the fuel(s) burned during the initial burner tuning or the burner tuning described above that occurs 90 to 120 production days after the initial burner tuning.
10. All number 2 and on-spec used oil burned in this emissions unit shall have a sulfur content equal to or less than 0.5%, by weight.
11. All number 4 fuel oil burned in this emissions unit shall have a sulfur content equal to or less than 0.8%, by weight.
12. All number 6 fuel oil burned in this emissions unit shall have a sulfur content equal to or less than 1%, by weight.

C. Monitoring and/or Record Keeping Requirements

1. The permittee shall operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a daily basis.
2. The permittee shall maintain monthly records of the following information:
 - a. The total asphalt production rate and slag mix production rate, in tons per month.
 - b. Beginning after the first 12 calendar months of operation under the provisions of this permit, the rolling, 12-month summations of the monthly total asphalt and slag mix production rates.

Also, during the first 12 calendar months of operation under the provisions of this permit, the permittee shall record the cumulative total asphalt and slag mix production rates for each calendar month.
3. The permittee shall receive a chemical analysis with each shipment of used oil from the supplier. The analysis shall identify the name and address of the supplier, the supplier's USEPA identification number, and the following information:
 - a. the date of the shipment or delivery;
 - b. the quantity of used oil received;
 - c. the Btu value of the used oil, in Btu/gallon;

- d. the flash point of the used oil, in Btu/gallon;
- e. the arsenic content, in ppm;
- f. the cadmium content, in ppm;
- g. the chromium content, in ppm;
- h. the lead content, in ppm;
- i. the PCB content, in ppm;
- j. the total halogen content, in ppm; and
- k. the mercury content, in ppm.

Each analysis shall be kept in a readily accessible location for at least 5 years and shall be made available to Ohio EPA's Northeast District Office upon verbal or written request. The Director or any authorized representative of the Director may require or may conduct periodic, detailed chemical analysis through an independent laboratory or any used oil shipment received by this facility, of any used oil stored at this facility, or of any used oil sampled at the dryer.

- 4. The permittee shall collect or require the oil supplier to collect a representative grab sample for each shipment of oil that is received for burning in this emissions unit. The permittee shall perform or require the supplier to perform the analysis for sulfur content and heat content in accordance with the following ASTM methods: ASTM method D4294, ASTM method D240, or ASTM method 6010 for sulfur content; and ASTM method D240 for heat content. Alternative, equivalent methods may be used upon written approval by Ohio EPA's Northeast District Office.
- 5. For each shipment of oil received for burning in this emissions unit, the permittee shall maintain records of the total quantity of oil received and the permittee's or oil supplier's analysis for sulfur content and heat content.
- 6. The permittee shall properly operate and maintain portable devices to monitor the concentration of NO_x, CO, O₂, and CO₂ present in the flue gases generated within the drum and/or stack during the burner performance tuning. The monitoring equipment shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall maintain records of each portable monitoring device's calibration.

7. While performing the required burner tuning, the permittee shall record the following information:
 - a. the date of the burner tuning;
 - b. results of the evaluation of the operating parameters listed above;
 - c. a detailed list of adjustments and/or repairs made to bring the operating parameters into conformance with the manufacturer's specifications; and
 - d. the type of fuel(s) employed during the burner tuning.

8. The permittee shall perform daily visible emission checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the enclosures for the hot aggregate elevator, vibrating screens and weigh hopper serving this emissions unit. If visible particulate emissions are observed, the permittee shall note the following in the operation log:
 - a. the color of the visible particulate emissions;
 - b. the cause of the visible particulate emissions;
 - c. the total duration of the visible particulate emission incident; and
 - d. corrective actions taken to eliminate the visible particulate emissions.

The permittee may, upon receipt of written approval from Ohio EPA's Northeast District Office, modify the above-mentioned visible particulate emissions check frequency if operating experience indicates that less frequent checks would be sufficient to ensure compliance with the visible particulate emissions requirements.

6. The permittee shall perform daily visible emission checks, when the emissions unit is in operation and when the weather conditions allow, for any abnormal visible particulate emissions from the stack, aggregate storage bins and cold aggregate elevator/conveyor serving this emissions unit. If abnormal visible emissions are observed, the permittee shall note the following in the operation log:
 - a. the color of the abnormal visible particulate emissions;
 - b. the cause of the abnormal visible particulate emissions;
 - d. the total duration of any abnormal visible particulate emissions incident; and
 - e. any corrective actions taken to eliminate the abnormal visible particulate emissions.

The permittee may, upon receipt of written approval from the Ohio EPA's Northeast District Office or local air agency modify the above-mentioned visible particulate emissions check frequency if operating experience indicates that less frequent checks would be sufficient to ensure compliance with the visible particulate emissions requirements.

7. The permit to install for this emissions unit (P901) was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Heptane

TLV (mg/m³): 1,640

Maximum Hourly Emission Rate (lbs/hr): 3.43

Predicted 1-Hour Maximum Ground-Level

Concentration (ug/m³): 4.9

MAGLC (ug/m³): 39,048

8. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
 - a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
 - b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
 - c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

9. If the permittee determines that the “Air Toxic Policy” will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a “modification” under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the “Air Toxic Policy:”

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the “Air Toxic Policy”; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the “Air Toxic Policy” for the change.

D. Reporting Requirements

1. The permittee shall submit pressure drop deviation (excursion) reports that identify that all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above.
2. The permittee shall submit deviation (excursion) reports which identify all exceedances of the rolling, 12-month asphalt production restrictions and for the first 12 calendar months of operation under the provisions of this permit, all exceedances of the maximum allowable cumulative asphalt production levels.
3. The permittee shall notify the USEPA and the Ohio EPA if any of the used oil exceeds the used oil specifications found in OAC rule 3745-279-11 and the applicable portions of 40 CFR, Part 761 and shall also notify Ohio EPA if any used oil exceeds the mercury limitation and falls below the heat content limitation within thirty days after the exceedance occurs. If the permittee is burning used oil which exceeds the specifications found in OAC rule 3745-279-11 and the applicable portions of 40 CFR, Part 761, the permittee is subject to that rule and must comply with all applicable provisions of that rule.
4. The permittee shall submit burner tuning reports to Ohio EPA's Northeast District Office that summarize the results of each burner tuning. These reports are due within 30 days of the date that the burner tuning was performed.
5. The permittee shall submit quarterly deviation (excursion) reports that identify any of the following occurrences:

- a. identify all days during which any abnormal visible particulate emissions were observed from the stack, aggregate storage bins and cold aggregate elevator/conveyors serving this emissions unit;
 - b. identify all days during which any visible fugitive particulate emissions were observed from the enclosures for the hot aggregate elevator, vibrating screens, weigh hopper; and
 - c. describe any corrective actions taken to eliminate the abnormal visible particulate emissions.
6. The permittee shall submit deviation (excursion) reports which identify all exceedances of the fuel sulfur content restrictions specified in sections B.10. through B.12.
 7. Deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

E. Testing Requirements

1. Compliance with the emissions limitations in section A.1 of these terms and conditions shall be determined in accordance with the following methods:

- 1.a Emission Limitations:
0.04 gr of PE/dscf of exhaust, 11.15 lbs of PE/hr, and 6.10 TPY of PE

Applicable Compliance Methods:

Compliance with the hourly PE limitation above shall be determined by stack testing as outlined in section E.2. below.

The annual emission limitation was established by multiplying the maximum annual asphalt production rate of 400,000 tons by an emission factor of 0.0305 lb of PE/ton of product (developed using 0.04 gr/dscf) and dividing by 2000 lbs/ton. Therefore, provided compliance is shown with this annual asphalt production rate, compliance with the emission limitation will be assumed. Compliance with the annual asphalt production rate shall be demonstrated by the monitoring and record keeping in Section C.2.

- 1.b Emission Limitations:
47.45 lbs of CO/hr and 26.00 TPY of CO

Applicable Compliance Methods:

Compliance with the hourly CO emission limitation above shall be determined by stack testing as outlined in section E.2. below.

The annual emission limitation was established by multiplying the maximum annual asphalt production rate of 400,000 tons by an emission factor of 0.1300 lb of CO/ton of product (from AP-42, Table 11.1-7, dated 04/2004) and dividing by 2000 lbs/ton. Therefore, provided

compliance is shown with this annual asphalt production rate, compliance with the emission limitation will be assumed. Compliance with the annual asphalt production rate shall be demonstrated by the monitoring and record keeping in Section C.2.

- 1.c Emission Limitations:
20.08 lbs of NO_x/hr and 11.00 TPY of NO_x

Applicable Compliance Methods:

Compliance with the hourly NO_x emission limitation above shall be determined by stack testing as outlined in section E.2. below.

The annual emission limitation was established by multiplying the maximum annual asphalt production rate of 400,000 tons by an emission factor of 0.0550 lb of NO_x/ton of product (from AP-42, Table 11.1-7, dated 04/2004) and dividing by 2000 lbs/ton. Therefore, provided compliance is shown with this annual asphalt production rate, compliance with the emission limitation will be assumed. Compliance with the annual asphalt production rate shall be demonstrated by the monitoring and record keeping in Section C.2.

- 1.d Emission Limitations:
66.07 lbs of SO₂/hr (slag mixes), 21.2 lbs of SO₂/hr (non-slag mixes) and 20.8 TPY of SO₂ as a rolling, 12-month summation

Applicable Compliance Methods:

Compliance with the hourly SO₂ emission limitations above shall be determined by stack testing as outlined in section E.2. below.

The annual emission limitation was established by multiplying the maximum annual asphalt production rate for slag mix of 150,000 tons by an emission factor of 0.1810 lb of SO₂/ton of product (based on stack testing performed in October 2000 and September 2003) and dividing by 2000 lbs/ton and adding to this the product of multiplying the maximum annual asphalt production rate for non-slag mix of 250,000 tons by an emission factor of 0.0580 lb of SO₂/ton (from AP-42, Table 11.1-7, dated 04/2004) and dividing by 2000 lbs/ton. Therefore, provided compliance is shown with this annual asphalt production rate, compliance with the emission limitation will be assumed. Compliance with the annual asphalt production rate shall be demonstrated by the monitoring and record keeping in Section C.2.

- 1.e Emission Limitations:
59.13 lbs of VOC/hr and 32.40 TPY of VOC as a rolling, 12-month summation

Applicable Compliance Methods:

Compliance with the hourly VOC emission limitation above shall be determined by stack testing as outlined in section E.2. below.

The annual emission limitation was established by multiplying the maximum annual asphalt production rate for slag mix of 400,000 tons by an emission factor of 0.1620 lb of VOC/ton of

product (based on stack testing performed in September 2003) and dividing by 2000 lbs/ton. Therefore, provided compliance is shown with this annual asphalt production rate, compliance with the emission limitation will be assumed. Compliance with the annual asphalt production rate shall be demonstrated by the monitoring and record keeping in Section C.2.

1.f Emission Limitation:

Visible emissions from the stack serving this emissions unit shall not exceed 20% opacity, as a six-minute average.

Applicable Compliance Method:

Compliance with the visible emission limitation shall be determined using Method 9 of 40 CFR, Part 60, Appendix A.

1.g Emission Limitation:

Emissions of fugitive PE shall not exceed 2.56 TPY

Applicable Compliance Method: Compliance with the annual emissions limitation shall be assumed based upon the following worst case calculations:

Total fugitive emissions equal the summation of the fugitives from the cold end and the hot end of the plant operations.

Fugitives emissions from the cold end are calculated as follows

$((400,000 \text{ tons of material/year} \times 0.0051 \text{ lb PE/ton of material}) + (376,800 \text{ tons of aggregate/year} \times 0.0069 \text{ lb PE/ton of aggregate}) + (169,200 \text{ tons of sand/year} \times 0.0021 \text{ lb PE/ton of sand})) \times (1 \text{ ton}/2000 \text{ pounds}) = 2.50 \text{ tons of PE}$

Fugitives emissions from the hot end are calculated as follows

$(400,000 \text{ tons of asphalt produced} \times 0.0003 \text{ lb of PE/ton of asphalt produced}) \times (1 \text{ ton}/2000 \text{ pounds}) = 0.06 \text{ tons of PE.}$

Total fugitive emissions are therefore 2.56 tons.

The emission factors in the above equations are derived from AP-42, Fifth edition, Table 11.12-2 (10/01) and from AP-42, Fifth edition, 11.1.2.5 (12/00)

1.h Emission Limitation:

No visible emissions of fugitive dust from the enclosures for the hot aggregate elevator, vibrating screens, and weigh hopper.

Applicable Compliance Method:

Compliance with the above visible emission limitation shall be determined using Method 22 of 40 CFR, Part 60, Appendix A.

1.i Emission Limitation:

Visible emissions of fugitive dust (from areas other than the enclosures for the hot aggregate elevator, vibrating screens, and weigh hopper) shall be less than or equal to 10% opacity, as a 3-minute average.

Applicable Compliance Method:

Compliance with the above visible emission limitation shall be determined using Method 9 of 40 CFR, Part 60, Appendix A, except that the data reduction and average opacity calculation shall be based upon sets of twelve consecutive visible particulate emissions observations recorded at fifteen-second intervals.

2. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:

a. The emission testing shall be conducted within six (6) months of issuance of this permit. However, if no slag mix is produced within this time period, the testing for SO₂ while producing slag mix can be delayed until up to one month after the first batch of slag mix is produced.

b. The emission testing shall be conducted to demonstrate compliance with the following:

i. 11.15 lbs of PE/hr and 0.04 gr of PE/dscf of exhaust gas

ii. 47.45 lbs of CO/hr

iii. 66.07 lbs/hr of SO₂ (slag mixes)

iv. 21.2 lbs/hr of SO₂ (non-slag mixes)

v. 59.13 lbs/hr of VOC

vi. 20.08 lbs/hr of NO_x

c. The following test methods shall be employed to demonstrate compliance with the above emission limitations:

i. Methods 1 - 4 of 40 CFR, Part 60, Appendix A

ii. for PE: Method 5, of 40 CFR, Part 60, Appendix A.

iii. for SO₂: Method 6 or 6C, of 40 CFR, Part 60, Appendix A.

iv. for CO: Method 10, of 40 CFR, Part 60, Appendix A.

v. for NO_x: Method 7 or 7E of 40 CFR, Part 60, Appendix A.

- vi. for VOC: Method 25 of 40 CFR, Part 60, Appendix A.

The tests shall be conducted while the emissions unit is operating at its maximum capacity unless otherwise specified or approved by Ohio EPA's Northeast District Office.

- d. Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the times and dates of the tests, and the persons who will be conducting the tests. Failure to submit such notification for review and approval prior to the tests may result in the field office's refusal to accept the results of the emissions tests.
- e. Personnel from Ohio EPA's Northeast District Office shall be permitted to witness the tests, examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.
- f. A comprehensive written report on the results of the emissions tests shall be signed by the person or persons responsible for the tests and submitted to Ohio EPA's Northeast District Office within 30 days following completion of the tests. The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from Ohio EPA's Northeast District Office.

F. Miscellaneous Requirements

- 1. In accordance with the provisions of OAC rule 3745-31-05, the following special terms and conditions of this permit to install are federally enforceable: A-F.