



State of Ohio Environmental Protection Agency

Street Address:

Lazarus Gov. Center
122 S. Front Street
Columbus, OH 43215

TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center
P.O. Box 1049
Columbus, OH 43216-1049

RE: FINAL PERMIT TO INSTALL MODIFICATION

CERTIFIED MAIL

LUCAS COUNTY

Application No: 04-01315

Fac ID: 0448960003

DATE: 7/21/2005

Stansley Mineral Resources
Chip Tokar
3810 Herr Road
Sylvania, OH 43560

	TOXIC REVIEW
	PSD
	SYNTHETIC MINOR
	CEMS
	MACT
	NSPS
	NESHAPS
	NETTING
	MAJOR NON-ATTAINMENT
	MODELING SUBMITTED
	GASOLINE DISPENSING FACILITY

Enclosed Please find a modification to the Ohio EPA Permit To Install referenced above which will modify the terms and conditions.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
309 South Fourth Street, Room 222
Columbus, Ohio 43215

Sincerely,

Michael W. Ahern, Manager
Permit Issuance and Data Management Section
Division of Air Pollution Control

CC: USEPA

TDES



FINAL ADMINISTRATIVE MODIFICATION OF PERMIT TO INSTALL 04-01315

Application Number: 04-01315
Facility ID: 0448960003
Permit Fee: **\$0**
Name of Facility: Stansley Mineral Resources
Person to Contact: Chip Tokar
Address: 3810 Herr Road
Sylvania, OH 43560

Location of proposed air contaminant source(s) [emissions unit(s)]:
3810 Herr Road
Sylvania, Ohio

Description of proposed emissions unit(s):
Reassign facility ID for PTI 04-01315.

The above named entity is hereby granted a modification to the permit to install described above pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this modification does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described source(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans included in the application, the above described source(s) of pollutants will be granted the necessary operating permits.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and

regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions

may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this

permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the emissions unit(s) covered by this permit.

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
CO	7.7
NOx	24.8
PE	1.33
SO2	3.7
VOC	1.67

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

- The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
B001 - Portable 600 kilowatt diesel fueled generator, Caterpillar model 3414 with 890 bhp internal combustion engine with timing retard and positive crankcase ventilation	OAC rule 3745-31-05(A)(3)	5.3 pounds of CO per hour, 11.8 pounds of NOx per hour, 0.39 pound of PE per hour, 3.1 pounds of SO2 per hour, 0.56 pound of VOC per hour, and see A.2.b, A.2.c and A.2.d.
	OAC rule 3745-17-07(A)(1)	20% opacity as a 6-minute average except as provided by rule.
	OAC rule 3745-17-11(B)(5)(b)	0.062 lb PE/mm BTU
	OAC rule 3745-18-06(B)	Exempt, see A.2.a.
	OAC rule 3745-21-07(B)	None, see A.2.b.
	OAC rule 3745-21-08(B)	None, see A.2.b.
	OAC rule 3745-23-06(B)	None, see A.2.b.
	OAC rule 3745-31-02(A)(2)	4.5 tons of carbon monoxide (CO) per rolling 12-month period, 10 tons of nitrogen oxides (NOx) per rolling 12-month period, 0.33 ton of particulate emissions (PE) per rolling 12-month period, 2.7 tons of sulfur dioxide (SO2) per rolling 12-month period, and 0.47 ton of volatile organic compounds (VOC) per rolling 12-month period.

2. Additional Terms and Conditions

- 2.a** Exemption from OAC rule 3745-18-06 requirements for SO₂: stationary internal combustion engine less than 10 mmBtu per hour.
- 2.b** The permittee has satisfied the “best available control techniques and operating practices” and “latest available control techniques and operating practices” required pursuant to OAC rules 3745-21-07, 3745-21-08 and 3745-23-06 by committing to comply with the best available technology requirements established pursuant to OAC rule 3745-31-05(A)(3).
- 2.c** The permittee shall utilize only commercially available diesel fuel, with a maximum sulfur content of 0.5% by weight, for combustion in this emissions unit.
- 2.d** The requirements of this rule also include compliance with the requirements of OAC rules 3745-17-07(A)(1) and 3745-17-11(B)(5)(b).

B. Operational Restrictions

- 1. The permittee shall maintain and operate a positive crankcase ventilation system at all times when the emissions unit is in operation.
- 2. Engine ignition shall be retarded at least 4 degrees from peak power settings at all times when the emissions unit is in operation.
- 3. The maximum rolling 12-month summation of fuel usage for this emissions unit shall not exceed 75,000 gallons.

C. Monitoring and/or Recordkeeping Requirements

- 1. For each day during which the permittee burns a fuel other than diesel fuel with a maximum sulfur content of 0.5% by weight, the permittee shall maintain a record of the type, sulfur content and quantity of fuel burned in this emissions unit.
- 2. The permittee shall maintain daily records that document any time periods when the positive crankcase ventilation system was not in service when the emissions unit was in operation.
- 3. The permittee shall maintain daily records that document any time periods when the engine ignition was not retarded at least 4 degrees from peak power settings when the emissions unit was in operation.
- 4. The permittee shall maintain a rolling 12-month summation of the number of gallons of fuel used in this emissions unit.

D. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports that identify each day during which a fuel other than diesel fuel with a maximum sulfur content of 0.5% by weight is used in this emissions unit.
2. The permittee shall submit deviation (excursion) reports that identify each day during which the positive crankcase ventilation system was not in service when the emissions unit was in operation.
3. The permittee shall submit deviation (excursion) reports that identify each day during which the engine ignition was not retarded at least 4 degrees from peak power settings when the emissions unit was in operation.
4. The permittee shall submit deviation (excursion) reports identifying any monthly record which shows that the gallons per year of fuel used exceeds the applicable limitation.
5. Each report shall be submitted to the Toledo Division of Environmental Services within 30 days of the discovery of the deviation.

E. Testing Requirements

1. Compliance with the emission limitation(s) of these terms and conditions shall be determined in accordance with the following methods(s):

- a. Emission Limitation: 20% opacity as a six-minute average.

Applicable Compliance Method: If required, the permittee shall demonstrate compliance with this emission limitation through visible emission readings performed in accordance with Method 9 of 40 CFR Part 60 Appendix A using the methods and procedures specified in OAC 3745-17-03(B)(1).

- b. Emission Limitation: 5.3 pounds CO per hour.

Applicable Compliance Method: Compliance shall be based upon the maximum hourly fuel usage rate of 44.2 gallons per hour times the emission factor of 0.85 lb/mmBtu times the heat content of 0.14 MMBtu/gallon. This emission factor is specified in USEPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, dated 10/96 Section 3.4, Table 3.4-1.

If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in Method 10 of 40 CFR Part 60, Appendix A.

- c. Emission Limitation: 4.5 tons CO per rolling, 12-month period.

Applicable Compliance Method: This emission limitation was established to reflect the potential to emit for this emissions unit at the maximum allowable 75,000 gallons per rolling, 12-month period. Compliance may be demonstrated through calculations performed as follows: 0.85 lb/MMBtu times the rolling 12-month summation of fuel usage, in gallons, times the heat content of 0.14 MMBtu/gallon and divide by 2,000 pounds per ton.

- d. Emission Limitation: 11.8 pounds of NOx per hour.

Applicable Compliance Method: Compliance shall be based upon the maximum hourly fuel usage rate of 44.2 gallons per hour times the emission factor of 1.9 lbs/MMBtu times the heat content of 0.14 MMBtu/gallon. This emission factor is specified in USEPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, dated 10/96 Section 3.4, Table 3.4-1.

If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in Method 7 of 40 CFR Part 60, Appendix A.

- e. Emission Limitation: 10 tons NOx per rolling, 12-month period.

Applicable Compliance Method: This emission limitation was established to reflect the potential to emit for this emissions unit at the maximum allowable 75,000 gallons per rolling 12-month period. Compliance may be demonstrated through calculations performed as follows: 1.9 lbs/MMBtu times the rolling 12-month summation of fuel usage, in gallons, times the heat content of 0.14 MMBtu/gallon and divide by 2,000 pounds per ton.

- f. Emission Limitation: 0.39 pound PE per hour.

Applicable Compliance Method: Compliance shall be based upon the maximum hourly fuel usage rate of 44.2 gallons per hour times the emission factor of 0.062 lb/MMBtu times the heat content of 0.14 MMBtu/gallon. This emission factor is specified in USEPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, dated 10/96 Section 3.4, Table 3.4-2.

If required, the permittee shall demonstrate compliance with this emission limitation through emission testing performed in accordance with Method 5 of 40 CFR Part 60 Appendix A using the methods and procedures specified in OAC rule 3745-17-03(B)(10).

- g. Emission Limitation: 0.33 ton PE per rolling, 12-month period.

Applicable Compliance Method: This emission limitation was established to reflect the potential to emit for this emissions unit at the maximum allowable 75,000 gallons per rolling 12-month period. Compliance may be demonstrated through calculations performed as follows: 0.062lbsMMBtu times the rolling 12-month summation of fuel usage, in gallons, times the heat content of 0.14 MMBTU/gallon and divide by 2,000 pounds per ton. .

- h. Emission Limitation: 3.1 pounds of SO₂ per hour.

Applicable Compliance Method: Compliance shall be based upon the maximum hourly fuel usage rate of 44.2 gallons per hour times the emission factor of $1.01 \cdot S$ lbs/MMBTU , where $S=0.5$, times the heat content of 0.14 MMBTU/gallon. This emission factor is specified in USEPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, dated 10/96 Section 3.4, Table 3.4-1.

If required, the permittee shall demonstrate compliance with this emission limitation through emission testing performed in accordance with Method 6 of 40 CFR Part 60 Appendix A using the methods and procedures specified in OAC rule 3745-18-04.

- i. Emission Limitation: 2.7 tons SO₂ per rolling, 12-month period.

Applicable Compliance Method: This emission limitation was established to reflect the potential to emit for this emissions unit at the maximum allowable 75,000 gallons per rolling 12-month period. Compliance may be demonstrated through calculations performed as follows: $1.01 \cdot S$ lbs/MMBTU , where $S=0.5$, times the rolling 12-month summation of fuel usage, in gallons, times the heat content of 0.14 MMBTU/gallon and divide by 2,000 pounds per ton.

- j. Emission Limitation: 0.56 pound VOC per hour.

Applicable Compliance Method: Compliance shall be based upon the maximum hourly fuel usage rate of 44.2 gallons per hour times the emission factor of 0.09 lb/MMBTU times the heat content of 0.14 MMBtu/gallon. This emission factor is specified in USEPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, dated 10/96 Section 3.4, Table 3.4-1.

If required, the permittee shall demonstrate compliance with this emission limitation through emission testing performed in accordance with Method 25 of 40 CFR Part 60 Appendix A using the methods and procedures specified in OAC rule 3745-21-10.

- k. Emission Limitation: 0.47 ton VOC per rolling, 12-month period.

Applicable Compliance Method: This emission limitation was established to reflect the potential to emit for this emissions unit at the maximum allowable 75,000 gallons per rolling 12-month period. Compliance may be demonstrated through calculations performed as follows: 0.09 lb/MMBTU times the rolling, 12-month summation of fuel usage, in gallons, times the heat content of 0.14 MMBTU/gallon and divide by 2,000 pounds per ton.

F. Miscellaneous Requirements

1. Pursuant to Ohio Administrative Code (OAC) rule 3745-31-03(A)(1)(p)(i), the permittee of a portable or mobile emissions unit may relocate within the State of Ohio without first obtaining a PTI providing the following criteria are met:
 - a. the portable emissions unit is equipped with the best available control technology for such portable emissions unit;
 - b. the portable emissions unit is operating pursuant to a currently effective permit to permit to install, permit to operate or registration;
 - c. the applicant has provided proper notice of intent to relocate the portable emissions unit to the Toledo Division of Environmental Services (TDES) and the appropriate field office having jurisdiction over the new site within a minimum of thirty days prior to the scheduled relocation; and,
 - d. in the TDES's and the appropriate field office's judgement, the proposed site is acceptable under the rule 3745-15-07 of the Administrative Code.

2. In the alternative, pursuant to OAC rule 3745-31-03(A)(1)(p)(ii), the permittee of a portable or mobile emissions unit may relocate within the State of Ohio without first obtaining a PTI providing the following criteria of OAC rule 3745-31-05(F) are met:
 - a. the portable emissions unit permittee possesses an Ohio EPA PTI, PTO or registration status;
 - b. the portable emissions unit is equipped with best available technology;
 - c. the portable emission unit owner has identified the proposed site to Ohio EPA;
 - d. Ohio EPA has determined that the portable emissions unit, at the proposed site, will have an acceptable environmental impact;
 - e. a public notice, consistent with Chapter 3745-47 of the Administrative Code, is published in the county where the proposed site is located;

- f. the owner of the proposed site has provided the portable emissions unit owner with approval or equivalent declaration that it is acceptable to the site owner to move the portable emissions unit to the proposed site; and
- g. the portable emissions unit owner has provided the Ohio EPA with fifteen days written notice of the relocation.

Any site approvals issued by the Ohio EPA, pursuant to this section, shall be valid for no longer than three years and are subject to renewal.

- 3. In order for the TDES and the appropriate field office having jurisdiction over the new site to determine compliance with all of the above criteria, the owner or operator of the portable or mobile emissions unit must file a "Notice of Intent to Relocate", within the specified time frame (30 or 15 days) prior to the relocation of the emissions unit with the Toledo Division of Environmental Services (348 S. Erie St., Toledo, Ohio 43602)) and with the appropriate field office having jurisdiction over the new site. Upon receipt of the notice, the TDES and/or the appropriate field office having jurisdiction over the new site, will evaluate the request in accordance with the above criteria.
- 4. The following terms and conditions are federally enforceable: A., B., C., D. and E.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

- The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
B002 - Portable 320kilowatt diesel fueled generator, Caterpillar model 3406 with 487 bhp internal combustion engine with timing retard and positive crankcase ventilation	OAC rule 3745-31-05(A)(3)	3.3 pounds of CO per hour, 15.4 pounds of NOx per hour, 1.1 pounds of PE per hour, 1 pound of SO2 per hour, 1.2 pounds of VOC per hour, and see A.2.b, A.2.c and A.2.d
	OAC rule 3745-17-07(A)(1)	20% opacity as a 6-minute average except as provided by rule.
	OAC rule 3745-17-11(B)(5)(a)	0.062 lb PE/mm BTU
	OAC rule 3745-18-06(B)	Exempt, see A.2.a
	OAC rule 3745-21-07(B)	None, see A.2.b
	OAC rule 3745-21-08(B)	None, see A.2.b
	OAC rule 3745-23-06(B)	None, see A.2.b.
	OAC rule 3745-31-02(A)(2)	3.2 tons of carbon monoxide (CO) per rolling 12-month period, 14.8 tons of nitrogen oxides (NOx) per rolling 12-month period, 1 ton of particulate emissions (PE) per rolling 12-month period, 1 ton of sulfur dioxide (SO2) per rolling 12-month period, and 1.2 tons of volatile organic compounds (VOC) per rolling 12-month period.

2. Additional Terms and Conditions

- 2.a** Exemption from OAC rule 3745-18-06 requirements for SO₂: stationary internal combustion engine less than 10 mmBtu per hour.
- 2.b** The permittee has satisfied the “best available control techniques and operating practices” and “latest available control techniques and operating practices” required pursuant to OAC rules 3745-21-07, 3745-21-08 and 3745-23-06 by committing to comply with the best available technology requirements established pursuant to OAC rule 3745-31-05(A)(3).
- 2.c** The permittee shall utilize only commercially available diesel fuel, with a maximum sulfur content of 0.5% by weight, for combustion in this emissions unit.
- 2.d** The requirements of this rule also include compliance with the requirements of OAC rules 3745-17-07(A)(1) and 3745-17-11(B)(5)(b).

B. Operational Restrictions

- 1. The permittee shall maintain and operate a positive crankcase ventilation system at all times when the emissions unit is in operation.
- 2. Engine ignition shall be retarded at least 4 degrees from peak power settings at all times when the emissions unit is in operation.
- 3. The maximum rolling, 12-month summation of fuel usage for this emissions unit shall not exceed 48,000 gallons.

C. Monitoring and/or Recordkeeping Requirements

- 1. For each day during which the permittee burns a fuel other than diesel fuel with a maximum sulfur content of 0.5% by weight, the permittee shall maintain a record of the type, sulfur content and quantity of fuel burned in this emissions unit.
- 2. The permittee shall maintain daily records that document any time periods when the positive crankcase ventilation system was not in service when the emissions unit was in operation.
- 3. The permittee shall maintain daily records that document any time periods when the engine ignition was not retarded at least 4 degrees from peak power settings when the emissions unit was in operation.
- 4. The permittee shall maintain monthly records of the cumulative rolling 12-month summation of fuel used in this emissions unit.

D. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports that identify each day during which a fuel other than diesel fuel with a maximum sulfur content of 0.5% by weight is used in this emissions unit.
2. The permittee shall submit deviation (excursion) reports that identify each day during which the positive crankcase ventilation system was not in service when the emissions unit was in operation.
3. The permittee shall submit deviation (excursion) reports that identify each day during which the engine ignition was not retarded at least 4 degrees from peak power settings when the emissions unit was in operation.
4. The permittee shall submit deviation (excursion) reports identifying any monthly record which shows that the gallons per rolling 12-month period of fuel used exceeds the applicable limitation.
6. Each report shall be submitted to the Toledo Division of Environmental Services within 30 days of the discovery of the deviation.

E. Testing Requirements

1. Compliance with the emission limitation(s) of these terms and conditions shall be determined in accordance with the following methods(s):

- a. Emission Limitation: 20% opacity as a six-minute average.

Applicable Compliance Method: If required, the permittee shall demonstrate compliance with this emission limitation through visible emission readings performed in accordance with Method 9 of 40 CFR Part 60 Appendix A using the methods and procedures specified in OAC 3745-17-03(B)(1).

- b. Emission Limitation: 3.3 pounds CO per hour.

Applicable Compliance Method: Compliance shall be based upon an emission factor of 0.95 lb/MMBtu time the maximum fuel usage rate of 24.9 gallons per hour times the heat content of 0.14 MMBtu/gallon. This emission factor is specified in USEPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, dated 10/96 Section 3.3, Table 3.3-1.

If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in Method 10 of 40 CFR Part 60, Appendix A.

- c. Emission Limitation: 3.2 tons CO per rolling, 12-month period.

Applicable Compliance Method: This emission limitation was established to reflect the potential to emit for this emissions unit at the maximum allowable 48,000 gallons per rolling 12-month period. Compliance may be demonstrated through calculations performed as follows: 0.95 lb/MMBtu times the rolling, 12-month summation of fuel usage, in gallons, times the heat content of 0.14 MMBtu/gallon and divide by 2,000 pounds per ton.

- d. Emission Limitation: 15.4 pounds of NOx per hour.

Applicable Compliance Method: Compliance shall be based upon an emission factor of 4.41 lbs/MMBtu time the maximum fuel usage rate of 24.9 gallons per hour times the heat content of 0.14 MMBtu/gallon. This emission factor is specified in USEPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, dated 10/96 Section 3.3, Table 3.3-1.

If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in Method 7 of 40 CFR Part 60, Appendix A.

- e. Emission Limitation: 14.8 tons NOx per rolling, 12-month period.

Applicable Compliance Method: This emission limitation was established to reflect the potential to emit for this emissions unit at the maximum allowable 48,000 gallons per rolling 12-month period. Compliance may be demonstrated through calculations performed as follows: 4.41 lbs/MMBtu times the rolling, 12-month summation of fuel usage, in gallons, times the heat content of 0.14 MMBtu/gallon and divide by 2,000 pounds per ton.

- f. Emission Limitation: 1.1 pound PE per hour.

Applicable Compliance Method: Compliance shall be based upon an emission factor of 0.31 lb/MMBtu times the maximum fuel usage rate of 24.9 gallons per hour times the heat content of 0.14 MMBtu/gallon. This emission factor is specified in USEPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, dated 10/96 Section 3.3, Table 3.3-1.

If required, the permittee shall demonstrate compliance with this emission limitation through emission testing performed in accordance with Method 5 of 40 CFR Part 60 Appendix A using the methods and procedures specified in OAC rule 3745-17-03(B)(10).

- g. Emission Limitation: 1.0 tons PE per rolling, 12-month period.

Applicable Compliance Method: This emission limitation was established to reflect the potential to emit for this emissions unit at the maximum allowable

48,000 gallons per rolling, 12-month period. Compliance may be demonstrated through calculations performed as follows: 0.31 lb/MMBtu times the rolling, 12-month summation of fuel usage, in gallons, times the heat content of 0.14 MMBTU/gallon and divide by 2,000 pounds per ton.

- h. Emission Limitation: 1 pound of SO₂ per hour.

Applicable Compliance Method: Compliance shall be based upon an emission factor of 0.29 lb/MMBTU times the maximum fuel usage rate of 24.9 gallons per hour times the heat content of 0.14 MMBTU/gallon. This emission factor is specified in USEPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, dated 10/96 Section 3.3, Table 3.3-1.

If required, the permittee shall demonstrate compliance with this emission limitation through emission testing performed in accordance with Method 6 of 40 CFR Part 60 Appendix A using the methods and procedures specified in OAC rule 3745-18-04.

- i. Emission Limitation: 1 ton SO₂ per rolling, 12-month period.

Applicable Compliance Method: This emission limitation was established to reflect the potential to emit for this emissions unit at the maximum allowable 48,000 gallons per rolling, 12-month period. Compliance may be demonstrated through calculations performed as follows: 0.29 lb/MMBTU times the rolling, 12-month summation of fuel usage, in gallons, times the heat content of 0.14 MMBTU/gallon and divide by 2,000 pounds per ton.

- j. Emission Limitation: 1.2 pounds VOC per hour.

Applicable Compliance Method: Compliance shall be based upon an emission factor of 0.35 lb/MMBTU times the maximum fuel usage rate of 24.9 gallons per hour times the heat content of 0.14 MMBtu/gallon. This emission factor is specified in USEPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, dated 10/96 Section 3.3, Table 3.3-1.

If required, the permittee shall demonstrate compliance with this emission limitation through emission testing performed in accordance with Method 25 of 40 CFR Part 60 Appendix A using the methods and procedures specified in OAC rule 3745-21-10.

- k. Emission Limitation: 1.2 tons VOC per rolling, 12-month period.

Applicable Compliance Method: This emission limitation was established to reflect the potential to emit for this emissions unit at the maximum allowable 48,000 gallons per rolling, 12-month period. Compliance may be demonstrated through calculations performed as follows: 0.35 lb/MMBTU times the rolling, 12-

month summation of fuel usage, in gallons, times the heat content of 0.14 MMBTU/gallon and divide by 2,000 pounds per ton.

F. Miscellaneous Requirements

1. Pursuant to Ohio Administrative Code (OAC) rule 3745-31-03(A)(1)(p)(i), the permittee of a portable or mobile emissions unit may relocate within the State of Ohio without first obtaining a PTI providing the following criteria are met:
 - a. the portable emissions unit is equipped with the best available control technology for such portable emissions unit;
 - b. the portable emissions unit is operating pursuant to a currently effective permit to permit to install, permit to operate or registration;
 - c. the applicant has provided proper notice of intent to relocate the portable emissions unit to the Toledo Division of Environmental Services (TDES) and the appropriate field office having jurisdiction over the new site within a minimum of thirty days prior to the scheduled relocation; and,
 - d. in the TDES's and the appropriate field office's judgement, the proposed site is acceptable under the rule 3745-15-07 of the Administrative Code.

2. In the alternative, pursuant to OAC rule 3745-31-03(A)(1)(p)(ii), the permittee of a portable or mobile emissions unit may relocate within the State of Ohio without first obtaining a PTI providing the following criteria of OAC rule 3745-31-05(F) are met:
 - a. the portable emissions unit permittee possesses an Ohio EPA PTI, PTO or registration status;
 - b. the portable emissions unit is equipped with best available technology;
 - c. the portable emission unit owner has identified the proposed site to Ohio EPA;
 - d. Ohio EPA has determined that the portable emissions unit, at the proposed site, will have an acceptable environmental impact;
 - e. a public notice, consistent with Chapter 3745-47 of the Administrative Code, is published in the county where the proposed site is located;
 - f. the owner of the proposed site has provided the portable emissions unit owner with approval or equivalent declaration that it is acceptable to the site owner to move the portable emissions unit to the proposed site; and
 - g. the portable emissions unit owner has provided the Ohio EPA with fifteen days written notice of the relocation.

Any site approvals issued by the Ohio EPA, pursuant to this section, shall be valid for no longer than three years and are subject to renewal.

3. In order for the TDES and the appropriate field office having jurisdiction over the new site to determine compliance with all of the above criteria, the owner or operator of the portable or mobile emissions unit must file a "Notice of Intent to Relocate", within the specified time frame (30 or 15 days) prior to the relocation of the emissions unit with the Toledo Division of Environmental Services (348 S. Erie St., Toledo, Ohio 43602)) and with the appropriate field office having jurisdiction over the new site. Upon receipt of the notice, the TDES and/or the appropriate field office having jurisdiction over the new site, will evaluate the request in accordance with the above criteria.
4. The following terms and conditions are federally enforceable: A., B., C., D. and E.